

# ViewSonic® LARGE FORMAT DISPLAY **CDE6510**

## Key Features

4K Ultra HD Resolution | 4K Resolution |  
Broadcast Content from Android Apps | Diverse  
Android apps rich content | Intel OPS  
Expansion Slot for Computing | Computing  
expansion | Integrated USB Multimedia  
Player | USB playback photos, music & video |  
vController™ Software: Remote Display  
Management | vController™ software: remote  
display management



## Product Description

The ViewSonic CDE6510 is a great value 65" 4K LED commercial display with high-reliability 16 hours per day/7 days a week operating time. The embedded Android SOC enables CDE6510 to install Android apps for rich content broadcasting while the Intel OPS PC slot supports higher computing performance with 4K DisplayPort for a wide range of user scenarios. A built-in browser offers a convenient method for displaying internet content without a PC. In addition to versatile connectivity options, including 4K DisplayPort, HDMI, VGA, USB, IR, RJ45, the display comes with a convenient USB multimedia playback function. With 3840 x 2160 resolution, 350-nit brightness with 178-degree wide viewing angles, and 2 x 10W stereo speakers, the slim-bezel CDE6510 delivers vivid images and remarkable sound for superior multimedia performance. The HDMI CEC pass-through support provides one control for multiple HDMI-connected devices while the free-bundled vController software makes remote display management easier via RS232/RJ45 port. The display also comes equipped with Blue Light Filter technology to create a more comfortable viewing experience.

**Visit Us** - [www.viewsonic.com](http://www.viewsonic.com)

**LCD PANEL**

Panel Size:	65"
Type/ Tech:	TFT LCD Module with DLED Backlight
Display Area (mm):	1428.48 (H) x 803.52 (V)
Aspect Ratio:	16:9
Resolution:	3840x2160 @60Hz
Colors:	1.07B colors
Brightness:	350 nits (typ.)
Contrast Ratio:	4000:1 (typ.)
Response Time:	8 ms
Viewing Angles:	H = 178, V = 178 (typ.)
Backlight:	DLED
Backlight Life:	30,000 Hours Min.
Hardness:	3H

**INPUT**

HDMI:	x 4
RGB / VGA:	x 1
DisplayPort:	x 1
Audio:	x1 PC audio (3.5 mm)
RS232:	x 1
PC Slot:	x 1 (optional VPC12-WPO-2)
IR:	x 1

**OUTPUT**

RS232:	x 1
IR:	x 1

**LAN**

RJ45:	x 1
-------	-----

**USB**

Type A:	x 1 for 5V/2A
2.0 Type A:	x 2 (USB Playback)
3.0 Type A:	x 1 (USB Playback)

**SPEAKERS**

10W x 2
---------

**COMPATIBILITY**

VGA:	1920 x 1080
DisplayPort:	480i, 480p, 720p, 1080i, 1080p, 4K2K@30Hz
HDMI:	480i, 480p, 720p, 1080i, 1080p, 4K2K@60Hz

**POWER**

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption:	Normal 165 W, Max 295 W

**ERGONOMICS**

Wall Mount (VESA®):	400 x 400mm ; Screw: M6* (10+X) mm. (X=thickness of wall mount plate)
---------------------	---

**OPERATING CONDITIONS**

Temperature (° C):	5°C to 40°C
Humidity:	20% ~ 80% non-condensing

**DIMENSIONS****(W X H X D)**

Physical (mm / inch):	1458.7 x 938.8 x 540 mm / 57.43 x 36.96 x 21.26 in. (with Stand)
Physical w/o Stand (mm / inch):	1458.7 x 834.7 x 81.6 mm / 57.43 x 32.86 x 3.21 in. (w/o Stand)
Packaging (mm / inch):	1655 x 1078 x 280 mm / 65.16 x 42.44 x 11.02 in

**WEIGHT**

Net (kg / lb):	28.9 kg / 63.71 lbs (with Stand)
Net w/o Stand (kg / lb):	24.8 kg / 54.67 lbs (w/o stand)
Gross (kg / lb):	34.84 kg / 76.80 lbs

**REGULATIONS**

Standard:	US NRTL with Canada, FCC, Energy star, Mexico CoC and energy , CE, CB, RoHS, ErP, REACH, WEEE, RCM
-----------	--

**WHAT'S IN THE BOX?**

1. CDE6510 commercial display
2. Remote Control with batteries
3. User manual CD wizard
4. Quick Start Guide
5. Power Cables
6. RS232 cable
7. RS232 daisy chain cable (2.4mm – 2.4mm)
8. IR sensor cable