

EPF-HPSM-18-0.5HP

18" Explosion Proof Fan - 3990 CFM - 1/2 HP - 115-230V - Class 1 Group D & Class 2 Groups F & G

Product ID: 146356

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPF-HPSM-18-0.5HP Explosion Proof High Volume Ventilation Fan Type: High Pressure High Volume Ventilation Fan Propeller Dimensions: 18" Diameter Propeller Material: Spark-Resistant Cast Aluminum Weight: 55 lbs Voltage: Multi-Voltage - 115-230V AC Motor: 1/2 HP Fully Enclosed Explosion Proof Rotations Per Minutes (RPM): 1750 Peak CFM (@ 0" SP): 3990 Max Sound Levels @ 5`: 23 (sones), 73.21 (db)

Ambient Temp Range: -20°C to +55°C Temperature Rating: T3B Wiring: Hard-Wire Mounting: Permanent Mount

Ratings/Features:

Listed for United States Class I, Divisions 1 & 2, Group D Class II, Divisions 1 & 2, Groups F & G Spark-Resistant Propeller Up To 3990 CFM Air Movement Rated for Hazardous Environments Made in the USA **Special Orders- Requirements** Contact us for special requirements **Toll Free:** 1-800-369-6671 **Intl:** 1-214-616-6180 **Fax:** 1-903-498-3364 **E-mail:** sales@larsonelectronics.com

Made in the USA

The EPF-HPSM-18-0.5HP from Larson Electronics is a high pressure, high volume explosion proof ventilation fan that operates on 115-230V AC voltage. This high volume explosion proof ventilation fan features an 18" diameter spark resistant cast aluminum blade that moves air at a rate of up to 3990 cubic feet per minute (CFM) for superior ventilation and air movement. The EPF-HPSM-18-0.5HP is powered by a fully enclosed and explosion proof 1/2 horsepower motor.



PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS PRODUCT

The EPF-HPSM-18-0.5HP explosion proof fan is rated for Class I Group D and Class II Groups F & G hazardous environments. The 18" diameter propeller on this explosion proof high pressure ventilation fan is constructed from cast aluminum to resist sparking further increasing the safety of the hazardous environment in which the fan is being utilized. This single phase explosion proof ventilation fan has a 1/2 horsepower fully enclosed motor that can spin the propeller at a rate of 1750 RPM.

Voltage: The EPF-HPSM-18-0.5HP explosion proof ventilation fan is multi-voltage capable and can operate on voltages ranging from 115-230V AC.

Wiring: The EPF-HPSM-18-0.5HP is a hard-wired ventilation fan that should be installed according to national, state and local electrical and mechanical codes. **Applications:** Class I Group D and Class II Groups F & G hazardous areas that require ventilation including but not limited to the following: clean rooms, marijuana extraction rooms, laboratory hoods, oil refineries, grain mills, chemical plants, welding shops, chemical storage areas and battery changing areas. At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message <u>sales@larsonelectronics.com</u> for more information about our custom options tailored to meet your specific industry needs.

Made in USA Quality

CFM Static Pressure (SP) Ratings

1. Fully enclosed explosion proof 1/2 HP motor.

- 2. Spark-resistant cast aluminum 18" diameter propeller.
- 3. Class I Group D and Class II Groups F & G rated.
- 4. Multi-voltage capable.
- 5. Moves up to 3990 cubic feet of air per minute.
- 6. Fully assembled and ready to install
- 2. 1/8" SP 3780 CFM 3. 1/4" SP - 3480 CFM 4. 3/8" SP - 3020 CFM
- 5. 1/2" SP 2250 CFM

0" SP - 3990 CFM



Frequently Asked Questions (FAQ)















www.LarsonElectronics.com Email: sales@LarsonElectronics.com Fax: 903.498.3364





Links (Click on the below items to view):

- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 3, Misc
- Dimensional Drawing 2D
- MSDS (Material Safety Data Sheet
- RoHS Certificate (Restriction of Hazardous Substances)
- SpecSheetRussian
- SpecSheetSpanish
- USA NEC Certificate (Commonly referred to as UL Certificate)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map