



Boost user productivity and enhance performance with fast A3 printing and copying. Save time and make office tasks more efficient with scan-to-email, digital sending and optional faxing, and a choice of paper-handling and finishing options.



HP LaserJet M9059  
Multifunction Printer

**A great choice for workgroups of 30 to 50 users in large and medium-sized businesses, who require fast (and extra fast), high volume, cost-effective printing and copying with digital sending, scanning, optional faxing, and professional finishing.**

**Simplify everyday office tasks and save valuable time.**

The EasySelect Control Panel provides an intuitive, consistent user experience across the HP lineup. Enjoy fast printing and copying at up to 50 ppm. Save time: integrate documents into workflows with scan-to-email and additional digital sending for easy conversion of documents from paper to electronic format. Add the HP LaserJet MFP Analog Fax Accessory 300<sup>1</sup> to send and receive documents with ease. Conserve paper with two-sided copying and scanning enabled by the dual-head colour scanner.

**Increase user productivity and improve performance.**

Produce complex documents with a range of finishing choices: 8-bin mailbox for easy sorting/collating, stacker for up to 3,000 sheets, stapler/stacker and multi-function finisher for creating booklets. Quickly capture high quality colour images at 600x600 dpi with the dual-head colour scanner. Boost productivity and save paper with two-sided printing, copying and scanning. Extend the MFP's capabilities by adding advanced document capture, job accounting, and security solutions.

**Count on this HP LaserJet MFP to deliver a consistently reliable experience.**

Get peace of mind with industry-renowned HP LaserJet reliability. Achieve consistent, trouble-free printing using the Original HP LaserJet print cartridge with Smart printing technology. Produce great-looking documents with 1200 dpi print quality. Easily order and manage supplies with HP SureSupply<sup>2</sup>. Speed up management processes with HP WebJetadmin for remote configuration and proactive fleet management. Experience reliable sharing in large workgroups with HP Jetdirect networking.

<sup>1</sup> Fax capability is optional; please purchase separately

<sup>2</sup> Programme features and availability may vary by country  
For more information, visit [www.hp.com/learn/suresupply](http://www.hp.com/learn/suresupply).



## Series at a glance



### HP LaserJet M9059 Multifunction Printer

- HP LaserJet M9059 MFP: print and copy speed of up to 50 ppm
- 1200 dpi effective output quality
- 600x600 dpi scan resolution
- 80 GB Hard Disk
- 394 MB RAM expandable up to 512 MB RAM
- 533 MHz processor
- Instant-on Technology
- third party connectivity via USB Host
- Gigabit Ethernet Connectivity
- standard input capacity of 3200-sheets with a 100-sheet multipurpose tray
- two 500-sheet input trays
- 2000-sheet input tray and 100-sheet automatic document feeder

## Recommended accessories



[J7972G](#)  
HP 1284B Parallel Card



[J8007G](#)  
HP Jetdirect 690n IPv6/IPSec  
802.11g Wireless Print  
Server



[C8091A](#)  
HP Staple Cartridge Refill



[C8092A](#)  
HP 5000-staple Cartridge



[C9153A](#)  
HP 220-volt User  
Maintenance Kit



[Q5693A](#)  
HP LaserJet MFP 8-bin  
Mailbox



[C8084A](#)



[C8085A](#)



[C8088B](#)



[Q3701A](#)



[Q7719A](#)



[J8019A](#)

HP LaserJet MFP 3000-sheet  
Stacker

HP LaserJet MFP 3000-sheet  
Stapler/Stacker

HP LaserJet MFP  
Multifunction Finisher

HP LaserJet MFP Analog Fax  
Accessory 300

HP 256MB 100-pin DDR  
DIMM

HP Secure High Performance  
EIO Hard Disk

## Operating and warranty specifications

<b>Operating environment</b>	Operating temperature: 15 to 32.5° C. Recommended operating temperature: 17.5 to 25° C. Operating humidity: 20 to 80% RH. Operating humidity recommended: 30 to 70% RH. Storage temperature: 0 to 35° C. Storage humidity: 15 to 90% RH. Noise level per ISO 9296: sound power: LwAd 7.5 B(A) (active), 5.6 B(A) (ready). Sound pressure: LpAm 58 dB(A) (active), 39 dB(A) (ready)
<b>Certifications</b>	CISPR 22: 2005/EN 55022: 2006 Class A, EN 61000-3-2: 2000, EN 61000-3-3: 1995, EN 55024: 1998, FCC Title 47 CFR, Part 15 Class A/ICES-003, Issue 4/GB9254-1998, GB17625.1-2003, EMC Directive 2004/108/EC and the Low Voltage Directive 2006/95/EC, and carries the CE-Marking accordingly. Regulatory standards: Argentina (TUV S Mark-Rs. 92/98/Ds. 1009/98), Australia (AS/NZ 3260), Canada (cULCAN/ CSA C22.2 No. 60950-00), China (GB4943), Czech Republic (CSN-IEC 60950-IEC 60825-1), Estonia (EEI-EN60950-IEC 60825-1), EU (CE Mark-Low Voltage Directive 2006/95/EC), Germany (TUV-EN60950-IEC 60825-1), Hungary (MEEI-IEC 60950-IEC 60825-1), Japan Radio Law, Lithuania (LS-IEC 60950-IEC 60825-1), Mexico (NOM NYCENOM 019 SCFI), Poland (B Mark-IEC 60950-IEC 60825-1), Russia (GOST-R50377), Slovakia (IEC 60950-IEC 60825-1), Slovenia (SQI-IEC 60950-EN60825-1), South Africa (IEC 60950-IEC 60825-1), USA (UL-UL 60950; FDA-21 CFR Chapter 1 Subchapter J for lasers); Class 1 Laser/LED Product. ENERGY STAR: No
<b>Warranty</b>	90 days parts-only warranty. Warranty and support options vary by product, country and local legal requirements.

## Ordering information



### HP LaserJet M9059 Multifunction Printer [\(CE800A\)](#)

HP LaserJet 9059 MFP, Euro and UK plug power cord, print cartridge, documentation CD, control panel overlay, two standard 500-sheet input trays, 100-sheet multi-purpose tray, 2000-sheet input tray, choice of output paper handling device, automatic duplexer accessory (pre-installed), HP Jetdirect Embedded Print Server, automatic document feeder (ADF). Printer must be ordered with one of the four available paper output accessories.

## Accessories, Supplies and Support

### Accessories

<a href="#">J7972G</a>	HP 1284B Parallel Card
<a href="#">C8091A</a>	HP Staple Cartridge Refill
<a href="#">C8092A</a>	HP 5000-staple Cartridge
<a href="#">C9153A</a>	HP 220-volt User Maintenance Kit
<a href="#">Q5693A</a>	HP LaserJet MFP 8-bin Mailbox
<a href="#">C8084A</a>	HP LaserJet MFP 3000-sheet Stacker
<a href="#">C8085A</a>	HP LaserJet MFP 3000-sheet Stapler/Stacker
<a href="#">C8088B</a>	HP LaserJet MFP Multifunction Finisher
<a href="#">Q3701A</a>	HP LaserJet MFP Analog Fax Accessory 300
<a href="#">Q7719A</a>	HP 256 MB 100-pin DDR DIMM
<a href="#">J8019A</a>	HP Secure High Performance EIO Hard Disk
<a href="#">J7989G</a>	HP High Performance Serial ATA Hard Disk
<a href="#">T1936AA</a>	HP MFP Digital Sending Software 4.0
<a href="#">J8018A</a>	HP Secure High Performance Hard Disk Drive

### Supplies

<a href="#">CE266C</a>	HP LaserJet CE266C Contract Black Print Cartridge
------------------------	---

### Connectivity

<a href="#">J8007G</a>	HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print Server
<a href="#">J7934G</a>	HP Jetdirect 620n Fast Ethernet Print Server

### Service & support

<a href="#">UP833E</a>	HP Care Pack, Next Business Day Hardware Support, 5 years
<a href="#">UP848E</a>	HP Care Pack, Next Business Day Hardware Support, 4 years
<a href="#">UP845E</a>	HP Care Pack, Next Business Day Hardware Support, 3 years
<a href="#">UP846E</a>	HP Care Pack, Next Business Day Hardware Support, 1 year
<a href="#">UP847PE</a>	HP Care Pack, Post Warranty Next Business Day Hardware Support, 1 year

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>

For workflow, device management and other solutions, please visit the Global Solutions catalog: [www.hp.com/go/gsc](http://www.hp.com/go/gsc)



# Technical specifications

<b>Print technology</b>	Monochrome Laser		
<b>Print speed</b>	A4black:Up to 50 ppm, color.A3:Up to 28 ppm. First page out black,<9.5 sec (from ready) All printed pages originate from the default tray of a HP LaserJet 9040/9050mfpwith a High-Capacity Input (HCI) Tray 4.		
<b>Processor</b>	533 MHz. MIPS 20KC Processor (Unity ASIC)		
<b>Memory</b>	384 MB. Expandable to 512 MB replacing 128 MB (DIMM Slot 2) with 256 MB. No open slot available. Hard Disk Capacity:Standard, 80 GB		
<b>Print</b>	Quality	Resolution Enhancement technology (REI)	
	Resolution	Black:HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi	
	Printer languages	HP PCL 6, HP PCL 5e, HP postscript level 3 emulation, direct PDF printing (v 1.3) with at least 128 MB memory enabled, XHTML-Print v0.95, HP PJI (Printer Job Language), PML (Printer Management Language); 80 internal scalable TrueType fonts; additional font solutions available	
	Economical printing	Economode (saves toner), immediate return to Power-safe mode after each print job due to Instant-on fuser technology (saves electricity). Standard automatic two-sided printing and N-up printing (saves paper)	
	Typefaces/fonts	80internal TrueType fonts scalable in HP PCL and HP Postscript level 3 emulation; additional font solutions available	
	Duty cycle (monthly,A4)	Up to 300000 pages	
	Recommended monthly page volume	15000 to 50000	
	Print margins (mm)	Top:2.1 mm. Left:3.2 mm. Right:3.7 mm. Bottom:2.9 mm	
	Maximum print area	303.4 x 468 mm	
<b>Fax</b>	Modem speed	33.6 Kbps (with optional analog fax accessory)	
	Fax memory	Dependent upon available disk space	
	Fax resolution	Standard:300 x 300 dpi (with optional analog fax accessory). Superfine:300 x 300 dpi (with optional analog fax accessory). Photo:200 x 100 dpi (with optional analog fax accessory)	
	Quick dialing	Up to 100	
<b>Digital sending</b>	File formats	PDF, JPEG, TIFF,MTIFF	
	Features	Standard:Scan to e-mail, Desktop folder, Network folder. LDAP addressing. User Authentication: PIN, LDAP/Active Directory with Kerberos. Optional:Send to LAN Fax, Internet Fax, printer,application, FTP,workflow, OCR. Advanced user authentication solutions.	
<b>Scan</b>	Type	Flatbed,ADF. Colour scanning:Yes	
	Scan resolution	Optical:Up to 600 dpi. Enhanced:Up to 600 dpi	
	Bit depth	30-bit	
	Grey scale levels	256	
	Scannable area	Maximum media size:27.9 x 43.2 cm	
	Margins for scanned items	Left:4.2 mm (A4). Top:4.2 mm (A4). Right:4.2 mm (A4). Bottom:4.2 mm (A4)	
<b>Copy</b>	Copy speed	Up to 50 cpm	
	Copy resolution	Up to 600 x 600 dpi	
	Multiple copies	Up to 999	
	Reduce/enlarge	25 to 400%	
<b>Media handling</b>	<b>Input:</b>	<b>Capacity</b>	<b>Weight</b>
	Tray 1	sheets: 100, envelopes: 10	64 to 227 g/m <sup>2</sup>
	Tray 2	sheets: 500	64 to 199 g/m <sup>2</sup>
	Tray 3	sheets: 500	64 to 199 g/m <sup>2</sup>
	ADF		
	<b>Output:</b>	Sheets: Up to 3000 (with stacker or stapler/stacker). Envelopes: Up to 10	
	Duplex printing:Automatic (standard)		
<b>Media types</b>	Paper (bond, colour, letterhead, plain, preprinted, prepunched, recycled, rough), labels, cardstock, transparencies		
<b>Interface and connectivity</b>	Hi-Speed USB 2.0, HP Jetdirect Gigabit Ethernet Embedded Print Server, 1 open EIO slot, Jetlink connection for paper handling device, host USB port (compatible with USB 2.0 specifications) for additional functionality, 1 Foreign Interface Harness (FIH). Optional:HP external and internal Jetdirect Print Servers		
<b>Operating systems compatibility</b>	Microsoft® Windows® XP Home, XP Professional; Windows Vista® Ready; OS/2 v3.0 or higher; Mac OS X v10.2.8, v10.3, v10.4 or higher; Linux; AutoCAD. Current printer drivers and software for all supported operating systems are available at <a href="http://www.hp.com/support">http://www.hp.com/support</a> . Depending on the configuration of Windows-driven computers, the installation program for the printer software automatically checks the computer for Internet access to obtain the latest software		
<b>Network operating systems compatibility</b>	Microsoft® Windows® Server 2003, XP, 2003 64-bit, XP 64-bit; Windows Vista®, Windows Vista® 64-bit (for Microsoft® IPv6 compatible with Microsoft® Windows® 2003, XP, and Windows Vista®); Novell® 5.1 and higher Mac OS X v10.2, v10.3, v10.4 and higher; RED HAT Linux 7.x and higher, SUSE Linux 8.x and higher; HP-UX 10.20, 11.x, 11.i; Solaris® 2.5 and higher (SPARC® systems only); IBM® AIX 3.2.5 and higher; MPE-iX; Citrix® MetaFrame Server; Windows® Terminal Services		
<b>Minimum system requirements</b>	Microsoft® Windows® 2000: 300 MHz processor, 64 MB RAM; Microsoft® Windows® XP Home and XP Professional: 233 MHz processor, 64 MB RAM; 180 MB of free hard disk space for Windows®, CD-ROM drive or Internet connection. Mac OS X v10.2.8, v10.3, v10.4 or higher with 128 MB RAM, CD-ROM, 160 MB of free hard disk space. For Mac OS v10.4 and higher, PowerPC and Intel® Core Processor Macs are supported		
<b>Control panel</b>	3 light-emitting device (LED) indicator lights, 10-key numeric pad, graphical touchscreen display (193 x 72 mm)		
<b>Power</b>	Requirements:Input voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consumption:1022 watts (active/printing), 1030 watts (copy), 331 watts (ready), 244 watts (sleep), 2 watts (off); Typical Electricity Consumption (TEC): 18.9 kWh/Week. Power reported is highest values measured for printing and copying using all standard voltages.		
<b>Dimensions (w x d x h)</b>	Out of package:With 8-bin mailbox: 1092 x 838 x 1219 mm, with stacker: 1168 x 787 by 1194 mm, with stapler/stacker: 1168 x 787 x 1194 mm, with multifunction finisher: 1295 x 787 x 1194 mm. Packaged:978 x 914 x 1448 mm (without finishing output solution)		
<b>Weight</b>	Out of package:143kg (without finishing output solution). Packaged:181.4 kg (without finishing output solution)		
<b>Printer management</b>	Embedded Web server, HP Web Jetadmin		
<b>Security management</b>	SNMPv3, SSL/TLS, 802.1X authentication (EAP-PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication. Support for WJA-10 IPsec Configuration using IPsec Plug-in		

<http://www.hp.com/uk>



© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



Published in EMEA 07/09 4AA2-5257EEE