

## MIL-F-16377/10

### **300BP Series**

Standard Mount Flush Mount

PRODUCT SPECIFICATION

# **Overhead Lighting**

## **300BP Series**

The 300BP Series is a watertight four lamp fluorescent luminaire designed for general purpose naval lighting in wet maritime environments.

#### Mounting

Mounts to ceiling surfaces or flush within them.

#### **Light Source**

Four 8W T5 lamps, powered by four 120V 60Hz ballasts.

#### Lens

A specular aluminum reflector with a clear and white prismatic ¼" masked acrylic lens provides directional focusing

#### Housing

Constructed from marine grade aluminum.

#### Finish

Polyester powder-coated after phosphate pretreatment for superior adhesion and corrosion resistance.

Cable

Supplied with 10 ft. of LSTHOF-3 cable.

#### Standard Mounting

Overall Dimensions: 29" X 7-5/8" X 3-1/2". Net weight: 12 lbs. 0 oz. maximum. Approximate shipping weight for package of six: 81 lbs.

#### Flush Mounting

Overall Dimensions: 31-5/16" X 9-15/16" X 3-1/2". Net weight: 13 lbs. 13 oz. maximum. Approximate shipping weight for package of six: 93 lbs.

#### Certifications

First Article Qualified.

\*Contact factory for more specified options.



M16377/10-145.4 NSN 6210-00-548-0227 Standard Mount



M16377/10-145.5 NSN 6210-01-149-2193 Flush Mount



MIL-SPEC SLANT M16377 / 10

SYMBOL one

three

two

V Amber	<b>Symbol</b> 145.4 145.5	<b>Mounting</b> Standard Mount Flush Mount	one F two B R y	Mounting Flush mount Lamp Filter Tube Blue Red Amber	three S SS	Switch option(s) One DPST switch Two DPST switches
---------	---------------------------------	--	--------------------------------	---	------------------	--

Replacement Item	L.C. Doane Part #	Symbol	NSN
Ballast	P-337-S	M16377/45-001	6250-00-295-2735
8W T5 lamps	P-1-S	MS15588-3	6240-00-299-5546
White Diffusing lens	B-1727-L	M16377/11-001	6210-00-399-7035
Clear/White Prismatic lens	B-1725-NS	M16377/10-002	6210-01-309-2321
DPST Toggle Switch	P-573-S	MS16569-1	5930-00-719-9659
Shockmount	B-1591-BS	M16377/41-009	6210-00-973-1747

Modifications are available to meet custom requirements. Specifications and dimensions are subject to change without notice.