

HP Retail Monitors



Make a modern impression on your customers

Deliver an enhanced experience to both your customers and store associates with the eye-catching family of HP Retail Monitors that come in a variety of sizes and both touch and non-touch options. Store associates will enjoy the familiar, user-friendly technology and customers will benefit from the display of useful product and promotional content as well as the ability to easily enter loyalty information and other preferences.



Wide aspect for a wide range of apps

Thin sleek, virtually borderless, widescreen design and high resolution allow these displays to complement your environment. With your choice of screen size from 10.1 to 15.6 diagonal inches (25.6 to 39.6 cm), mounting options, and touch or non-touch, you gain the flexibility you need to meet both your customer's and associate's needs.

Durability for high-traffic areas

Place the sturdy, dust-resistant, easy-to-clean displays in a range of high-traffic areas; attached to one of HP's platforms as a customer-facing display or used as a stand-alone display.

Easy Interactivity

The Projective Capacitive ten-point touch technology provides a familiar, intuitive experience that responds to dry or wet fingers, and beep-on-touch audibly confirms successful touchscreen interaction.

Backed by world-class support specialists.

Rest assured that your IT investment is supported by a three-year standard limited warranty and optional HP Care Packs.¹


HP Retail Monitors Specifications

Specification	HP L7010t 10.1 in Retail Touch Monitor (T6N30AA)	HP L7014 14-in Retail Monitor (T6N31AA)	HP L7014t 14-in Retail Touch Monitor (T6N32AA)	HP L7016t 15.6-in Retail Touch Monitor (V1X13AA)
Native Resolution	1280x800 @60Hz	1366x768 @60Hz	1366x768 @60Hz	1366 x 768 @ 60Hz
Response Time	30 ms on/off (typ.)	16 ms on/off (typ.)	16 ms on/off (typ.)	8 ms on/off (typ.)
Panel Active Area	216.96mm x 135.6mm	309.4mm x 173.95mm	309.4mm x 173.95mm	216.96mm x 135.6mm
Viewing Angle	Horizontal: 160 degrees; Vertical: 160 degrees (CR<10 typ.)	Horizontal: 90 degrees; Vertical: 60 degrees (CR<10 typ.)	Horizontal: 90 degrees; Vertical: 60 degrees (CR<10 typ.)	Horizontal: 170 degrees; Vertical: 160 degrees (CR<10 typ.)
Display Type	ADS w/LED backlight	TN w/LED backlight	TN w/LED backlight	TN w/LED backlight
Brightness	220 nits (with glass)	200 nits (with glass)	200 nits (with glass)	360 nits (with glass)
Tilt adjustability	-5 to +135 degrees	-5 to +135 degrees	-5 to +135 degrees	-5 to +135 degrees
Interface / Connection	1x DisplayPort 1.2, HDCP Support	1x DisplayPort 1.2, HDCP Support	1x DisplayPort 1.2, HDCP Support	1x DisplayPort 1.2, HDCP Support
Touch Panel Type	Projected Capacitive Touch Panel (up to 10 touch points)	N/A	Projected Capacitive Touch, Panel, > 10 points	Projected Capacitive Touch Panel, > 10 points
Touch Positional Accuracy	±1.0 mm for all areas of touchable active area	N/A	±1.0 mm for all areas of touchable active area	Within 1.0mm each target & 10% Jitter limit on moving
Touch Resolution Accuracy	4096 x 4096	N/A	4096 x 4096	25ppi (Min.) Based on WIN8 definition ppi (Pixel per inch)
Dimensions (WxDxH)	245.9mm x 41.5mm x 172.2mm (9.7 inches x 1.7inches x 6.8 inches), unpacked without stand	339.8mm x 41.5mm x 218mm (13.4in x 1.7in x 8.6in), unpacked without stand	339.8mm x 41.5mm x 218mm (13.4 in x 1.7 in x 8.6 in), unpacked without stand	397.3mm x 45mm x 251.4mm (15.6in x 1.8in x 9.9 in) unpacked without stand
Weight	1.15kg (2.54lbs), unpacked without stand	1.68kg (3.71lb), unpacked without stand	1.70kg (3.76lbs), unpacked without stand	3.0kg (6.61lbs), unpacked without stand
Option kit Contents	HP Retail Display Head, Setup poster, and Documentation CD.			
Service and Warranty	Your HP Peripheral Limited Warranty is a three (3) year advanced exchange parts replacement warranty.			

Configuration Options

HP 15.6-in (39.6cm) Retail Touch Monitor


Mounted to an HP RP5 Retail System as CFD.



Requires:


HP 700mm Cable Kit for CFD on RP9 (V7563AA)

Connected to an HP Retail System without a 12 V powered USB port.



HP 300cm DP and USB B to A Cable for L7016t, L7014t, L7010t (V4P96AA)
 HP Compact Stand (W0Q45AA)
 45W Power Adapter (H6Y88AA)


Connected to an HP RP5 Retail System with a 12 V powered USB port.



HP 300cm DP and USB Power Y Cable for L7010t, L7014t, L7016t (V4P94AA)
 HP Monitor Stand for L7016t (W0Q45AA)

HP 14-in (35.5cm) Retail Touch Monitor


Mounted to an HP Retail System as CFD.



Requires:


HP 700mm Cable Kit for CFD on RP9 (V7563AA)

Connected to an HP RP5 Retail System with a 12 V powered USB port.



HP 300cm DP and USB Power Y Cable for L7010t, L7014t, L7016t (V4P94AA)
 HP compact Stand (T6N33AA)

Connected to an HP Retail System without a 12 V powered USB port.




HP 300cm DP and USB B to A Cable for L7016t, L7014t, L7010t (V4P96AA)
 HP Compact Stand (T6N33AA)
 HP 45 W Power Adapter (H6Y88AA)


Configuration Options cont.

HP 14-in (35.5cm) Retail Monitor


Mounted to an HP Retail System as CFD.



Connected to an HP RP5 Retail System with a 12 V powered USB port.



Connected to an HP Retail System or PC without a 12 V powered USB port.



Requires:

HP 700mm Cable Kit for CFD on RP9 (V7563AA)

HP 300cm DP and USB Power Cable for L7014

(V4P95AA)

HP Monitor Stand for L7010t, L7014, L7014t (T6N33AA)


HP 300cm DisplayPort Cable for L7014 (V4P97AA)

HP Monitor Stand for L7010t, L7014, L7014t (T6N33AA)


HP 45 W Power Adapter (H6Y88AA)

HP L7010t 10.1 (25.6cm) in Retail Touch Monitor


Mounted to an HP RP9 Retail System as CFD with a 12 V powered USB port.



Connected to an HP RP5 Retail System with a 12 V powered USB port.



Connected to an HP Retail System or PC without a 12 V powered USB port.



Requires:

HP 700mm Cable Kit for CFD on RP9 (V7563AA)

HP 300cm DP and USB Power Y Cable for L7010t,

L7014t, L7016t (V4P94AA)

HP Monitor Stand for L7010t, L7014, L7014t (T6N33AA)









HP 300cm DisplayPort and USB B to A Cable for L7016t,

L7014t, L7010t (V4P96AA)

HP Monitor Stand for L7010t, L7014, L7014t (T6N33AA)

HP 45 W Power Adapter (H6Y88AA)

Recommended Options and Accessories

<p>HP Monitor Stand for L7010t, L7014, L7014t</p>		<p>Use the fixed-height stand to place your display in standalone configurations. Find a comfortable viewing position with adjustable tilt of -5° to +180°. Product Number: T6N33AA</p>
<p>HP Monitor Stand for L7016</p>		<p>Use the fixed-height stand to place your display in standalone configurations. Find a comfortable viewing position with adjustable tilt of -5° to +180°. Product Number: W0Q45AA</p>
<p>HP 700mm Cable Kit for CFD on RP9</p>		<p>Use the kit to attach your HP L7010t, L7014, L7014t, or L7016t Display to an HP RP9 Retail System as a customer-facing display. Product Number: V7563AA</p>
<p>HP 300cm DP and USB Power Y Cable for L7010t, L7014t, L7016t</p>		<p>Use the cable to attach your HP L7010t, L7014t, or L7016t Display to an HP RP9 or HP RP5 Retail System through the USB Power connector in a standalone configuration. Product Number: V4P94AA</p>
<p>HP 300cm DP and USB Power Cable for L7014</p>		<p>Use the cable to attach your HP L7014 Display to an HP RP9 or HP RP5 Retail System through the USB Power connector in a standalone configuration. Product Number: V4P95AA</p>
<p>HP 300cm DP and USB B to A Cable for L7016t, L7014t, L7010t</p>		<p>Use the cable to attach your HP L7010t, L7014t, or L7016t to an HP RP5 Retail System without the 12v USB connector, HP Desktop Mini, or other desktop PC in a standalone configuration. The HP 45w Smart AC Adapter, part number H6Y88AA, is required to power the monitor. Product Number: V4P96AA</p>
<p>HP 300cm DP Cable for L7014</p>		<p>Use the cable to attach your HP L7014 to an HP RP5 Retail System without the 12v USB connector, HP Desktop Mini, or other desktop PC in a standalone configuration. The HP 45w Smart AC Adapter, part number H6Y88AA, is required to power the monitor. Product Number: V4P97AA</p>
<p>HP 45w Smart AC Adapter</p>		<p>Use the cable to power your HP L7010t, L7014, L7014t, or L7016t in a standalone monitor configuration when attached to your HP RP5 Retail System without the 12v USB power connector, an HP Desktop Mini, or other desktop PC. Product Number: H6Y88AA</p>

1. Sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP Services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Learn more at hp.com/go/POS

To learn more about the HP RP9 Retail System visit hp.com/us/en/retail-solutions/all-in-one-retail-systems



Technology at Work.®

JANAM



XT2 Rugged Touch Computer

Ultra-Rugged. Ultra-Compact.

With more focus on customer satisfaction than ever before, organizations are increasing their technology investments to automate workflows, improve workforce productivity and ultimately enhance customer service. Mobile workers are seeking devices that enable better communication and more collaboration to shift from a reactive to a proactive service model.

As technologies evolve, customers no longer need to compromise style and size for functionality and reliability. Janam's Android™-powered XT2 touch computer is the lightest and most rugged device in its class and is equipped with the latest technological advancements to help mobile workers do their jobs more effectively and efficiently, all with a style that is sleek and cutting-edge.

Smaller, Lighter and Faster.

Weighing only 10 ounces and featuring a brilliant 5-inch touch screen strengthened with Corning Gorilla® Glass 3, the XT2 provides maximum durability and an optimized balance between screen viewability and device weight and size. As the only rugged mobile computer in its class to run Android 5, the XT2 is certified to support all Google APIs including Google Play and Google Maps, enabling access to applications that provide even greater visibility and access to business-critical information.

Offering 802.11a/b/g/n, Bluetooth 4.0 and 4G LTE connectivity, the XT2 is designed to help mobile workers save time and make better informed decisions. Equipped with Zebra's slim-format SE4710 scan engine, the XT2 can quickly and accurately capture barcode data from more than 2 feet away. NFC and RFID reading capabilities enable the XT2 to improve inventory management and traceability operations. It's technology at work™



The right features. The right price.

- » Pocket-sized powerhouse weighing only 10 ounces
- » Android 5 operating system
- » Brilliant 5-inch color display with Corning Gorilla Glass 3
- » High-performance 1D and 2D barcode scanning
- » RFID and NFC reading capabilities
- » 4G LTE WWAN
- » Qualcomm quad-core CPU
- » Multiple 5'/1.5m drops to concrete per MIL-STD 810G
- » Sealed to IP67 standards against dust and immersion in up to 3 feet of water
- » 8.0MP/2.0MP front- and rear-facing color auto-focus cameras
- » Dual-band 802.11a/b/g/n Wi-Fi and Bluetooth 4.0 connectivity
- » High-sensitivity GPS
- » 3000mAh Li-ion battery

XT2 Specifications



TECHNICAL

Operating System	Android™ 5.x Lollipop
Processor	Quad-core Qualcomm MSM8916 CPU @1.2GHz
Memory	1GB/8GB (WLAN) or 2GB/16GB (WWAN)
Expansion	User-accessible microSD card slot with SD and SDHC support
Power	3000mAh rechargeable Li-ion battery (4000mAh optional)

PHYSICAL

Dimensions	6.1" L x 3.2" W x .9" D / 155mm L x 83mm W x 24mm D
Weight	9.8oz / 279g including battery; 10oz / 293g including battery and MSR
Display	5.0" High Definition (720x1280) WXGA with Corning® Gorilla® Glass 3; exceptionally bright, outdoor viewable; anti-raindrop
Touch Panel	Capacitive touch screen

ENVIRONMENTAL

Operating Temperature	-4° to 140°F / -20° to 60° C
Storage Temperature	-40° to 158°F / -40° to 70° C
Humidity	Non-condensing, 95%
Drop	Multiple 5ft / 1.5m drops to concrete on all sides across a wide temperature range per MIL-STD 810G
Water & Dust	IP67
Vibration	Amplitude 2MM from 10Hz to 33Hz in all three axes, 1 hour per axis
Electro Static Discharge (ESD)	+/- 15kV air; +/- 8kV contact

INTERFACE FEATURES

Audio	3.5mm headset jack; speaker; microphone
Alerts	Vibration; LED indicators
Connectors	USB 2.0
LED Indicators	two dual-color LED indicators
External Buttons	4 hard keys (home; menu; back button; user-programmable)

DATA CAPTURE

Imager	Zebra SE4710 1D/2D imager
Magnetic Stripe Reader	ANSI/ISO-7813 full track; AES-128 CBC mode; DUKPT support
RFID/NFC	Reads ISO14443 Type A; ISO14443 Type B; MIFARE UltraLight; MIFARE UltraLight C; MIFARE 1k/4k/Plus; MIFARE DESFire; MIFARE DESFire EV1; NFC in the 13.56 MH range

WIRELESS COMMUNICATION

WWAN	EDGE/GPRS/GSM; WCDMA; LTE
WLAN	Dual-band 802.11a/b/g/n; Cisco certified
Security	Authentication: EAP (TLS, PEAP-MSCHAPv2, PEAP-GTC, PEAP-TLS, TTLS, EAP-FAST, LEAP) Encryption: WPA2; WPA (TKIP); WEP
WPAN	Bluetooth v4.0

MOBILE APPURTENANCES

Motion Sensor	Gyroscope; Accelerometer; Ambient light sensor; Proximity sensor
GPS	Qualcomm® IZat™: Gen 8 support for three bands concurrently (GPS, BeiDou and GLONASS or Galileo)
Camera	8.0MP color rear-facing autofocus camera with user-controllable LED flash and 2.0MP front-facing camera

ACCESSORIES

Single Slot USB/Charging Cradle Kit
Four Slot Charging Cradle Kit
USB Syncing/charging cable with locking screws
Charging adapter
Extended battery kit
Holster

SAFETY/REGULATORY

Safety	CSA C22.2 No.60950-1-03; EMC; RF; SAR; LED
Radio	FCC; IC; GCF & PTCRB; CE
Environmental	RoHS and WEEE compliant

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684