

NEW Hydraulic Chucks

- **PIONEER** Hydraulic Chucks meet industry standards
- 0.0001" or less run-out providing premium performance in drilling and reaming applications.
- Positive Locking System
- Pre-Balanced to G2.5 @ 25,000 RPM or >1gmm
- Coolant thru the center
- Superior Vibration Dampening
- Works with **PIONEER** HC Sealed and MC Std Collets



Shank	Part Number	ID Size	Proj	Min. Tool Enters	Max Tool Enters
CAT40	CAT40-HC050-0254	0.5000	2.54	1.42	1.81
	CAT40-HC075-0254	0.7500	2.54	1.61	2.00
CAT40 Dual Contact	CAT40-HC075-0254-B	0.7500	2.54	1.61	2.00
CAT50	CAT50-HC075-0319	0.7500	3.19	1.61	2.00
	CAT50-HC125-0319	1.2500	3.19	2.00	2.40
HSK063A	HSK063A-HC050-0315	0.5000	3.15	1.42	1.81
	HSK063A-HC075-0315	0.7500	3.15	1.61	2.00



Sealed Hydraulic Collets

- 0.0001" TIR
- Sealed for Coolant Thru
- Interchangeable with industry standard collets

Coming Soon!

ID Size	HC075	HC125
0.0125	HC075-0125	
0.1875	HC075-0187	
0.2500	HC075-0250	HC125-0250
0.3750	HC075-0375	HC125-0375
0.5000	HC075-0500	HC125-0500
0.6250	HC075-0625	HC125-0625
0.7500		HC125-0750
0.8750		HC125-0875
1.0000		HC125-1000
6mm	HC075-M060	
8mm	HC075-M080	
10mm	HC075-M100	HC125-M100
12mm	HC075-M120	HC125-M120
14mm	HC075-M140	HC125-M140
16mm	HC075-M160	HC125-M160
18mm		HC125-M180
20mm		HC125-M200
25mm		HC125-M250

Please see PioneerNA.com for Hydraulic Chuck operation manual.
Please contact customer service for pricing and availability.
sales@PioneerNA.com | 847-593-6000



Pioneer North America

641 Fargo Ave, Elk Grove Village, IL 60007
847-593-6000 | SALES@PioneerNA.com
www.PioneerNA.com