

Frequency	50Hz
-----------	------

Output

Grip cable retention	Yes
----------------------	-----

Outlets	(8) IEC-320-C13
---------	-----------------



Outlet Control	No
----------------	----

Protection & Filtering

Spike/Surge Suppression	None
-------------------------	------

EMI/RFI Filter	None
----------------	------

Control & Interface

Operating Temperature	60 Degrees C
-----------------------	--------------

Serial Interface	None
------------------	------

Environmental Interface	No
-------------------------	----

Ethernet Interface	No
--------------------	----

Voltage Monitoring	no
--------------------	----

Environmental & Approval Standards

Approvals	CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011 Safety - Part 1: General Requirements, IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1 EN 55022:2010 Radio Disturbance characteristics - Limits and methods of measurement. EN 55024:2010 Immunity characteristics - Limits and methods of measurement.
-----------	--

Electromagnetic compatibility	EN 61000-6-2:2005 Part 6-2: Generic standards - Immunity for industrial environments EN 61000-6-4:2007+A1:2011 Part 6-4: Generic standards - Emission standard for industrial environments
-------------------------------	--

Environmental	RoHS Directive – 2011/65/EU, EN 50581 : 2012, REACH Regulation (CE No. 1907/2006), WEEE directive 2012/19/EU, PEP ecopassport (Basic ePDUs) Packaging: 100% recycled, 100% recyclable: no plastic, no metal, no foam.
---------------	---

Manufacturing Plant	ISO 9001:2008 / ISO 14001:2004
---------------------	--------------------------------

Warranty

Standard warranty	2 years
-------------------	---------

[Privacy Policy](#)
[Terms & Conditions](#)
[Copyright](#)

© 2017 Eaton
 All Rights Reserved