





→ See all Eaton 9PX Documentation

→ See all Eaton 9PX models



9PX5KiBP

Eaton 9PX 5000i HotSwap

General	
Topology	On-line double conversion with PFC (Power Factor Correction) system
Configuration	Rack/Tower
Part Number	9PX5KiBP
Rating (VA/Watts)	5000/4500
Dimensions (H x W x D, mm)	440 x 130 x 685
Weight (kg)	48
Warranty	2 years warranty

Electrical Input

Connection Hardwired - see manual for terminal block layout



Input Voltage Range	76-276V without derating (up to 100–276V with derating)	
Nominal Voltage	200/208/220/230/240V	
Frequency	50/60 Hz autoselection	
Frequency Range	40-70 Hz	
Short Circuit Current	90 A	
THDI	<5%	

Elec	rical		arit.
LICU	uicai	Out	Juι

Voltages 200/208/220/230/240V +/- 1%

Voltage THD < 2%

Outlets (3) IEC-320-C13 Hardwired - see manual for terminal block layout (2) IEC-320-C19








Overload Capacity	102-110%: 120s, 110-125%: 60s, 125-150%: 10s, >150%: 500ms	
Efficiency (Normal Mode)	Up to 94% in Online mode, 98% in Hi-Efficiency mode	
Output Frequency	50/60 Hz autoselect, frequency converter as standard	

3:1

Battery



Battery Management ABM® and Temperature compensated charging method (user selectable), automatic battery test, deep discharge protection, automatic recognition of external battery units.

Extended Battery Capability EBM (3U)

Communications	
User Interface	Multilingual graphical LCD display
Communication Ports	1 USB port, 1 RS232 serial port (USB and RS232 ports cannot be used simultaneously), 4 dry contacts (DB9), 1 mini terminal block for remote On/Off and 1 for remote power Off, 1 DB15 for parallel operation
Communication Slot	1 slot for Network-MS card, ModBus-MS or Relay-MS cards.

Environmental & Standards		
Audible Noise	<45dB	
Operating Temperature	0 to 40°C continuous	
Safety markings	IEC/EN 62040-1, UL 1778, CSA 22.2	
EMC Markings	IEC/EN 62040 -2 , FCC Class A, IEC/EN 62040-3 (Performance)	
Approvals	CE, CB report (TUV), UL	

Options

Parallel/Redundant Operation	
Option	Part Number
Eaton 9PX ModularEasy 6000i	9PXMEZ6Ki
Batteries	
Option	Part Number
Faton 9PX FRM 180V	9PXFRM180

In the interests of continuous product improvement all specifications are subject to change without notice.

Privacy Policy
Terms & Conditions
Copyright

© 2017 Eaton All Rights Reserved