

## Component / VGA Video and Audio to HDMI Converter - PC to HDMI - 1920x1200

Product ID: VGA2HD2



The VGA2HD2 Component/VGA to HDMI® Video Converter offers seamless conversion from an analog VGA or Component video source, such as a Computer, DVR, or DVD player, to a digital HDMI® output.

The converter helps reduce equipment costs by eliminating the need to upgrade individual analog components, by offering a solution that converts an analog video source (RGB/YPbPr) for use with a digital HDMI® display.

This versatile analog-digital converter not only supports resolutions up to 1920x1200 including high-definition 1080p, but also enables you to convert and combine an analog RCA audio source into its digital HDMI® output signal.

The VGA2HD2 Component/VGA to HDMI converter is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Converting an analog video output signal from a computer for use with an HDTV
- Removing the clutter at the back of a monitor/display, by replacing multiple cables with a single HDMI® cable
- Connect a laptop computer to a boardroom projector or display, for on-screen presentations

### Features

- Supports YPbPr (component input) and HD15 PC VGA input
- Supports input resolutions up to 1080p (HDTV) and 1920 x 1200 (PC)
- Includes Component to VGA adapter cable

<b>Hardware</b>	Warranty	2 Years
	Active or Passive Adapter	Active
	Audio	Yes
	AV Input	Component YCbCr Audio RCA VGA
	AV Output	HDMI
<b>Performance</b>	Supported Resolutions	Maximum of 1080p for HD Input, and 1920x1200 for PC input
	Wide Screen Supported	Yes
<b>Connector(s)</b>	Connector A	1 - Component Video (3 x RCA) Male Input 1 - Stereo Audio (2 x RCA) Female Input 1 - VGA (15 pin, High Density D-Sub) Female Input
	Connector B	1 - HDMI (19 pin) Female Output
<b>Special Notes / Requirements</b>	System and Cable Requirements	HDMI® M/M Cable (Destination) VGA M/M Cable (If using VGA as source)
<b>Power</b>	Center Tip Polarity	Positive
	Input Current	0.3A
	Input Voltage	100 ~ 240 AC
	Output Current	1.2A
	Output Voltage	5 DC
	Plug Type	N
	Power Consumption (In Watts)	6
	Power Source	AC Adapter Included
<b>Environmental</b>	Humidity	20~90% RH
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-20°C to 60°C (4°F to 140°F)
<b>Physical Characteristics</b>	Color	Black
	Product Height	30 mm [1.2 in]
	Product Length	110 mm [4.3 in]
	Product Weight	188 g [6.6 oz]
	Product Width	78 mm [3.1 in]

<b>Packaging Information</b>	Shipping (Package) Weight	540 g [19.1 oz]
<b>What's in the Box</b>	Included in Package	1 - PC/HD to HDMI Converter with Audio 1 - VGA to Component (RCA) Breakout Cable 1 - Universal Power Adapter (US/UK/EU/AUS)

Product appearance and specifications are subject to change without notice.