

DIMM DDR2 PC2-6400 800 MHz



Features

- ▶ Fully PC-6400 Compliant
- ▶ Backwards compatible with PC2-4300 (DDR2 533) PC2-5300 (DDR2 667)
- ▶ JEDEC-Standard 240-pin Dual Inline Memory Module (DIMM)
- ▶ Unbuffered
- ▶ Cas Latency 5
- ▶ Power Supply: 1.8V ± 0.2V
- ▶ 64ms, 8k refresh
- ▶ Serial Presence Detect (SPD)
- ▶ Pure Power and Ground Planes
- ▶ Gold PCB connector

Ordering Information

	DENSITY	REFERENCE	EAN
Optima	1GB	DIMM101GBN/6400/2CBX	3536401460596
Optima	2GB	DIMM102GBN/6400/2CBX	3536401460602
Optima	Kit 2GB (2x1GB)	KCDIMM2GBN/6400/2-BX	3536401002345
Optima	Kit 4GB (2x2GB)	KCDIMM4GBN/6400/2-BX	3536401002475
Premium	1GB	D1GBN08Q800J-SB	3536401462347
Premium	2GB	D2GBN16Q800J-SB	3536401461869
Premium	Kit 2GB (2x1GB)	KD2GBN08Q800J-SB	3536401002574
Premium	Kit 4GB (2x2GB)	KD4GBN16Q800J-SB	3536401002444
Premium	Kit 8GB (4x2GB)	KD8GBN16Q800J-SB	3536401002611

Some of our capacities are also available in Premium packagings for distribution and integration purposes. Premium range modules are supplied without cooling kits. For more informations, please contact us.



Optima packaging



Premium packaging



Not sure of your memory needs ?

Try our online configurator !

PNY.EU



Product and specifications discussed here in are for evaluation and reference purpose only and are subject to change by PNY Technologies without notice.

For more information, visit : WWW.PNY.EU