







System Specification	WorkCentre 3335	WorkCentre 3345
One-Sided Speed		
8.5 x 11 in.	Up to 35 ppm	Up to 42 ppm
A4 / 210 x 297 mm	Up to 33 ppm	Up to 40 ppm
8.5 x 14 in. / 216 x 356 mm	Up to 28 ppm	Up to 34 ppm
Two-Sided Speed		
8.5 x 11 in.	Up to 17 ppm	Up to 21 ppm
A4 / 210 x 297 mm	Up to 16 ppm	Up to 20 ppm
8.5 x 14 in. / 216 x 356 mm	Up to 14 ppm	Up to 17 ppm
Monthly Duty Cycle <sup>1</sup>	Up to 50,000 pages / month	Up to 80,000 pages / month
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 4,000 pages	Up to 6,000 pages
Processor	1 GHz	
Memory	1.5 GB	
Connectivity	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi	
Paper Handling	WorkCentre 3335	WorkCentre 3345
Document Feeder		
Capacity <sup>3</sup>	Automatic Document Feeder (ADF): 50 sheets	Reversing Automatic Document Feeder (RADF): 50 sheets
Sizes	Custom Sizes: 5.6 x 5.8 in. to 8.5 x 14 in. / 142 x 148 mm to 216 x 356 mm	1
Weights	16 lb. to 28 lb. bond / 60 to 105 gsm	12.5 lb. to 28 lb. bond / 50 to 105 gsm
Bypass Tray		
Capacity <sup>3</sup>	50 sheets	50 sheets
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm	
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm	
Media Types	Archive Bond Card Stock Custom Envelopes Heavyweight Labels Lightweight Plain Preprinted Recycled Transparencies	

Tray 1	33373343 Water director Frinter	
Capacity <sup>3</sup>	250 sheets	
Sizes	Custom Sizes 3.9 x 5.8 in. to 8.5 x 14 in. / 99 x 147 mm to 216 x 356 mm	
Weights		
Media Types	16 lb. bond to 43 lb. bond / 60 to 163 gsm  Archive Bond Card Stock Heavyweight Lightweight Plain Recycled	
Additional Tray		
Capacity <sup>3</sup>	550 sheets	
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm	
Weights	16 lb. to 43 lb. bond / 60 to 163 gsm	
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled	
Total Capacity		
Device Standard Capacity <sup>3</sup>	300 sheets	
Device Total Capacity <sup>3</sup>	850 sheets	
Paper Output		
Output Capacity <sup>3</sup>	150 sheets	
Automatic 2-Sided	Standard	
Device Specification	WorkCentre 3335	WorkCentre 3345
Electrical Requirements		
North America	110-127 VAC +/- 10 %, 50/60 Hz +/- 3 Hz, 7A	
Europe	220-240 VAC +/- 10 %, 50/60 Hz +/- 3 Hz, 5A	
Power Consumption		
Operation <sup>4</sup>	Maximum 700 watts	
Standby Mode	Maximum 50 watts	
Power Off Mode <sup>4</sup>	Maximum 0.1 watts	
Sleep Mode <sup>4</sup>	Maximum 3.5 watts	
Warm-up (from Sleep Mode)	As fast as 35 seconds	
Operating Environment		
Required Temperature Range Storage Operating	32°F to 104°F / 0°C to 40°C 50°F to 90°F / 10°C to 32°C	
Required Reletive Humidity	20% to 80%	
Sound Power Levels		
Operating	55 dB(A) or less	57 dB(A) or less
Standby	26 dB(A) or less	26 dB(A) or less
Sound Pressure Levels	EE JD(A) as less	[7.4D/A\
Operating	55 dB(A) or less	57 dB(A) or less
Standby	26 dB(A) or less	26 dB(A) or less

ACIOX WORKCEITHE		
Dimensions and Weight (unpacka	ged)	
WorkCentre 3335	Width: 16.3 in. / 414.6 mm  Depth: 16.6 in. / 420.6 mm  Height: 17.7 in. / 449 mm  Weight: 34.19 lb. / 15.51 kg	
WorkCentre 3345	Width: 18.5 in. / 469 mm  Depth: 17.5 in. / 444.3 mm  Height: 19 in. / 482.6 mm  Weight: 38.07 lb. / 17.27 kg	
550-sheet Paper Tray	Width: 14.4 in. / 366 mm Depth: 17.9 in. / 454 mm Height: 5.7 in. / 146 mm Weight: 11.82 lb. / 5.36 kg	
Dimensions and Weight (package	1)	
WorkCentre 3335	Width: 21 in. / 533 mm Depth: 21.6 in. / 549 mm Height: 23.6 in. / 600 mm Weight: 46.5 lb. / 19.26 kg	
WorkCentre 3345	Width: 23.1 in. / 588 mm Depth: 21.6 in. / 549 mm Height: 24.6 in. / 626 mm Weight: 47.1 lb. / 21.4 kg	
550-sheet Paper Tray	Width: 22.2 in. / 563 mm Depth: 19.6 in. / 497 mm Height: 11.2 in. / 285 mm Weight: 16.8 lb. / 7.62 kg	
System Certification/Regulatory C	ompliance	
Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition Section 508 NOM GS Mark EAC ROHS Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix™ Certified Cerner (undergoing evaluation) Apple® AirPrint® 1.5 certification Google Cloud Print™ (device is compliant/tested, but has not been formerly certified) Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR®® ECOLOGO® EPEAT (United States)® To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.	
Сору	WorkCentre 3335	WorkCentre 3345
Document Scanner  Document Scanner Size	Automatic Document Feeder with 50-sheet capacity  Platen: Up to 8.5 x 11.7 in / A4  ADE: 9 5 x 14 in / 216 x 256 mm	Reversing Automatic Document Feeder with 50-sheet capacity  Platen: Up to 8.5 x 11.7 in / A4  PADE: 8.5 x 14 in / 216 x 256 ppgs
s. 1 s 1	ADF: 8.5 x 14 in. / 216 x 356 mm	RADF: 8.5 x 14 in. / 216 x 356 mm
Simplex Speed	Up to 30 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	Up to 40 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm
Duplex Speed	Up to 12 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	Up to 8.4 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm
First-Copy-Out Time	As fast as 13 seconds from the Platen	
Sides (input:output)	1:1 and 1:2	1:1, 1:2, 2:2, and 2:1
Quantity	1 to 999	
Resolution	Up to 600 x 600 dpi	

Сору	WorkCentre 3335 WorkCentre 3345	
Reduction/Enlargement	Variable zoom from 25 % to 400 % in 1 % increments	
Concurrency	Concurrent scanning and printing	
Copy Features	Automatic Background Suppression Darkness Control ID Card Copy Margin Shift N-up Job Build Photo Mode Program Ahead Booklet Creation Book Copying with Center Erase Edge Erase Job Interrupt Poster Copying	
Print	WorkCentre 3335 WorkCentre 3345	
First-Page-Out Time	As fast as 6.5 seconds <sup>5</sup>	
Resolution	Up to 1200 x 1200 dpi image quality	
Page Description Languages	PostScript 3 compatible PCL® 5e, 6 PDF Direct TIFF JPEG	
Maximum Print Area	4 mm edge of paper	
Print Features	Watermarks Collation Automatic Two-sided Printing N-up Poster Printing Booklet Print Custom Page Size Fit to Page Scaling Draft Mode Earth Smart Printing Print from USB Job Scheduling Print from Local Drive Save Save and Print	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL	
Operating Systems	Microsoft® Windows® Vista and later Mac OS® 10.8.x and later Various Linux® and Unix distributions	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD  NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)  AppleTalk®: EtherTalk®  Microsoft Windows Networking over IP  Bonjour® / Airprint®  IPv6  Secure FTP  Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP	
Font Capability	136 PostScript fonts 111 scalable PCL fonts 1 Bitmap PCL font	
Mobile Solutions and Mobile Device	e Apps	
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	

	33373343 Multifuliction Printer		
Mobile Solutions and Mobile Device			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Apple® AirPrint®	Print email, photos and important office documents directly from an Appl AirPrint, an iPhone or iPad automatically locates and connects to the AirPr	e iPhone® or iPad® with no drivers to install and no cables to connect. With int-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print notebook computers and any other web-connected device. <sup>6</sup>	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.		
Scan	WorkCentre 3335	WorkCentre 3345	
Capability	Color and Black-and-white		
Concurrency	Scan while the system is printing copy or network print jobs, or while it is to	ransferring scan to network or fax jobs	
Input Speed - Black and White	Scan up to 20 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	Scan up to 24 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	
Input Speed - Color	Scan up to 6 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	Scan up to 8 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	
Resolution	Black and White: Optical – 600 x 600 dpi Enhanced up to 4800 x 4800 dpi		
Bit Depth	8-bit Grayscale		
Maximum Scan Area	Platen: Up to 8.5 x 11 in. / A4 Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm		
Network Filing Protocol	FTP SMB/SMB2 SMTP/POP3		
File Formats	PDF Single-page and Multi-page TIFF JPEG BMP		
Scan Driver Compatibility	WIA TWAIN		
Supported Scan Destinations	Scan to Email (SMTP/POP3) Scan to WSD Scan to Application (TWAIN Network) Scan to WSD (WSD Scan) Scan to Mac 10.9 or later (Network/Mac ICA) Scan to USB Scan to Network Computer (SMB/FTP) Scan to Folder		
Security	WorkCentre 3335	WorkCentre 3345	
Security Features	802.1x Secure HTTPS (SSL/TLS) Secure IPP Secure Print SSL IP Filtering IPv6 SNMP v3 WEP (64-/128-bit) WPA2-PSK (AES) WPA / WPA2-Personal WPA / WPA2-Enterprise Network Address Book Authentication (LDAP, Windows Kerberos)		
WiFi Security			
	Authentication Method	Encryption	
	Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2™ Enterprise	WEP 64 / 128-bit ASCII / HEX TKIP AES TKIP AES	

	3333/3343 Multifulletion Fillitel		
WiFi Security			
	WPA Enterprise Authentication Method options:  • PEAPVO MS-CHAPV2  • EAP-TLS  • EAP-TTLS PAP  • EAP-TTLS CHAP		
Fax <sup>7</sup>	WorkCentre 3335	WorkCentre 3345	
Fax Speed	33 Kbps		
Memory	5 MB	50 MB	
Resolution	Standard: Black and White: 203 x 98 dpi / Color: 200 x 200 dpi (TX only) Fine: Black and White: 203 x 196 dpi / Color: 200 x 200 dpi (TX only) Super Fine: Black and White: 600 x 600 dpi / Color: 200 x 200 dpi (TX only)		
Compression	MH/MR/MMR/JBIG/JPEG		
Fax Features	Address Book (Up to 200 speed dials, 209 group dials) Auto Redial Auto Reduction Color Fax Send Delayed Send Fax Forward to Email/Fax Junk fax Protection Memory Receive PC Fax (Windows only) Secure Fax		
Device Management			
Xerox® CentreWare® Web			
Device Status	Web server embedded  Tray status/contents Consumables status		
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete		
Job Submission	Print-ready files (PS, PCL®5c/6, PDF, TIFF Output feature selection		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.		
Browsers	Microsoft® Internet Explorer 6, 7 Firefox® 2., 3 Safari® 3.0		
Xerox® CentreWare® Internet Service	es – Integrated Device Web Page		
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> </ul>		
Xerox® Standard Accounting (Stand	lard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)		
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>		
Remote Print Services	Remote Print Services		
Xerox <sup>®</sup> MeterAssistant <sup>®</sup> Service	Automates the process of collecting and submitting meter reads for tracki time-consumingend-user involvement and ensures that meter reads are so	5 5	
Xerox® SuppliesAssistant® Service	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistar sent to Xerox®, allowing for problems to be solved faster with increased up	3	

what's in the Box		
	WorkCentre 3335 Multifunction Printer or WorkCentre 3345 Multifunction Printer Standard Capacity Print cartridge: 2,600 pages Software and Documentation CD (with Safety, Regulatory, Recycling and Disposal Guides), Print Drivers and Warranty Statement Installation Guide Quick Use Guides Power cord, USB Cable Fax cord	
Supplies and Accessories	Quantity	Part Number
Supplies		
Extra-High Capacity Print Cartridges	15,000 standard pages <sup>8</sup>	106R03624
High Capacity Print Cartridges	8,500 standard pages <sup>8</sup>	106R03622
Standard Capacity Print Cartridges	2,600 standard pages <sup>8</sup>	106R03620
Drum Cartridge	30,000 standard pages <sup>9</sup>	101R00555
Accessories		

097N02254

097N02255

497K17980 497K17990

<sup>1</sup>Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Expected regular monthly throughput.

Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

Near Field Communication (NFC) Enablement Kit

Card Reader Enablement Kit (without Card Reader)

Card Reader Enablement Kit (with Card Reader)

Depending on the specific mobile device, versions or vendor, the mobile device may require a free download of the app from the appropriate store(s).

Requires analog phone line.

550-sheet Paper Tray

Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

10Xerox® WorkCentre® 3345 only.