



GENERAL INDUSTRIAL FILTRATION PRODUCTS

Fulflo[®] TL 3000 Filtration Products

Parker Stores
2007

FF TL 3K-07



Fulflo® Single Cartridge Plastic Filter Housings

Fulflo® filter housings are manufactured from the highest quality, FDA grade, 100% polypropylene and acrylic styrene. Leak-proof sealing is accomplished by compression against a top seated EPDM o-ring located in the housing's sump. Thick wall and added ribs make the housings ideal for a wide range of applications. Polypropylene construction provides excellent chemical resistance with most acids, alcohol, ammonia, oils, plating solutions and many aggressive chemicals. Housings supplied with and without pressure release valves. Rated for temperatures to 125°F (52°C) and pressures to 125 psig (8.75 bar).



Commercial Models
Clear and Opaque



Full-Flow (B-B)
Opaque
Holds 4-1/2" cartridges



Valve-In-Head
Three-function valve with shut-off, by-pass & flow.
Clear and Opaque



High-Purity
100% virgin polypropylene

10" and 20" Commercial Opaque Housings

Model Number	Type	Pipe Size	Head	Pressure Release	Sump	No. / case
FH0110BL34PR	10" Commercial Opaque	3/4"	Black	Yes	Blue	12
FH0120BL34PR	20" Commercial Opaque	3/4"	Black	Yes	Blue	6

10" and 20" Commercial Clear Housings

Model Number	Type	Pipe Size	Head	Pressure Release	Sump	No. / case
FH0110CB34PR	10" Commercial Clear	3/4"	Black	Yes	Clear	12
FH0120CB34PR	20" Commercial Clear	3/4"	Black	Yes	Clear	6

Valve-In-Head Housings (Three-function valve with flow, shut-off, by-pass.)

Model Number	Type	Pipe Size	Head	Pressure Release	Sump	No. / case
FH0110VH34C	10" Valve-In-Head	3/4"	White	No	Clear	12

Natural Polypropylene Housings

Model Number	Type	Pipe Size	Head	Pressure Release	Sump	No. / case
FH0110NP34	10" Natural Polypropylene	3/4"	NP	No	NP	12

10" Full-Flow Blue / Black Housings (B-B) - Accepts 4-1/2" OD Full-Flow Cartridges

Model Number	Type	Pipe Size	Head	Pressure Release	Sump	No. / case
FH0210BL34PR	10" FULL-FLOW	3/4"	BLACK	YES	BLUE	4
FH0210BL1PR	10" FULL-FLOW	1"	BLACK	YES	BLUE	4

20" Full-Flow Blue / Black Housings (B-B) - Accepts 4-1/2" OD Full-Flow Cartridges

Model Number	Type	Pipe Size	Head	Pressure Release	Sump	No. / case
FH0220BL1PR	20" FULL-FLOW	1"	BLACK	YES	BLUE	4
FH0220BL15PR	20" FULL-FLOW	1-1/2"	BLACK	YES	BLUE	4



Fulflo® Pleated Filter Cartridges for Plastic Housings

With Cellulose-Free Filter Media For Water Filtration Applications



Specifications	
FILTER MEDIA	SYNTHETIC (100% CELLULOSE-FREE)
END CAPS	PLASTISOL (PVC)
CENTER TUBES	POLYPROPYLENE
TEMPERATURE RANGE	40°F to 140°F (4.4°C to 60°C)
MAXIMUM PRESSURE DIFFERENTIAL	25 PSID
RECOMMENDED CHANGE OUT	20 PSID
FLOW RATE PER 10" STANDARD CARTRIDGE	3-10 GPM*
FLOW RATE PER 10" FULL-FLOW CARTRIDGE	8-15 GPM*
* DEPENDENT ON MICRON RATING	

Standard 2-3/4" OD x 9-3/4" length

Product Code	Length	Media Type	Micron Rating	Number Per Case
FC05975S1	9-3/4"	POLYPROPYLENE	1	24
FC05975S5	9-3/4"	POLYPROPYLENE	5	24
FC05975S20	9-3/4"	POLYESTER	20	24
FC05975S50	9-3/4"	POLYESTER	50	24
FC05975S100	9-3/4"	POLYESTER	100	24

Standard 2-3/4" OD x 20" length

Product Code	Length	Media Type	Micron Rating	Number Per Case
FC0520S035	20"	POLYPROPYLENE	0.35	24
FC0520S1	20"	POLYPROPYLENE	1	24
FC0520S5	20"	POLYPROPYLENE	5	24
FC0520S20	20"	POLYESTER	20	24
FC0520S50	20"	POLYESTER	50	24

Full-Flow (B-B) 4-1/2" OD x 9-3/4" length

Product Code	Length	Media Type	Micron Rating	Number Per Case
FC05975B1	9-3/4"	POLYPROPYLENE	1	8
FC05975B5	9-3/4"	POLYPROPYLENE	5	8
FC05975B20	9-3/4"	POLYESTER	20	8

Note: Cartridges listed above fit in Full-Flow filter housings.

Full-Flow (B-B) 4-1/2" OD x 20" length

Product Code	Length	Media Type	Micron Rating	Number Per Case
FC0520B1	20"	POLYPROPYLENE	1	4
FC0520B5	20"	POLYPROPYLENE	5	4
FC0520B20	20"	POLYESTER	20	4

Note: Full-Flow cartridges listed above fit in Full-Flow filter housings.

Fulflo® C-MAX™ Extruded Carbon Filter Cartridges

Solid block activated carbon cartridges for wide range of applications

Applications

- Chlorine taste & odor reduction
- Sediment reduction
- VOC reduction
- Cyst reduction
- Lead reduction
- Pre and post-RO treatment



Specifications	
Specifications	Data
OPERATING TEMPERATURE	40°F to 165°F (4.4°C to 73.8°C)
MAXIMUM PRESSURE DIFFERENTIAL	60 PSID
RECOMMENDED CHANGE OUT	30 PSID
FILTER MEDIA	ACTIVATED CARBON
END CAPS, CENTER TUBES, NETTING	POLYPROPYLENE

MAX-ETW: Economical, thick-wall carbon block cartridges for chlorine taste and odor

Part Number	Type	OD	Length	Micron Rating	Chlorine Reduction	No. / case
MAXETW-975	THICK-WALL	2-7/8"	9-3/4"	5 NOMINAL	3,000 GALLONS	12
MAXETW-20	THICK-WALL	2-7/8"	20"	5 NOMINAL	6,000 GALLONS	6
MAXETW-FF975	THICK-WALL (FULL-FLOW)	4-5/8"	9-3/4"	5 NOMINAL	11,000 GALLONS	4
MAXETW-FF20	THICK-WALL (FULL-FLOW)	4-5/8"	20"	5 NOMINAL	20,000 GALLONS	6

Note: MAX-ETW are identified by white end caps.

MAX-CL: Thick-wall carbon block for long life and increased chlorine taste and odor reduction; removes extra fine sediment and rust particles

Part Number	Type	OD	Length	Micron Rating	Chlorine Reduction	No. / case
MAXCL-975	THICK-WALL	2-7/8"	9-3/4"	0.5 NOMINAL	20,000 GALS.	12
MAXCL-20	THICK-WALL	2-7/8"	20"	0.5 NOMINAL	45,000 GALS.	6
MAXCL-FF975	THICK-WALL (FULL-FLOW)	4-5/8"	9-3/4"	0.5 NOMINAL	70,000 GALS.	4
MAXCL-FF20	THICK-WALL (FULL-FLOW)	4-5/8"	20"	0.5 NOMINAL	150,000 GALS.	6

Note: MAX-CL are identified by green end caps.

Fulflo® Granular Activated Carbon Cartridges (GAC)

Granular Activated Carbon Cartridges (GAC)						
Part Number	Type	OD	Length	Micron Rating	No. / case	
GAC10N	GAC	2-3/4"	9-3/4"	NR	24	
GAC20NRW	GAC	2-3/4"	20"	NR	24	
GAC-BB10	GAC (FULL-FLOW)	4-1/2"	9-3/4"	NR	8	
GAC-BB20	GAC (FULL-FLOW)	4-1/2"	20"	NR	8	



Process Advanced Filtration Division
 2340 Eastman Avenue - Oxnard, California 93030
 Toll Free: +1 877 784 2234 Phone: +1 805 604 3400
 PAFsales@parker.com www.parker.com