

The WorkCentre 4265 streamlines everyday office communications, providing the solutions you need to collaborate more effectively through simplified digital and paper-driven workflows – securely and cost effectively.



System Specifications	WorkCentre 4265/S	
Single-sided Speed	Up to 53 ppm A4 (210 x 297 mm)	
Automatic Two-sided Speed	Up to 48 ppm A4 (210 x 297 mm)	
Monthly Duty Cycle ¹	Up to 250,000 pages / month	
Recommended Average Monthly Print Volume ²	Up to 20,000 pages / month	
Hard Drive / Processor / Memory	320 GB / 1 GHz / 2 GB	
Connectivity	10/100/1000Base-TX Ethernet, High-Speed USB 2.0, Wireless 802.11 b/g/n	
User Interface	7-inch Capacitive Colour Touch Screen	
Copy and Print		
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 enhanced image quality	
First-print-out Time	As fast as 8 seconds	
First-copy-out Time	As fast as 5 seconds	
Page Description Languages	Adobe® PostScript® 3 compatibility, PCL® 5c/e / PCL 6 emulations, XML Paper Specification (XPS®)	
Print Features	Booklet Printing, Proof Print, Skip Blank Pages, N-up, Collation, Scaling, Reduce/Enlarge, Fit to Page, Covers, Custom-size Pages, Delay Print, Banner Sheet, Print from USB	
Mobile Printing	Apple® AirPrint, Web Printing Service, Xerox® Mobile Print Solution (Optional), Xerox® Mobile Print Cloud (Optional), Xerox® PrintBack	
Scan		
Standard Features	Destinations: Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Single/Multi-Page PDF / XPS / TIFF, Linearised PDF	
Optional Features	Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Alliance Partners	
Fax		
Optional Features	Embedded Fax ³ , LAN Fax, Server Fax	
Security		
Standard Features	802.1X, Convenience Authentication, Kerberos Authentication (Unix / Linux / Windows ADS), LDAP Authentication (Secure LDAP), Local PIN Based Guest Login, Simple Authentication (one account with user name and Password), SMB Authentication (ADS), SMTP User Credentials via Kerberos, SMTP User Credentials via SMB (NTLM), Scan to Email with Authentication, Access Controls, User Permissions, Secure Print, Secure Fax Receive, SNMP v3, IPv6, SSL, SMTP over SSL, Smart Card Enablement Kit (CAC/PIV), USB port disablement, Audit Log, FIPS 140-2 Encryption, 256-bit Hard Disk Encryption, Image Overwrite, Software Verification Test, IP Filtering, HTTPS, SFTP, Common Criteria Certification (ISO 15408)	
Accounting		
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email)	
Optional Features	Equitrac Express®, Equitrac Office®, YSoft® SafeQ®, Network Accounting Enablement, other solutions available through various Xerox Alliance Partners	

Device Specification				
Control Panel Languages	English French Italian	, German, Spanish, Brazilian Portuguese, Russian,	Dutch Swedish Danish Finnish Norweai	an Turkish Polish Czech
control l'anci Languages	Hungarian, Greek	, oerman, spanish, brazilian rortaguese, Russian,	butti, swealsh, banish, rinnish, riorwegi	
Accessories				
Optional Accessories	520-sheet Paper Tray 4-Tray Stand (IOT plus 3 additional trays) 2-Tray Stand (IOT plus additional tray) 2100-sheet High Capacity Feeder Offset Catch Tray Network Accounting Enablement Network Fax Server Enablement Fax Kit (Universal) Foreign Device Interface Smart Card Enablement Kit (CAC/PIV) Wireless Kit			
Electrical Requirements				
	Voltage: 220-247 VAC	+6%,-10%		
	Frequency: 50/60 Hz, 4	4.5 A		
Power Consumption				
Printing	Less than 900 watts			
Standby Mode	Less than 30 watts			
Power Save Mode	Less than 1.5 watts			
Warm up (from Power Save)	< 30 seconds			
Warm up (from power on)	< 60 seconds			
Operating Environment	1			
Required Temperature Range	10° to 30° C	10° to 30° C		
Required Relative Humidity	Less than 85%			
Sound Pressure Levels	Operating: 59.0 dB(A),	Standby – Fan On: 37.0 dB(A); Fan Off: 30 dB(A)	
Dimensions and Weights (Unpackaged)	Width	Depth	Height	Weight
WorkCentre 4265/S	621 mm	511 mm	624 mm	42.32 kg
Dimensions and Weights (Packaged)	Width	Depth	Height	Weight
WorkCentre 4265/S	840 mm	613 mm	736 mm	50.82 kg
Certifications				
	UL 60950-1/CSA 6095 EAC ENERGY STAR® qualifie GS Mark Blue Angel certification NOM Ukraine ECOLOGO® India BIS Registration Chile Energy and Safet	ed n per Ral UZ-171 for Germany		
Paper Handling				
Duplex Automatic Document Feeder (DA				
Capacity ⁴	100 sheets			
Speed (black and white)	Up to 55 images per minute (ipm) (simplex) – black and white and colour Up to 70 ipm (duplex) – black and white and colour			
Sizes	Custom sizes: 145 x 145 mm to 216 x 356 mm			
Weights	50 to 105 gsm			
Bypass Tray				
51	1			
	100 sheet			
Capacity ⁴ Sizes Weights		3 mm to 216 x 356 mm		

Media Types	Plain Paper
	Bond Punched
	Punched Pre-Printed
	Recycled
	Envelopes
	Transparencies
	Labels
	Card Stock
	Letterhead Lightweight
	Heavyweight
	Archive
	Custom
	Other
Tray 1 (Standard)	520 Juli
Capacity ⁴ Sizes	520 sheets Custom sizes: 98 x 148 mm to 216 x 356 mm
Weights	60 to 105 gsm
Media Types	Plain Paper
	Bond
	Punched
	Pre-Printed
	Recycled
	Envelopes Transparencies
	Labels
	Card Stock
	Letterhead
	Lightweight
	Heavyweight Archive
	Custom
	Other
Tray 2 (Optional)	
Capacity ⁴	520 sheets
Sizes	Custom sizes: 98 x 148 mm to 216 x 356 mm
Weights	60 to 105 gsm
Media Types	Plain Paper Bond
	Punched
	Pre-Printed
	Recycled
	Envelopes
	Transparencies Labels
	Card Stock
	Letterhead
	Lightweight
	Heavyweight
	Archive Custom
	Other
Trays 3 and 4 (Optional)	
Capacity ⁴	520 sheets each
Sizes	Custom sizes: 98 x 148 mm to 216 x 356 mm
Weights	60 to 105 gsm
Media Types	Plain Paper
	Bond Punched
	Pre-Printed
	Recycled
	Envelopes
	Transparencies
	Labels
	Card Stock Letterhead
	Lightweight
	Heavyweight
	Archive
	Custom
	Other

High Capacity Feeder (Optional)		
Capacity ⁴	2,100 sheets	
Sizes	Standard selectable sizes: A5, A4	
Weights	60 to 105 gsm	
Media Types	Plain Paper Bond Punched Pre-Printed Recycled Card Stock Letterhead Lightweight Heavyweight Post Card Archive Custom Other	
Total Capacity		
Device Standard Capacity ⁴	620 sheets	
Device Total Capacity ⁴	3,240 sheets	
Paper Output		
Capacity ⁴	Up to 500 sheets, automatic two-sided	
Offset Catch Tray (Optional)		
Capacity ⁴	Up to 500 sheets, 50-sheet single-position stapling	
Сору		
Scanner	Single-Pass (dual-head) Duplex Automatic Document Feeder with 100-sheet capacity	
First-copy-out Time	As fast as 5 seconds	
Sides (input/output)	1-1, 1-2, 2-2, 2-1	
Quantity	1 to 999	
Resolution (max.)	600 x 600 dpi	
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)	
Copy Feαtures	CollationBackground SuppressionBook CopyingBook Copying with Centre EraseBookle CreationBuild JobCoversEdge EraseID Card CopyImage ShiftJob InterruptLighten/DarkenMixed-size OriginalsN-upProgramme AheadReduce/Enlarge 25 to 400 % (from Platen and ADF)Save Job SettingsTransparency Separators	

Print			
First-print-out Time	As fast as 8 seconds		
Print Resolution	Up to 1200 x 1200 enhanced image quality		
Print Features	Application Defaults Banner Sheet Booklet Printing Collation Custom page size Delayed Print Fit to Page Job Monitoring N-Up Paper Selection by Attribute Print Around Print from USB Memory Print to / From Hard Drive Proof Print Saved Job Scaling Secure Print Skip Blank Pages Store and Recall Driver Settings Watermark		
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PRN, TXT, PDF, TIFF, JPEG		
Operating Systems	Windows® XP/2003 Server/2008 Server/2012 Server/Vista/7/8Mac OS® 10.5/10.6/10.7/10.8/10.9Citrix Presentation Server 4.5Citrix XenApp 5.0 & upOracle® Solaris 10, 11Redhat®Fedora® Core 18HP-UX® 11iv3IBM® AIX® 5openSUSE® 12 x64Ubuntu® 12.10 x64Xerox® Global Print Driver®Xerox® Mobile Express Driver®		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD Apple® Bonjour® IPv4 IPv6 Secure FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP		
Fonts	136 PostScript fonts 111 PCL® fonts		
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox [®] devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.		
Scan			
Capability	Black and white and colour scanning		
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs		
Input Speed	Up to 55 ipm simplex (black and white and colour) Up to 70 ipm duplex (black and white and colour)		
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi		

Fax Mailboxes Secure Fax

Network Protocol	FTP SFTP SMB HTTP HTTPS WSD	
File Formats	TIFF Multipage TIFF JPEG PDF Image only PDF Linearised PDF XPS	
Supported Scan Destinations	Scan to Home Scan to PC via SMB Scan to Email Secure Scan to Email Scan to Folder Scan to SMB, FTP, SFTP, Client Scan to Network (WIA, TWAIN) Scan to HTTP, HTTPS WSD Scanning	
Scan to Email	 Direct document email from device Manual or directory Exchange/Notes/LDAP address searching Email From field auto-populated from LDAP when network authentication is used 	
Network Scanning	Uses templates to send scanned images to predefined locations	
Scan to USB	Scans can be loaded directly onto a user's portable USB storage device	
Scanning Solutions		
Xerox® Scan to PC Desktop® Personal Edition (1 Seat)	 A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools Nuance PaperPort – image viewing and file management software Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan-enabled Xerox® multifunction printer to individual desktops 	
Security		
Security Features	256-bit AES HDD Encryption 802.1X Access Controls Audit Log Convenience Authentication FIPS 140-2 Encryption HTTPS (SSL) IP Filtering IPsec IPv6 Image Overwrite Kerberos Authentication LDAP Authentication SMB Authentication SMB Authentication (ADS) SNMPv3 Scan to Email with Authentication Secure Fax (enabled when Fax Kit is added) Secure Print Smart Card Enablement Kit (CAC/PIV) User Permissions	
Embedded Fax ³ , LAN Fax, Server Fo	x (Optional)	
Fax Speed	33.6 Kbps	
Memory	320 GB (50 MB dedicated fax memory)	
Resolution	Up to 300 x 300 dpi (superfine) resolution	
Compression	MH, MR, MMR and JBIG	
Fax Features	Address Book Auto Answer Delay Auto Memory Resend Auto Redial Broadcast Sending Delayed Start Fax Forward to Email Fax Forward to Fax Fax Mailhoxes	

Device Management			
Management Support	 SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accountin and asset management. Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. CentreWare Integration available for Tivoli® NetView[®], Unicentre TNG[®], Microsoft Management Console (MMC), HP[®] OpenView[®] 		
Xerox® CentreWare® Web			
Xerox® Device Manager	 Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environmer It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: Device monitoring and troubleshooting Extensive reporting and discovery of new devices Usage collection, chargeback and billing capabilities 		
Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® devi types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available download. Information available at www.office.xerox.com/software-solutions.		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions.		
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions.		
CentreWare Internet Services – Integr	ated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian		
Remote Print Services			
Automated Meter Reads (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Accounting			
Xerox [®] Standard Accounting			
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 500 User accounts Up to 250 General accounts Up to 250 Group accounts		
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file 		
Accounting Options – Network Accoun	ting – Third Party Enablement (Optional)		
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface 		

	 WorkCentre 4265 Multifunction Printer Starter Toner Cartridge (30,000 print capacity⁵) Drum Cartridge (100,000 yield⁵) Installation Guide, Quick Use Guide, Documentation and Driver CD (Drivers, User Manual, System Admin Guide) Power Cable 			
Supplies and Accessories	Description	Quantity	Part Number	
Supplies ⁷	Black Toner Cartridge	Approx. 30,000 ⁵	106R02733	
	Staple Cartridge	15,000 staples	008R12941	
	Drum Cartridge	Approx. 100,000 pages ⁶	113R00776	
	Fuser Maintenance Kit (110v)	250,000 pages ⁶	115R00086	
	Bias Transfer Roll Maintenance Kit	125,000 pages ⁶	108R01266	
	Feed Roll Maintenance Kit	250,000 pages ⁶	108R01267	
Accessories	520-sheet Paper Tray	-	097N01524	
	4-Tray Stand (IOT plus 3 additional trays)	-	097503678	
	2-Tray Stand (IOT + 1 additional tray)	-	097503677	
	2100-sheet High Capacity Feeder	-	097N01684	
	500 sheet Offset Catch Tray	-	097N02155	
	Network Accounting Enablement	-	098504928	
	Network Fax Server Enablement	-	098504931	
	Fax Kit (Universal)	-	097N02154	
	Foreign Device Interface	-	097N01676	
	Smart Card Enablement Kit (CAC/PIV)	-	498K17546	
	Wireless Kit	-	097N02156	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput. ³ Requires analogue phone line.

⁶ Paper capacities an advective priorite inte.
 ⁶ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.
 ⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.
 ⁶ Approximate pages. Declared Yield based on A4-size 75 gsm pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.
 ⁷ Check for inclusion on your Xerox Service Agreement.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.



©2014 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, Global Print Driver®, MeterAssistant®, Mobile Express Driver®, Scan to PC Desktop®, SuppliesAssistant®, WorkCentre and Xerox Secure Access Unified ID System® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. 12/14 BR11353 W4XSS-01ED