



TVS-882BR-ODD-i7-32G (Legacy)

| | |
|--|---|
| CPU | Intel® Core™ i7-7700 4-core 3.6 GHz processor, Max turbo to 4.2 GHz |
| CPU Architecture | 64-bit x86 |
| Graphic Processors | 9th-generation Intel® HD Graphics |
| Floating Point Unit | Yes |
| Encryption Engine | Yes (AES-NI) |
| Hardware-accelerated Transcoding | Yes |
| System Memory | 32 GB UDIMM DDR4 (4 x 8GB) |
| Maximum Memory | 64 GB (4 x 16 GB) |
| Memory Slot | 4 x UDIMM DDR4 |
| Flash Memory | 512MB (DOM for dual OS) |
| Drive Bay | 8 x 3.5-inch SATA 6Gb/s, 3Gb/s |
| Drive Compatibility | 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives |
| 5.25-inch Expansion Bay | 1 x 5.25" disc burner or 2 x slim SATA disc burners *pre-installed with a Blu-ray ODD |
| Pre-installed in 5.25-inch Expansion Bay | LG WH16NS58D |
| Hot-swappable | Yes |
| M.2 Slot | 2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots The M.2 SSD is not included as standard. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD. |
| SSD Cache Acceleration Support | Yes |
| GPU pass-through | Yes |

| | |
|--|--|
| Gigabit Ethernet Port (RJ45) | 4 |
| Wake on LAN (WOL) | Yes |
| Jumbo Frame | Yes |
| PCIe Slot | 3 Slot 1: PCIe Gen 3 x8 Slot 2: PCIe Gen 3 x4 Slot 3: PCIe Gen 3 x4 |
| USB 3.2 Gen 1 port | 5 |
| USB 3.2 Gen 2 (10Gbps) Port | Yes (Optional) |
| IR Sensor | Yes |
| HDMI™ Output | 3, HDMI™ 1.4b |
| Audio Input | 2 x 6.3mm dynamic microphone input jacks |
| Audio Output | 2 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers) |
| Form Factor | Tower |
| LED Indicators | System status, M.2 SSD, 3.5" HDD |
| LCD Display/ Button | Yes |
| Buttons | Power, Reset, USB Auto Copy |
| Dimensions (HxWxD) | 9.24 × 14.56 × 12.59 inch |
| Weight (Net) | 24.76 lbs |
| Weight (Gross) | 27.16 lbs |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | Input: 100-240V~, 3-1.5A, 60-50Hz; Output: 250W |
| Power Consumption: HDD Sleep Mode | 33.083 W |
| Power Consumption: Operating Mode, Typical | 63.816 W Tested fully populated with WD10EFRX hard drives, TS128GMTS800 M.2 solid-state drives ,and Optical Disc Drive. |
| Fan | System fan: 3 x 80mm CPU fan: 1 x 90mm |
| Kensington Security Slot | Yes |
| Standard Warranty | 2 |

| | |
|---|------|
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 5000 |
|---|------|

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.