



UX-800P (Legacy)

JBOD Connection Interface	USB
Drive Bay	8 x 3.5-inch The system is shipped without HDD. For the HDD compatibility list, please visit https://www.qnap.com/compatibility/
Drive Compatibility	3.5-inch bays: 3.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s solid state drives You can only use one disk type (HDD or SSD) in a RAID group. Combining different types of disk in one RAID group is not supported.
Hot-swappable	Yes
Form Factor	Tower
Host Interface	USB 3.2 Gen 1 (Type B)
LED Indicators	Power, link, status
Buttons	Enter, select, power switch
Dimensions (HxWxD)	7.29 × 11.74 × 9.27 inch
Weight (Net)	16.09 lbs
Weight (Gross)	18.96 lbs
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	ATX Power Supply, 250W, 100-240Vac~, 50-60Hz
Power Consumption: HDD Sleep Mode	25.47 W
Power Consumption: Operating Mode, Typical	51.77 W Tested with drives fully populated.

System Warning	Buzzer
QTS / QuTS hero	Yes
Management	Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure 4. Smart fan control by detecting system and hard drive temperature

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.