



TS-1685-D1531-64G (Legacy)

CPU	Intel® Xeon® D-1531 6-core 2.2 GHz processor
CPU Architecture	64-bit x86
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
System Memory	64GB non-ECC RAM (16GB UDIMM x 4)
Maximum Memory	UDIMM: 64 GB (4 x 16 GB) RDIMM: 128GB (4 x 32 GB)
Memory Slot	4 x UDIMM DDR4 IMPORTANT: You can only use one type of dual in-line memory module (DIMM) at a time. Do not use registered DIMM (RDIMM) with unbuffer DIMM (UDIMM) memory.
Flash Memory	512MB (DOM for dual OS)
Drive Bay	12 x 3.5-inch + 4 x 2.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
M.2 Slot	6 x M.2 22110/2280/2260/2242 SATA 6Gb/s slot The M.2 SSD is not included as standard. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD.
SSD Cache Acceleration Support	Yes
GPU pass-through	Yes
Gigabit Ethernet Port (RJ45)	4
10 Gigabit Ethernet Port	2 x 10GBASE-T
Wake on LAN (WOL)	Yes

Jumbo Frame	Yes
PCIe Slot	3 Slot 1: PCIe Gen 3 x8 Slot 2: PCIe Gen 2 x4 Slot 3: PCIe Gen 3 x8
USB 3.2 Gen 1 port	3
Audio Output	1 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers) Only one of the above audio output ports can work at a time. If a speaker is connected, the sound will output through the speaker.
Form Factor	Tower
LED Indicators	System status, 2.5" SSD, M.2 SSD, 3.5" HDD
LCD Display/ Button	Yes
Buttons	Power, Reset, USB Auto Copy
Dimensions (HxWxD)	303.84 × 369.89 × 319.8 mm
Weight (Net)	13.39 kg
Weight (Gross)	15.96 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	100-240V~, 3-1.5A, 60-50Hz, 550W PSU
Power Consumption: HDD Sleep Mode	61.36 W
Power Consumption: Operating Mode, Typical	127 W
Fan	System fan: 3 x 92mm, 12VDC CPU fan: 2 x 90mm
System Warning	Buzzer
Kensington Security Slot	Yes
Standard Warranty	3
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	10000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical

performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.