

TS-453DU-RP-4G (Legacy)

| CPU | Intel® Celeron® J4125 4-core/4-thread processor, burst up to 2.7 GHz |
|---|---|
| CPU Architecture | 64-bit x86 |
| Graphic Processors | Intel® HD Graphics 600 |
| Floating Point Unit | Yes |
| Encryption Engine | Yes (AES-NI) |
| Hardware-accelerated Transcoding | Yes |
| System Memory | 4 GB SODIMM DDR4 (1 x 4 GB) |
| Maximum Memory | 8 GB (2 x 4GB) |
| Memory Slot | 2 x SODIMM DDR4 |
| | When installing two memory modules, please ensure that they are the same size and ideally use the same type of RAM for both memory slots. |
| Flash Memory | 4GB (Dual boot OS protection) |
| Drive Bay | 4 x 3.5-inch SATA 6Gb/s, 3Gb/s |
| | The system is shipped without HDD. For the HDD compatibility list, please visit <u>https://www.qnap.com/compatibility/</u> |
| Drive Compatibility | 3.5-inch bays:3.5-inch SATA hard disk drives2.5-inch SATA hard disk drives2.5-inch SATA solid state drives |
| Hot-swappable | Yes |
| M.2 Slot | Optional via a PCIe adapter |
| SSD Cache Acceleration Support | Yes |
| 2.5 Gigabit Ethernet Port (2.5G/1G/100M) | 2 (2.5G/1G/100M/10M) |
| | |

| Wake on LAN (WOL) | Yes |
|--|---|
| | Only the 2.5GbE port |
| Jumbo Frame | Yes |
| PCIe Slot | 1 Slot 1: PCIe Gen 2 x2 |
| | PCIe bandwidth limitations will restrict the NAS 10GbE performance. |
| USB 2.0 port | 2 |
| USB 3.2 Gen 1 port | 2 |
| USB 3.2 Gen 2 (10Gbps) Port | Optional via a PCIe adapter |
| HDMI™ Output | 1, HDMI™ 1.4b |
| Form Factor | 1U Rackmount |
| LED Indicators | HDD 1-4, Status, LAN, Expansion, Power |
| Buttons | Power, Reset |
| Dimensions (HxWxD) | 43.3 × 482.6 × 508.7 mm |
| Weight (Net) | 8.12 kg |
| Weight (Gross) | 10.1 kg |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | 250W (x2), 100-240V |
| Power Consumption: HDD Sleep Mode | 30.207 W |
| Power Consumption: Operating Mode, Typical | 45.3 W |
| | Tested with drives fully populated. |
| Fan | 2 x 40mm, 12VDC |
| System Warning | Buzzer |
| Standard Warranty | 3 |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 1500 |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.