



TS-463XU-4G (Legacy)

| | |
|--------------------------------|--|
| CPU | AMD G-Series GX-420MC 4-core 2.0 GHz processor |
| CPU Architecture | 64-bit x86 |
| Floating Point Unit | Yes |
| Encryption Engine | Yes (AES-NI) |
| System Memory | 4 GB SODIMM DDR3L (1 x 4 GB) |
| Maximum Memory | 16 GB (2 x 8 GB) |
| Memory Slot | 2 x SODIMM DDR3L For dual-DIMM configuration, you must use a pair of identical DDR3L modules. |
| Flash Memory | 512MB (Dual boot OS protection) |
| Drive Bay | 4 x 3.5-inch SATA 6Gb/s, 3Gb/s The system is shipped without HDD. For the HDD compatibility list, please visit https://www.qnap.com/compatibility/ |
| Drive Compatibility | 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives |
| Hot-swappable | Yes |
| M.2 Slot | Optional via a PCIe adapter |
| SSD Cache Acceleration Support | Yes |
| Gigabit Ethernet Port (RJ45) | 4 Expandable with an optional PCIe adapter |
| 10 Gigabit Ethernet Port | 1 x 10GBASE-T (10G/5G/2.5G/1G/100M) Pre-installed QXG-10G1T PCIe adapter |
| Wake on LAN (WOL) | Yes |
| Jumbo Frame | Yes |

| | |
|--|--|
| PCIe Slot | 1 Slot 1: PCIe Gen 2 x4 Pre-installed QXG-10G1T PCIe adapter |
| USB 2.0 port | 3 |
| USB 3.2 Gen 1 port | 2 |
| USB 3.2 Gen 2 (10Gbps) Port | Optional via a PCIe expansion adapter |
| Form Factor | 1U Rackmount |
| LED Indicators | HDD 1-4, Status, USB, LAN |
| Buttons | Power, Reset, USB Auto Copy |
| Dimensions (HxWxD) | 44 × 439 × 499 mm |
| Weight (Net) | 7.58 kg |
| Weight (Gross) | 9.54 kg |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | 250W, Input: 110-240 Vac~, 50-60Hz, 5A |
| Power Consumption: HDD Sleep Mode | 34.06 W |
| Power Consumption: Operating Mode, Typical | 50.46 W |
| System Warning | Buzzer |
| Standard Warranty | 3 |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 800 |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.