

# Brocade 10G-SFPP-USR-8 Datasheet

For Informational Purposes Only

Data Compiled by SanSpot

## Brocade 10G-SFPP-USR-8 Duplex SFP+ 10Gbps 100m MMF DDM 850nm

### 10G-SFPP-USR-8 Features

- Brocade 10GBASE-SR/SW Ethernet SFP+
- Up-to 100m over MMF @ 10Gbps
- 850nm Duplex SFP+ Transceiver
- 0°C - 70°C Operating Case Temperature
- SFF-8724 Digital optical monitoring
- Hot-swappable for SFP+ LC ports
- Brocade standard warranty
- End-to-end compatibility within Brocade platform
- Compliant with SFF-8431 & SFF-8432
- Brocade 10G-SFPP-USR-8 is RoHS compliant

### Applications

- 10 Gigabit Ethernet
- Ethernet 10GBASE-SR
- 10 Gbps

### Description

The Brocade 10G-SFPP-USR-8 10GBASE-SR/SW Ethernet transceiver is a Duplex SFP+ transceiver for optical communications, rated for distances up to 100m and a maximum bandwidth of 10Gbps. The 10G-SFPP-USR-8 transceiver operates at 850nm wavelength. Brocade Ethernet 10GBase-USR SFP+, SFP+ transceiver module, 8-PACK, 10000 Mbit/s, LC, Wavelength:850 nm, Multi-mode, Maximum Distance: 330ft. Digital Diagnostics Monitoring Interface (DDMI) , Full duplex mode , Hot swap module replacement

### About this Data Sheet

*This data sheet has been compiled by SanSpot as a service to its clients and is based on publicly available information from the manufacturer at the time of this publication. For most up-to-date information, please visit manufacturer website. SanSpot is not responsible for omissions or typographical errors.*