


Use

Points

180° Tee Bottom Outlet WWW

Normal size	Dimensions						Ordering Code
	A in.	A mm	B in.	B mm	C in.	C mm	
3/4 x 1/2	4.500	114.3	3.000	76.2	1.875	47.6	020015-U10-P6*
3/4 x 3/4	4.500	114.3	3.000	76.2	1.875	47.6	020020-U10-P6*
1 x 1/2	3.000	76.2	3.000	76.2	2.062	52.4	025015-U10-P6*
1 1/2 x 1/2	4.500	114.3	4.500	114.3	2.312	58.7	038015-U10-P6*
2 x 1/2	6.000	152.4	5.000	127.0	2.562	65.1	051015-U10-P6*
2 1/2 x 1/2	7.500	190.5	5.750	146.1	2.812	71.4	063015-U10-P6*
3 x 1/2	9.000	228.6	6.500	165.1	3.062	77.8	076015-U10-P6*
4 x 1/2	12.000	304.8	8.500	215.9	3.562	90.5	100015-U10-P6*

*The last digit referse to surface quality, according to Table 1



180° Tee Bottom Outlet WCW DT-23T

Normal size	Dimensions						Ordering Code
	A in.	A mm	B in.	B mm	C in.	C mm	
3/4 x 1/2	4.500	114.3	3.000	76.2	0.875	22.2	020015-U11-P6*
3/4 x 3/4	4.500	114.3	3.000	76.2	0.875	22.2	020020-U11-P6*
1 x 1/2	3.000	76.2	3.000	76.2	1.062	27.0	025015-U11-P6*
1 1/2 x 1/2	4.500	114.3	4.500	114.3	1.312	33.3	038015-U11-P6*
2 x 1/2	6.000	152.4	5.000	127.0	1.562	39.7	051015-U11-P6*
2 1/2 x 1/2	7.500	190.5	5.750	146.1	1.812	46.0	063015-U11-P6*
3 x 1/2	9.000	228.6	6.500	165.1	2.062	52.4	076015-U11-P6*
4 x 1/2	12.000	304.8	8.500	215.9	2.562	65.1	100015-U11-P6*

*The last digit referse to surface quality, according to Table 1

