

4G (15L) Cabinet datasheet



► Technical description

Regulatory Approval/Code Reference	
Regulatory Approval/Code Reference	Incidental storage or use of flammable and combustible liquids
OSHA 29 CFR 1910.106(d)(3)(i&ii)	Design, construction, and capacity of storage cabinets - (i) Maximum capacity
International Fire Code	3404.3.2 - Liquid storage cabinets, 3404.3.2.1.1- Material
	3404.3.2.1.2 - Labeling, 3404.3.2.1.3 - Doors, 3404.3.2.1.4 Bottom
NFPA 1, The Uniform Fire Code –2006 Edition	60.1.2.23 Hazardous Materials Storage Cabinets
NFPA Code 30 – 2008 Edition	Chapter 9
The National Fire Code of Canada (NFC) 1995 Edition	Section 4.2.10.5 references storage cabinets must conform to ULC-C1275
	ULC/ORD-C1275-84
FM Global	Not Approved

► Description product

- Capacity: 15 L Cabinet.
- Exterior Dimensions (H x W x D): 565 mm x 432 mm x 432 mm.
- Interior Dimensions (H x W x D): 461 mm x 351 mm x 351 mm.
- Door Opening Dimensions (H x W): 410 mm x 347 mm.
- Material Specifications: Cabinet architecture is 18ga steel thought, with fully welded construction. 2" leak tight sump, continuous door hinge Galvanized spill slope shelf (s). Powder coat finish: 2.4 to 2.5 mills avg.
- Package Dimensions (H x W x D): 584 mm x 559 mm x 457 mm.
- Spill Containment Sump: 6.35 L.
- Estimated Ship Weight: 28.1 Kg.
- Number of Shelves: 1.
- Shelf Load: 159 Kg.
- Justrite standard color options: Yellow.

► List of Cabinets sku's

- ARSE CTJM1: 4G CAB MAN YL FLAM CTOP EX.
- ARSE CTJA1: 4G CAB SC YL FLAM CTOP EX.

4G (15L) Cabinet datasheet

