

NEC MultiSync® C501
LCD 50" Midrange Large Format Display

Datasheet



Seamless integration for great visual performance

Its thin bezel and super slim design perfectly complements today's modern surroundings whilst multiple display inputs support flexibility and freedom. With fixing points conveniently located on the back of the screen, external equipment can be attached with seamless simplicity. Reasonable brightness levels offer visibility in controlled light surroundings. The professional haze filter is allowing excellent readability. Landscape and portrait capability matches the needs of both corporate huddle spaces and retail signage applications. With a built-in media player, the NEC C Series runs content directly from a USB drive or microSDHC card as a standalone solution but can also download contents via network. Futureproof connectivity handles input from multiple sources. Don't let technology impact design – get seamless integration with the NEC C Series!

Benefits

FullHD LCD technology – eye-pleasing black levels and impressive contrast ratios for ergonomic viewing and less fatigue in conferencing scenarios.

Modern and slim design – robust yet elegant allowing for an unobtrusive integration into any application and environment.

Ease of use and operation – smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.

Mission-critical 24/7 ready operation – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

All-in-one Signage solution integrated – the integrated mediaplayer for simple signage use supports easy content playback and management.

Product Information

Product Name	NEC MultiSync® C501
Product Group	LCD 50" Midrange Large Format Display
Order Code	60004237

Display

Panel Technology	AMVA3 with Edge LED backlights
Active Screen Area (W x H) [mm]	1,095 x 616
Screen Size [inch/cm]	50 / 125.7
Brightness [cd/m²]	450, 280 Eco (shipment setting)
Contrast Ratio (typ.)	4000:1
Viewing Angle [°]	178 / 178 (at contrast ratio > 10:1)
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	6.5 (grey-to-grey)
Haze Level [%]	Pro (44)
Supported Orientation	Face Up ¹ ; Landscape; Portrait

Resolution

Native Resolution	1920 x 1080
Supported Resolutions	1024 x 768; 1280 x 800; 1440 x 900; 1920 x 1200; 1280 x 1024; 1280 x 960; 1600 x 1200; 800 x 600 1280 x 720; 1360 x 768; 1680 x 1050; 1280 x 768; 1400 x 1050; 1920 x 1080;

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 91.1 (analog and digital)
Vertical Frequency [Hz]	24 - 85

Connectivity

Input Video Analogue	1 x VGA
Input Video Digital	1 x DisplayPort (with HDCP); 3 x HDMI (with HDCP)
Input Audio Analogue	2 x 3,5 mm jack
Input Audio Digital	1 x DisplayPort; 3 x HDMI
Input Control	1 x LAN 100Mbit; 1 x Remote Control (3.5 mm jack); 1 x RS232
Input Data	1 x microSD (MediaPlayer); 1 x USB 2.0 (MediaPlayer)
Output Audio Analogue	1 x 3,5 mm jack
Output Control	remote control wire (3,5mm jack)

Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable

Electrical

Power Consumption [W]	65 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS

Environmental Conditions

Operating Temperature [°C] +0 to +40

Operating Humidity [%] 20 to 80

Mechanical

Dimensions (W x H x D) [mm] 1,125 x 645 x 45

Weight [kg] 16.1

Bezel Width [mm] 12.4 (left and right); 12.4 (top and bottom)

VESA Mounting [mm] 300 x 300 (FDMI); 4 holes; M6

Ingress Protection IP5X (front); IP2X (back)

MediaPlayer

Supported File Storage / File System MicroSDHC / FAT16, FAT32; USB 2.0 / FAT16, FAT32

Supported Image Formats JPG (baseline, progressive, RGB, CMYK); max. resolution 5000 x 5000; PNG (interlace, alpha channel); max. resolution 4000 x 4000

Supported Video Formats MP4 / MOV / FLV (video H.264, audio MP3, AAC); max. resolution 1080p at 30 Hz, 1080i at 60 Hz; MPG (video mpeg1/2, audio mpeg audio layer2/3, AAC-LC); MP @ ML, MP @ HL; WMV (video H.264, wmv advanced L3, wmv simple / main, audio mp3 wmv std); max. resolution 1080p at 30 Hz, 1080i at 60 Hz

Supported Audio Formats MP3 (MP3); max. bit-rate 320 kBit/s; WAV (LPCM); max. 48 kHz sampling

Available Options

Accessories Feet (ST-401); Trolley (PDMHM-L); Wall mount (PDW C L and P, PD02W T M L, PD03W T M P)

Green Features

Energy Efficiency Ambient light sensor; Carbon savings meter; Energy consumption: 81 kWh/1000 h; Energy efficiency class: G

Ecological Materials Manuals on CD; Optional feet

Ecological Standards EnergyStar 8.0

Additional Features

Special Characteristics Ambient Light Sensor; AMX NetLinX Support; ASCII Control Commands; Automated Email Alert; CEC Support; Crestron Connected Support; Crestron RoomView Support; Display Browser Control; Emergency Notification; Full System Scheduler; KeyGuide; MediaPlayer with Browser Control; NaViSet Administrator 2 - free download; OmniColor Control; OSD rotation for portrait mode; PjLink Support; Powered USB-Port; Removable Logo; Secure Mode Operation; Slim LED Indicator; SNMP Support; TileMatrix (10 x 10)

Colour Versions Black Front Bezel, Black Back Cabinet

Safety and Ergonomics CE; EMC Class B; FCC; PSB; RoHS; TÜV GS; UL/C-UL or CSA; VCCI

Pixel Failure Class ISO 9241-307, Class 2

Audio Integrated Speakers (10 W + 10 W)

Shipping Content CD-ROM (User Guides/Manuals); Display; HDMI Cable; Power Cable; Remote Control

Warranty 3 years warranty incl. backlight; additional services available

Operating Hours 24/7

¹ adjusted usage conditions for face up/down installations, please refer to operational guidelines or contact our support



VCCI



TÜV GS



RoHS



CE

This document is © 2024 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 27.04.2024