



NEC MultiSync® E506  
LCD 50" Essential Large Format Display

## Datasheet



### Enter the world of professional signage

In a digitised world, signage no longer is static. Information transfer via digital posters and information boards are common methods of information transfer. With E506 you can boost your business at low TCO, but with high reliability. Information where the audience stands close is perfectly transferred on this 50" screen. With the integrated media player, the display is designed for simple signage usage directly from a USB drive and once installed starts playing the content automatically at a certain time with the embedded autostart time schedule function. In this way the display helps you saving time and money. The 50" display of the 6<sup>th</sup> generation of our E Series is the perfect choice for essential applications in Retail Signage, Restaurants and Manufacturing & Engineering.

## Benefits

**Reduced Installation and Operating Costs** - highly energy efficient LED backlit display ensures low power consumption, longer backlight lifetime and lighter design for easy transportation, mounting and integration.

**Slim Design and Integrated Speakers** - the aesthetic design is pleasing to the eye and enables easy, low cost installation.

**Future Ready Connectivity** - featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

**Effortless content playback** - the integrated USB media player supports various image video file formats for effortless and standalone content playback.

**Professional integration** - enriched with essential RS232 functionality, IR and button lock out as well as digital audio output S/PDIF, the display can easily be integrated into professional applications in public environments.

## Product Information

Product Name	NEC MultiSync® E506
Product Group	LCD 50" Essential Large Format Display
Order Code	60004022

## Display

Panel Technology	S-PVA with direct LED backlight
Active Screen Area (W x H) [mm]	1.096 x 616
Screen Size [inch/cm]	50 / 127
Aspect Ratio	16:9
Brightness [cd/m <sup>2</sup> ]	350
Contrast Ratio (typ.)	3000:1
Viewing Angle [°]	176 horizontal / 176 vertical (typ. at contrast ratio 20:1)
Response Time (typ.) [ms]	8
Panel Refresh Rate [Hz]	60
Haze Level [%]	Standard (2)
Supported Orientation	Landscape

## Resolution

Native Resolution	1920 x 1080			
Supported Resolutions	1024 x 768; 1280 x 1024;	1280 x 720; 1280 x 800;	1920 x 1080; 640 x 480;	800 x 600
Supported on HDMI only	1080i (50 Hz); 1080i (60 Hz); 1080p (24 Hz);	1080p (30 Hz); 1080p (50 Hz); 1080p (60 Hz);	480i (60 Hz); 480p (60 Hz); 576i (50 Hz);	576p (50 Hz); 720p (50 Hz); 720p (60 Hz)

## Connectivity

Input Video Analogue	1 x VGA; Component (RCA); Composite (RCA)
Input Video Digital	3 x HDMI
Input Audio Digital	3 x HDMI
Output Audio Digital	1 x SPDIF
Remote Control	Remote Control IR; RS-232C (9-pin D-sub) Input

## Electrical

Power Consumption [W]	79 shipping
Power Savings Mode [W]	< 0.5 (ECO Standby)
Power Management	VESA DPMS

## Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	10 to 80
Storage Humidity [%]	5 to 85
Storage Temperature [°C]	-10 to +60

## Mechanical

Dimensions (W x H x D) [mm]	Without stand: 1.123 x 646 x 77
Weight [kg]	Without stand: 12.88
Bezel Width [mm]	11.9 (left, right and top); 14.9 (bottom)

VESA Mounting [mm] 4 holes; 400 x 200 (FDMI); M6

---

### MediaPlayer

Supported Video Container Formats	MPG, MPEG, MPEG2-TS, MPEG2-PS, MP4, MKV, AVI, Motion JPEG
Supported Video Codecs	MPEG1, MPEG2, H.264, JPEG
Supported Audio Codecs (Video)	MPEG Audio Layer 2, MPEG Audio Layer 3, AC-3

---

### Available Options

Accessories	Feet (ST-50E); Trolley (PDMHM-L); Wall mount (PDW S 32-55L)
-------------	---

---

### Green Features

Energy Efficiency	Annual energy consumption: 123 kWh (based on 4 operating hours per day); ECOMode; Energy efficiency class: A; LED backlight; Low power consumption
Ecological Standards	EnergyStar 7.0

---

### Additional Features

Special Characteristics	Audio settings with equalizer; Colour temperature mode; Energy saving picture mode; Mac and Windows compatible; Retail picture mode; Scheduler; USB Media Player
Safety and Ergonomics	C-tick; CE; Energy Star 7.0; FCC Class B; PSB; REACH; RoHS; SASO; UL/C-UL or CSA
Pixel Failure Class	ISO 9241-307, Class 3
Audio	Integrated Speakers (10 W + 10 W)
Shipping Content	Display; Power Cable; Remote Control; VGA cable
Warranty	3 years warranty incl. backlight
Operating Hours	12/7

---



C-tick



CE



RoHS



FCC Class B

This document is © 2024 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 25.04.2024