

ezWireLess Kit

A comprehensive security kit with a wireless NVR and Wi-Fi cameras.

Two options tailored to meet your needs:

4 Channel X5C (ezNVR) (1TB hard drive preloaded) + 1080p C3W (ezGuard) (2.8mm) × 4

8 Channel X5C (ezNVR) (1TB hard drive preloaded) + 1080p C3W (ezGuard) (2.8mm) × 4

X5C (ezNVR)

C3W (ezGuard)




Easy to set up

We pre-pair the X5C (ezNVR) and the C3W (ezGuard) for you. All you have to do is set up the X5C (ezNVR), and you are good to go!

Supports up to 4 or 8 Full HD Wi-Fi cameras

The X5C (ezNVR) supports up to 4 or 8 Full HD Wi-Fi cameras and provides multi-split screen modes for monitoring different rooms simultaneously and a strong wall-penetrating signal so that one X5C (ezNVR) can cover a whole store.




Sound and Light, Dual Protection

The C3W (ezGuard) has a compact design but powerful features. With light and sound alarms, it can effectively deterintruders.







Wireless NVR

Flexible and easy to set up

A wireless NVR with HDMI and VGA outputs that can support up to 4 or 8 HD Wi-Fi cameras and has a strong, wall-penetrating signal.

Key Features



Supports 720p/1080p cameras



Up to 6TB storage for 24/7 continuous live viewing and recording



Wi-Fi signal range up to 300ft/100m

BEZVIZ




Connect up to 8 1080p Wi-Fi cameras (720p default with 1080p manual option)



Supports ONVIF conformant cameras

Application Scenario



Specifications Model X5C-4,X5C-8

Network Specifications

Antenna Number 2

Maximum Wireless Access Bandwidth 30mbps

Maximum Wireless Range 100m

Radio Frequency 2.4 GHz

Ethernet Port One 10/100M adaptable Ethernet port

Wired Access Bandwidth 50mbps

Video Output

VGA 1 channel (Homologous to HDMI output)

HDMI 1 Channel

Audio/Video Codec

Access Camera Number 4 / 8

Video Compression H.264

Decoded Playback Supports 4*1080P / Supports 8*1080P

Video Record Management

Video Capture Manual video recording; dynamic detection video;

regular video recording; alarm recording

Backup Modes Supports hard disk backup, web application backup

HDD

Type One Built-in SATA port

Capability Supports 1TB to 6TB 3.5inch HDD

External Interface

Audio Output Support

Hardware Reset Support

USB2.0 Port

Dimensions (mm) 270mm x 235mm x 44.5mm

Net Weight <=900g



C3W (ezGuard)

Dual Sound and Light Protection

A HD/Full HD Wi-Fi camera with active defense, two-way audio and a durable design for all-weather protection.

Key Features



720p/1080p



Two-way audio. Pickup distance up to 5 meters.



Supports 2.4GHz Wi-Fi (IEEE802.11b, 802.11g,802.11n)



True Day/Night camera with auto-switching. Infrared night vision up to 30 meters.

SEZVIZ



IP66 Dustproof and Waterproof



Active Defense



Supports MicroSD card slot, up to 128GB



Specifications Model CS-CV310-A0-1B2WFR

Camera

Lens

Image Sensor 1/2.7" Progressive Scan CMOS

0.02Lux @(f/2.2, AGC ON), 0 Lux with IR Minimum Illumination

Shutter Speed Self-adaptive shutter

2.8mm@F2.2, Angle of View: 103°(Horizontal), 118°(Diagonal)

4mm@F2.0, Angle of View: 87°(Horizontal), 104°(Diagonal)

6mm@F2.0, Angle of View: 54°(Horizontal), 62°(Diagonal)

Day & Night IR-cut filter with auto-switching

M12 Lens Mount

Up to 98.4ft (30 meters) IR Range

DNR 3D DNR

WDR Digital WDR

Compression

Video Compression H.264 Main Profile

HD, Balanced and Smooth. Adaptive bit rate. Video Bit Rate

Image

1920x1080, supports dual-stream Max. Resolution

Image Settings Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)

BLC Support

Network Interface

Communication Interface RJ45 10M/100M self-adaptive Ethernet port * 1

Wireless Specifications

Standard IEEE802.11 b/g/n

Frequency Range 2.4GHz to 2.4835GHz

Channel Bandwidth Supports 20MHz

64/128-bit WEP, WPA/WPA2, Security

WPA-PSK/WPA2-PSK

Transmission Rate 11b: 11Mbps, 11g: 54Mbps, 11n: 135Mbps

General

Supports microSD card (≤ 128 GB) Storage

-22°F to 140 °F (-30°C ~ 60°C), Humidity 95% or less **Operating Conditions**

(non-condensing)

Power Supply DC12V±10%

Power Consumption 6W Max(ICR 9W)

150.44mm x 85.80mm x 71.64mm Dimensions

Weight 326g

IP Grade **IP66**

IR Range Max. 30 meters

Core Technology

Intelligent motion detection **Smart Alarm**

Wi-Fi Pairing Wi-Fi one-key configuration/ AP pairing

EZVIZ Cloud proprietary protocol Interface Protocol

Anti-Flicker, Dual-stream, Heartbeat Messages, Mirror Image, General Features

Password Protection, Watermark

Package Contents:

- 1080p FHD Wi-Fi Camera (with adapter) x 4 or 8
- 4/8 Channel Wireless NVR (with adapter) x1
- Power Extension Cord (18m/60ft) x 4
- Ethernet Cable (2m/6ft) x 1
- HDMI Cable (2m/6ft) x 1
- 1 TB Hard Drive (Installed) x 1
- Quick Start Guide x 1

Certificates

X5C (ezNVR) FCC/CE/UL/IC/NOM/REACH/WEEE/ROHS/IFETEL
C3W (ezGuard) - FCC/CE/KC/WEEE/RCM/UL/MON/REACH

Requirements

For X5C (ezNVR)

- Operating Conditions: 0°C-40°C, humidity 90% or less

For C3W (ezGuard)

- Operating Conditions: -30°C-60°C, humidity 95% or less

When placing an AP device, please make sure to keep it at least 3m/10ft from another AP device. When placing a wireless IP camera, please make sure to keep it at least 1m/3ft from other devices that may affect the signal.

Specifications are subject to change without notice. EZVIZ is a registered trademark of Hangzhou EZVIZ Network Co., Ltd.

Other brands and product names are trademarks or registered trademarks of their respective holders.