


Overview



HP 2620 Switch Series Family

Models

HP 2620-24 Switch

J9623A

HP 2620-24-PPoE+ Switch

J9624A

HP 2620-24-PoE+ Switch

J9625A

HP 2620-48 Switch

J9626A

HP 2620-48-PoE+ Switch

J9627A

Key features

- Cost-effective access layer switches
- Lite Layer 3 IPv4/IPv6 static and RIP routing
- 30 W PoE+ support on PoE models
- Gigabit fiber uplinks
- Enterprise-class features

Overview

Product overview

The HP 2620 Switch Series consists of five switches with 10/100 connectivity. The HP 2620-24 Switch is a fanless switch with quiet operation, making it ideal for deployments in open spaces. The HP 2620-24-PPoE+ Switch, HP 2620-24-PoE+ Switch, and HP 2620-48-PoE+ Switch are IEEE 802.3af- and IEEE 802.3at-compliant switches and provide up to 30 W per powered port. The HP 2620-48 Switch has variable speed fans for quiet operation.

All 2620 series switches include two 10/100/1000BASE-T ports and two SFP slots for Gigabit Ethernet uplink connectivity. An optional redundant external power supply is also available to provide redundancy in the event of a power supply failure.

With IPv4/IPv6 static and RIP routing, robust security and management features, free lifetime warranty, and free software updates, the HP 2620 Switch Series is a cost-effective solution for customers who are building converged enterprise edge networks.

Features and benefits

Quality of Service (QoS)

- **Layer 4 prioritization**
enables prioritization based on TCP/UDP port numbers
- **Traffic prioritization (IEEE 802.1p)**
allows real-time traffic classification into eight priority levels mapped to eight queues
- **Class of Service (CoS)**
sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- **Rate limiting**
sets per-port ingress enforced maximums and per-port, per-queue minimums

Connectivity

- **Auto-MDIX**
provides automatic adjustments for straight-through or crossover cables on all 10/100 and 10/100/1000 ports
- **IPv6**
 - **IPv6 host**
allows the switches to be managed and deployed at the edge of an IPv6 network
 - **Dual stack (IPv4/IPv6)**
provides a transition mechanism from IPv4 to IPv6; supports connectivity for both protocols
 - **MLD snooping**
forwards IPv6 multicast traffic to the appropriate interface; prevents IPv6 multicast traffic from flooding the network
- **IEEE 802.3af Power over Ethernet (PoE)**
provides up to 15.4 W per port to IEEE 802.3af-compliant PoE-powered devices such as IP phones, wireless access points, and security cameras
- **IEEE 802.3at Power Over Ethernet Plus**
provides up to 30 W per port to IEEE 802.3 for PoE-/PoE+-powered devices such as video IP phones, IEEE 802.11n wireless access points, and advanced pan/tilt/zoom security cameras
- **Pre-standard PoE support**
detects and provides power to pre-standard PoE devices; see list of supported devices in the product FAQ at www.hp.com/networking/support
- **Single IP address management**
provides single IP address management for a virtual stack of up to 16 switches

Resiliency and high availability

- **External redundant power supply**
provides high reliability



Overview

- **IEEE 802.3ad Link Aggregation Protocol (LACP) and HP port trunking**
support up to 24 trunks, each with up to 8 links (ports) per trunk
- **IEEE 802.1s Multiple Spanning Tree**
provides high link availability in multiple VLAN environments by allowing multiple spanning trees
- **NEW SmartLink**
provides easy-to-configure link redundancy of active and standby links

Manageability

- **Dual flash images**
provides independent primary and secondary operating system files for backup while upgrading
- **Friendly port names**
allows assignment of descriptive names to ports
- **Multiple configuration files**
stores easily to the flash image
- **Port mirroring**
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **sFlow (RFC 3176)**
delivers wire-speed traffic accounting and monitoring configured by SNMP and CLI with three terminal encrypted receivers
- **RMON (remote monitoring)**
provides advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Find-Fix-and-Inform**
finds and fixes common network problems automatically, then informs the administrator
- **NEW Comware CLI**
- **Comware-compatible CLI**
bridges the experience of HP Comware CLI users who are using the HP ProVision software CLI
- **Display and fundamental Comware CLI commands**
are embedded in the switch CLI as native commands; display output is formatted as on Comware-based switches, and fundamental commands provide a Comware-familiar initial switch setup
- **Configuration Comware CLI commands**
when Comware commands are entered, CLI help is elicited to formulate the correct ProVision software CLI command

Layer 2 switching

- **VLANs**
provide support for 512 VLANs and 4,094 VLAN IDs
- **Jumbo packet support**
improves the performance of large data transfers; supports frame size of up to 9220 bytes
- **IEEE 802.1v protocol VLANs**
isolate select non-IPv4 protocols automatically into their own VLANs
- **NEW Per-VLAN Spanning Tree Plus (PVST+)**
allows each VLAN to build a separate spanning tree to improve link bandwidth usage in network environments with multiple V

Layer 3 routing

- **Static IP routing**
provides manually configured routing; includes ECMP capability
- **Routing Information Protocol (RIP)**
provides RIPv1 and RIPv2 routing

Security

- **Access control lists (ACLs)**
provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number

Overview

- **Source-port filtering**
allows only specified ports to communicate with each other
- **RADIUS/TACACS+**
eases switch management security administration by using a password authentication server
- **Secure shell**
encrypts all transmitted data for secure remote CLI access over IP networks
- **Secure Sockets Layer (SSL)**
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Port security**
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC address lockout**
prevents particular configured MAC addresses from connecting to the network
- **Secure FTP**
allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Custom banner**
displays security policy when users log in to the switch
- **Identity-driven ACL**
enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- **STP BPDU port protection**
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **STP root guard**
protects the root bridge from malicious attacks or configuration mistakes
- **DHCP protection**
blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection**
blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **Multiple user authentication methods**
 - **IEEE 802.1X**
uses an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server to authenticate in accordance with industry standards
 - **Web-based authentication**
provides a browser-based environment, similar to IEEE 802.1X, to authenticate clients that do not support the IEEE 802.1X supplicant
 - **MAC-based authentication**
authenticates the client with the RADIUS server based on the client's MAC address
- **Authentication flexibility**
 - **Multiple IEEE 802.1X users per port**
provides authentication of multiple IEEE 802.1X users per port; prevents a user from "piggybacking" on another user's IEEE 802.1X authentication
 - **Concurrent IEEE 802.1X, Web, and MAC authentication schemes per port**
switch port will accept up to 32 sessions of IEEE 802.1X, Web, and MAC authentications
- **Port mirroring for network threats**
provides sampled port traffic using sFlow technology to the HP Network Immunity Manager (NIM) application for Network Behavior Anomaly Detection (NBAD) analysis to detect threats and mitigate threats at the port where the threat originated
- **Per-port broadcast throttling**
selectively configures broadcast control on heavy traffic port uplinks

Convergence

- **IP multicast snooping and data-driven IGMP**
automatically prevent flooding of IP multicast traffic
- **LLDP-MED (Media Endpoint Discovery)**
defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
facilitates easy mapping using network management applications with LLDP automated device discovery protocol

Overview

- **PoE and PoE+ allocations**
support multiple methods (automatic, IEEE 802.3at dynamic, LLDP-MED fine grain, IEEE 802.3af device class, or user specified) to allocate and manage PoE/PoE+ power for more efficient energy savings
- **LLDP-CDP compatibility**
receives and recognizes CDP packets from Cisco's IP phones for seamless interoperation

Monitor and diagnostics

- **Port mirroring**
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **Software updates**
free downloads from the Web

Flexibility

- **Quiet operation**
 - **Fanless design (2620-24 switch)**
enables quiet operation for deployment in open spaces
 - **Variable-speed fans (2620-24-PPoE+, 2620-24-PoE+, 2620-48, and 2620-48-PoE+ switches)**
improve fan speed for the operating environment while keeping noise and energy consumption levels to a minimum
- **Flexible mounting**
 - **Rackable**
can be mounted in a standard 19-inch rack using included hardware
 - **Surface mountable**
can be mounted above or below a surface (such as on a desk or table) using included hardware

Warranty and support

- **Lifetime Warranty 2.0**
advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)†
- **Electronic and telephone support (for Lifetime Warranty 2.0)**
limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**
to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

† Hardware warranty replacement for as long as you own the product, with next business day advance replacement (available in most countries) with a five-year hardware warranty replacement for the disk drive included with HP AllianceONE Services z1 Module, HP Threat Management Services z1 Module, HP PCM+ Agent with AllianceONE Services z1 Module, and HP MSM765 z1 Mobility Controller. For details, refer to the HP Software License, Warranty, and Support booklet at: www.hp.com/networking/warranty.

Configuration

Build To Order:

BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

HP 2620-24 Switch	J9623A
<ul style="list-style-type: none">• 2 autosensing 10/100/1000 port(RJ-45)• 24 autosensing 10/100 ports (RJ-45)• 2 open mini-GBIC (SFP) slots• min=0 \ max=2 SFP Transceivers• 1U - Height	See Configuration Note:1, 2
PDU CABLE NA/MEX/TW/JP	J9623A#B2B
<ul style="list-style-type: none">• C15 PDU Jumper Cord (NA/MEX/TW/JP)	
PDU CABLE ROW	J9623A#B2C
<ul style="list-style-type: none">• C15 PDU Jumper Cord (ROW)	
HP 2620-24 PPoe+ Switch	J9624A
<ul style="list-style-type: none">• 2 autosensing 10/100/1000 port(RJ-45)• 12 RJ-45 autosensing 10/100 ports• 12 RJ-45 autosensing 10/100 PoE+ ports• 2 open mini-GBIC (SFP) slots• min=0 \ max=2 SFP Transceivers• 1U - Height	See Configuration Note:1, 2
PDU CABLE NA/MEX/TW/JP	J9624A#B2B
<ul style="list-style-type: none">• C15 PDU Jumper Cord (NA/MEX/TW/JP)	
PDU CABLE ROW	J9624A#B2C
<ul style="list-style-type: none">• C15 PDU Jumper Cord (ROW)	
HP 2620-24-PoE+ Switch	J9625A
<ul style="list-style-type: none">• 2 autosensing 10/100/1000 port(RJ-45)• 24 RJ-45 autosensing 10/100 PoE+ ports• 2 open mini-GBIC (SFP) slots• min=0 \ max=2 SFP Transceivers• 1U - Height	See Configuration Note:1, 2
PDU CABLE NA/MEX/TW/JP	J9625A#B2B
<ul style="list-style-type: none">• C15 PDU Jumper Cord (NA/MEX/TW/JP)	
PDU CABLE ROW	J9625A#B2C
<ul style="list-style-type: none">• C15 PDU Jumper Cord (ROW)	
HP 2620-48 Switch	J9626A
<ul style="list-style-type: none">• 2 RJ-45 autosensing 10/100/1000 port (RJ-45)• 48 RJ-45 autosensing 10/100 ports (RJ-45)• 2 open mini-GBIC (SFP) slots• min=0 \ max=2 SFP Transceivers• 1U - Height	See Configuration Note:1, 2
PDU CABLE NA/MEX/TW/JP	J9626A#B2B
<ul style="list-style-type: none">• C15 PDU Jumper Cord (NA/MEX/TW/JP)	



Configuration

PDU CABLE ROW J9626A#B2C
• C15 PDU Jumper Cord (ROW)

HP 2620-48-PoE+ Switch J9627A
• 48 RJ-45 autosensing 10/100 PoE+ ports See
• 2 autosensing 10/100/1000 port (RJ-45) Configuration
• 2 open mini-GBIC (SFP) slots Note:1, 2
• min=0 \ max=2 SFP Transceivers
• 1U - Height

PDU CABLE NA/MEX/TW/JP J9627A#B2B
• C15 PDU Jumper Cord (NA/MEX/TW/JP)

PDU CABLE ROW J9627A#B2C
• C15 PDU Jumper Cord (ROW)

Configuration Rules:

Note 1 The following Transceivers install into this Switch:
J9054C - HP X111 100M SFP LC FX Transceiver
J9099B - HP X112 100M SFP LC BX-D Transceiver
J9100B - HP X112 100M SFP LC BX-U Transceiver
J4860C - HP X121 1G SFP LC LH Transceiver
J4859C - HP X121 1G SFP LC LX Transceiver
J4858C - HP X121 1G SFP LC SX Transceiver
J9142B - HP X122 1G SFP LC BX-D Transceiver
J9143B - HP X122 1G SFP LC BX-U Transceiver
J8177C - HP X121 1G SFP RJ45 T Transceiver

Note 2 Localization required on orders without #B2B or #B2C options.

Configuration Information - Factory Integrated Models - Box Level CTO

HP 2620-24 Swtich J9623A
• 2 autosensing 10/100/1000 port (RJ-45) See
• 24 autosensing 10/100 ports (RJ-45) Configuration
• 2 open mini-GBIC (SFP) slots Note:1, 2, 3
• min=0 \ max=2 SFP Transceivers
• 1U - Height

PDU CABLE NA/MEX/TW/JP J9623A#B2B
• C15 PDU Jumper Cord (NA/MEX/TW/JP)

PDU CABLE ROW J9623A#B2C
• C15 PDU Jumper Cord (ROW)

HP 2620-24 PPoe+ Switch J9624A
• 2 autosensing 10/100/1000 port (RJ-45) See
• 12 RJ-45 autosensing 10/100 ports Configuration
• 12 RJ-45 autosensing 10/100 PoE+ ports Note:1, 2, 3
• 2 open mini-GBIC (SFP) slots
• min=0 \ max=2 SFP Transceivers
• 1U - Height



Configuration

PDU CABLE NA/MEX/TW/JP	J9624A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU CABLE ROW	J9624A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
HP 2620-24-PoE+ Switch	J9625A
<ul style="list-style-type: none"> • 24 RJ-45 autosensing 10/100 PoE+ ports • 2 autosensing 10/100/1000 port(RJ-45) • 2 open mini-GBIC (SFP) slots • min=0 \ max=2 SFP Transceivers • 1U - Height 	See Configuration Note:1, 2, 3
PDU CABLE NA/MEX/TW/JP	J9625A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU CABLE ROW	J9625A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
HP 2620-48 Switch	J9626A
<ul style="list-style-type: none"> • 48 autosensing 10/100 ports (RJ-45) • 2 autosensing 10/100/1000 port(RJ-45) • 2 open mini-GBIC (SFP) slots • min=0 \ max=2 SFP Transceivers • 1U - Height 	See Configuration Note:1, 2, 3
PDU CABLE NA/MEX/TW/JP	J9626A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU CABLE ROW	J9626A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
HP 2620-48-PoE+ Switch	J9627A
<ul style="list-style-type: none"> • 48 RJ-45 autosensing 10/100 PoE+ ports • 2 autosensing 10/100/1000 port (RJ-45) • 2 open mini-GBIC (SFP) slots • min=0 \ max=2 SFP Transceivers • 1U - Height 	See Configuration Note:1, 2, 3
PDU CABLE NA/MEX/TW/JP	J9627A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU CABLE ROW	J9627A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	

Configuration Rules:

Note 1 The following Transceivers install into this Switch:

HP X111 100M SFP LC FX Transceiver	J9054C
HP X112 100M SFP LC BX-D Transceiver	J9099B
HP X112 100M SFP LC BX-U Transceiver	J9100B
HP X121 1G SFP LC LH Transceiver	J4860C
HP X121 1G SFP LC LX Transceiver	J4859C



Configuration

HP X121 1G SFP LC SX Transceiver	J4858C
HP X122 1G SFP LC BX-D Transceiver	J9142B
HP X122 1G SFP LC BX-U Transceiver	J9143B
HP X121 1G SFP RJ45 T Transceiver	J8177C

Note 2 Localization required on orders without #B2B or #B2C options.

Note 3 If this switch is factory installed in HP Universal Racks, Then the J9583A#0D1 is required.

Remarks:

Drop down under power supply should offer the following options and results:

Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)

- Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)

Internal Power Supplies

- Power supplies included in base model.

Enter the following menu selections as integrated to the CTO Model X server above if order is factory built.

Transceivers

SFP Transceivers		
HP X111 100M SFP LC FX Transceiver		J9054C
HP X112 100M SFP LC BX-D Transceiver		J9099B
HP X112 100M SFP LC BX-U Transceiver		J9100B
HP X121 1G SFP LC LH Transceiver		J4860C
HP X121 1G SFP LC SX Transceiver		J4858C
HP X121 1G SFP LC LX Transceiver		J4859C
HP X122 1G SFP LC BX-D Transceiver		J9142B
HP X122 1G SFP LC BX-U Transceiver		J9143B
HP X121 1G SFP RJ45 T Transceiver		J8177C

Cables

Multi-Mode Cables		
HP .5m Multi-mode OM3 LC/LC FC Cable		AJ833A
HP 1m Multi-mode OM3 LC/LC FC Cable		AJ834A



Configuration

HP 2 m Multimode OM3 LC/LC FC Cable	AJ835A
HP 5 m Multimode OM3 LC/LC FC Cable	AJ836A
HP 15 m Multimode OM3 LC/LC FC Cable	AJ837A
HP 30 m Multimode OM3 LC/LC FC Cable	AJ838A
HP 50 m Multimode OM3 LC/LC FC Cable	AJ839A
HP Premier Flex LC/LC OM4 2f 1m Cbl	QK732A
HP Premier Flex LC/LC OM4 2f 2m Cbl	QK733A
HP Premier Flex LC/LC OM4 2f 5m Cbl	QK734A
HP Premier Flex LC/LC OM4 2f 15m Cbl	QK735A
HP Premier Flex LC/LC OM4 2f 30m Cbl	QK736A
HP Premier Flex LC/LC OM4 2f 50m Cbl	QK737A

Switch Enclosure Options

Rack Mount Kit System (std 0 // max 1) User Selection (min 1 // max 1) per switch enclosure

HP X410 1U Univ 4-post Rack Mnt Kit	J9583A See Configuration Note:1
-------------------------------------	--

Note 1 Default with switch.

External Redundant Power supplies	HP 630 Red and/or External Power Supply Height = 1U	J9443A See Configuration Note:1, 2, 4
	HP 600 Redundant and Extrnl Power Supply Height = 1U	J8168A See Configuration Note:1, 3, 4

Rules:

Note 1 See BCS/HPN Rack Menu for integration details.

Note 2 Supported on J9625A, J9627A only.

Note 3 Supported on J9623A, J9624A, J9626A only.

Note 4 Localization required



Technical Specifications

HP 2620-24 Switch (J9623A)	I/O ports and slots	<p>24 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full</p> <p>1 RJ-45 serial console port</p> <p>2 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>2 open mini-GBIC (SFP) slots</p>
Physical characteristics	Dimensions	17.44(w) x 10(d) x 1.73(h) in (44.3 x 25.4 x 4.39 cm) (1U height)
	Weight	5.71 lb (2.59 kg), Fully loaded
Memory and processor	Processor	PowerPC FreeScale 8313 @ 400 MHz, 512 MB flash, 512 MB SDRAM, 4 MB flash ROM; packet buffer size: 1 MB
Mounting		Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
Performance	IPv6 Ready Certified	
	100 Mb Latency	< 8.3 μ s (LIFO 64-byte packets)
	1000 Mb Latency	< 2.9 μ s (LIFO 64-byte packets)
	Throughput	up to 9.5 million pps
	Routing/Switching capacity	12.8 Gb/s
	MAC address table size	16000 entries
Environment	Operating temperature	32°F to 131°F (0°C to 55°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 90% @ 149°F (65°C), noncondensing
	Altitude	up to 10,000 ft (3 km)
	Acoustic	Power: 0 dB, Pressure: 0 dB No Fan
Electrical characteristics	Achieved Miercom Certified Green Award	
	Frequency	50/60 Hz
	Maximum heat dissipation	95 BTU/hr (100.23 kJ/hr)
	AC voltage	100-127/200-240 VAC
	Maximum power rating	28 W
	Idle power	13.3 W
	PoE power	0 W
Safety		EN 60950/IEC 60950; CAN/CSA 22.2 No. 60950; EN 60825; UL 60950
Emissions		FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
Immunity	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6

Technical Specifications

	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management Services	command-line interface; Web browser	
	3-year, 4-hour onsite, 13x5 coverage for hardware (HS980E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (HS982E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HS987E)	
	3-year, 24x7 SW phone support, software updates (HS986E)	
	Installation with minimum configuration, system-based pricing (U4826E)	
	Installation with HP-provided configuration, system-based pricing (U4830E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (HS990E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (HS992E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HS997E)	
	4-year, 24x7 SW phone support, software updates (HS996E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (HT001E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware (HT003E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HT008E)	
	5-year, 24x7 SW phone support, software updates (HT007E)	
	3 Yr 6 hr Call-to-Repair Onsite (HS984E)	
	4 Yr 6 hr Call-to-Repair Onsite (HS994E)	
	5 Yr 6 hr Call-to-Repair Onsite (HT005E)	
	1-year, 4-hour onsite, 13x5 coverage for hardware (HS970E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware (HS972E)	
	1-year, 6 hour Call-To-Repair Onsite for hardware (HS974E)	
	1-year, 24x7 software phone support, software updates (HS976E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HS977E)	
	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS968E)	
	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS969E)	
	3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS978E)	
	3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS979E)	
	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS988E)	
	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS989E)	
	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS998E)	
	5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS999E)	

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

HP 2620-24-PPoE+ Switch (J9624A)	I/O ports and slots	<p>12 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full</p> <p>12 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full</p> <p>1 RJ-45 serial console port</p> <p>2 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>2 open mini-GBIC (SFP) slots</p>
Physical characteristics	Dimensions	17.44(w) x 10(d) x 1.73(h) in (44.3 x 25.4 x 4.39 cm) (1U height)
	Weight	7.03 lb (3.19 kg)
Memory and processor	Processor	PowerPC FreeScale 8313 @ 400 MHz, 512 MB flash, 512 MB SDRAM, 4 MB flash ROM; packet buffer size: 1 MB
Mounting		Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
Performance	IPv6 Ready Certified	
	100 Mb Latency	< 8.3 μ s (LIFO 64-byte packets)
	1000 Mb Latency	< 2.9 μ s (LIFO 64-byte packets)
	Throughput	up to 9.5 million pps
	Routing/Switching capacity	12.8 Gb/s
	MAC address table size	16000 entries
Environment	Operating temperature	32°F to 131°F (0°C to 55°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 90% @ 149°F (65°C), noncondensing
	Altitude	up to 10,000 ft (3 km)
	Acoustic	Power: 37.1 dB, Pressure: 25.9 dB
Electrical characteristics	Achieved Miercom Certified Green Award	
	Frequency	50/60 Hz
	Maximum heat dissipation	177 BTU/hr (186.74 kJ/hr), (switch only: 177 BTU/hr; combined switch + max. PoE devices: 679 BTU/hr)
	AC voltage	100-127/200-240 VAC
	Maximum power rating	38.5 W
	Idle power	22.0 W
	PoE power	128 W
Safety		EN 60950/IEC 60950; CAN/CSA 22.2 No. 60950; EN 60825; UL 60950
Emissions		FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
Immunity	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5

Technical Specifications

	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management Services	command-line interface; Web browser	
	3-year, 4-hour onsite, 13x5 coverage for hardware (HS980E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (HS982E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HS987E)	
	3-year, 24x7 SW phone support, software updates (HS986E)	
	Installation with minimum configuration, system-based pricing (U4826E)	
	Installation with HP-provided configuration, system-based pricing (U4830E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (HS990E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (HS992E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HS997E)	
	4-year, 24x7 SW phone support, software updates (HS996E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (HT001E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware (HT003E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HT008E)	
	5-year, 24x7 SW phone support, software updates (HT007E)	
	3 Yr 6 hr Call-to-Repair Onsite (HS984E)	
	4 Yr 6 hr Call-to-Repair Onsite (HS994E)	
	5 Yr 6 hr Call-to-Repair Onsite (HT005E)	
	1-year, 4-hour onsite, 13x5 coverage for hardware (HS970E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware (HS972E)	
	1-year, 6 hour Call-To-Repair Onsite for hardware (HS974E)	
	1-year, 24x7 software phone support, software updates (HS976E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HS977E)	
	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS968E)	
	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS969E)	
	3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS978E)	
	3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS979E)	
	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS988E)	
	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS989E)	
	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS998E)	
	5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS999E)	

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

HP 2620-24-PoE+ Switch (J9625A)	I/O ports and slots	<p>24 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Media Type: Auto-MDIX; Duplex: half or full</p> <p>1 RJ-45 serial console port</p> <p>2 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>2 open mini-GBIC (SFP) slots</p>
	Physical characteristics	<p>Dimensions 17.44(w) x 14.5(d) x 1.73(h) in (44.3 x 36.83 x 4.39 cm) (1U height)</p> <p>Weight 10.67 lb (4.84 kg), Fully loaded</p>
	Memory and processor	<p>Processor PowerPC FreeScale 8313 @ 400 MHz, 512 MB flash, 512 MB SDRAM, 4 MB flash ROM; packet buffer size: 1 MB</p>
	Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
	Performance	<p>IPv6 Ready Certified</p> <p>100 Mb Latency < 8.3 μs (LIFO)</p> <p>1000 Mb Latency < 2.9 μs (LIFO)</p> <p>Throughput up to 9.5 million pps</p> <p>Routing/Switching capacity 12.8 Gb/s</p> <p>MAC address table size 16000 entries</p>
	Environment	<p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 15% to 90% @ 149°F (65°C), noncondensing</p> <p>Altitude up to 10,000 ft (3 km)</p> <p>Acoustic Power: 34.0 dB, Pressure: 29.7 dB</p>
	Electrical characteristics	<p>Achieved Miercom Certified Green Award</p> <p>Frequency 50/60 Hz</p> <p>Maximum heat dissipation 270 BTU/hr (284.85 kJ/hr), (switch only: 270 BTU/hr; combined switch + max. PoE devices: 1751 BTU/hr)</p> <p>AC voltage 100-127/200-240 VAC</p> <p>Maximum power rating 39.5 W</p> <p>Idle power 22.8 W</p> <p>PoE power 382 W</p>
	Safety	EN 60950/IEC 60950; CAN/CSA 22.2 No. 60950; EN 60825; UL 60950
	Emissions	FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
	Immunity	<p>EN EN 55024, CISPR 24</p> <p>ESD IEC 61000-4-2</p> <p>Radiated IEC 61000-4-3</p> <p>EFT/Burst IEC 61000-4-4</p> <p>Surge IEC 61000-4-5</p>

Technical Specifications

	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management Services	command-line interface; Web browser	
	3-year, 4-hour onsite, 13x5 coverage for hardware (HS980E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (HS982E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HS987E)	
	3-year, 24x7 SW phone support, software updates (HS986E)	
	Installation with minimum configuration, system-based pricing (U4826E)	
	Installation with HP-provided configuration, system-based pricing (U4830E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (HS990E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (HS992E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HS997E)	
	4-year, 24x7 SW phone support, software updates (HS996E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (HT001E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware (HT003E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HT008E)	
	5-year, 24x7 SW phone support, software updates (HT007E)	
	3 Yr 6 hr Call-to-Repair Onsite (HS984E)	
	4 Yr 6 hr Call-to-Repair Onsite (HS994E)	
	5 Yr 6 hr Call-to-Repair Onsite (HT005E)	
	1-year, 4-hour onsite, 13x5 coverage for hardware (HS970E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware (HS972E)	
	1-year, 6 hour Call-To-Repair Onsite for hardware (HS974E)	
	1-year, 24x7 software phone support, software updates (HS976E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HS977E)	
	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS968E)	
	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS969E)	
	3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS978E)	
	3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS979E)	
	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS988E)	
	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS989E)	
	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS998E)	
	5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS999E)	

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Technical Specifications

HP 2620-48 Switch (J9626A)	I/O ports and slots	<p>48 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full</p> <p>1 RJ-45 serial console port</p> <p>2 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>2 open mini-GBIC (SFP) slots</p>
Physical characteristics	Dimensions	17.44(w) x 10(d) x 1.73(h) in (44.3 x 25.4 x 4.39 cm) (1U height)
	Weight	6.48 lb (2.94 kg), Fully loaded
Memory and processor	Processor	Power PC FreeScale 8313 @ 400 MHz, 512 MB flash, 512 MB SDRAM, 4 MB flash ROM; packet buffer size: 2 MB
Mounting		Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
Performance	IPv6 Ready Certified	
	100 Mb Latency	< 8.3 μ s (LIFO)
	1000 Mb Latency	< 2.9 μ s (LIFO)
	Throughput	up to 13.0 million pps
	Routing/Switching capacity	17.6 Gb/s
	MAC address table size	16000 entries
Environment	Operating temperature	32°F to 131°F (0°C to 55°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 90% @ 149°F (65°C), noncondensing
	Altitude	up to 10,000 ft (3 km)
	Acoustic	Power: 36.5 dB, Pressure: 24.5 dB
Electrical characteristics	Achieved Miercom Certified Green Award*	
	Frequency	50/60 Hz
	Maximum heat dissipation	148 BTU/hr (156.14 kJ/hr)
	Voltage	100-127/200-240 VAC
	Maximum power rating	43.5 W
	Idle power	19.4 W
Safety		EN 60950/IEC 60950; CAN/CSA 22.2 No. 60950; EN 60825; UL 60950
Emissions		FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
Immunity	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8

Technical Specifications

	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management Services	command-line interface; Web browser	
	3-year, 4-hour onsite, 13x5 coverage for hardware (HS980E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (HS982E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HS987E)	
	3-year, 24x7 SW phone support, software updates (HS986E)	
	Installation with minimum configuration, system-based pricing (U4826E)	
	Installation with HP-provided configuration, system-based pricing (U4830E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (HS990E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (HS992E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HS997E)	
	4-year, 24x7 SW phone support, software updates (HS996E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (HT001E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware (HT003E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HT008E)	
	5-year, 24x7 SW phone support, software updates (HT007E)	
	3 Yr 6 hr Call-to-Repair Onsite (HS984E)	
	4 Yr 6 hr Call-to-Repair Onsite (HS994E)	
	5 Yr 6 hr Call-to-Repair Onsite (HT005E)	
	1-year, 4-hour onsite, 13x5 coverage for hardware (HS970E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware (HS972E)	
	1-year, 6 hour Call-To-Repair Onsite for hardware (HS974E)	
	1-year, 24x7 software phone support, software updates (HS976E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HS977E)	
	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS968E)	
	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS969E)	
	3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS978E)	
	3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS979E)	
	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS988E)	
	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS989E)	
	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS998E)	
	5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS999E)	

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 2620-48-PoE+ Switch (J9627A)

I/O ports and slots

48 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Media Type:



Technical Specifications

	Auto-MDIX; Duplex: half or full
	1 RJ-45 serial console port
	2 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
	2 open mini-GBIC (SFP) slots
Physical characteristics	Dimensions 17.44(w) x 14.5(d) x 1.73(h) in (44.3 x 36.83 x 4.39 cm) (1U height)
	Weight 11.53 lb (5.23 kg), Fully loaded
Memory and processor	Processor Power PC FreeScale 8313 @ 400 MHz, 512 MB flash, 512 MB SDRAM, 4 MB flash ROM; packet buffer size: 2 MB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
Performance	IPv6 Ready Certified
	100 Mb Latency < 8.3 μ s (LIFO)
	1000 Mb Latency < 2.9 μ s (LIFO)
	Throughput up to 13.0 million pps
	Routing/Switching capacity 17.6 Gb/s
	MAC address table size 16000 entries
Environment	Operating temperature 32°F to 131°F (0°C to 55°C)
	Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 15% to 90% @ 149°F (65°C), noncondensing
	Altitude up to 10,000 ft (3 km)
	Acoustic Power: 34.0 dB, Pressure: 25.3 dB
Electrical characteristics	Achieved Miercom Certified Green Award
	Frequency 50/60 Hz
	Maximum heat dissipation 325 BTU/hr (342.88 kJ/hr), (switch only: 325 BTU/hr; combined switch + max. PoE devices: 1833 BTU/hr)
	AC oltage 100-127/200-240 VAC
	Maximum power rating 54.9 W
	Idle power 29.6 W
	PoE power 382 W
Safety	EN 60950/IEC 60950; CAN/CSA 22.2 No. 60950; EN 60825; UL 60950
Emissions	FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
Immunity	EN EN 55024, CISPR 24
	ESD IEC 61000-4-2
	Radiated IEC 61000-4-3
	EFT/Burst IEC 61000-4-4
	Surge IEC 61000-4-5
	Conducted IEC 61000-4-6
	Power frequency magnetic field IEC 61000-4-8

Technical Specifications

	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management Services	command-line interface; Web browser	
	3-year, 4-hour onsite, 13x5 coverage for hardware (HS980E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (HS982E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HS987E)	
	3-year, 24x7 SW phone support, software updates (HS986E)	
	Installation with minimum configuration, system-based pricing (U4826E)	
	Installation with HP-provided configuration, system-based pricing (U4830E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (HS990E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (HS992E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HS997E)	
	4-year, 24x7 SW phone support, software updates (HS996E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (HT001E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware (HT003E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HT008E)	
	5-year, 24x7 SW phone support, software updates (HT007E)	
	3 Yr 6 hr Call-to-Repair Onsite (HS984E)	
	4 Yr 6 hr Call-to-Repair Onsite (HS994E)	
	5 Yr 6 hr Call-to-Repair Onsite (HT005E)	
	1-year, 4-hour onsite, 13x5 coverage for hardware (HS970E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware (HS972E)	
	1-year, 6 hour Call-To-Repair Onsite for hardware (HS974E)	
	1-year, 24x7 software phone support, software updates (HS976E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HS977E)	
	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS968E)	
	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS969E)	
	3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS978E)	
	3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS979E)	
	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS988E)	
	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS989E)	
	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS998E)	
	5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS999E)	
	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
Standards and protocols (applies to all products in HTML and telnet management series)	Device management RFC 1591 DNS (client)	

Technical Specifications

General protocols

- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1v VLAN classification by Protocol and Port
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- IEEE 802.3ad Link Aggregation Control Protocol (LACP)
- IEEE 802.3x Flow Control
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 868 Time Protocol
- RFC 951 BOOTP
- RFC 1058 RIPv1
- RFC 1350 TFTP Protocol (revision 2)
- RFC 1542 BOOTP Extensions
- RFC 2030 Simple Network Time Protocol (SNTP) v4
- RFC 2131 DHCP
- RFC 2453 RIPv2
- RFC 3046 DHCP Relay Agent Information Option

IP multicast

- RFC 3376 IGMPv3 (host joins only)

IPv6

- RFC 1981 IPv6 Path MTU Discovery
- RFC 2460 IPv6 Specification
- RFC 2710 Multicast Listener Discovery (MLD) for IPv6
- RFC 2925 Remote Operations MIB (Ping only)
- RFC 3019 MLDv1 MIB
- RFC 3315 DHCPv6 (client only)
- RFC 3513 IPv6 Addressing Architecture
- RFC 3596 DNS Extension for IPv6
- RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6
- RFC 4022 MIB for TCP
- RFC 4113 MIB for UDP
- RFC 4251 SSHv6 Architecture
- RFC 4252 SSHv6 Authentication
- RFC 4253 SSHv6 Transport Layer
- RFC 4254 SSHv6 Connection
- RFC 4293 MIB for IP
- RFC 4419 Key Exchange for SSH
- RFC 4443 ICMPv6
- RFC 4541 IGMP & MLD Snooping Switch
- RFC 4861 IPv6 Neighbor Discovery
- RFC 4862 IPv6 Stateless Address Auto-configuration

MIBs

- RFC 1213 MIB II
- RFC 1493 Bridge MIB
- RFC 1724 RIPv2 MIB
- RFC 2021 RMONv2 MIB
- RFC 2096 IP Forwarding Table MIB
- RFC 2613 SMON MIB

Technical Specifications

RFC 2618 RADIUS Client MIB
RFC 2620 RADIUS Accounting MIB
RFC 2665 Ethernet-Like-MIB
RFC 2668 802.3 MAU MIB
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2737 Entity MIB (Version 2)
RFC 2863 The Interfaces Group MIB
RFC 2925 Ping MIB

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
RFC 3176 sFlow
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
SNMPv1/v2c/v3
XRMON

QoS/CoS

RFC 2474 DiffServ Precedence, including 8 queues/port
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
Ingress Rate Limiting

Security

IEEE 802.1X Port Based Network Access Control
RFC 1492 TACACS+
RFC 2138 RADIUS Authentication
RFC 2866 RADIUS Accounting
Secure Sockets Layer (SSL)

Accessories

HP 2620 Switch Series accessories

Transceivers	HP X121 1G SFP LC SX Transceiver	J4858C	
	HP X121 1G SFP LC LX Transceiver	J4859C	
	HP X121 1G SFP LC LH Transceiver	J4860C	
	HP X121 1G SFP RJ45 T Transceiver	J8177C	
	HP X111 100M SFP LC FX Transceiver	J9054C	
	HP X112 100M SFP LC BX-D Transceiver	J9099B	
	HP X112 100M SFP LC BX-U Transceiver	J9100B	
	HP X122 1G SFP LC BX-D Transceiver	J9142B	
	HP X122 1G SFP LC BX-U Transceiver	J9143B	
	Cables	HP 0.5 m Multimode OM3 LC/LC Optical Cable	AJ833A
HP 1 m Multimode OM3 LC/LC Optical Cable		AJ834A	
HP 2 m Multimode OM3 LC/LC Optical Cable		AJ835A	
HP 5 m Multimode OM3 LC/LC Optical Cable		AJ836A	
HP 15 m Multimode OM3 LC/LC Optical Cable		AJ837A	
HP 30 m Multimode OM3 LC/LC Optical Cable		AJ838A	
HP 50 m Multimode OM3 LC/LC Optical Cable		AJ839A	
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable		QK732A	
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable		QK733A	
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable		QK734A	
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable		QK735A	
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable		QK736A	
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable		QK737A	
Mounting Kit		HP X410 1U Universal 4-post Rack Mounting Kit	J9583A
HP 2620-24 Switch (J9623A)		HP 600 Redundant and External Power Supply	J8168A
HP 2620-24-PPoE+ Switch (J9624A)		HP 600 Redundant and External Power Supply	J8168A
HP 2620-24-PoE+ Switch (J9625A)	HP 630 Redundant and/or External Power Supply	J9443A	
	HP 620 Redundant/External Power Supply	J8696A	
HP 2620-48 Switch (J9626A)	HP 600 Redundant and External Power Supply	J8168A	
	HP 2620-48-PoE+ Switch (J9627A)	HP 630 Redundant and/or External Power Supply	J9443A
	HP 620 Redundant/External Power Supply	J8696A	

Accessory Product Details

HP X121 1G SFP LC SXPorts

Transceiver (J4858C)

Physical characteristics

A small form-factor pluggable (SFP) Gigabit SX

Environment

transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.

Electrical characteristics Cabling

1 LC 1000BASE-SX port; Duplex: full only

Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm)

Weight: 0.04 lb. (0.02 kg)

Transceiver form factor: SFP

Operating temperature: 32°F to 158°F (0°C to 70°C)

Operating relative humidity: 5% to 85%, noncondensing

Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C)

Altitude: up to 10,000 ft. (3 km)

Power consumption typical: 0.4 W

Power consumption maximum: 0.7 W

Type:

- 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;

Maximum distance:

- 2-220 m (62.5 µm core diameter, 160 MHz*km bandwidth)
- 2-275 m (62.5 µm core diameter, 200 MHz*km bandwidth)
- 2-500 m (50 µm core diameter, 400 MHz*km bandwidth)
- 2-550 m (50 µm core diameter, 500 MHz*km bandwidth)

Cable length: 2-550m

Fiber type: Multi Mode

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X121 1G SFP LC LXPorts

Transceiver (J4859C)

Physical characteristics

HP X121 1G SFP LC LX Transceiver: An SFP format

Environment

gigabit transceiver with LC connectors using LX technology.

Cabling

1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only

Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm)

Weight: 0.04 lb. (0.02 kg)

Operating temperature: 32°F to 158°F (0°C to 70°C)

Operating relative humidity: 0% to 85%, noncondensing

Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C)

Altitude: up to 10,000 ft. (3 km)

Type:

- Either single mode or multimode; 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;

Maximum distance:

- 2-550 m (multimode 62.5 µm core diameter, 500 MHz*km bandwidth)
- 2-550 m (multimode 50 µm core diameter, 400 MHz*km bandwidth)
- 2-550 m (multimode 50 µm core diameter, 500 MHz*km bandwidth)
- 2-10,000 m (single-mode fiber)

Accessory Product Details

Notes	A mode conditioning patch cord may be needed in some multimode fiber installations. Wavelength: 1310nm Power Consumption: < 500mW Typical
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X121 1G SFP LC LHPorts Transceiver (J4860C)

A small form-factor pluggable (SFP) Gigabit LH transceiver that provides a full-duplex Gigabit solution up to 70 km on single-mode fiber.

Physical characteristics Environment

1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics); Duplex: full only
Dimensions: 2.17(d) x 0.60(w) x 0.46(h) in. (5.5 x 1.53 x 1.18 cm)
Weight: 0.04 lb. (0.02 kg)
Operating temperature: -40°F to 185°F (-40°C to 85°C)
Operating relative humidity: 0% to 95% @ 77°F (25°C), noncondensing
Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)
Altitude: up to 10,000 ft. (3 km)

Cabling

Cable type:

- Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;

Maximum distance:

- 10-70,000 m (single-mode fiber)

Notes

Power consumption is 0.8 watts typical with 1 watt maximum at 100% utilization.
For distances less than 20 km, a 10 dB attenuator must be used.
For distances between 20 km and 40 km, a 5 dB attenuator must be used.

Attenuators can be purchased from most cable vendors.

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP X121 1G SFP RJ45 T Transceiver (J8177C)	Ports	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T); Duplex: full only
HP X121 1G SFP RJ45 T Transceiver: An SFP format gigabit transceiver with RJ45 connectors using 1000BaseT technology.	Physical characteristics	Dimensions: 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm) Weight: 0.06 lb. (0.03 kg)
	Environment	Operating temperature: 32°F to 158°F (0°C to 70°C); with 100 LFM airflow over the SFP module Operating relative humidity: 0% to 95% @ 75°F (25°C), noncondensing Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C) Nonoperating/Storage relative humidity: 0% to 95% @ 77°F (25°C), noncondensing Altitude: up to 10,000 ft. (3000 km)
	Cabling	Cable type: 1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T; Maximum distance: <ul style="list-style-type: none">• 100 m
	Notes	Power consumption is nominally 1 watt. For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J8177C 1000Base-T Mini-GBIC" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J8177C Gigabit copper mini-GBIC is not supported on dual-personality ports. The J8177C is capable of 100 Mb operation. This is supported on only the HP E8200zl, E5400zl, and HP E6200-24G-mGBIC y1 Switches using software version K.12.21 or later. Use the "auto-100" port setting to enable 100 Mb operation. Important: The earlier J8177B does not support 100 Mb operation. When used in the Switch gl 20-Port 10/100/1000 Module (J4908A), the J8177C mini-GBIC can be installed in either the upper or lower mini-GBIC port, but will block access to the other port.
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

<p>HP X111 100M SFP LC FX Transceiver (J9054C)</p>	<p>Ports</p> <p>Physical characteristics</p> <p>Environment</p> <p>Cabling</p>	<p>1 LC 100BASE-FX port (IEEE 802.3u Type 100BASE-FX); Duplex: half or full</p> <p>Dimensions: 2.7(d) x 0.54(w) x 0.48(h) in. (6.86 x 1.38 x 1.22 cm)</p> <p>Weight: 0.06 lb. (0.03 kg)</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity: 5% to 95%</p> <p>Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)</p> <p>Nonoperating/Storage relative humidity: 5% to 85%</p> <p>Altitude: up to 10,000 ft. (3 km)</p> <p>Type:</p> <ul style="list-style-type: none"> • 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively <p>Maximum distance:</p> <ul style="list-style-type: none"> • 2 km (full duplex) or 412 m (half duplex)
<p>Notes</p>	<p>Transmitter wavelength: 1310nm</p> <p>Power consumption is 1.1 watt maximum.</p>	<p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J9054B 100-FX SFP-LC Transceiver" on the "HP Mini-GBICs and SFPs" Manuals Web page.</p>
<p>Services</p>	<p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	

<p>HP X112 100M SFP LC BX-D Transceiver (J9099B)</p> <p>A small form-factor pluggable (SFP) 100-Megabit BX (bi-directional) "downstream" transceiver that provides 100 Mbps full-duplex connectivity up to 10 km on one strand of singlemode fiber. The J9099B connects to the J9100B "upstream" transceiver, or to any IEEE-standard 100BASE-BX10-U ("upstream") device.</p>	<p>Ports</p> <p>Physical characteristics</p> <p>Environment</p> <p>Cabling</p> <p>Notes</p>	<p>1 LC 100BASE-BX10 port (IEEE 802.3ah Type 100BASE-BX10-D); Duplex: full only</p> <p>Dimensions 2.7(d) x 0.55(w) x 0.48(h) in. (6.86 x 1.39 x 1.22 cm)</p> <p>Weight 0.04 lb. (0.03 kg)</p> <p>Operating temperature 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity 0% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)</p> <p>Type:</p> <p>Single-mode fiber optic, complying with ITU-T G.652;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • 0.5-10,000 m (single-mode fiber) <p>Transmit wavelength: 1550 nm. Receive wavelength: 1310 nm.</p> <p>Power consumption is 1.1 watt maximum.</p> <p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J9099B connects to the J9100B "upstream" transceiver, or to any IEEE-standard 100BASE-BX10-U ("upstream") device. (A 100-BX-D transceiver can only connect to a 100-BX-U product. You cannot connect two 100-BX-D transceivers together.)</p>
--	--	--

Accessory Product Details

	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.
<p>HP X112 100M SFP LC BX-U Transceiver (J9100B)</p> <p>A small form-factor pluggable (SFP) 100-Megabit BX (bi-directional) "upstream" transceiver that provides 100 Mbps full-duplex connectivity up to 10 km on one strand of singlemode fiber. The J9100B connects to the J9099B "downstream" transceiver, or to any IEEE-standard 100BASE-BX10-D ("downstream") device.</p>	Ports	1 LC 100BASE-BX10 port (IEEE 802.3ah Type 100BASE-BX10-U); Duplex: full only
	Physical characteristics	<p>Dimensions 2.7(d) x 0.55(w) x 0.48(h) in. (6.86 x 1.39 x 1.22 cm)</p>
	Environment	<p>Weight 0.07 lb. (.03 kg)</p>
		<p>Operating temperature 32°F to 158°F (0°C to 70°C)</p>
		<p>Operating relative humidity 0% to 95%, noncondensing</p>
		<p>Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)</p>
	Cabling	<p>Type:</p> <p>Single-mode fiber optic, complying with ITU-T G.652;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • 0.5-10,000 m (single-mode fiber)
Notes	<p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J9100B connects to the J9099B "downstream" transceiver, or to any IEEE-standard 100BASE-BX10- D ("downstream") device. (A 100-BX-U transceiver can only connect to a 100-BX-D product. You cannot connect two 100-BX-U transceivers together.)</p> <p>Transmit wavelength: 1310 nm. Receive wavelength: 1550 nm.</p> <p>Power consumption is 1.1 watts maximum.</p>	
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Accessory Product Details

<p>HP X122 1G SFP LC BX-D Transceiver (J9142B)</p> <p>A small form-factor pluggable (SFP) Gigabit-BX (bi-directional) "downstream" transceiver that provides a full-duplex Gigabit solution up to 10 km on one strand of single-mode fiber. The J9142B connects to the J9143B "upstream" transceiver, or to any IEEE-standard 1000BASE-BX10-U ("upstream") device.</p>	<p>Ports</p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only</p> <p>Physical characteristics</p> <p>Dimensions 2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)</p> <p>Weight 0.04 lb. (0.02 kg)</p> <p>Environment</p> <p>Operating temperature 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity 0% to 95%, non-condensing</p> <p>Non-operating/ Storage temperature -40°F to 185°F -40°C to 85°C</p> <p>Cabling</p> <p>Type: Single-mode fiber optic, complying with ITU-T G.652;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • 0.5-10,000 m (single-mode fiber) <p>Notes</p> <p>Transmit wavelength: 1490 nm. Receive wavelength: 1310 nm. Power consumption is 1 watt maximum. For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J9142B connects to the J9143B "upstream" transceiver, or to any IEEE-standard 1000BASE-BX10-U ("upstream") device. (A 1000-BX-D transceiver can only connect to a 1000-BX-U product. You cannot connect two 1000-BX-D transceivers together.)</p> <p>Services</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
---	--

<p>HP X122 1G SFP LC BX-U Transceiver (J9143B)</p> <p>A small form-factor pluggable (SFP) Gigabit-BX (bi-directional) "upstream" transceiver that provides a full-duplex Gigabit solution up to 10 km on one strand of single-mode fiber. The J9143B connects to the J9142B "downstream" transceiver, or to any IEEE-standard 1000BASE-BX10-D ("downstream") device.</p>	<p>Ports</p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only</p> <p>Physical characteristics</p> <p>Dimensions 2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)</p> <p>Weight 0.04 lb. (0.02 kg)</p> <p>Environment</p> <p>Operating temperature 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity 0% to 95%, non-condensing</p> <p>Non-operating/ Storage temperature -40°F to 185°F -40°C to 85°C</p> <p>Cabling</p> <p>Type: Single-mode fiber optic, complying with ITU-T G.652;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • 0.5-10,000 m (single-mode fiber) <p>Notes</p> <p>Transmit wavelength: 1310 nm. Receive wavelength: 1490 nm. For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J9143B connects to the J9142B "downstream" transceiver, or to any IEEE-standard 1000BASE-BX10-D ("downstream") device. (A 1000-BX-U transceiver can only connect to a 1000-BX-D product. You cannot connect two 1000-BX-U transceivers together.)</p>
---	---



Accessory Product Details

Services

Power consumption is 1 watt maximum.

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP 1 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ834A)**

Notes

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP 2 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ835A)**

Notes

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.

Accessory Product Details

- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
 - Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
 - Jacket Color: Aqua for OM3 multimode per TIA 598
 - Boot Color: White
 - Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
 - Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
 - Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg
- Services** Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5 m Multimode OM3 Cabling LC/LC Optical Cable (AJ836A)

- Cable type:**
50/125 µm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;
- Maximum distance:**
10Gbps Transfer Rate (Ethernet): 300m
- Notes** Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.
- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
 - Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
 - Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
 - CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
 - BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
 - Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
 - Jacket Color: Aqua for OM3 multimode per TIA 598
 - Boot Color: White
 - Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
 - Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
 - Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg
- Services** Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.

Accessory Product Details

- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP Premier Flex LC/LC Notes
Multi-mode OM4 2 fiber
1m Cable (QK732A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP Premier Flex LC/LC Notes
Multi-mode OM4 2 fiber
2m Cable (QK733A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC Notes
Multi-mode OM4 2 fiber
5m Cable (QK734A)**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC Notes
Multi-mode OM4 2 fiber
15m Cable (QK735A)**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC Notes
Multi-mode OM4 2 fiber
30m Cable (QK736A)**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC Notes
Multi-mode OM4 2 fiber
50m Cable (QK737A)**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP X410 1U Universal 4-post Rack Mounting Kit (J9583A)

Notes	The rack mounting kit supports the 1U, full width switches in the following switch series and the power supply: V1810 Series, E2510 Series, E2520 Series, E2610 Series, E2810 Series, E2910 Series, E3500 Series, and the E620 Power Supply This universal rack mounting kit is design to fit the following racks: HP 10K 10642, HP 10K 10842, Panduit CN, Panduit CS, Wrightline Vantage S2, APC Netshelter 600mm, and APC Netshelter 800mm. It may well fit many other brands and models too.
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 600 Redundant and Ports External Power Supply (J8168A)

Physical characteristics	<p>6 redundant power supply ports Restrictions: Each port can provide redundant +12 V power to a connected switch; only one port can provide power at a given time</p> <p>2 external power supply ports Restrictions: Provides 50 VDC external PoE to up to two switch devices; provides max. of 408 W full power to one device, and half power (204 W each) if connected to two devices</p> <p>Dimensions 12.83(d) x 17.44(w) x 1.73(h) in. (32.59 x 44.3 x 4.39 cm) (1U height)</p> <p>Weight 11.78 lb. (5.34 kg), Fully loaded</p>
Mounting	1U rack-mountable and wall-mountable enclosure using standard mounting hardware
Environment	<p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 15% to 95% @ 149°F (65°C), noncondensing</p> <p>Altitude up to 15,000 ft. (4.6 km)</p> <p>Acoustic Noise emission LwA=59.2 dB at virtual workspace, according to DIN 45635 T.19</p>
Electrical characteristics	<p>Description The unit automatically adjusts to any voltage between 100-240 V and either 50 or 60 Hz</p> <p>Voltage 100-240 VAC</p> <p>Current 9/5 A</p> <p>Maximum power rating 800 W</p> <p>RPS power 180 W</p> <p>PoE power 408 W</p> <p>Frequency 50/60 Hz</p> <p>Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>
Safety	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950
Emissions	FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
Immunity	EN EN 55024, CISPR 24

Accessory Product Details

ESD	IEC 61000-4-2; 4 kV CD, 8 kV AD
Radiated	IEC 61000-4-3; 3 V/m
EFT/Burst	IEC 61000-4-4; 1.0 kV (power line), 0.05 kV (signal line)
Surge	IEC 61000-4-5; 1 kV/2 kV AC
Conducted	IEC 61000-4-6; 3 V
Power frequency magnetic field	IEC 61000-4-8; 1 A/m, 50 or 60 Hz
Voltage dips and interruptions	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods
Harmonics	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3

Management Notes

Provides information via port interfaces of attached devices
Supported devices

- HP Switch 2600-PWR Series, Switch 2610 Series, Switch 2610-PWR Series, Switch 2800 Series, Switch 2810 Series, Switch 5300xl Series, Switch 3400cl Series, Switch 6400cl Series, and Secure Router 7000dl Series

Services

3-year, 4-hour onsite, 13x5 coverage for hardware (U9270E)
3-year, 4-hour onsite, 24x7 coverage for hardware (U9271E)
4-year, 4-hour onsite, 13x5 coverage for hardware (UR854E)
4-year, 4-hour onsite, 24x7 coverage for hardware (UR855E)
5-year, 4-hour onsite, 13x5 coverage for hardware (UR857E)
5-year, 4-hour onsite, 24x7 coverage for hardware (UR858E)
3 Yr 6 hr Call-to-Repair Onsite (UW371E)
4 Yr 6 hr Call-to-Repair Onsite (UW372E)
5 Yr 6 hr Call-to-Repair Onsite (UW373E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 630 Redundant and/or External Power Supply (J9443A)

Physical characteristics

Dimensions 15(d) x 8.5(w) x 1.73(h) in. (38.1 x 21.59 x 4.39 cm) (1U height)

Environment

Weight 7.9 lb. (3.58 kg)

Operating temperature 32°F to 131°F (0°C to 55°C)

Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing

Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)

Nonoperating/Storage relative humidity 15% to 90% @ 149°F (65°C), noncondensing

Altitude up to 10,000 ft. (3 km)

Acoustic Power: 54.2 dB; ISO 7779, ISO 9296

Electrical characteristics

Maximum heat dissipation 535 BTU/hr (564.42 kJ/hr), for the actual 630 power supply. PoE-powered device heat dissipation assumed to be outside the 630 power supply.

Voltage 100-127/200-240 VAC

Current 8/4 A



Accessory Product Details

Maximum power rating	740 W
PoE power	398 W
RPS power	185 W
PoE power	398 W
Frequency	50/60 Hz
Notes	<p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).</p> <p>200-240 V power cords shipped with the 630 power supply have a wall plug rated as close to 13 A as specific country standards allow.</p>

Notes	<p>The HP 630 RPS/EPS supports the HP 2910al and 3500yl-PoE+ Switches. The HP Switch 5400zl Series is not supported.</p> <p>The 630 RPS/EPS includes two 2-m RPS/EPS cables, which can be used to carry either RPS or PoE+ power to the switch.</p> <p>Minimum software versions required: 2910al PoE+ switches require W.14.35 or later and 3500yl-PoE+ switches require K.14.52 or later</p>
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (U9270E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (U9271E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR854E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR855E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR857E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR858E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW371E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW372E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW373E)</p> <p>Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

HP E620 Redundant/External Power Supply (J8696A)	Ports	<p>2 redundant power supply ports</p> <p>Restrictions: 195 W available per port</p>
		<p>2 external power supply ports</p> <p>Restrictions: 398 W available per port</p>
	Physical characteristics	<p>Dimensions 15.4(d) x 17.4(w) x 1.73(h) in. (39.12 x 44.2 x 4.39 cm) (1U height)</p> <p>Weight 15.2 lb. (6.89 kg)</p>
	Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
	Environment	<p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing</p>

Accessory Product Details

	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 90% @ 149°F (65°C), noncondensing
	Altitude	up to 10,000 ft. (3 km)
	Acoustic	LwA per ISO 7779: 54.2 dB
Electrical characteristics	Maximum heat dissipation	400 BTU/hr (422 kJ/hr), for the actual 620 itself. PoE-powered device heat dissipation assumed to be outside the 620.
	Voltage	100-127/200-240 VAC
	Current	16/8 A
	Maximum power rating	1440 W
	RPS power	390 W
	PoE power	796 W
	RPS	12 V
	PoE	-50 V
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. Above figures are for maximum RPS and PoE power being supplied to two switches simultaneously. 200 - 240 V power cords shipped with the 620 have a wall plug rated as close to 13 A as specific country standards allow.
Safety		CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950
Emissions		FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
Immunity	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management		Unmanaged power supply; provides information via LEDs (LEDs repeated on front and back panel) or through port interfaces of attached devices
Notes		The 620 supports the HP Switch 2900 Series (RPS) and 3500yl Series (RPS/PoE), as well as 6200yl (RPS) switches. The HP Switch 5400zl Series is not supported. The 620 includes four 2 m RPS/EPs cables. These cables can be used to carry either RPS or PoE power to the switch being powered.

Accessory Product Details

Services

3-year, 4-hour onsite, 13x5 coverage for hardware (U9270E)
3-year, 4-hour onsite, 24x7 coverage for hardware (U9271E)
4-year, 4-hour onsite, 13x5 coverage for hardware (UR854E)
4-year, 4-hour onsite, 24x7 coverage for hardware (UR855E)
5-year, 4-hour onsite, 13x5 coverage for hardware (UR857E)
5-year, 4-hour onsite, 24x7 coverage for hardware (UR858E)
3 Yr 6 hr Call-to-Repair Onsite (UW371E)
4 Yr 6 hr Call-to-Repair Onsite (UW372E)
5 Yr 6 hr Call-to-Repair Onsite (UW373E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit: www.hp.com/networking

© Copyright 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.