

MasterPulse Pro

Virtual 7.1 Channel Surround Sound with Exclusive Bass FX Technology



Product Features

- Groundbreaking audio experience Virtual 7.1 channel surround and 44mm drivers provide superior sound and immerse you in the experience
- Patented Bass FX technology Exclusive bass effect design lets you apply a responsive bass boost by simply putting on or taking off side panels
- Sound card with in-line remote control box Toggle 7.1 surround, switch listening modes, adjust volume and microphone settings
- Colorful mood RGB LEDs in the ear cups offer multi-color illumination allowing you to adjust the overall look either based on your rig's color scheme or your outfit
- Extreme comfort Extra padded ear cups and suspension headband ensure both high comfort and great noise cancelation

D						0.00	
$D \supset C$		Δ	nt	Or.	ms	ı tı	On
Pac	nau	-1		OI.	HIC	וטו	OH

Package Information					
Package Dimensions	25.3*23.8*10.7 cm				
	9.96*9.37*4.21 inch				
Carton Dimensions	56.5*49.2*27.8cm				
	22.24*19.37*10.94 inch				
Pallet Dimensions	120*100*206.6cm				
	47.24*39.37*81.34 inch				
Unit / Cartons	10 PCS				
Carton / Pallet	28 ctns				
20' Container	2800 pcs				
40' Container	5880 pcs				

On top of a full suite of advanced components, crystal-clear 7.1 channel audio and 44mm drivers, MasterPulse Pro over-ear headset features Bass FX - removable magnetic side panels that allow you to customize your audio experience. Close the panels to increase the treble and passive noise isolation or remove them to open up sound and enhance bass tones. The inline remote control box allows for quick on-the-fly adjustments while the padded ear cups and suspension headband ensures a comfortable fit. Ear cups also offer illumination with multiple color options. Control "the beat at your fingertips" with the MasterPulse

Pro over-ear headset. Specification

UPC code

Earphones				
Driver	44mm driver			
Frequency Response	20~20,000Hz			
Impedance	50Ω			
Sensitivities (@100Hz)	118 dB ±3 dB			
	109 dB ± 3 dB (bass off)			
Max output power	100mW			
Cable Length	2m			
Connector	USB gold-plated			

Microphone			
Pick-up Pattern	Omni-Directional		
Frequency Response	100~10,000Hz		
Sensitivity	-34±3 dB		
	(0dB=1V/pa.1KHz)		
Signal to Noise Ratio	50dB or More		
EAN code	4719512052471		

884102028588

