MW6463056CEMFGN(A)

Aquia® IV WASHLET®+ S550e One-Piece Toilet - 1.28 & 0.9 GPF

FEATURES

- Concealed supply connection for seamless installation
- DYNAMAX TORNADO FLUSH® utilizes 360° cleaning power to reach every part of the bowl
- Ultra high-efficiency dual flush 1.28 & 0.9 GPF (4.8 & 3.4 LPF)
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces
- Completely skirted design for a sleek and understated look that's easier to clean
- UNIVERSAL HEIGHT
- Chrome push-button
- 12" Rough-in
- Elongated front bowl toilet and WASHLET+ S550e set
- EWATER+® auto-cleans wand and bowl
- On-demand remote function cleans wand with EWATER+
- PREMIST® of bowl before each use
- Remote control operated
- Auto flush available as upgrade
- Auto Open / Close lid
- Night light

MODELS

MW6463056CEMFGNA (#01)

With CEFIONTECT ceramic glaze, WASHLET+ S550e with contemporary design and Auto Flush

- CST646CEMFGNAT40
 Elongated bowl with CEFIONTECT
- **SW3056AT40** WASHLET+ S550e
- THU765
 Auto Flush Kit
- MW6463056CEMFGN (#01)

Same as MW6463056CEMFGNA without Auto Flush

OPTIONAL COMPONENTS

- TSU48.10 10" Unifit Rough-In
- TSU48.14 14" Unifit Rough-In
- 9AU321-A
- THU848#01-A

Push Button Assembly - Cotton

- THU848#PN-A
 - Push Button Assembly Polished Nickel
- THU848#BN-A

Push Button Assembly - Brushed Nickel

COLORS/FINISHES

• #01 Cotton













PRODUCT SPECIFICATION

The one-piece, ultra high-efficiency, DYNAMAX TORNADO FLUSH toilet shall be dual flush 1.28 GPF/0.9 GPF. Toilet shall be coated with CEFIONTECT, elongated front bowl, high profile tank, UNIVERSAL HEIGHT, complete skirted bowl and chrome pushbutton.

Toilet shall be TOTO Model MW6463056CEMFGN_#01.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1, ASME A112.19.14
- Certifications: IAPMO(cUPC®), EPA WaterSense,
 State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- Complies with CA Prop 65 warning requirements
- ADA compliant (MW6463056CEMFGNA only)







Aquia® IV WASHLET®+ S550e One-Piece Toilet - 1.28 & 0.9 GPF

SPECIFICATIONS


Water Use	1.28 & 0.9 GPF (4.8 & 3.4 LPF)
Flush System	DYNAMAX TORNADO FLUSH®
Min. Water Pressure	8 psi (Flowing)
Water Surface	7" × 5"
Trap Diameter	2-1/4"
Rough-in	12" (10" and 14" options available)
Trap Seal	2-1/8"
Warranty	One Year Limited Warranty
Material	Vitreous China
Shipping Weight	112 lbs.
Shipping Dimensions	29-1/2" L x 17-5/8" W x 28-1/8" H

See SW3056AT40 Specification Sheet for details on included WASHLET.

INSTALLATION NOTES


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS



TOTO_®

These dimensions and specifications are subject to change without notice