



All the features of
industry tested UltraLife™

ultra life+™

Sizes available:
2430, 3030 Std., Long stroke, 3036 Std. & Long stroke, 3036

PREMIUM SPRING BRAKES

To Go Where No Spring Brake Has Gone Before

- Proprietary TSE All-N-One™ integrated pressure plate and diaphragm assembly eliminating plate shifting, increasing power spring and diaphragm life.
- Proprietary TSE Sealed When It Counts™ utilizes air pressure in chamber to push the diaphragm against the housing drain holes to create a secure seal against moisture and contaminants while driving. When parked, drain holes open up to allow draining and ventilation. (see drawing)
- New urethane powder coating applied over our proven 8-step e-coat base provides industry leading long-term resistance to humidity and corrosion.
- Dust cap has pressure relief feature to prevent back pressure or vacuum in spring compartment.
- Complete unit is one pound lighter than UltraLife™ providing superior strength and durability.
- Up to 10-year parts and corrosion resistance warranty. (Vocational/Severe Duty: 5 year)*

*Contact TSE for warranty details.

PERFORMANCE FEATURES

TSE ULTRALIFE PLUS™ PREMIUM SPRING BRAKES



| PART NUMBER | CATEGORY | DESCRIPTION | B DIMENSION | CAGED |
|--------------------|---|--|-------------|-------|
| 3030TNW3ULP-80060 | Tandem with Welded Clevis for Truck & Trailer Application | T-3030 3.0" stroke + welded clevis | 2.25" | Y |
| 3030TL2ULP-80026 | Tandem with Clevis for Truck & Trailer Application | T-3030 2.5" stroke + clevis | 5.75" | Y |
| 3030TL3ULP-80011 | Tandem with Clevis for Truck & Trailer Application | T-3030 3.0" stroke + clevis | 5.75" | Y |
| 3030TN2ULP-80049 | Direct Fit Units (Clamped + Threaded Rod) | T-3030 2.5" stroke + clevis | 5.75" | Y |
| 3030TN3ULP-80053 | Direct Fit Units (Clamped + Threaded Rod) | T-3030 3.0" stroke + clevis | 5.75" | Y |
| 3030TLW2ULP-80045 | Direct Fit Units (Tamper Proof + Welded Clevis) | T-3030 2.5" stroke + welded clevis | 6.80" | Y |
| 3030TLW3ULP-80036 | Direct Fit Units (Tamper Proof + Welded Clevis) | T-3030 3" stroke + welded clevis | 6.80" | Y |
| 3030TN3ULP-C | Generic Will-Fit Units | T-3030 3.0" stroke + clevis | 7.35" | N |
| 3030TN2ULP-C | Generic Will-Fit Units | T-3030 2.5" stroke | 7.85" | N |
| 3030TN2ULP-C | Generic Will-Fit Units | T-3030 2.5" stroke + clevis | 7.85" | N |
| 3030TL2ULP-80031 | Tandem with Clevis for Truck & Trailer Application | T-3030 2.5" stroke + long rod + clevis | 9.75" | Y |
| 3030TL3ULP-80017 | Tandem with Clevis for Truck & Trailer Application | T-3030 3.0" stroke + long rod + clevis | 9.75" | Y |
| 3030TN2ULP-HNTRX-C | Direct Fit Units (Clamped + Threaded Rod) | T-3030 2.5" stroke + long rod + clevis | 9.75" | N |
| 3030TN3ULP-HNTRX-C | Direct Fit Units (Clamped + Threaded Rod) | T-3030 3.0" stroke + long rod + clevis | 9.75" | N |



2310 Industrial Drive S.W.
Cullman, Alabama 35055

WWW.TSEBRAKES.COM
256 736-6275

©2019 TSE Brakes, Inc.