

32" (31.5" viewable) Full HD LED Commercial Display



CDE3204



The ViewSonic CDE3204 is a great value, high performance 32" (31.5" viewable) Full HD LED commercial display for hotel, restaurant and hospitality environments. In addition to versatile connectivity options, including HDMI, VGA, DVI, SPDIF, YPbPr, the display comes with a simple and convenient USB multimedia playback functionality. With 1920 x 1080 resolution, 350-nit brightness, wide viewing angles and dual 10W stereo speakers, the slim-bezel CDE3204 delivers vivid images and remarkable sound for superior multimedia performance. The HDMI CEC pass-through support provides one-touch-play, with additional features for multiple connected devices such as HD set-top-boxes, media players, and Blu-ray™ players. An RS232 port with IR pass-through provides automated control for hospitality installation. Creating a more comfortable viewing experience, the display is equipped with Flicker-Free and Blue Light Filter technologies. In addition, free-bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop.

Integrated USB Multimedia Player

This display features an integrated media player with a convenient USB playback function. Now photos, music, and 1080p video can be quickly displayed on-screen directly from a USB drive - without the need for a PC.



Free Bundled vController™ Software

Included vController™ software provides a simple and intuitive interface for remote management, OSD-related settings, and scheduling on deployed displays through RS232 or LAN.



Hospitality Mode

This display is great for multi-screen setups in hotels, restaurants, sports bars, or retail outlets that require duplicated setup and customizable presets. With a USB-programmable hospitality setting, each display will have the same customized channel default, audio level, front-panel lockout, and auto power-up settings.



Control Multiple Devices

RS232 IR pass-through offers local control for set-top boxes, and other RS232 connected devices, directly with the display's remote controller. HDMI CEC functionality offers local control of DVD players, sound systems, and other HDMI connected devices, directly with the display's remote controller.



Enhanced Viewing Comfort

Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods.



Dual Integrated Speaker

Designed with dual integrated speakers, this display combines incredible screen performance with stereo sound for an immersive multimedia experience. An additional speaker can be added via the SPDIF audio-out port for expanding sound to different locations in the room or venue, via cable.



Technical Specifications

LCD PANEL	Panel Size	32" (31.5" diagonal)
	Type/ Tech	ADS type
	Display Area (mm)	698.4 (H) x 392.85 (V)
	Aspect Ratio	16:09
	Resolution	1920 x 1080
	Colors	16.7 M colors
	Brightness	350 nits (typ.)
	Contrast Ratio	1200:1 (typ.)
	Response Time	8 ms
	Viewing Angles	H = 178, V = 178 (typ.)
	Backlight	ELED
	Backlight Life	50,000 Hours (typ.)
	Hardness	Hard coating(3H), Anti-glare treatment of the front polarizer (Haze 1%)
<hr/>		
INPUT	HDMI	x 2 (HDMI1.4)
	RGB / VGA	x 1
	DVI	x 1
	Audio	x 1
	CVBS	x 1
	YPbPr	x 1
	RS232	x 1
<hr/>		
OUTPUT	Audio	x 1
	SPIDF	x 1
	IR	x 1
<hr/>		
USB	Type A	x 1
<hr/>		
SPEAKERS		10W x 2
<hr/>		
COMPATIBILITY	VGA	480i, 480p,720p,1080i,1080p
	DVI	480i, 480p,720p,1080i,1080p
	HDMI	480i, 480p,720p,1080i,1080p
<hr/>		
CONTROLS	Physical- Top OSD	POWER, MUTE, INPUT, VOL -/+, UP, DOWN, MENU Picture Mode, Contrast, Brightness, Sharpness, Tint, Color, Blue Light Filter, Color Temp, Zoom Mode, DLC Sound Mode, Digital Output, Surround Sound, AVC, Balance Sleep Timer, Time Zone, DST, Time Format, Clock, Time Management Menu Language, Transparent, OSD Time Out, Restore Default, Software Update(USB), CEC, Blue Screen, Monitor ID, HDMI Mode System Lock, Change Password, Input Block

POWER	Voltage	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
	Consumption	Normal 41W, Max 68W
ERGONOMICS	Wall Mount (VESA®)	200x4200mm ; Screw: M4*L8
OPERATING CONDITIONS	Temperature (° C)	0 to 40°C (Landscape)/0 to 35°C (Portrait)
	Humidity	20% ~ 80% non-condensing
"DIMENSIONS (W x H x D)"	Physical (inch / mm)	733 x 468.5 x 191.4 mm / 28.86 x 18.44 x 7.54 in
	Physical w/o Stand (inch / mm)	733 x 431.2 x 57.0 mm / 28.86 x 16.98 x 2.24 in
	Packaging (inch / mm)	794 x 496 x138 mm / 31.26 x 19.53 x 5.43 in
WEIGHT	Net (lb / kg)	6.4 kg / 14.11 lbs
	Net w/o Stand (lb / kg)	6.3 kg / 13.89 lbs
	Gross (lb / kg)	8.07 kg / 17.79 lbs
What's in the box?	<ol style="list-style-type: none"> 1. CDE3204 commercial display 2. Remote Control with batteries 3. User manual CD wizard 4. Quick Start Guide 5. Power Cables 	
CONTACT Details	Gross (lb / kg)	19.8 kg / 43.65 lbs
REGULATIONS	Standard	UL, FCC, Energy Star 7.0, EPEAT, Mexico Energy, CE, ErP, EAC

ViewSonic® Limited Warranty

ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

For more product information, visit us at www.viewsoniceurope.com

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.