

1/2" STEEL STRAPPING SYSTEMS

EASY-TO-USE, EFFICIENT SYSTEM PROVIDES MAXIMUM STRENGTH PACKAGING, BUNDLING & PALLETIZING

Contains open seals for flat surfaces

Consists of the following components:

- 1- PF404 1/2" x 0.20" steel strapping
- 1- PC446 cutter 3/8" - 1 1/4"
- 1- PC938 3/8" to 3/4" wide standard tensioner
- 1- PA550 1/2" wide sealer for open seals
- 1- PF408 1/2" wide open seals 2000/box
- 1- PE555 dispenser

Model No. PB654



1/2" POLYPROPYLENE STRAPPING SYSTEMS

Consists of the following components:

- 1- PF985 1/2" x 5600', 750-lb. strength poly strapping
- 1- PE555 dispenser
- 1- PA555 1/2" poly sealer
- 1- PC939 polypropylene and polyester tensioner
- 1- PF408 1/2" open seals, 2000/box

Model No. PD023



POLYPROPYLENE & POLYESTER STRAPPING DISPENSERS

- Cart includes large storage tray for strapping accessories
- For use with 1/2" - 3/4" strapping
- Heavy-duty 8" rubber wheels for easy maneuverability
- Accommodates core inside diameter: 8"



5/8" POLYESTER STRAPPING KITS

Consists of the following components:

- 1- PE555 Dispenser
- 1- PG175 5/8" x 4000', 1400 lbs. strength polyester strapping
- 1- PF991 5/8" open seals, 1000/box
- 1- PF992 5/8" polyester sealer
- 1- PF993 polyester strapping tensioner



KLETON

Model

No.

PG187

KLETON

Model

No.

PF807

STEEL & PLASTIC STRAPPING DISPENSER

- Strapping cart is designed to be compatible with polyester, polypropylene and steel strapping
- The unique multi-tier discs accommodate three core strapping sizes: 16" x 3", 16" x 6", and 8" x 8"
- Rubber rollers prevent strapping from unrolling
- Cart includes large storage tray for strapping accessories
- Heavy-duty 8" rubber wheels for easy maneuverability



KLETON

Model

No.

PE555

PG283

Colour

Blue & Yellow

Black

PE555

1/2" POLYESTER STRAPPING KITS

Consists of the following components:

- 1- PB021 1/2" x 3900', 600-lb strength polyester strapping
- 1- PB753 dispenser
- 1- PA555 1/2" poly sealer
- 1- PC939 polypropylene and polyester tensioner
- 1- PA509 1/2" open seals, 2000/box



Model

No.

PD027

EDGEBOARD CORNER PROTECTORS

- Improves stocking strength and cushions package edges against hard knocks
- Also helps improve the flow of strapping and stretch film around the product
- 20 per bundle



CORNER EDGE Products Ltd.

PRE-BUNDLED PACKS

Model No.	Leg"	Thickness"	Length"
PB264	2.5 x 2.5	0.200	36
PB265	2.5 x 2.5	0.200	42
PB266	2.5 x 2.5	0.200	48
PB267	3 x 3	0.200	36
PB268	3 x 3	0.200	42
PB269	3 x 3	0.200	48

Note: Pallet quantities are available.

Other thicknesses and lengths available upon request.

PACKAGING SUPPLIES

STEEL STRAPPING

- Strongest material for a wide range of strapping requirements
- Ideal for heavy shipments that require stronger protection over polypropylene and polyester
- Black painted and waxed finished
- Oscillated wound



KLETON

Model No.	Strap Width"	Strap Thickness"	Feet/Coil	Strength (Lbs.)
PG001	3/8	0.015	5310	680
PG002	3/8	0.020	3800	900
PG003	1/2	0.015	3550	910
PF404	1/2	0.020	2940	1200
PG004	1/2	0.023	2370	1380
PG005	5/8	0.015	2820	1125
PF405	5/8	0.020	2360	1500
PG006	5/8	0.023	1890	1725
PG007	3/4	0.015	2385	1360
PF406	3/4	0.020	1960	1800
PG008	3/4	0.023	1580	2070
PF407*	1 1/4	0.031	760	5500

* Ribbon wound

STEEL STRAPPING TENSIONERS

PUSH BAR STYLE

- Accepts steel strapping 0.020" thick
- Light tension, limited take-up
- Ideal for applications on small, round or irregular surfaces



PA567

FEED-WHEEL STYLE

- Accepts steel strapping 0.035" thick
- Fast and easy operation
- Medium/heavy tension, unlimited take-up
- Ideal for applications on flat surfaces



PC938

PE350

KLETON

PUSH BAR STYLE


Model No.	Description	Width"
PA567	Standard	3/8 - 1/2
PE350	Heavy-Duty	3/8 - 3/4

FEED-WHEEL STYLE

Model No.	Description	Width"
PC938	Standard	3/8 - 3/4
PC399	Heavy-Duty	3/4 - 1 1/4

STEEL SEALS

- All fully galvanized steel
- Open (Snap-on) type:
Used on flat and smooth surfaces
- Fully closed (push) type:
Used on curver and irregular surfaces



Open Type

Closed Type

KLETON

Model No.	Strap Width"	Qty /Box
OPEN (SNAP-ON)		
PF408	1/2	2000
PF409	5/8	2000
PF410	3/4	2000
PF411	1/2	5000
PF412	5/8	5000
PF413	3/4	5000
PF414	1 1/4	1000

Model No.	Strap Width"	Qty /Box
FULLY CLOSED (PUSH)		
PF415	1/2	2000
PF416	5/8	2000
PF417	3/4	2000
PF418	1/2	5000
PF419	5/8	5000
PF420	3/4	5000
PF421	1 1/4	1000

SAFETY CUTTERS FOR STEEL STRAPPING

STANDARD-DUTY

- Cuts steel strapping 3/8-1 1/4" wide x .036" thick
- Safety design holds strapping in place to prevent injuries from flying ends
- Rubber pads gently release strapping when being cut

Model No. PC446



HEAVY-DUTY

- Cuts steel strapping 3/8-2" wide x .050" thick
- Powerful drop-forged steel design
- Heavy-duty performance for industrial applications
- 24" long

Model No. PC479



KLETON

MANUAL SEALLESS STEEL STRAPPING TOOL

- Multi purpose tool cuts, tightens and seals for optimal working efficiency
- Keeps straps secure with punch joint sealing
- Made to withstand high volume usage
- Type: Push Bar
- Fits Strap Width: 1/2" - 3/4"
- Fits Strapping Thickness: 0.015" - 0.027"

Model No. PF705



KLETON

STEEL STRAPPING SEALERS

STANDARD STEEL STRAPPING SEALER, FOR USE WITH OPEN SEALS

- Double notch creates a strong interlocking joint
- Heat-treated steel construction for added durability
- Ball handles provide a superior grip
- Ideal for use with feed-wheel tensioners

Model No.	Width"	Strap Thickness"
PA550	1/2	0.018 - 0.023
PA562	5/8	0.018 - 0.023
PA551	3/4	0.018 - 0.027



KLETON

STANDARD STEEL STRAPPING SEALER, FOR USE WITH CLOSED & SEMI-CLOSED SEALS

- Single notch
- Chrome-plated steel construction
- Ball handles provide a superior grip
- Ideal for use with push-bar style tensioners

Model No.	Width"	Strap Thickness"
PE351	1/2	0.018 - 0.023
PE352	5/8	0.018 - 0.023
PE353	3/4	0.018 - 0.027



HEAVY-DUTY STEEL STRAPPING SEALER

- Single notch
- Heat-treated steel construction for added durability
- Ideal for use with push-bar style tensioners
- For use with 1 1/4" wide steel strapping
- 28" long
- Accepts steel strapping between 0.025" to 0.035" thick

Model No. PB016 (for closed & semi-closed seals)

Model No. PF687 (for open seals)



POLYESTER STRAPPING

- Ideal for medium to heavy-duty palletizing
- Moisture-resistant, safe to handle and recyclable
- Approved by the Association of American Railroads (AAR)
- Strap Thickness: 0.035"
- Colour: Green
- Core Size: 16" x 6"



KLETON

Model No.	Grade	Strap Width"	Strength lbs.	Feet /Coil	Wt. lbs.
PF175	Manual	5/8	1400	4000	55.65

SERRATED STRAPPING SEALS

- Serrated seals for use with polyester strapping




KLETON

Sold per Box

Model No.	Type	Fits Strap Width"	Qty /Box
PF991	Open	5/8	1000

POLYPROPYLENE STRAPPING

- Ideal for light-duty palletizing and bundling
- Lightweight, easy-to-use and recyclable



KLETON

Model No.	Grade	Strap Width"	Strap Thickness"	Colour	Strength (Lbs.)	Feet/ Coil	Weight (Lbs.)	Core Size"
PF983	Machine	3/8	0.024	White	300	12900	28	8 x 8
PF984	Machine	1/2	0.023	White	300	9900	31	8 x 8
PF985	Manual	1/2	0.035	Black	750	5600	40	16 x 6
PF986	Manual	1/2	0.032	Black	600	7200	31	16 x 6
PF987	Manual	1/2	0.032	Black	600	7200	31	8 x 8
PF988	Manual	5/8	0.030	Black	700	6000	31	8 x 8

POLYPROPYLENE STRAPPING

- The most inexpensive of all strapping materials
- Lightweight, easy to apply and recyclable
- Manual application is ideal for low and moderate volume users
- Ideal for light duty palletizing, unitizing, carton closing and bundling



SAMUEL
PACKAGING SYSTEMS GROUP

Model No.	Colour	Strap Width"	Strength lbs.	Coil"	Coils /Carton	Dim. Core" W"	Wt. lbs.
PF078	Black	3/4	1050	4500	1	8 8	31
PF074	Black	5/8	1100	4400	1	16 6	40

POLYPROPYLENE STRAPPING WITH BUCKLES

- Hand strap for large or small packages of all shapes
- Self-dispensing box for convenience
- Includes 360 steel buckles
- Length: 3300'
- Colour: Black
- Strength: 300 lbs.
- Strapping Material: Polypropylene
- Fits Strapping Width: 1/2"

Model No. PG010



POLYPROPYLENE STRAPPING SEALER

- Heat-treated steel construction for superior strength and durability
- Prevents strapping from loosening during transit
- Long 18" handle requires less effort
- Use on steel seals

Model No.	Strap Width"	Strap Thickness"
PA555	1/2	≤ 0.027
PA556	5/8	0.023 - 0.039
PF459	3/4	≤ 0.027



KLETON

POLYPROPYLENE & POLYESTER STRAPPING TENSIONER

- Ideal for applications on flat surfaces
- Accepts strapping 3/8 - 3/4" wide and up to 0.035" thick
- Superior design and performance
- Premium copper bushings
- Built-in strapping cutter

Model No. PC939



KLETON

SEALS & BUCKLES FOR POLYPROPYLENE STRAPPING

Steel Seals



Wire Buckles



Plastic Buckles



Model No.	Strap Width"	Type	Qty /Box
STEEL SEALS			
PA509	1/2	Open	2000
PA510	5/8	Open	2000
PC886	3/4	Open	1000
PLASTIC BUCKLES			
PA500	3/8	Plastic	1000
PA498	1/2	Plastic	2000
WIRE BUCKLES			
PA501	1/2	Wire	2000
PA502*	1/2	H.D. Wire	1000
PA503	5/8	Wire	2000
PA504*	5/8	H.D. Wire	1000

*Recommended for strap with strength over 400 lbs.

PACKAGING SUPPLIES

PROLITE™ HAND STRETCH FILM

- New technology allows lighter gauge to perform like 60-75 gauge films
- Silent and clear film resists puncturing
- 14" x 1500' x 47ga (355 mm x 457m x 12 microns)

Prices are subject to market fluctuations

Model No. PE520



STRETCH WRAP DISPENSERS

- For a smooth, tight application of stretch wrap
- Tension control knob on top ensures a tight, smooth wrap; also provides a second hand grip for added stability
- Adjusts to hold rolls from 11" to 18" wide
- Wt.: 4 lbs.

Model No. PE354



MACHINE STRETCH FILM

- General purpose
- Engineered cast co-extruded film
- Cost effective
- 2 side cling
- Up to 250% stretch
- Each roll is packaged in a box
- Colour: Clear
- Type: Cast
- Width: 20"
- Length: 6000'
- Gauge: 80 Gauge (20.3 micrometers)

Prices are subject to market fluctuations

Model No. PF736



EXTENDED CORE HAND STRETCH WRAP

- 20" web for faster wrapping
- Cast co-extruded premium film
- 5" extended application handles
- No dispenser required
- Save time and energy
- Colour: Clear

Prices are subject to market fluctuations



Model No.	Width"	Length'	Gauge
PF731	20	1000	80 (20.3 micrometers)
PF732	20	700	120 (30 micrometers)

BUBBLE SHIPPING MAILER

- Protective shipping envelopes offer superior protection
- Lightweight saves on shipping costs
- Self-sealing adhesive closure
- Material: Kraft
- Colour: Golden Kraft



Model No.	Length"	Width"
PG238	10	6
PG239	10	5
PG240	8	4
PG241	12	7-1/4
PG242	12	8-1/2
PG243	14-1/4	8-1/2
PG244	14-1/2	9-1/2
PG245	16	10-1/2
PG246	19	12-1/2
PG247	20	14-1/4

STRETCH WRAP

- Conventional cast hand film
- Quiet
- High clarity
- Limited neck down
- Colour: Clear

Prices are subject to market fluctuations



Model No.	Width"	Length'	Gauge
PF718	14	1476	80 (20.3 micrometers)
PF719	13	1476	75 (19 micrometers)
PF720	13	1476	65 (16.5 micrometers)
PF721	12	1476	47 (12 micrometers)
PF722	18	1500	80 (20.3 micrometers)
PF724	18	1000	120 (30.5 micrometers)
PF725	15	1500	80 (20.3 micrometers)

BANDING FILM

- Premium cast bundling film
- Ideal for unitizing several small items into one package
- Can be applied to the top of a pallet load to enhance stability
- One handle included in each case
- Colour: Clear

Prices are subject to market fluctuations




Model No.	Width"	Length'	Gauge	Qty /Case
PF727	3	1500	80 (20.3 micrometers)	18 Rolls
PF728	5	700	115 (29.2 micrometers)	12 Rolls
PF729	5	1500	80 (20.3 micrometers)	12 Rolls
PF730	3	700	115 (29.2 micrometers)	18 Rolls

STRETCH WRAP

- Conventional blown hand film
- Cost effective
- High puncture resistance
- Aggressive cling
- Outstanding containment
- Colour: Opaque Black

Prices are subject to market fluctuations



Model No.	Width"	Length'	Gauge
PF723	15	1500	80 (20.3 micrometers)
PF733	18	1500	80 (20.3 micrometers)

PACKING LIST ENVELOPES

- Ideal for packing slips, invoices, spec sheets, warranties, instructions, etc.
- Style: Backloading
- Qty/Case: 1000



Model No.	Message	Length"	Width"	Inside Dimensions"
PF878	Bilingual "Packing List Enclosed"	4-1/2	5-1/2	4 x 5
PF880	English "Packing List Enclosed"	4-1/2	5-1/2	4 x 5
PF879	Blank	4-1/2	5-1/2	4 x 5
PF881	Blank	7	5-1/2	6-1/2 x 5
PF882	Bilingual "Packing List Enclosed"	7	5-1/2	6-1/2 x 5
PF883	Blank	10	5-1/2	9-1/2 x 5

PACKING LIST ENVELOPES

- Polyethylene envelopes are 100% waterproof and self-adhesive on any surface
- Will not peel off in transit
- Top loading style
- Once packing list is inserted in envelope, no dirt or moisture can penetrate
- Inside dimensions: 4 1/2" x 5 1/2"
- Weight: 7 lbs.
- 1000 per case



Model No. AMB459
Mfg. No. TC-1

CARTON SIZER

- Ideal for cutting boxes down to the desired depth
- Lowers cost on shipping and packaging fill materials
- 12" ruler allows for precise measuring
- Replacement blade: PF346

Model No. PF345



HEAVY-DUTY STAPLE GUN

- All-steel construction with rubberized handle for superior grip
- Easy squeeze, double leverage handle reduces operator fatigue
- Hand-contoured handle features molded plastic handle stop
- Bottom loading with jam proof mechanism
- Adjustable driving force facilitates use
- Accepts staples in three lengths: 5/16", 3/8" and 1/2", with a crown width of 3/8"



Model No. PE337

aurora tools®

AURORA STAPLES

- Cold rolled steel construction
- 3/8" (10.5 mm) flat crown staples
- For use in most industrial staple guns
- 500 per box



aurora tools®

Model No.	Dimensions
ON919	5/16" (8 mm)
ON920	3/8" (10 mm)
ON921	1/2" (12 mm)

CORRUGATED CARTONS

- 125 to 200-lb. test cartons withstand rough handling during shipment
- Shipping flat to save storage space



Withstands rough handling during shipment

Model No.	Dimensions L" x W" x D"	Test lbs.	Model No.	Dimensions L" x W" x D"	Test lbs.	Model No.	Dimensions L" x W" x D"	Test lbs.
APPROX. 20 TO 30-LB. CAPACITY			APPROX. 50-LB. CAPACITY			APPROX. 70-LB. CAPACITY		
PA136	6 x 6 x 6	125C	PB501	14 x 14 x 14	175C	PA125	21 x 20 x 16	200C
PA137	7 x 4 x 4	125C	PA116	15 x 11 x 11	175C	PA135	24 x 14 x 24	200C
PA138	8 x 6 x 4	125C	PA117	16 x 12 x 10	175C	PA129	24 x 19 x 24	200C
PA140	8 x 8 x 8	125C	PA118	16 x 16 x 16	175C	PA131	26 x 19 x 30	200C
PA141	9 x 6 x 6	125C	PA122	18 x 12 x 6	175C	PB502	26 x 26 x 26	200C
PA112	10 x 10 x 10	125C	PA123	18 x 12 x 9	175C	PB503	30 x 30 x 30	200C
PA113	11 x 10 x 3	125C	PA120	18 x 12 x 12	175C	PB504	36 x 36 x 36	200C
PA132	12 x 12 x 7	125C	PA121	18 x 15 x 10	175C			
PA114	12 x 12 x 12	125C	PA119	18 x 18 x 18	175C			
PA139	13 x 8 x 6.5	125C	PA126	20 x 20 x 20	175C			
PA115	13 x 10 x 10	125C	PA111	21 x 14.5 x 15	175C			
PA133	14 x 12 x 8	125C	PA127	21 x 15 x 11	175C			
			PA124	24 x 19 x 19	175C			

POLY TUBING

- Need special size bags for odd-shaped or extra-large products
- Just cut the length you need, insert your product and seal the ends for a custom fit every time
- 4-mil poly tubing available in 3" width to 24" width,
- 2 mil also available



Model No.	Roll Size"	Roll Dia. (+/-2")	Approx. lbs. Roll	Approx. Length/Roll'
PF105	3	19	25	2604
PF107	5	14.5	25	1563
PF096	6	18.5	50	1832
PF099	8	15.5	50	1563
PF103	10	14.5	50	1562
PF098	12	13	50	1302
PF101	16	11.5	50	977
PF097	24	9.5	50	651

HEAT IMPULSE SEALERS

- Used for sealing polyethylene, polypropylene, and PVC bags
- Compact design
- Lightweight
- Easy to operate
- 110 V
- Seal width of 2 mm



Model No.	Size"	Power
PF464	8	260 W
PF465	12	380 W

PACKAGING SUPPLIES

TAPE DISPENSERS

- Industrial quality tape guns constructed of steel and high impact plastic frame
- Adjustable brake lets you choose the desired release tension



PE321

Retractable safety blade protects operator from injury



PF713

Non-retractable blade with safety cap

Model No.	Description	Blade
PE321	2" Standard-Duty, Plastic	Retractable
PE322	2" Heavy-Duty, Steel	Retractable
PE323	3" Heavy-Duty, Steel	Retractable
PF712	2" Standard-Duty, Plastic	Non-retractable
PF713	2" Heavy-Duty, Steel	Non-retractable
PF714	3" Heavy-Duty, Steel	Non-retractable

ACRYLIC BOX SEALING TAPE

- Quality acrylic adhesive tape provides consistent performance
- Ideal for long term storage and lightweight carton sealing
- Works well in extreme temperatures
- Will not yellow with age
- Colour: Clear



Model No.	Dimensions	Thickness	
		Microns	Mils
PF231	48 mm x 66 m (2" x 216')	40	1.6
PF232	48 mm x 100 m (2" x 328')	40	1.6
PF233	48 mm x 100 m (2" x 328')	50	2.0
PF234	72 mm x 66 m (3" x 216')	40	1.6
PF235	48 mm x 132 m (2" x 432')	40	1.6

TARTAN™ 369 BOX SEALING TAPE

TARTAN™ 369 GENERAL PURPOSE

- Offers good holding power for lightweight cartons
- Utility grade polypropylene



SCOTCH® 371 INDUSTRIAL

- Known for its consistent adhesive
- Sticks instantly to any shape or surface

Model No.	Dimensions	Total Thickness	Rolls /Case
TARTAN™ 369 GENERAL PURPOSE			
PB883	2" x 328' (48 mm x 100 m)	1.6 mil, 25 micrometers	36
PC881	2" x 432' (48 mm x 132 m)	1.6 mil, 25 micrometers	48
PA586	2" x 2997' (48 mm x 914 m)	1.6 mil, 25 micrometers	6
SCOTCH® 371 INDUSTRIAL			
PB884	2" x 328' (48 mm x 100 m)	2.0 mil, 30 micrometers	36

HIGHLAND™ 203 MASKING TAPE

- General purpose
- Pressure sensitive
- Ideal for holding, bundling, sealing and non-critical masking
- 55 m (180') per roll



Model No.	Width	Rolls /Case
AMA015	12 mm (1/2")	72
PC049	18 mm (3/4")	48
PC050	24 mm (1")	36
PC051	36 mm (1 1/2")	24
PC052	48 mm (2")	24
PC588	72 mm (3")	12

HOT MELT BOX SEALING TAPE

- Possesses superior holding power and tensile strength
- Ideal for use with boxes containing high amounts of recycled content
- Suitable for shipping and short-term storage
- Type: Hand
- Colour: Clear



Model No.	Dimensions	Thickness Mils
PG127	48 mm x 66 m (2" x 216')	1.6
PG128	48 mm x 100 m (2" x 328')	1.6
PG129	48 mm x 100 m (2" x 328')	2.0
PG130	72 mm x 66 m (3" x 216')	1.6
PG131	48 mm x 132 m (2" x 432')	1.6

SCOTCH® 3771 BOX SEALING TAPE WITH MESSAGE

- 3M™ #371 box sealing tape
- All messages are red on white
- Trilingual (English, French, Spanish)
- 48 mm x 100 m rolls
- Adhesive: Hot Melt
- Material: Polypropylene
- Colour: clear

PA601



Model No.	Message	Thickness		Rolls /Case
		Microns	Mils	
PA600	If seal is broken...	30	2.0	36
PA601	Fragile handle with care	30	2.0	36

TARTAN™ 8934 FILAMENT TAPE

- Ideal for light to medium-duty strapping
- Abrasion and moisture resistant
- Allows printing and illustrations to be seen through tape
- 100-lb. tensile strength



Model No.	Dimensions	Rolls /Case
PC595	1/2" x 180' (12 mm x 55 m)	72
PC596	3/4" x 180' (18 mm x 55 m)	48
PC597	1" x 180' (24 mm x 55 m)	36
PC749	2" x 180' (48 mm x 55 m)	24
PE355	1" Filament Tape Dispenser	-

SCOTCH® PERFORMANCE 231 MASKING TAPE

- Excellent for reducing paint edge buildup
- Leaves no adhesive residue
- Excellent holding capability
- High performance
- Capable of 250°F for 1 hour
- 55 m (180') per roll



Model No.	Width	Rolls /Case
PC538	18 mm (3/4")	48
PC485	24 mm (1")	36
PC539	36 mm (1 1/2")	24
PC531	48 mm (2")	24
PC486	72 mm (3")	12

VINYL DUCT TAPE 3903

- General purpose vinyl duct tape
- Ideal for sealing and protecting surfaces and openings from dust, dirt and moisture
- Good for colour coding, general maintenance as well as wrapping and bundling
- Leaves less adhesive residue on surfaces than the traditional cloth duct tapes
- Easy to tear by hand
- 50 mm x 45.5 m (2" x 149.25')
- Thickness: 6.3 mils



Model No.	Colour	Rolls /Case
PB961	Grey	24
PB962	Blue	24
PB963	Green	24
PB964	Yellow	24
PB965	White	24

MULTI-PURPOSE SILVER DUCT TAPE

- Ideal for many duct and moisture sealing, holding, protecting and bundling applications
- Polyethylene-coated cloth backing
- Rubber adhesive, high tack, easy tear
- 2" x 150' (48 mm x 45.7 m)
- 6-mil thick
- 24 rolls per case

Model No. PE464



TARTAN™ 3939 SILVER DUCT TAPE

- Ideal for many duct and moisture sealing, holding, protecting, and bundling applications
- Polyethylene coated cloth backing
- Rubber adhesive
- High tack
- Easy tear
- 48 mm x 55 m (2" x 180')
- Thickness: 9 mils

Model No. PC419



DT17 SUPER-DUTY DUCT TAPE

- Ultra-thick, water-resistant backing resists wear and abrasion while still tearing easily by hand
- Superior strength for the most demanding applications
- Excellent for repairing, seaming, extra-strength bundling and helps in protecting metal parts and surfaces against sandblast overspray
- Aggressive rubber adhesive grips instantly to a wide variety of surfaces, including metal, glass, plastic and sealed concrete
- Tightly woven scrim provides high tensile strength, which is ideal for bundling applications
- Rolls stay cleaner with low-tack roll sides
- Width: 48 mm (2")
- Length: 32 m (105')
- Thickness: 17 mils
- Colour: Black

Model No. PG124



GENERAL PURPOSE MASKING TAPE

- Designed for all general purpose masking projects offering a good adhesion to a wide variety of surfaces
- Resists lifting or curling
- Removes easily and cleanly
- Colour: Beige



Model No.	Length	Width
PF886	55 m (180')	18 mm (3/4")
PF887	55 m (180')	24 mm (1")
PF888	55 m (180')	48 mm (2")

UTILITY GRADE DUCT TAPE

- Colour: Silver
- Ideal for a wide variety of projects and applications
- Water resistant
- Easy to tear



Model No.	Length	Width	Thickness
PF689	45 m (150')	50 mm (2")	6 mils
PG374	55 m (180')	50 mm (2")	7.5 mils
PF688	55 m (180')	50 mm (2")	9 mils

DT8 ALL-PURPOSE DUCT TAPE

- Hand-tearability, high tensile strength and conformability
- Ideal for contoured surfaces and quick labelling
- Good tensile strength for light-duty bundling
- Use for poly abatement, quick repairs, splicing, temporary holding and fast attachments
- Aggressive, synthetic and natural rubber adhesive provides instant adhesion to a wide variety of surfaces, including metal, glass, plastic and sealed concrete
- Tightly woven scrim provides high tensile strength, which is ideal for bundling applications
- Width: 48 mm (2")
- Length: 55 m (180')
- Thickness: 8 mils



Model No.	Colour	Rolls /Case
PG118	Black	24
PG116	Silver	24

DT11 HEAVY-DUTY DUCT TAPE

- Hand-tearability, high tensile strength and conformability
- Moisture-resistant seal in many containment situations, such as pipe sealing and attaching heavy poly-draping
- Sticks immediately and stays on irregular, hard-to-bond surfaces without lifting
- Width: 48 mm (2")
- Length: 55 m (180')
- Thickness: 11 mils



Model No.	Colour	Rolls /Case
PG122	Black	24
PG120	Silver	24

SUPER 77 SPRAY ADHESIVE

- Ideal for permanently adhering lightweight materials to metal, wood and cardboard
- Two actuators: standard (round) and wide (fan) spray patterns
- High tack, fast drying
- Coverage: 163 sq.ft.
- Net content: 16.5 oz
- 12 per case

Model No. PA003



HI-STRENGTH 90 ADHESIVE

- Ideal for adhering to particle board, polyethylene, polypropylene, rubber and wood
- 1" to 3" adjustable spray width
- 1 to 2-minute drying time
- Coverage: 100 sq.ft.
- Net content: 17.6 oz
- 12 per case

Model No. PA001



HI-TACK 76 ADHESIVE

- Ideal for adhering paper, fabric, cork, foil, rubber and more
- Excellent when strength or high temperature resistance is needed
- 1" to 3" adjustable spray width
- Coverage: 100 sq.ft.
- Net content: 18.1 oz
- 12 per case

Model No. PA002



INDUSTRIAL MARKERS & BAGS

FOR COLD SURFACES

B® PAINTSTIK® -50° TO 150°F



The Original ALL Purpose Cold Surface Markers

- Real paint in stick form
- Ideal for long-lasting, weather, fade and abrasion resistant identification
- Leaves bright, highly visible marks on all materials, including asphalt, aluminum, glass, plastic, marble, lumber and steel
- Writes on rough, smooth, oily, wet, dry, icy and rusty surfaces



Model No.	Colour	Model No.	Colour
PA298	White	NE264	Green
PA320	Black	PA300	Orange
PA309	Yellow	PA353	Grey
NE265	Red	PA348	Blue

B-L® BLUE PAINTSTIK® -50° TO 150°F

Makes permanent marks that bleed through painted surfaces. Available in blue only.

Model No. PA356

BALL PAINT MARKER® -50° TO 150°F

- Produce long lasting, weather and water resistant fine line marks with real paint that dries in minutes
- Writes like a pencil on metal, wood, plastics, rubber - any surface or material
- Packaged in unbreakable 2-oz. plastic bottles with cap to prevent drying or leaking



Model No.	Colour	Model No.	Colour
PA339	White	PA345	Green
PA340	Yellow	PA343	Orange
PA341	Red	PA342	Black
PA344	Blue		

PAINT-RITER™ WINDOW MARKER

- Removable on any non-porous surface
- Writes on glass, steel, aluminum, plastic and rubber
- Dries quickly to avoid smudging or running
- Easy removal with water and a cloth (or run the car through car wash)
- Fabric nib won't scratch delicate surfaces
- Marker Type: Liquid



OR073



Model No.	Colour
OR073	Yellow
OR074	Green
OR075	Orange
OR076	Pink
OR077	Blue
OR078	Purple

QUIK STIK® TWIST-UP PAINT MARKERS

- All purpose paint marker for marking metal, wood, glass, plastic, cardboard and more
- Fast drying paint is fade and weather resistant
- 20% more marks than other brands
- Easy-to-use twist-up holder with self-storing cap keeps hands and clothing clean
- 72 per case



Model No.	Colour
PB937	White
PB938	Yellow
PB939	Red
PB940	Black
OP543	Fluorescent Yellow
OP544	Fluorescent Green
OP545	Fluorescent Orange
OP546	Fluorescent Pink

VALVE ACTION® PAINT MARKERS



MARKING RANGE -50° TO 150°F.

- A fast drying, lead free paint marker ideal for all surfaces
- Weather and fade resistant
- Replaceable fibre tip ensures full use of the marker



Model No.	Colour
PA418	White
PA431	Black
PA420	Red
PA422	Green
PA419	Yellow
PA423	Aluminum
PA421	Blue
PE935	Fluorescent Yellow
PE936	Fluorescent Green
PE937	Fluorescent Orange
PE938	Fluorescent Pink

REPLACEMENT TIPS (12/PKG)

Model No. PA424

PRO-LINE HP® MARKERS

- High performance paint marker has unsurpassed writing capabilities on oily, soapy and wet surfaces
- Excellent on most metals, coatings, plastics, glass, ceramics and other non-porous materials
- Low in halogenated compounds and sulphur allowing use in stainless steel and other corrosion sensitive applications



Xylene Free!

Model No.	Colour
PE507	White
PE508	Yellow
PE509	Red
PE510	Black
PE511	Blue
PE512	Green
PE513	Silver
PE514	Orange



PAINT-RITER™ WATER-BASED PAINT MARKER

- Ideal for making clear, bold markings on almost any surface in environments where VOC issues and Xylene use is a concern
- Fast-drying and provides long-lasting, wear- and weather-resistant
- Safe for almost any surface, such as glass, plastic, pipes and tubes, rubber and tires, steel and iron
- Can be used for identification, quality control and parts inspection
- Marker Type: Liquid
- Marking Temperature Range: 40°F - 150°F (4°C - 66°C)
- Tip Size: 4.5 mm
- Mark Size: Approx. 1/8"



OR046



Model No.	Colour	Dry Time
OR046	White	1 - 2 Minutes
OR047	Yellow	1 - 2 Minutes
OR048	Red	1 - 2 Minutes
OR049	Black	1 - 2 Minutes
OR050	Orange	1 - 2 Minutes
OR051	Blue	1 - 2 Minutes
OR052	Green	1 - 2 Minutes
OR053	Purple	1 - 2 Minutes
OR054	Pink	1 - 2 Minutes

#15 SHARPIE® MARKERS

Fine point marker. Extra tough tip that will not spread or mush. High visibility ink.



Model No.	Colour
PA393	Black
PA395	Blue
PA392	Red

RECLOSABLE POLY BAGS

- Zippered opening allows for easy sealing, opening and resealing
- Keeps out dirt and moisture
- Hang-holes allow user to hang on hooks or pegs
- 2-mil or 4-mil thickness for heavier duty applications



Model No.	Length"	x	Width"	Qty /Case
2-MIL THICKNESS				
PE714	2	x	3	1000
PE716	3	x	3	1000
PE731	7	x	10	1000
4-MIL THICKNESS				
PG387	3	x	4	100
PG388	3	x	5	100
PG389	4	x	4	100
PG390	4	x	6	100
PG391	5	x	8	100
PG392	6	x	9	100
PG393	8	x	10	100
PG394	9	x	12	100
PG395	12	x	15	100

Custom sizes and printed bags available. Please inquire.

WHITE BLOCK RECLOSABLE BAGS

- White block area – use marker, pen or pencil to identify label or contents
- Zippered opening
- 2-mil thickness
- 1000 bags per case
- Accepted for use in Canadian food processing facilities



Model No.	Length"	x	Width"
PE736	2	x	2
PE737	2	x	3
PF848	5	x	8
PE743	6	x	6
PF849	8	x	10

POLY BAGS

- Hang-holes allow users to hang on hooks or pegs
- Zippered opening allows for easy opening and resealing
- Type: Reclosable
- Thickness: 2 mils



Model No.	Length"	x	Width"	Qty /Bundle
PF915	4	x	3	100
PF919	5	x	3	100
PF922	4	x	4	100
PF925	6	x	4	100
PF928	8	x	4	100
PF929	7	x	5	100
PF932	8	x	5	100
PF935	6	x	6	100
PF937	8	x	6	100
PF942	9	x	6	100
PF946	10	x	8	100
PF949	6	x	9	100
PF950	12	x	9	100
PF954	12	x	10	100
PF957	13	x	10	100
PF958	12	x	12	100
PF961	15	x	12	100
PF965	20	x	15	100

SR SERIES FOOD PACKAGING BULK POUND BAGS

- Excellent seal strength and thickness, while offering safe and durable storage for fruit and vegetable produce and other dry goods
- Ideal for farmers markets, grocery stores and restaurants
- Accepted for use in Canadian food processing facilities
- Easy individual bag dispensing
- Type: Open Top
- Thickness: 0.85 mil
- Colour: Clear
- Weight Capacity: 1 lbs.



Model No.	Length"	x	Width"
PG318	8	x	5
PG319	10	x	4
PG320	11-1/2	x	5
PG321	13-1/2	x	5
PG322	15	x	5
PG323	15	x	6
PG324	16	x	7
PG325	20	x	7
PG326	18	x	8
PG327	20	x	8
PG328	20	x	12
PG329	26	x	12

HEAVY-DUTY BAG TAPERS & TAPE

- Bag taper with tape cutter
- Easy to use: just twist bag shut and move through slot



Model No.	Description	Wt. lbs.
PE356	Bag Sealer w/Cutter	2
PE383	Replacement Blade	-

BAG SEALING TAPE

- For use with bag taper
- PVC tape provides an excellent seal for poly bags



Model No.				Description
White	Yellow	Blue	Green	
PF208	PF209	PF211	PF212	3/8" x 216' PVC Tape

WHITE BLOCK POLY BAGS

- Hang-holes allow users to hang on hooks or pegs
- Identify contents by writing on the white block area
- Zippered opening allows for easy opening and resealing
- Type: Reclosable, White Block
- Thickness: 2 mils



Model No.	Length"	x	Width"	Qty /Bundle
PF916	4	x	3	100
PF918	5	x	3	100
PF926	6	x	4	100
PF933	8	x	5	100
PF941	9	x	6	100
PF948	10	x	8	100
PF951	12	x	9	100
PF963	15	x	12	100



KNIVES & CUTTERS

HEAVY-DUTY UTILITY KNIVES



PA227



PB861



PA228



PB949



PB834



PA190



PA212



PA224



PA246



PB860

Model No.	Mfg. No.	Description
PA227	L-1	Heavy-Duty Knife
PA228	L-2	Heavy-Duty Knife w/an Ergonomically-Designed Handle that Features a Rubber Grip Insert
PB861	NL-AL	Auto-Lock Heavy-Duty Hand-Saver Utility Knife
PB949	NA-1	Cushion Grip Cutter w/Auto-Lock Blade Slide
PA190	180	Quality at an Economical Price. Features Snap-Off Blades
PA224	H-1	Extra Heavy-Duty Cutter w/Rubber Grip Insert
PB834	SK-4	Carton Cutter Knife w/Self-Retracting Blade for Enhanced User Safety
PA212	CL	18mm Heavy-Duty Utility Knife with Ratchet Lock
PA246	SL-1	All Purpose Utility Knife
PB860	1118008	18 mm All-Over Rubber Grip HD Utility Knife

REPLACEMENT BLADES

Model No.	Use With	Blades /Pkg.
PA238	All Knives Except PB949, PA190 and PA224	10
PA239	All Knives Except PB949, PA190 and PA224	50
PA199	PA190 and PB949	10
PA731	PA190 and PB949	50
PB835	PB834 Only	10
VQ359	PA224 Only	5
VQ360	PA224 Only	20

STAINLESS STEEL SCISSORS

- Serrated edge grips material
- Industrial strength high-impact ABS handle and stainless steel blades
- Symmetrical handle design for right- and left-hand use
- Handle: ring



Model No.	Mfg. No.	Overall Length"
PC910	SCS-1	5
PC900	SCS-2	7

CARTON CUTTERS

- Cut cartons quickly and safely with this OLFA carton cutter
- Blade is shielded by a built-in guard when blade loses contact with the cutting surface
- Comfortable, ergonomic grip reduces fatigue
- Use in commercial, industrial, retail and distribution facilities



Model No.	Mfg. No.	
PC563	OLO-CACT	-

HEAVY-DUTY UTILITY KNIVES W/RATCHET LOCK

- Knife with ratchet-lock mechanism
- Wraparound anti-slip rubber grip and acetone-resistant handle
- Multi-purpose metal pick
- Replacement blades are available both in solid or snap off style
- Blade size: 18 mm



Model No.	Mfg. No.	Style	Qty /Pkg.
PF611	L5	-	-
REPLACEMENT BLADES			
PC908	LH-20B	Snap-Off	5
PC909	LSOL-10B	Solid	10

SAFETY KNIVES WITH CONCEALED BLADE

- Adjustable blade positioning design which allows for four cutting points on a single-edge utility blade
- Highly productive, it delivers 4x's more cuts than a single-edge, fixed blade "gooseneck" safety knife
- Uses the Olfa SKB-10 blade
- Fits both right and left-handed users with no blade adjustment necessary

Model No. PE929
Mfg. No. SK-10



REPLACEMENT BLADES

Model No. PE990 10/pkg.
Mfg. No. SKB-10/10B



INDUSTRIAL UTILITY KNIVES



PF710



PF711



PE813



PE345



PE814



PF708



PE549



PF812



PE812



PE815



Model No.	Description
PF708	18 mm Blade, Self-Retracting
PF710	25 mm Blade, Screw-Lock, Heavy-Duty
PF711	18 mm Blade, Screw-Lock, Heavy-Duty
PE813	18 mm Blade, Screw-Lock, Industrial-Duty
PE814	18 mm Blade, Auto-Lock, Industrial-Duty
PE549	18 mm Blade, Auto-Lock, Standard-Duty, Lightweight
PE345	9 mm Blade, Auto-Lock, Standard-Duty
PE812	18 mm Blade, Auto-Lock, Heavy-Duty, Rubber Handle
PE815	9 mm Blade, Auto-Lock, Utility Grade

REPLACEMENT BLADES

Model No.	Use With
PF709	PF708 Only, 10/Pkg.
PF205	PF711, PE813, PF814, PE549 and PE812, 10/Pkg.
PE407	PE815, PE345 and PE346, 10/Pkg.
PE410	PF710 and PE349, 10/Pkg.

ELECTRONIC DIGITAL WEIGHING SCALES

- Compact design 12 1/2" D x 11 3/4" W x 45/8" H (32 cm x 30 cm x 12 cm)
- Check-weighing function (HI/LO/Target) and a secondary counting function
- Offers four capacities (3, 6, 15, & 30 kg / 6, 12, 30 & 60 lbs.) and four weighing modes (g, kg, lbs., oz.)
- Removable stainless steel platform 11 3/4" D x 8 3/4" W (30 cm x 22 cm)
- ABS enclosure
- Large LCD display with both front and rear indicators and level indicator for weighing accuracy
- Rechargeable battery with low battery indicator and AC adapter (included)



IA991



Model No.	Mfg. No.	Capacity kg/g./lbs./oz.	Graduation kg/g./lbs./oz.
NOT LEGAL FOR TRADE			
IA988	KWS-SW06	3/3000/6/96	0.001/1/0.002/0.05
IA989	KWS-SW12	6/6000/12/192	0.002/2/0.005/0.1
IA990	KWS-SW30	15/15000/30/480	0.005/5/0.01/0.2
IA991	KWS-SW60	30/30000/60/960	0.01/10/0.02/0.5
LEGAL FOR TRADE			
IA992	KWS-SW06	3/3000/6/96	0.001/1/0.002/0.05
IA993	KWS-SW12	6/6000/12/192	0.002/2/0.005/0.1
IA994	KWS-SW30	15/15000/30/480	0.005/5/0.01/0.2
IA995	KWS-SW60	30/30000/60/960	0.01/10/0.02/0.5

DIGITAL SCALE WITH DUAL DISPLAY

- Ideal for high humidity and dusty work environments
- Large stainless steel platform is removable for easy cleaning
- Convenient displays on front and rear of the scale allow use from both sides of the worktable
- Meets IP66 (dust tight and protected against a strong water jet) standards

FEATURES:

- Large LCD type display with backlight
- ABS enclosure
- Water and dust resistant
- Secondary counting function
- Four direct keys: Zero, tare, units/counting, on/off
- Four weight modes: g, kg, oz., lbs.
- A/C power or rechargeable battery (not included)
- Dimensions: 9" W x 9 1/2" D x 5 3/4" H



PE129



Model No.	Mfg. No.	Capacity	Graduation
NOT LEGAL FOR TRADE			
PE126	KWD 500-5	5 lbs./2.5 kg	0.002 lbs./0.001 kg
PE127	KWD 500-10	10 lbs./5 kg	0.005 lbs./0.002 kg
PE128	KWD 500-20	20 lbs./10 kg	0.01 lbs./0.005 kg
PE129	KWD 500-50	50 lbs./20 kg	0.02 lbs./0.01 kg
LEGAL FOR TRADE			
IA591	KWD 500-5	5 lbs./2.5 kg	0.002 lbs./0.001 kg
IA592	KWD 500-10	10 lbs./5 kg	0.005 lbs./0.002 kg
IA593	KWD 500-20	20 lbs./10 kg	0.01 lbs./0.005 kg
IA594	KWD 500-50	50 lbs./20 kg	0.02 lbs./0.01 kg

DIGITAL COUNTING SCALES

- Used for counting and quantity checking
- Primary counting function
- High accuracy load cell
- Large LCD display
- Rechargeable battery
- Full digital calibration
- Tare function
- Auto zero tracking
- Quantity set alarm (checking)
- Backlight display
- Accumulation memory quantity
- 1-year warranty

NOT LEGAL FOR TRADE



HX133



Model No.	Mfg. No.	Capacity	Graduation	Counting Resolutions
IB733	KCS 301-6	13.2 lbs./6 kg	0.0004 lbs./0.2 g	1/30 000
IA590	KCS 301-15	33 lbs./15 kg	0.001 lbs./0.5 g	1/30 000
HX133	KCS 301-30	66 lbs./30 kg	0.002 lbs./1 g	1/30 000

COMPASS SERIES SCALES

- Simplified two-button operation
- Large backlit display increases readability in dim lighting conditions
- Standard stainless steel pan for durable use
- Ingenious space-saving design, which allows you to stack up to 4 scales to save storage space
- LCD Display with white backlight
- Tare to capacity by subtraction
- 1000 hours with disposable batteries
- 3 AA batteries (included) or AC adapter (not included)



IC006



NOT LEGAL FOR TRADE

Model No.	Mfg. No.	Capacity	Graduation	Platform Dimensions L" x W"
IC006	CX221	220 g	0.1g	5 1/2" x 5"
IC007	CX621	620 g	0.1 g	5 1/2" x 5"
IC008	CX1201	1200 g	0.1 g	5 1/2" x 5"
IC009	CX2200	2000 g	1g	5 1/2" x 5"
IC010	CX5200	5200 g	1g	5 1/2" x 5"

ACCESSORIES

IC011	30330714	Power Adapter
IC012	30467763	Carrying Case

DIGITAL BENCH TOP SCALE

- Auto off (after 120 seconds of inactivity)
- Full tare capacity
- Bright-blue backlit LCD display
- Low battery and overload indications
- Stainless steel platform
- Transparent cover protects the scale when not in use
- 7 Weighing modes: kg, lbs., g, oz., lb-oz, lb-1/4oz, 1/4oz
- Power supply: 4 x AA rechargeable batteries and power adapter included
- Capacity: 33 lbs. / 15 kg.
- Graduations: 2 g
- Platform Dimensions: 7" L x 7" W



NOT LEGAL FOR TRADE

Model No. IB735
Mfg. No. 6015C



SCALES

RECEIVING SCALES

These scales are heavy-duty, general purpose and are suitable for light industrial or shipping applications. The easy-to-read indicator is connected to the base by an 8' coiled cord that allows convenient remote placement. Large removable stainless steel platform allows for easy clean up. A keypad toggle allows easy kg/lbs. selection.

NOT LEGAL FOR TRADE



HX632

FEATURES:

- Kg/lbs. modes
- Programmable Auto-Off function
- Removable stainless steel platform (HX632, HX633, IA558, IA782, and IA783)
- Fixed mild steel checkered platform (IA564 and IA453)
- 4 1/2" x 1 1/2" LCD display (HX632, HX633 and IA558)
- 3" x 1 1/4" LCD display (IA564 and IA453)
- Platform dimensions: 11 3/4" x 12 1/4" (HX632, HX633, IA558, IA564 and IA453) 14" x 16" (IA752 and IA783)
- Zero, tare and kg/lbs. (toggle) keys
- Heavy-duty 8' coiled cord
- Power supply: Six AA alkaline batteries (not included) or 120 V AC adapter (included)
- 1-year warranty



Model No.	Mfg. No.	Capacity	Graduation
HX632	KPS-50-2	110 lbs./50 kg	0.05 lbs./20 g
HX633	KPS-100-2	220 lbs./100 kg	0.1 lbs./50 g
IA558	KPS-150-2	300 lbs./150 kg	0.2 lbs./100 g
IA564	KPS-68MS	150 lbs./68 kg	0.2 lbs./100 g
IA782	KPS-60SS	130 lbs./60 kg	0.05 lbs./20 g
IA783	KPS-150SS	330 lbs./150 kg	0.1 lbs./50 g
IA453	KPS-180MS	400 lbs./180 kg	0.5 lbs./200 g

INDUSTRIAL HANGING SCALES

- Cast aluminum scratch resistant body
- Clear shatter resistant face plate
- 7.5" diameter, kg and lbs. dial
- Heavy-duty welded steel shackle ring
- Large pointed J-hook
- 1-year warranty

IA545



NOT LEGAL FOR TRADE



Model No.	Mfg. No.	Capacity	Graduation
IA543	KHS-C360	60 kg/125 lbs.	200 g/0.5 lbs.
IA544	KHS-C3120	120 kg/250 lbs.	500 g/1 lbs.
IA545	KHS-C3250	250 kg/540 lbs.	1 kg/2 lbs.

MINI DIGITAL CRANE SCALES

- Stainless steel load receptor
- Cast aluminum housing
- LCD screen viewable from 22'
- Tare, Hold, Unit (between kg and lbs.), Zero
- Programmable auto-off, auto-zero, manual zero, backlight
- Removable hook for easy cleaning
- For use in a dry environment and areas of low humidity
- 1-year warranty

IA787



NOT LEGAL FOR TRADE



Model No.	Mfg. No.	Capacity	Graduation
IA784	KHS 200-30	60 lbs./30 kg	0.02 lbs./0.01 kg
IA785	KHS 200-60	120 lbs./60 kg	0.05 lbs./0.02 kg
IA786	KHS 200-150	300 lbs./150 kg	0.1 lbs./0.05 kg
IA787	KHS 200-300	600 lbs./300 kg	0.2 lbs./0.1 kg

DIGITAL RECEIVING SCALE

- The durable receiving scale is great for weighing small items up to 220 lbs.
- Features a smooth easy to clean platform and hand-held remote that can also be mounted to the wall
- Easily portable and simple to use
- White backlight LCD
- Weighing Units: Pounds (lb), Kilograms (kg), Pounds & Ounces (lb/oz)



NOT LEGAL FOR TRADE



Model No.	Mfg. No.	Capacity	Graduation	Platform Dim. L" x W"
IC671	603SC	220 lbs.	1 lbs.	11.7 x 11.7

TOP LOADING SCALES

- Large stainless steel and enamel platforms to accommodate a variety of package sizes
- Bold graphics improve reading accuracy and ease
- Portable, rugged and reliable



PE446

NOT LEGAL FOR TRADE



Model No.	Mfg. No.	Capacity	Case Finish	Platform Dim. W" x D"
PE446	KAM1101PL	11 lbs./5 kg	Enamel	7 1/2 x 7 1/2
PE447	KAM2501SPL	26 lbs./12 kg	Stainless Steel	7 1/2 x 7 1/2
PE449	KAM5002PL	50 lbs./22 kg	Enamel	10 3/4 x 9 1/2

TOP LOADING SCALES

- Brushed stainless steel body and stainless platform
- Portable rugged and reliable
- Bold large numbers for easy readability
- Rotating dial
- Tare function



IB736



Model No.	Mfg. No.	Capacity	Graduation	Platform Dim. L" x W"
IB736	620SC	2.2 lbs./1 kg	5 g/0.25 oz.	6 x 6
IB737	6215C	5 lbs./2.2 kg	5 g/0.5 oz.	6 x 6
IB738	6225C	25 lbs./12 kg	50 g/0.125 lbs.	8 x 8

CYCLONE BENCH AND PLATFORM SCALE

- Durable thick stainless steel platter allows for heavy loads without bending
- 2 scales in one - Dual range- always the right sensitivity no matter how light or heavy the load
- Back support - Ideal for weighing products in bags or that which require extra support.
- Post mounted indicator - Makes it easy to see the screen
- Three weighing modes: lb., kg, pcs
- Ideal for shipping, receiving, check weighing or counting
- Battery or adapter operated



NOT LEGAL FOR TRADE

Model No.	Capacity Range 1	Graduation Range 1	Capacity Range 2	Graduation Range 2
15-3/4" L x 19-7/10" W				
IB770	0-60 kg / 0-150 lbs.	20 g / 0.05 lbs.	60-150 kg / 150-300 lbs.	50 g / 0.1 lbs.
17-3/4" L x 23-3/5" W				
IB771	0-150 kg / 0-300 lbs.	50 g / 0.1 lbs.	150-300 kg / 300-600 lbs.	100 g / 0.2 lbs.

TOP GUN ELECTRONIC PLATFORM SCALES

- For use in dry environments and areas with low humidity
- Counting function (secondary)
- Hi/Target/Lo (check weighing)
- Accumulation function
- Removable stainless steel platter (1.2 mm gauge) 12" W x 18" D (30.5 x 45.7 cm)
- Built-in level
- Adjustable lockable anti-slip leveling feet
- Predefined capacity settings eliminate installation errors
- Mobile installation
- Choice of ABS or stainless steel indicators



Model No.	Mfg. No.	Indicator*	Frame**	Capacity	Graduation
NOT LEGAL FOR TRADE					
IB011	KPLMS 1218-60	KIN 1000 (ABS)	MS	60 kg/150 lbs.	0.02 kg/0.05 lbs.
IB012	KPLMS 1218-60	KIN 2000 (WR)	MS	60 kg/150 lbs.	0.02 kg/0.05 lbs.
IB013	KPLMS 1218-150	KIN 1000 (ABS)	MS	150 kg/300 lbs.	0.05 kg/0.1 lbs.
IB014	KPLMS 1218-150	KIN 2000 (WR)	MS	150 kg/300 lbs.	0.05 kg/0.1 lbs.
LEGAL FOR TRADE					
IB015	KPLMS 1218-60	KIN 1000 (ABS)	MS	60 kg/150 lbs.	0.02 kg/0.05 lbs.
IB016	KPLMS 1218-60	KIN 2000 (WR)	MS	60 kg/150 lbs.	0.02 kg/0.05 lbs.
IB017	KPLMS 1218-150	KIN 1000 (ABS)	MS	150 kg/300 lbs.	0.05 kg/0.1 lbs.
IB018	KPLMS 1218-150	KIN 2000 (WR)	MS	150 kg/300 lbs.	0.05 kg/0.1 lbs.

*Indicator

ABS = ABS Plastic
WR = Stainless Steel

** Frame


MS = Mild Steel

VN SERIES ECONOMICAL FLOOR SCALES

The Ohaus VN Series of floor platforms and scales are the value solution to your dry weighing needs in industrial and commercial applications. Its high-quality construction is designed to minimize distortion under heavy loads, and ensures years of dependable performance. NTEP certification ensures consistent weighing results.

Standard features of the VN Series include:

- 5 mm/0.196" painted carbon steel weighing platform top plate with raised cross-hatch surface for added slip resistance
- Four NTEP-certified shear beam load cells protected to IP67
- Side-access NEMA 4X/IP65 dust and water protected stainless steel junction box with 16 1/2" indicator cable
- Four self-swiveling ball-in-cap feet, with top-access leveling adjustment for easy installation
- Internal structural bracing ensures platform rigidity
- Carbon steel eyebolts attached to side of platform for easy lifting and positioning
- T31P indicator includes: Backlit LCD display with 1" high digits, lbs. and kg weighing units, counting mode for inventory applications, 16 1/2" indicator cable, wall bracket for easy mounting, 80-hour internal rechargeable battery and AC adapter




NOT LEGAL FOR TRADE

Model No.	Mfg. No.	Capacity	Graduation	Platform Dim. L" x W" x H"
IA560	VN31P5000L	5000 lbs./2500 kg	1 lbs./0.5 kg	48 x 48 x 3 1/2
IA561	VN31P5000X	5000 lbs./2500 kg	1 lbs./0.5 kg	60 x 60 x 3 1/2
IA562	80252565		Floor Ramp, 4' Wide	
IA563	80252566		Floor Ramp, 5' Wide	

MOBILE PLATFORM SCALE

- No lifting required, roll your dolly directly onto the ramp
- Mobile Wheels and handle allow for effortless movement
- Rugged mild steel checkered platform
- Ideal for small barrels, drums, kegs, tanks, pails and cylinders (non-flammable and non explosive substances)
- Accurate, efficient and profitable - HI/LO/Target, parts counting, %, TARE & data comparison features
- 2 preprogrammed weighing modes kg/lb.
- 3 programmable modes: lb:oz, PCS, %
- Tare, hold, print, zero tracking & digital calibration
- Auto-power off and backlight
- Programmable serial output
- Printing simplified - USB and RS232 interfaces
- Graduations: 0.2 lbs./0.1 kg

NOT LEGAL FOR TRADE



Model No.	Mfg. No.	Capacity	Platform Size L" x W"
IB776	851313	132 lbs. / 60 kg	18 x 18
IB777	851314	330 lbs. / 150 kg	24 x 24
IB778	851315	660 lbs. / 300 kg	30 x 30

WAREHOUSE MONITORING INSTRUMENTS

INFRARED THERMOMETER

- Built-in laser pointer identifies target area
- Digitally adjustable emissivity
- Max, min, average and differential readings
- Backlit display
- High and low alarms
- Low battery indication and auto shut-off
- Temperature Range: -25.6° - 752°F (-32° - 400°C)
- Accuracy: ±4°F(2°C) or ±2% rdg.
- Spot Size Ratio: 12:1



REED

Model No.	Mfg. No.	Description
IB967	R2300	Infrared Thermometer

LIGHT METER

- Capable of measuring in both Footcandle (Fc) and Lux
- Easy-to-read backlit LCD display
- 42-segment Digital analog bargraph
- Min/Max and Relative Mode functions
- Peak and data hold functions
- Low battery indicator and auto shut off
- The tethered sensor allows for flexible operation while taking measurements
- Measuring Range: 0-400000 lux (0-400000 ftc)
- Accuracy: ±(5% rdg.+ 0.5% Full Scale)
- Response Time: 13.3 Times/Second (Bargraph), 1.3 Times/Second (Numeric Display)
- **Includes:** Light meter, sensor cover, protective holster, carrying case, battery



REED

Model No.	Mfg. No.	Description
IC655	R8130	Light Meter
HN416	CA-05A	Carrying Case

SOUND LEVEL METER/DATA LOGGERS

- Measuring Range: Low: 30 to 90 dB; Med: 50 to 110 dB; High: 70 to 130 dB Auto: 30 to 130 dB
- Dynamic Range: 60 dB • Accuracy: ±1.4 dB
- Resolution: 0.1 dB • Sample Rate: Digital: 0.5 sec. Analog: 50 mS
- Frequency Range: 20 Hz to 8 kHz
- Frequency Weighting: A and C
- Microphone: 1/2" electret condenser
- Power Supply: 4 x AAA batteries
- Meets IEC 61672-1 Class 2 requirements
- Records up to 64000 datapoints (1 MB)
- 60 dB dynamic space in each range • Real time clock and calendar
- Fast/slow time weighting • Min/Max function • USB Interface
- Analog digital bar graph • Backlit LCD display
- Tripod mount design for long-term monitoring
- Includes windscreen, USB cable, Windows software, batteries and hard carrying case
- Model IC454 also includes calibrator and deluxe hard carrying case



IB749



IC454

REED

Model No.	Mfg. No.	Description
IB749	R8080	Sound Level Meter/Data Logger
IC454	R8080-KIT	Sound Level Meter/Data Logger with Calibrator
HN413	CA-52A	Carrying Case

WET-BULB GLOBE TEMPERATURE (WBGT) HEAT STRESS METER

- Measures ambient temperature, humidity, wet bulb temperature, black globe temperature, WBGT (wet bulb global temperature), heat stress index, dew point and pressure
- Heat Stress Index measures how hot it feels when humidity is combined with temperature, air movement and radiant heat
- Black Globe Temperature (GT) monitors the effects of direct solar radiation on an exposed surface
- In/Out function displays the WBGT value with or without direct sun exposure
- Multi-line backlit LCD display simultaneously displays 4 measurements – maximum, minimum, average and data hold functions
- Internal memory stores up to 99 measurements
- User selectable unit of measure (°F or °C)
- User-adjustable WBGT threshold alarm (audible)
- Tripod mountable for long-term monitoring
- Low battery indicator and auto shut-off after 15 minutes
- Air Temperature Range: 0 to 50°C (32 to 122°F)
- WBGT Temperature Range: 15° - 59°C (59° - 138.2°F)
- Humidity Range: 0% - 99.9% RH
- Power Supply: 4 x AAA Batteries included, Optional AC Adapter
- Operating Temperature: 32 to 122°F (0 to 50°C)
- Operating Humidity: <80% (non-condensing)



REED

Model No.	Mfg. No.	Description
IB908	R6200	Heat Stress Meter
IB908	R6200	Heat Stress Meter w/ISO Certificate
ACCESSORIES		
IB915	R9975	Humidity Calibration Standard, 75%
IB914	R9933	Humidity Calibration Standard, 33%
HN416	CA-05A	Carrying Case
IB820	R1500	Tripod with Instrument Adapter

TACHOMETERS

- Dual function unit with both contact and non-contact capabilities
- Supplied with adapters for fpm, rpm and surface speed measurements
- Non-contact function utilizes laser light beam for improved accuracy
- Recalls Max/Min and last values
- Large, easy-to-read display
- Autoranging with 0.05% accuracy
- Includes battery and carrying case
- Measuring Range: Photo: 5 to 99,999 rpm; Contact: 5 to 19,999 rpm; Surface Speed: 0.05 to 1999 mpm



HX386

REED

Model No.	Mfg. No.	Description
HX386	R7100	Photo/Contact Tachometer
IA046	ST-CONE	Replacement Contact Adapter
IA047	ST-WHEEL	Replacement Surface Speed Wheel
IA740	ST-FUNNEL	Replacement Funnel Tip
IA741	ST-SHAFT	Replacement Extension Shaft

INDOOR/OUTDOOR WIRELESS HUMIDEX THERMOMETERS

- Displays humidex and heat index
- Humidex and heat index is a combination of temperature and humidity into one number to reflect perceived temperature
- Heat stress index scale
- Indoor and outdoor temperature
- Outdoor humidity
- Min/max memory
- °C and °F switchable
- Wireless transmission range: 45 m/150'



IA504

BIOS
Weather

Model No.	Mfg. No.	Description
IA504	260BC	Wireless Humidex Thermometer