



WPT-03 - Wireless UHF Pendant Transmitter



VS1502



VP-4



WPRP-2 or WPRP-5

The **WPT-03 Wireless UHF Pendant Transmitter** is designed to send pre-programmed text messages directly to a designated pager or LED display.

When the WPT-03 is used with a main wireless paging controller, such as the **VNS5100**, the pendant's activation code can be used to generate automated text, audio or visual alerts to pagers, alphanumeric displays, speakers, strobe lights, e-mail and telephone subscribers.

In this configuration, when the WPT-03 button is pressed, a signal is sent to a wireless receiver connected to the main paging controller. The signal is received and compared to the programming in the main paging controller's database. If a match is found, an automated alert will be generated according to the programming.

Key Features:

- **Four Fully Programmable Messages**
- **Sends Messages Directly to a Pager**
- **300' - 1,000' Range (Can be Increased by Using a Data Repeater)**
- **Transmission Indicator**
- **Powered by Standard 9V Battery**
- **Desk or Wall Mount**

Options, Accessories and Complementary Products:

Part Number	Description
VSPS-03	Programming Kit
WPRP-2/WPRP-5	Data Repeater

Specifications:

Dimensions	2.75" x 3.5" x 1.0" (W x H x D)	Call Buttons	4 Button Configuration
Weight	3.5 oz. (Includes Battery)	Signalling Time	2 - 4 Seconds
Power	9V Battery	Stability	Better than 5 PPM
Color	Gray	Frequency	467.8000 MHz
Operating Temperature	32° - 140°F	Paging Format	POCSAG, 512 or 1200 BPS
Humidity	0% - 90%, Non-Condensing	Channel Spacing	12.5 KHz - Narrow Band
RF Power	10 mW	Activation Codes	4
Programming	PC Based Programming Kit	Limited Warranty	One Year Parts and Labor

*Specifications Are Subject to Change Without Notification