



Item # _____

Job _____

Metro C5 Pizza Series Heated Holding Cabinet

- **Control:** The C5 Pizza Series controls temperature for safe and hot holding of pizza and other foods. Temperature is displayed on an "always-on" analog thermometer for continuous monitoring of the cabinet temperature, even when turned off or unplugged.
- **Performance:** Rapid heat-up and recovery times are achieved with a thermostatically controlled ducted heating system. All models are Energy Star.
- **Sizes:** C5 Pizza Series cabinets are available in Full Height (74.75") and 1/2 Height (44.75") sizes.
- **Doors:** C5 Pizza Series cabinets are all available with a choice of insulated solid or clear double pane, insulated Low-E, tempered glass doors. Clear doors provide visibility of the contents of the cabinet without the heat loss associated with opening the door. Full Height cabinets are configured with Dutch style doors. All doors lift off and are field reversible.
- **Pass-Thru:** Pass-thru models are available for applications that require access from both the front and the back of the cabinet.
- **Capacity:** C5 Pizza Series cabinets are available configured with Universal Wire Slides or with Wire Shelves. Universal slides hold (2) 16" Pizza boxes front-to-back, 18" x 26" sheet pans, or (2) 12" x 20" steam table pans front-to-back on adjustable 1 1/2" increments. Wire shelves accommodate just about anything including small boxes and odd-sized pans or containers. Wire shelves and universal slides work together and can be intermixed when ordered as accessories.
- **Reliability:** Reliability and durability are designed into all C5 cabinets from the ground up. High-quality components and robust construction provide a long life of service and worry-free use.
- **Top-Mounted Controls:** Ergonomic user-friendly controls are mounted at the top of the cabinet for easier access, better readability, to prevent damage, and to simplify cleaning.
- **Passive Humidity:** An integral water pan system can be used to add humidity to the cabinet environment, improving the quality of food products that require a moist holding environment.
- **Construction:** Available in both stainless steel and aluminum.



Full Height Dutch Clear Doors



Options/Accessories:

- Pizza Wire Shelf (C5-ZSHELF)
- Stainless Steel Legs (C5-SSLEGS)
- Universal Slide Pair (C5-ZUSLIDECPR)
- Right Angle Plug (C5-RTANGPLG)
- Twist Lock Plug (C5-RTWSTPLG)
- Flush Door Latch (C5-LATCHFLUSH)
- Twist Lock Flush Door Latch (C5-LATCHTWST)
- Key Lock Flush Door Latch (C5-LATCHLOCK)
- 6" Casters (C5-6CASTER)
- Rear Rigid Casters (C5-5RDGCSTR)
- Corner Bumpers/Drip Trough (C5-BUMPDRIP)
- Left Hand Hinging (DD3768)
- Control Panel Cover (C5-COVER)

Note: Add an "A" to the end of the cabinet part number when ordering accessories.



Full Height Dutch Solid Doors



1/2 Height Clear Doors



1/2 Height Solid Doors



InterMetro Industries Corporation
 North Washington Street
 Wilkes-Barre, PA 18705
 www.metro.com



Metro C5 Pizza Series Heated Holding Cabinet

13.9Z

13.9Z

Metro C5 Pizza Series Heated Holding Cabinet



Metro C5 Pizza Series Heated Holding Cabinet

Specifications

- **Cabinet Material:** Type 304 stainless steel; 20-gauge polished exterior; 22-gauge interior, or .063" aluminum, brushed exterior, natural interior.
- **Insulation:** Full perimeter, 1" thick, high-density fiberglass. R Value = 4.2
- **Casters:** Four casters with 5" donut neoprene wheel, double ball bearing swivel, ball bearing axle, nickel plated, two with brake.
- **Solid Doors:** Fully insulated, double-panel, Type 304, 20-gauge polished exterior, 22-gauge interior stainless steel or .063" aluminum, brushed exterior, natural interior.
- **Hinges:** Self-closing, lift-off, double hinged, with long-life nylon bearings.
- **Gaskets:** High temperature, cabinet mounted, Santoprene gaskets.
- **Latches:** Chrome plated, high-strength magnetic pull latch with lever-action release.
- **Handles:** Four built-in polymer handles.
- **Universal Slides:** Universal wire slides; 1/4" diameter nickel-chrome wire adjustable on 1 1/2" increments. 16-gauge, Type 304, stainless steel vertical standards.
- **Wire Shelves:** Stainless steel wire shelves adjustable on 1 1/2" increments.
- **Cabinet Capacities:**

Cabinet Size	Universal Slides Capacity				Wire Shelves
	Slide Levels	16" Pizza Box	18" x 26" Sheet Pan	12" x 20" x 2 1/2" Steam Table Pan	
	Full Height/Dutch	17	34	17	
1/2 Height	8	16	8	16	2

*Capacity based on 3" slide spacing, (1) sheet pan per level, (2) 16" pizza boxes per level, or (2) steam table pans per level.

Display and Controls: Analog cabinet thermometer with independent thermostat control knob.

- **Heat Generation System:** Thermostatically controlled 1950 Watt heating element, ball bearing blower motor, and ducted air system.
- **Cord:** 7 1/2' cord with NEMA 5-20P plug. Cord mounted on top (Full Height & Pass Thru) or back (1/2 Height) can be field reversed.
- **Thermal Performance:** 70° F to 200° F operating temperature range.
- **Power Requirements:** 2000 Watts, 120 Volts, 60 Hz., single phase, 20 Amp. Service (16 Amps Draw).


Part Numbers

FULL HEIGHT CABINETS			
Part Number	Material	Doors	Holding Style
C5Z69-SDS-U	Stainless	Dutch Solid	Universal Slides
C5Z69-SDS-S	Stainless	Dutch Solid	(4) Shelves
C5Z69-SDC-U	Stainless	Dutch Clear	Universal Slides
C5Z69-SDC-S	Stainless	Dutch Clear	(4) Shelves
C5Z69-NDS-U	Aluminum	Dutch Solid	Universal Slides
C5Z69-NDS-S	Aluminum	Dutch Solid	(4) Shelves
C5Z69-NDC-U	Aluminum	Dutch Clear	Universal Slides
C5Z69-NDC-S	Aluminum	Dutch Clear	(4) Shelves
FULL HEIGHT, PASS THRU CABINETS			
Part Number	Material	Doors	Holding Style
C5Z69-SDC-UPDC	Stainless	Dutch Clear/Dutch Clear	Universal Slides
C5Z69-SDC-SPDC	Stainless	Dutch Clear/Dutch Clear	(4) Shelves
C5Z69-NDC-UPDC	Aluminum	Dutch Clear/Dutch Clear	Universal Slides
C5Z69-NDC-SPDC	Aluminum	Dutch Clear/Dutch Clear	(4) Shelves
1/2 HEIGHT CABINETS			
Part Number	Material	Doors	Holding Style
C5Z65-SFS-U	Stainless	Full Solid	Universal Slides
C5Z65-SFS-S	Stainless	Full Solid	(2) Shelves
C5Z65-SFC-U	Stainless	Full Clear	Universal Slides
C5Z65-SFC-S	Stainless	Full Clear	(2) Shelves
C5Z65-NFS-U	Aluminum	Full Solid	Universal Slides
C5Z65-NFS-S	Aluminum	Full Solid	(2) Shelves
C5Z65-NFC-U	Aluminum	Full Clear	Universal Slides
C5Z65-NFC-S	Aluminum	Full Clear	(2) Shelves
1/2 HEIGHT, PASS-THRU CABINETS			
Part Number	Material	Doors	Holding Style
C5Z65-SFC-UPFC	Stainless	Full Clear/Full Clear	Universal Slides
C5Z65-SFC-SPFC	Stainless	Full Clear/Full Clear	(2) Shelves
C5Z65-NFC-UPFC	Aluminum	Full Clear/Full Clear	Universal Slides
C5Z65-NFC-SPFC	Aluminum	Full Clear/Full Clear	(2) Shelves

Note: Add an "A" to the end of the cabinet part number when ordering accessories.

Dimensions

All cabinets are 28" wide and 38 1/4" deep (Pass-Thru are 40 1/2" deep)



Metro Heated cabinets are for hot food holding applications only.

All Metro Catalog Sheets are available on our Web Site: www.metro.com



InterMetro Industries Corporation
 North Washington Street, Wilkes-Barre, PA 18705
 Phone: 570-825-2741
 Fax: 570-825-2852

For Product Information:
 U.S. and Canada: 1.800.992.1776
 Outside U.S. and Canada: www.metro.com/contactus

L03-266
 Printed in U.S.A. Rev. 10/11

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2011 InterMetro Industries Corp.

