



System Specification	Phaser 3330	
<b>One-Sided Speed</b> A4 / 210 x 297 mm 216 x 356 mm	Up to 40 ppm Up to 34 ppm	
<b>Two-Sided Speed</b> A4 / 210 x 297 mm 216 x 356 mm	Up to 20 ppm Up to 17 ppm	
Monthly Duty Cycle <sup>1</sup>	Up to 80,000 pages / month	
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 6,000 pages	
Processor	1 GHz	
Memory	512 MB	
Connectivity	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi	
Paper Handling		
Bypass Tray		
Capacity <sup>3</sup>	50 sheets	
Sizes	Custom Sizes: 76 x 127 mm to 216 x 356 mm	
Weights	60 to 220 gsm	
Media Types	Archive Bond Card Stock Custom Envelopes Heavyweight Labels Lightweight Plain Preprinted Recycled Transparencies	
Tray 1		
Capacity <sup>3</sup>	250 sheets	
Sizes	Custom Sizes 99 x 147 mm to 216 x 356 mm	
Weights	60 to 163 gsm	
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled	
Additional Tray		
Capacity <sup>3</sup>	550 sheets	
Sizes	Custom Sizes: 76 x 127 mm to 216 x 356 mm	
Weights	60 to 163 gsm	

Additional Tray			
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled		
Total Capacity			
Device Standard Capacity <sup>3</sup>	300 sheets		
Device Total Capacity <sup>3</sup>	850 sheets		
Paper Output			
Output Capacity <sup>3</sup>	150 sheets		
Automatic 2-Sided	Standard		
Device Specification			
Electrical Requirements			
Europe	220-240 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 5A		
Power Consumption			
<b>Operation</b> <sup>4</sup>	Maximum 700 watts		
Standby Mode <sup>4</sup>	Maximum 50 watts		
Power Off Mode <sup>4</sup>	Maximum 0.1 watts		
Sleep Mode"	Maximum 3.5 watts		
Warm-up (from Sleep Mode)	As fast as 35 seconds		
Operating Environment			
Required Temperature Range Storage Operating	0°C to 40°C 10°C to 32°C		
Required Reletive Humidity	20% to 80%		
Sound Power Levels Operating Standby	54 dB(A) or less 26 dB(A) or less		
Sound Pressure Levels Operating Standby	54 dB(A) or less 26 dB(A) or less		
Dimensions and Weight (unpackaged)			
Phaser 3330	Width: 366 mm Depth: 366 mm Height: 289.6 mm Weight: 10.6 kg		
550-sheet Paper Tray	Width: 366 mm Depth: 454 mm Height: 146 mm Weight: 5.36 kg		
Dimensions and Weight (packaged)			
Phaser 3330	Width: 449.6 mm Depth: 449.6 mm Height: 403.9 mm Weight: 12.84 kg		
550-sheet Paper Tray	Width: 563 mm Depth: 497 mm Height: 285 mm Weight: 7.62 kg		

System Certification/Regulatory Compliance				
Certifications FCC Part 15 Class A				
	FCC Part 16 8         CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC         UL 60950-1/CSA 60950-1-07, 2nd Edition         Section 508         NOM         GS Mark         EAC         RoHS Directive 2011/65/EU         WEEE Directive 2012/19/EU         Citrix <sup>™</sup> Certified         Cerner (undergoing evaluation)         Apple <sup>®</sup> AirPrint <sup>®</sup> 1.5 certification         Googe Cloud Print <sup>®</sup> 2.0 Certification         Mopria <sup>®</sup> certified         Wi-Fi Alliance Certified         Blue Angel         MEDITECH         ENERGY STAR <sup>®</sup> ECOLOGO <sup>®</sup> EPEAT (United States)         To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			
Print				
First-Page-Out Time	As fast as 6.5 seconds <sup>5</sup>			
Resolution	Up to 1200 x 1200 dpi image quality			
Page Description Languages	PostScript 3 compatible PCL <sup>®</sup> 5e, 6 PDF Direct TIFF JPEG			
Maximum Print Area	4 mm from all edges			
Print Features	Watermarks Collation Automatic Two-sided Printing N-up Poster Printing Booklet Print Custom Page Size Fit to Page Scaling Draft Mode Earth Smart Printing Print from USB Job Scheduling Print from Local Drive Save Save			
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL			
Operating Systems	Microsoft® Windows® Vista and later Mac OS <sup>™</sup> 10.8.x and later Various Linux® and Unix distributions			
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® / Airprint® IPv6 Secure FTP Most protocols not in use can be disabled			
Administrative Protocols	DHCP, SNMP, WINS, SLP <sup>®</sup> v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP			
Font Capability	136 PostScript fonts 111 scalable PCL fonts 1 Bitmap PCL font			

Mobile Solutions and Mobile Device Apps			
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox <sup>®</sup> and non Xerox <sup>®</sup> devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox <sup>®</sup> and non Xerox <sup>®</sup> devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone <sup>®</sup> or iPad <sup>®</sup> with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Google Cloud Print <sup>™</sup>	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook <sup><math>m</math></sup> notebook computers and any other web-connected device. <sup>6</sup>		
Xerox <sup>®</sup> Print Service Plug-in for Android <sup>™</sup> (Free at Google Play™ Store)	The Xerox <sup>®</sup> Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play <sup>™</sup> store.		
Security			
Security Features	802.1x Secure HTTPS (SSL/TLS) Secure IPP Secure Print SSL IP Filtering IPv6 SNMP v3 IPsec WEP (64-/128-bit) WPA2-PSK (AES) WPA / WPA2-Personal WPA / WPA2-Enterprise		
WiFi Security			
	Authentication Method Open WPA PSK WPA PSK / WPA2 PSK WPA Enterprise WPA Enterprise / WPA2 <sup>™</sup> Enterprise WPA Enterprise Authentication Method options: • PEAPVO MS-CHAPV2 • EAP-TLS • EAP-TLS PAP • EAP-TTLS PAP	Encryption WEP 64 / 128-bit ASCII / HEX TKIP AES TKIP AES	
Device Management			
Xerox® CentreWare® Web			
Device Status	Web server embedded • Tray status/contents • Consumables status		
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete		
Job Submission	Print-ready files (PS, PCL <sup>®</sup> 5c/6, PDF, TIFF Output feature selection		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.		
Browsers	Microsoft® Internet Explorer 6, 7 Firefox® 2, 3 Safari® 3.0		
Xerox® CentreWare® Internet Services – Integrated Device Web Page			
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> </ul>		
Xerox $^{\circ}$ Standard Accounting (Standard)			

Xerox® Standard Accounting (Standard)				
Accounting	Up to 1,000 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)			
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>			
Remote Print Services				
Automated Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox <sup>®</sup> device usage. Eliminates the need for time-consumingend-user involvement and ensures that meter reads are submitted to Xerox on time.			
Automated Supplies Replenishment (ASR)	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.			
What's In The Box				
	<ul> <li>Phaser 3330 Printer</li> <li>Standard Capacity Print cartridge: 2,600 pages<sup>7</sup></li> <li>Software and Documentation CD (with Safety, Regulatory, Recycling and Disposal Guides), Print Drivers and Warranty Statement</li> <li>Installation Guide</li> <li>Quick Use Guides</li> <li>Power cord</li> </ul>			
Supplies and Accessories	Quantity	Part Number		
Supplies				
Extra-High Capacity Print Cartridges	15,000 standard pages <sup>7</sup>	106R03624		
High Capacity Print Cartridges	8,500 standard pages <sup>7</sup>	106R03622		
Standard Capacity Print Cartridges	2,600 standard pages <sup>7</sup>	106R03620		
Drum Cartridge	30,000 standard pages <sup>8</sup>	101R00555		
Accessories				
550-sheet Paper Tray	097N02254			
Near Field Communication (NFC) Enablement Kit	097N02255			
Phaser 3330 Card Reader Cover Kit	497K18010			

 $^1$  Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.  $^2$  Expected regular monthly throughput.

<sup>1</sup> Expected regular monthly throughput.
<sup>3</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.
<sup>6</sup> Power states defined per ENERGY STAR<sup>®</sup> Programme requirements for Imaging Equipment.
<sup>6</sup> Printing from USB.
<sup>6</sup> Depending on the specific mobile device, versions or vendor, the mobile device may require a free download of the app from the appropriate store(s).
<sup>7</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.
<sup>8</sup> Approximate pages. Declared Yield based on A4-size 75 gsm pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.



©2016 Xerox Corporation. All rights reserved. Xerox<sup>®</sup>, Xerox and Design<sup>®</sup>, CentreWare<sup>®</sup>, Global Print Driver<sup>®</sup>, Mobile Express Driver<sup>®</sup>, and Phase<sup>®</sup> are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR<sup>®</sup> partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. 11/16 BR19338 33355-01ED