# **INF5533e**

Customizable, open Android platform, 55-inch display for K-12

Part #: INF5533e

**InFocus** 

With 4K resolution, Total Touch Control<sup>™</sup>, built-in education features, and the ability to natively run Android apps, the JTouch Plus INF5533e is a fully customizable, all-in-one teaching, collaboration, and presentation solution - the most education-friendly JTouch ever.

# **Key Features**

- Navigate a friendly, easy-for-anyone interface with Total
   Touch Control™ no need for a remote
- Built-in whiteboard, browser, file explorer, as well as AirPlay and EShare for wireless casting
- Annotate over any application or video input
- Comment and draw over websites, documents, and more
- Brilliant 55-inch, 4K resolution screen with anti-glare
- Add any Android app
- Customize your whiteboard background



# Open Android Platform

Expand and customize your platform with any Android application or game. Simply download and install as you would on your phone.

#### Four Critical Applications

All JTouch Plus models include the four critical applications needed for interactive touch panels: Casting, Whiteboarding, Browsing, and File Viewing. Create on a full-featured digital whiteboard, present videos and photos, browse the web, easily connect and share content from your Apple, Windows, or Android devices with wireless casting.

# **Intuitive Touch**

Erase, zoom, and pull up menu options quickly and easily with incredibly intuitive touch gestures on the JTouch Plus. Use one finger to draw, two fingers to move, and three fingers to erase on the whiteboard or when annotating on any screen. A simple swipe gesture on either side of the screen reveals a full menu of further options.

#### Interactive whiteboard

Draw, write, and capture notes on a fully customizable, built-in digital whiteboard. Choose any background on a multi-screen canvas with room for free-form drawings, diagrams, and more. Draw using your finger or one of the provided styli using a complete collection of digital pens, highlighters, shapes, lines, and colors.

## **Multi-input Touch Monitor**

Plug up to eight devices into your INF5533e monitor. HDMI-based sources can also connect via five separate USB-B ports to access the panel's touch control. Front access IO ports make it convenient to connect, view, and touch control any user's PC temporarily with both HDMI and Touch USB.

## **Optional PC**

Turn your INF5533e into a fully integrated, powerful all-in-one Windows 10 PC with touch by adding the optional Core i5 OPS PC Module (coming soon).

## Specifications\*

Diagonal Size         55°           Resolution — Native         4K UHD (3840 x 2160)           Display Technology         Direct-LED backlight           Touch Screen Features         Antiglare, Anti-Fingerprint, 10-point IR touch           Glass Strength         4mm thick, heat treated           Scratch Resistance         7 Mehs           Contrast Ratio         12001           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176°           Speakers         Strevo 10W x 2           Speakers         Strevo 10W x 2           Display Connectors – Inputs         RS232, 25mm Pc audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard         AC 100 to 240V, 50/60           FC           System           Included Accessories           PC Hardwa         OPS Bay           System           Included Accessories         Power ord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         < 4.0 dBA at 77F	Display	INF5533e
Display Technology         Direct-LED backlight           Touch Screen Features         Anti-glare, Anti-Fingerprint, 10-point IR touch           Class Strength         4mt hick, heat treated           Scratch Resistance         7 Mohs           Contrast Ratio         1,200-1           Display Brightness         350 cd/m2           Referesh Rate         10- Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176           Speakers         Stereo 10W x 2           Speakers         Stereo 10W x 2           Display Connectors – Inputs         RS232, Component video, Composite video, HDMI x 4, Ry-45 (Ethernet), VGA, USB 3.0 x 2, Media USB (Android), PC Audio in (stereo, VGA Audio source), V6* Microphone (Mono linked to 0PS), USB 2.0 x 2, 0PS PC USB x 2, RCA L/R audio           Power Standard         Ac 100 to 240V, 50/60           PC Hardware         OPS Bay           Vester         VEX.           Viewing Conditions         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Variable Noise         4 of dAs at 77F / 25°C           Operating Conditions         32 to 104°F at 0 to 100000 ft / 10 to 40°C at 0 to 3048 m           Product Warranty <td>Diagonal Size</td> <td>55"</td>	Diagonal Size	55"
Touch Screen Features         Anti-glare, Anti-Fingerprint, 10-point IR touch           Glass Strength         4mm thick, heat treated           Contrast Ratio         1, 200:1           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0,429 mm           Viewing Angle         176°           Speakers         Stereo 10W x 2           Speakers         Stereo 10W x 2           Pixel Pitch         2,200 mopenent video, Composite video, HDMI x 4, RI-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA (Ra adio           Display Connectors – Outputs         RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard         0PS Bay           System           Included Accessories           Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Mudible Noise         4.40 dBA at 77F / 25°C           Operating Conditions         32 to 104F at 0 to 100000 ft/ 0 to 40°c at 0 to 3048 m           Mounting Pattern         Yesa           Product Warranty	Resolution – Native	4K UHD (3840 x 2160)
Glass Strength         4mm thick, heat treated           Scratch Resistance         7 Mohs           Contrast Ratio         1,200:1           Usipaly Prightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176°           Speakers         Stereo 10W x 2           Speakers         Stereo 10W x 2           Bisplay Connectors – Inputs         RS232, Component video, Composite video, HDMI x 4, RJ-45 [Ethernet), VGA, USB 3.0 x2, Media USB (Android), PCA L/R audio           Display Connectors – Outputs         RS232, Component video, Composite video, HDMI x 4, RJ-45 [Ethernet), VGA, USB 3.0 x2, Media USB (Android), PCA L/R audio           Power Standard         RS232, Somm PC audio, HDMI, SPDIF, 35mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard         OPS Bay           Forther         Power Standard           Product Accessories         OPS Bay           Product Dimensions         OPS Bay           Product Quick Scannies         Aud BAA at 77F / 25°C           Operating Conditions         32 to 104°F at 0 to 10000 ft / 0 condo 304° m           Operating Conditions         32 to 104°F at 0 to 10000 ft / 0 condo 304° m           Operating Conditions	Display Technology	Direct-LED backlight
Scratch Resistance         7 Mohs           Contrast Ratio         1,200-1           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         156*           Speakers         Stereo 10W x 2           Speakers         Stereo 10W x 2           Bisplay Connectors – Inputs         RS232, Component video, Composite video, HDMI x 4, RI-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), RCA L/R audio           Display Connectors – Outputs         RS232, 35mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard         PS232, 35mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard           Power Standard         OPS Bay           Power Standard           Power Standard         Power Code Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Power Standard         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Product Accessories         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         24 to 10 to 1000 of 1/0 cable to 3048 m           Operatin	Touch Screen Features	Anti-glare, Anti-Fingerprint, 10-point IR touch
Contrast Ratio         1,200:1           Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176*           Speakers         Sereo 10W x 2           Speakers         RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio in (stereo, VGA Audio source), 1/8* Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio           Display Connectors – Outputs         RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard         Act 100 to 240V, 50/60           PC         Virelandaria           Poster         Virelandaria           Vireless Collaboration         OPS Bay           Vireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77F / 25°C	Glass Strength	4mm thick, heat treated
Display Brightness         350 cd/m2           Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176°           Speakers         Stereo 10W x 2           RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio in (stereo, VGA Audio source), 1/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio           Display Connectors – Outputs         RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard         Ac 100 to 240V, 50/60           PC         PC           PC         POWER           Potation (See Scollaboration         Casting embedded           Audible Noise         A 40 dBA at 77°F / 25°C           Operating Conditions         32 to 104°F at 0 to 100000 ft / 0 to 40°C at 0 to 3048 m           Mounting Pattern         VESA 400x-600mm with MB screws           Product Warranty         2 years           Product Weight         84 lbs / 38.1 kg           Shipping Dimensions         84 lbs / 38.1 kg           Shipping Dimensions         85 years 24.15/ 96.2 x 1518.9 x 243.8 mm	Scratch Resistance	7 Mohs
Refresh Rate         120 Hz           Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         76°           Speakers         Stereo 10W x 2           Display Connectors – Inputs         RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio in (stereo, VGA Audio source), V8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RAC AU Ra audio           Power Standard         AC 100 to 240V, 50/60           PC         PC           PC Hardware         OPS Bay           System         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         C acting embedded           Audible Noise         < 4.0 dBA at 77°F / 25°C	Contrast Ratio	1,200:1
Response Time         8.0 ms           Pixel Pitch         0.429 mm           Viewing Angle         176°           Speakers         Stereo 10W x 2           Display Connectors – Inputs         RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8° Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio           Display Connectors – Outputs         RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard         AC 100 to 240V, 50/60           PC           PC Hardware         OPS Bay           System           Included Accessories         Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77°F / 25°C	Display Brightness	350 cd/m2
Pixel Pitch         0.429 mm           Viewing Angle         176°           Speakers         Stere OW × 2           RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio           Display Connectors – Outputs         RS232, 35mm PC audio, HDMI, SPDIF, 35mm Headphone, USB-B x2 (for touch control), RCA L/R audio           Power Standard         Ac 100 to 240V, 50/60           PC           PC         Virelandware           Power Cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter           Wireless Collaboration         Casting embedded           Wireless Collaboration         Casting embedded           Operating Conditions         32 to 104°F at 0 to 10000 ft / 0 to 3048 m           Mounting Pattern         VESA 400×600mm with M8 screws           Product Warranty         2 years           Product Dimensions         30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm           Product Weight         84 lbs / 38.1 kg           Shipping Dimensions         38 k 50.8 x 2.1518.9 x 243.8 mm	Refresh Rate	120 Hz
Viewing Angle       176°         Speakers       Stereo 10W x 2         Display Connectors – Inputs       RS232, Component video, Composite video, HDM1 x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio         Display Connectors – Outputs       RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio         Power Standard       AC 100 to 240V, 50/60         PC       The Ardware         PC Hardware       OPS Bay         System       Included Accessories         Wireless Collaboration       Casting embedded         Audible Noise       < 40 dBA at 77°F / 25°C	Response Time	8.0 ms
SpeakersStereo 10W x 2Display Connectors – InputsRS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audioDisplay Connectors – OutputsRS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audioPower StandardAC 100 to 240V, 50/60PCPCPCPC HardwareOPS BayIncluded AccessoriesPower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi AdapterWireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77"F / 25"C	Pixel Pitch	0.429 mm
RS232, Component video, Composite video, HDMI x 4, RJ-45 (Ethernet), VGA, USB 3.0 x2, Media USB (Android), PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audio  Display Connectors – Outputs RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio  Power Standard AC 100 to 240V, 50/60  PC  PC Hardware OPS Bay  System  Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter  Wireless Collaboration Casting embedded  Audible Noise 40 dBA at 77" F / 25"C  Operating Conditions 32 to 104" at 0 to 10000 ft / 0 to 40" cat 0 to 3048 m  Mounting Pattern VESA 400×600mm with M8 screws  Product Warranty 2 years  Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm  Product Weight 84 lbs, 79.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Viewing Angle	176°
Display Connectors – InputsPC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2, RCA L/R audioDisplay Connectors – OutputsRS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audioPower StandardAC 100 to 240V, 50/60PCPC HardwareOPS BaySystemIncluded AccessoriesPower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi AdapterWireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77"F / 25"C	Speakers	Stereo 10W x 2
Power Standard         AC 100 to 240V, 50/60           PC           PC Hardware         0PS Bay           System         Included Accessories           Wireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77°F / 25°C	Display Connectors – Inputs	PC Audio In (stereo, VGA Audio source), 1/8" Microphone (Mono linked to OPS), USB 2.0 x2, OPS PC USB x2,
PC           PC Hardware         0PS Bay           System         Included Accessories           Vireless Collaboration         Casting embedded           Audible Noise         < 40 dBA at 77°F / 25°C	Display Connectors – Outputs	RS232, 3.5mm PC audio, HDMI, SPDIF, 3.5mm Headphone, USB-B x2 (for touch control), RCA L/R audio
PC HardwareOPS BaySystemIncluded AccessoriesPower cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi AdapterWireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77"F / 25°COperating Conditions32 to 104"F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 mMounting PatternVESA 400×600mm with M8 screwsProduct Warranty2 yearsProduct Dimensions30.8 × 50.8 × 4.2 in / 782.3 × 1290.3 × 106.7 mmProduct Weight84 lbs / 38.1 kgShipping Dimensions38 × 59.8 × 9.6 in / 965.2 × 1518.9 × 243.8 mm	Power Standard	AC 100 to 240V, 50/60
Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise <40 dBA at 77°F / 25°C  Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m  Mounting Pattern VESA 400×600mm with M8 screws  Product Warranty 2 years  Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm  Product Weight 84 lbs / 38.1 kg  Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	PC	
Included Accessories Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter Wireless Collaboration Casting embedded Audible Noise < 40 dBA at 77°F / 25°C Operating Conditions 32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m  Mounting Pattern VESA 400×600mm with M8 screws Product Warranty 2 years Product Dimensions 30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm  Product Weight 84 lbs / 38.1 kg Shipping Dimensions 38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	PC Hardware	OPS Bay
Wireless CollaborationCasting embeddedAudible Noise< 40 dBA at 77°F / 25°C	System	
Audible Noise $< 40 \text{ dBA at } 77^{\circ}\text{F} / 25^{\circ}\text{C}$ Operating Conditions $32 \text{ to } 104^{\circ}\text{F at } 0 \text{ to } 10000 \text{ ft } / 0 \text{ to } 40^{\circ}\text{C at } 0 \text{ to } 3048 \text{ m}$ Mounting PatternVESA $400 \times 600 \text{ mm}$ with M8 screwsProduct Warranty $2 \text{ years}$ Product Dimensions $30.8 \times 50.8 \times 4.2 \text{ in } / 782.3 \times 1290.3 \times 106.7 \text{ mm}$ Product Weight $84 \text{ lbs } / 38.1 \text{ kg}$ Shipping Dimensions $38 \times 59.8 \times 9.6 \text{ in } / 965.2 \times 1518.9 \times 243.8 \text{ mm}$	Included Accessories	Power cord, Remote, Stylus, HDMI Cable, USB cable, Quick Start Guide, USB WiFi Adapter
Operating Conditions         32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m           Mounting Pattern         VESA 400×600mm with M8 screws           Product Warranty         2 years           Product Dimensions         30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm           Product Weight         84 lbs / 38.1 kg           Shipping Dimensions         38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Wireless Collaboration	Casting embedded
Operating Conditions0 to 40°C at 0 to 3048 mMounting PatternVESA 400×600mm with M8 screwsProduct Warranty2 yearsProduct Dimensions30.8 × 50.8 × 4.2 in / 782.3 × 1290.3 × 106.7 mmProduct Weight84 lbs / 38.1 kgShipping Dimensions38 × 59.8 × 9.6 in / 965.2 × 1518.9 × 243.8 mm	Audible Noise	< 40 dBA at 77°F / 25°C
Product Warranty2 yearsProduct Dimensions30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mmProduct Weight84 lbs / 38.1 kgShipping Dimensions38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Operating Conditions	
Product Dimensions       30.8 x 50.8 x 4.2 in / 782.3 x 1290.3 x 106.7 mm         Product Weight       84 lbs / 38.1 kg         Shipping Dimensions       38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Mounting Pattern	VESA 400×600mm with M8 screws
Product Dimensions         782.3 x 1290.3 x 106.7 mm           Product Weight         84 lbs / 38.1 kg           Shipping Dimensions         38 x 59.8 x 9.6 in / 965.2 x 1518.9 x 243.8 mm	Product Warranty	2 years
38 x 59.8 x 9.6 in / Shipping Dimensions 965.2 x 1518.9 x 243.8 mm	Product Dimensions	,
Shipping Dimensions 965.2 x 1518.9 x 243.8 mm	Product Weight	84 lbs / 38.1 kg
Shipping Weight 104 lbs / 47.2 kg	Shipping Dimensions	
	Shipping Weight	104 lbs / 47.2 kg

 $<sup>^{\</sup>star}$  Product specifications, terms, and offerings are subject to change at any time without notice.

### **Accessories**

1 Year Extended Warranty for Select 55-inch Touchscreens (EPW-55JT1)

Mobile Cart Pro for up to 75-inch Displays (Black) (INF-MOBCARTPRO-B)

SimpleShare Presentation System (INA-SIMPS1)

SimpleShare (INA-SIMS1)

SimpleShare Touch Presentation System (INA-SIMINT1)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

Wall Mount for up to 75-inch Display (INF-WALLMNT2)

Floor Stand for up to 75-inch Displays (INF-FLRSTND)

Mobile Cart for up to 75-inch Displays (INF-MOBCART)

Mobile Cart for Vertical Lift Mount (INA-CARTBB)

Vertical Lift Display Wall Mount (INA-MNTBB70)

VESA Interface Bracket for Vertical Lift Mounts (INA-VESABB)

Floor Support for Lift Wall Mount (INA-SUPPORTBB)

Lift Case for 55-inch to 65-inch Displays (CA-ATALIFT65)

Remote Control for Mondopad, BigTouch or JTouch (INA-REMOTE2)

Mini USB WiFi Adapter (INA-WIFIUSB-3)

Qwizdom Software Bundle (INS-QBUNDLE)

Oktopus Blend Software (INS-QBLEND1T40-1Y)

Ximbus Software (INS-QXIM1T40-1Y)

InFocus Whiteboard App for Android (INS-AND-WHIT)

InFocus Browser App for Android (INS-AND-BROW)

InFocus FileViewer App for Android (INS-AND-FILE)

2 Year Extended Warranty for Select 55-inch Touchscreens (EPW-55JT2)

3 Year Extended Warranty for Select 55-inch Touchscreens (EPW-55JT3)