

### **Overview**

# Handle business solutions securely, plus help conserve energy with HP EcoSmart toner

Choose an HP LaserJet Enterprise MFP designed to handle business solutions securely and efficiently, and helps conserve energy with HP EcoSmart toner black. Keep up with the demands of growing business with a printer you can rely on.[8]

#### The world's most secure printing[1]

Each printer in your fleet checks its operating code and repairs itself from attacks.

#### Low costs, low energy use

Avoid frustrating reprints, wasted supplies, and service calls using Original HP Toner cartridges.

#### Your whole fleet. At your control.

Centralize control of your printing environment with HP Web Jetadmin[4]—and help build business efficiency.

#### Give workgroups the speed they need

Help workgroups capture every page easily and detect potential errors or missed pages —every time.













#### **Features**

| World's most secure printing <sup>[1]</sup> |
|---|
|   |
| Enhanced user interface                     |
|   |
| Enhanced workflows                          |
|   |

[4] HP Web Jetadmin is available for download at no additional charge at http://www.hp.com/go/webjetadmin

[8] HP calculations based on Energy Star normalized TEC data comparing the HP LaserJet 500 series monochrome printers introduced in spring 2019 HP 89A/X/Y compared to HP 87A/X.

<sup>[1]</sup> Based on HP review of 2018 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit hp.com/go/PrintersThatProtect. For more information: http://www.hp.com/go/printersecurityclaims

# Specifications

| Print Resolution Technologies     | 300 dpi, 600 dpi, HP FastRes 1200, HP ProRes 1200   |
|-----------------------------------|---|
| Print quality black (best)        | Up to 1200 x 1200 dpi   |
| Print speed black (ISO, A4)       | Up to 43 ppm  |
| Print speed black (ISO, letter)   | Up to 45 ppm  |
| Print speed                       | Print speed up to 45 ppm (black)  |
| Functions                         | Print, copy, scan, fax  |
| Duplex printing                   | Automatic (standard)  |
| Duty cycle (monthly, A4)          | Up to 150,000 pages   |
| Duty cycle (monthly, letter)      | Up to 150,000 pages   |
| Printer smart software features   | Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB   |
| Copier smart software features    | Auto scale; Reduce/enlarge from scanner glass (25 to 400 percent);<br>Collate; Auto color detection; Two-sided copying; Image adjustments<br>(darkness, background cleanup, sharpness); Job build   |
| Scanner advanced features         | Optimize text/picture; Image adjustments; Job build; Output quality setting; Selectable scan resolution 75 to 600 dpi; Auto detect color; Edge Erase; Job notification; Blank page suppression; HP Quick Sets; HP EveryPage; Auto orientation; Embedded Optical Character Recognition (OCR), Auto crop to page; Auto-tone |
| Fax smart software features       | Stored faxes; Fax archiving; Fax forwarding; Scale to fit; Fax address book; LAN/Internet fax; Fax number confirmation; Holiday fax schedule  |
| Energy savings feature technology | HP Auto-On/Auto-Off Technology; Instant-on Technology; Instant-on Copy  |
| Replacement cartridges            | HP 89A Black Original LaserJet Toner Cartridge (~5,000 pages) CF289A;<br>HP89X High Yield Black Original LaserJet Toner Cartridge (~10,000 pages)<br>CF289X; HP89Y Extra High Yield Black Original LaserJet Toner Cartridge<br>(~20,000 pages) CF289Y <sup>[16]</sup>   |
| Supplies feature                  | HP JetIntelligence Cartridge  |
| Connectivity, standard            | 1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 Host; 1 Gigabit Ethernet; 1 Hardware Integration Pocket; 1 Fax;   |
| Connectivity, optional            | HP Jetdirect 2900nw Print Server J8031A; HP Jetdirect 3000w<br>NFC/Wireless Accessory J8030A; HP Jetdirect 3100w BLE/NFC/Wireless<br>Accessory 3JN69A   |
| Modem                             | 33.6 kbps   |
| Network capabilities              | Yes, via HP Jetdirect Ethernet embedded print server (standard) which supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); Optional 802.11a/b/g/n wireless networking and second Ethernet port.  |

| Wireless capability   | Optional, enabled with purchase of a wireless hardware accessory. Single band Wireless Station and Wi-Fi Direct functionality available with HP Jetdirect 3000w NFC/Wireless Accessory J8030A, Dual band Wireless Station and Wi-Fi Direct functionality available with HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A, Dual band Wireless Station functionality available with HP Jetdirect 2900nw Print Server J8031A  |
|---|--|
| Mobile printing capability  | Apple AirPrint™; Google Cloud Print™; HP ePrint; Mopria™ Certified; Roam capable for easy printing   |
| Network protocols, supported  | Via built-in networking solution: TCP/IP; IPv4; IPv6; Print: TCP-IP port 9100 Direct Mode; LPD (raw queue support only); Web Services Printing; IPP 2.0; Apple AirPrint™; HP ePrint; FTP Print; Google Cloud Print; Discovery: SLP; Bonjour; Web Services Discovery; IP Config: IPv4 (BootP; DHCP; AutoIP; Manual; TFTP Config; ARP-Ping); IPv6 (Stateless Link-Local and via Router; Stateful via DHCPv6); Management: SNMPv2/v3; HTTP/HTTPs; Telnet; TFTP Config; Syslog; Security: SNMPv3; SSL Cert Management; IPSec/Firewall; ACL; 802.1x   |
| Software included   | No software solutions are included in the Box, only on http://hp.com, http://123.hp.com  |
| Compatible Operating Systems  | Windows Client OS (32/64 bit), Win10, Win8.1, Win 8 Basic, Win8 Pro, Win8 Enterprise, Win8 Enterprise N, Win7 Starter Edition SP1, UPD Win7 Ultimate, Mobile OS, iOS, Android, Mac, Apple® macOS Sierra v10.12, Apple® macOS High Sierra v10.13, Apple® macOS Mojave v10.14, Discrete PCL6 Printer Driver, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for your (Product Name) User Guide, Search for the Supported Operating Systems section, UPD PCL6 / PS Printer Drivers, Supported Operating systems, For more information on the supported operating systems see www.hp.com/go/upd |
| Environmental   | Mercury free   |
| ENERGY STAR® certified  | Yes  |
| Energy efficiency   | EPEAT® Gold; ENERGY STAR® qualified; CECP; Blue Angel DE-UZ-205 <sup>[11]</sup>  |
| Blue Angel compliant  | Yes, Blue Angel DE-UZ 205—only ensured when using Original HP supplies   |
|   | 163, Blue Angel DE 02 203 only ensured when daining original in Supplies   |
| Copy speed (black, normal quality, A4)  | Up to 43 cpm   |
|   |  |
| A4)   | Up to 43 cpm   |
| A4) Copy speed black (normal, letter)   | Up to 43 cpm Up to 45 cpm  |
| A4) Copy speed black (normal, letter) Copy speed black duplex (A4)  | Up to 43 cpm Up to 45 cpm Up to 34 cpm   |
| A4) Copy speed black (normal, letter) Copy speed black duplex (A4) Copy speed black duplex (Letter)   | Up to 43 cpm  Up to 45 cpm  Up to 34 cpm  Up to 36 cpm  Scan to E-mail; Save-to-Network Folder; Save-to-USB drive; Send to Sharepoint; Send to FTP; Send to LAN Fax; Send to Internet Fax; OCR; Local Address Book; SMTP over SSL; Blank Page Removal; Edge Erase; Auto Color Sense; Auto Crop To Content; Compact PDF; Auto Tonescale; Auto   |
| Copy speed black (normal, letter) Copy speed black duplex (A4) Copy speed black duplex (Letter)  Digital sending standard features                                    | Up to 45 cpm  Up to 34 cpm  Up to 36 cpm  Scan to E-mail; Save-to-Network Folder; Save-to-USB drive; Send to Sharepoint; Send to FTP; Send to LAN Fax; Send to Internet Fax; OCR; Local Address Book; SMTP over SSL; Blank Page Removal; Edge Erase; Auto Color Sense; Auto Crop To Content; Compact PDF; Auto Tonescale; Auto Orientation; Multi-Pick Detect; Auto Straighten; Auto Crop To Page; OCR  Authentication; Digital fax (send to LAN, Internet); HP Digital Sending Software; Local Address Book; OCR; Send-to-folder; Send-to-printer;  |
| Copy speed black (normal, letter) Copy speed black duplex (A4) Copy speed black duplex (Letter)  Digital sending standard features  Digital sending optional features | Up to 43 cpm  Up to 34 cpm  Up to 36 cpm  Scan to E-mail; Save-to-Network Folder; Save-to-USB drive; Send to Sharepoint; Send to FTP; Send to LAN Fax; Send to Internet Fax; OCR; Local Address Book; SMTP over SSL; Blank Page Removal; Edge Erase; Auto Color Sense; Auto Crop To Content; Compact PDF; Auto Tonescale; Auto Orientation; Multi-Pick Detect; Auto Straighten; Auto Crop To Page; OCR  Authentication; Digital fax (send to LAN, Internet); HP Digital Sending Software; Local Address Book; OCR; Send-to-folder; Send-to-printer; Send-to-workflow   |

| Scan speed (normal, A4)                      | Up to 45 ppm/64 ipm (b&w), up to 45 ppm/58 ipm (color)   |
|--|--|
| Scan speed (normal, letter)                  | Up to 48 ppm/68 ipm (b&w), up to 48 ppm/60 ipm (color)   |
| Scan file format                             | Digital Send: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF/A (OCR), HTML (OCR), CSV (OCR); Scan to easy access USB: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF/A (OCR), HTML (OCR), CSV (OCR); Print from easy access USB: PDF, PS, Print Ready files (.prn, .pcl, .cht)   |
| Scan input modes                             | Front panel applications: Copy, E-mail, Save to Network Folder, Save to USB, Save to Device Memory, Open Extensibility Platform (OXP) applications   |
| Scan technology                              | Contact Image Sensor (CIS)   |
| Scanner type                                 | Flatbed, ADF   |
| Display area (imperial)                      | 6.37 x 4.78 in   |
| Display area (metric)                        | 162 x 121.5 mm   |
| Display                                      | 8.0 in (20.3 cm), touchscreen (1024x768), LCD (color graphics), smooth gesture, enabled touchscreen  |
| Minimum dimensions (W x D x H)               | 482 x 496 x 497 mm   |
| Minimum dimensions (W $\times$ D $\times$ H) | 18.98 x 19.52 x 19.55 in   |
| Weight                                       | 22.13 kg <sup>[2]</sup> (With print cartridges)  |
| Weight                                       | 49.16 lb<br>(With print cartridges)  |
| Power consumption                            | 629 watts (Printing), 28.8 watts (Ready), 5.3 watts (Sleep), 0.74 watts (Auto-Off/Auto-On), LAN connection: 0.06 watts (Auto-Off), 0.06 watts (Off) <sup>[3]</sup>   |
| Power supply type                            | Built-in 115V or 220V Power Supply   |
| What's in the box                            | HP LaserJet Enterprise Flow M528c MFP; HP Original LaserJet Introductory Toner Cartridge (~7,500 pages); Regulatory flyer (CD replacement); Unpack flyer; Installation Guide; Power cord; Warranty Cards; Support flyers/phone number list; Control Panel Overlay Label Sets (Flow); Overlay keyboard (ABJ); Fax cable; Japan jtr errata (ABJ) <sup>[1]</sup>  |
| Services (Care Pack)                         | UB7B2E - HP 3 years Next Business Day w/DMR LaserJet M528 SVC; UB7B3E - HP 4 years Next Business Day w/DMR LaserJet M528 SVC; UB7B4E - HP 5 years Next Business Day w/DMR LaserJet M528 SVC; UB7B5E - HP 3 years 4 hours 9x5 w/DMR LaserJet M528 SVC; UB7B6E - HP 4 years 4 hours 9x5 w/DMR LaserJet M528 SVC; UB7B7E - HP 5 years 4 hours 9x5 w/DMR LaserJet M528 SVC; UB7C1E - HP 3 years ChnlPartsOnly LaserJet M528 SVC; UB7C2E - HP 4 years ChnlPartsOnly LaserJet M528 SVC; UB7C3E - HP 5 years ChnlPartsOnly LaserJet M528 SVC; UB7C4PE - HP 1 year PW Next Business Day w/DMR LaserJet M528 SVC; UB7C5PE - HP 2 years PW Next Business Day w/DMR LaserJet M528 SVC; UB7C6PE - HP 1 year PW w/DMR 4 hours 9x5 LaserJet M528 SVC; UB7C7PE - HP 2 years PW w/DMR 4 hours 9x5 LaserJet M528 SVC; UB7D0PE - HP 1 year PW ChnlPartsOnly LaserJet M528 SVC; UB7D1PE - HP 2 years PW ChnlPartsOnly LaserJet M528 SVC |

Warranty

One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (wty code 4G; wty ID A001)

# Additional specifications

| ADF Capacity   | 100  |
|--|--|
| Accessories  | HP LaserJet 550 Sheet Paper Tray F2A72A, HP LaserJet Printer Cabinet F2A73A, HP Secure Hard Disk Drive with FIPS Validation (TAA Compliant) 1PV95A, TAA FIPS/CC HDD Accessory 5EL03A, HP Jetdirect 3000w NFC/Wireless Accessory J8030A, HP Jetdirect 2900nw Print Server J8031A, HP JetDirect 3100w BLE/NFC/Wireless Accessory 3JN69A, HP 1 GB DDR3 x32 144-Pin 800 MHz SODIMM E5K48A, HP 2 GB DDR3x32 144-Pin 800 MHz SODIMM Accessory E5K49A, HP Removable Hard Drive Enclosure 2NR12A, Accessibility Assistant 2MU47A HP Accessibility Kit 2TD64A, HP Foreign Interface Harness B5L31A, HP LaserJet Keyboard Overlay Kit Sweden A7W14A, HP USB Universal Card Reader X3D03A, HP HIP2 Keystroke Reader Y7C05A, HP Logic Card Reader 4QL32A |
| Acoustic power emissions (active scan)                   | 6.7 B(A)   |
| Acoustic power emissions (active, printing)              | 6.8 B(A)   |
| Acoustic power emissions (ready)                         | 4.0 B(A)   |
| Acoustic pressure emissions bystander (active scan)      | 52 dB(A)   |
| Acoustic pressure emissions bystander (active, printing) | 54 dB(A)   |
| Acoustic pressure emissions bystander (ready)            | 25 dB(A)   |
| Auto fax reduction supported                             | Yes  |
| Automatic document feeder capacity                       | Standard, 100 sheets   |
| Automatic paper sensor                                   | No   |
| Best technical electricity consumption (TEC)             | 1.414 KWh/week <sup>[9]</sup>  |
| Best technical electricity consumption (TEC) footnote    | Best TEC is not applicable to ES 2.0 TEC. This measurement was made with the printer configuration optimized for energy efficiency. Minimum sleep delay was used, Wi-Fi Direct was disabled and Active I/O - Energy Efficient Ethernet - was used.   |
| Bit depth  | 24-bit   |
| Bottom margin (A4)                                       | 4.3 mm   |
| Cable included   | No, please purchase USB cable separately   |
| Capacity   | 320 GB   |
| Certifications and compliances                           | CSA (Canada), ACA (Australia), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), MIC (South Korea), NOM (Mexico), Nemko, Fimko, Demko, Semko (Nordic), Eastern European approvals, CE Marking, FCC approval, Energy Star, TCO '99, Windows certified (Microsoft Windows 2000 and Microsoft Windows XP), UL listed   |
| Color scanning   | Yes  |
|  |  |

more information see http://hplipopensource.com/hplipweb/index.html,

Unix Model Script Printer Driver for more information see

http://hp.com/go/unixmodelscripts, Readiris

| Driver updates                       | Current HP printer drivers and software can be obtained from the HP Customer Care Web site: In the US, go to http://www.hp.com/support/ljM528mfp; Outside the US, go to http://www.hp.com/support 1 Select the country/region 2 Select Software and Drivers 3 Select Printer 4 Enter a product name/number 5 The operating system is automatically detected 6 Select a driver or other software 7 Then select DOWNLOAD |
|--------------------------------------|--|
| Duplex ADF scanning                  | Yes, single pass duplex scanning   |
| Electromagnetic compatibility        | CISPR 22:2008 (International) - Class A, CISPR32:2012 (International) - Class A, EN 55032: 2012 (EU) - Class A, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010, EMC Directive 2014/30/EU, FCC CFR 47 Part 15 Class A/ICES-003, Issue 6 Class A. Other EMC approvals as required by individual countries.   |
| Enhanced scanning resolution         | Up to 600 dpi  |
| Envelope Feeder                      | No   |
| FCC Class A emissions                | FCC Class A emissions - for use in commercial environments, not residential environments   |
| Fax Auto Redial                      | Yes  |
| Fax Broadcast Locations              | 210  |
| Fax PC Interface Supported           | Yes  |
| Fax Polling                          | Yes (poll to receive only)   |
| Fax Remote Retrieval                 | No   |
| Fax Speed Dials, Maximum Number      | Up to 1000 numbers (each with 210 destinations)  |
| Fax Transmission Speed               | 33.6 kbps  |
| Fax delayed sending                  | No   |
| Fax forwarding                       | Yes  |
| Fax memory                           | Up to 500 pages  |
| Fax memory                           | Up to 500 pages  |
| Fax resolution black                 | Up to 203 x 196 dpi  |
| Fax telephone mode supported         | No   |
| Fax transmission speed (letter)      | 3 sec per page   |
| File Format Supported                | CSV; HTML; JPG; MTIFF; PDF; PDF/A; RTF; Text; TIFF; Unicode Text; XPS  |
| Finished output handling             | Sheetfed   |
| First copy out black (A4)            | As fast as 6.5 sec   |
| First copy out black (A4, sleep)     | As fast as 13 sec  |
| First copy out black (letter)        | As fast as 6.5 sec   |
| First copy out black (letter, sleep) | As fast as 13 sec  |
| First page out black (A4, ready)     | As fast as 6 sec   |
| First page out black (A4, sleep)     | As fast as 13 sec  |
| First page out black (letter, ready) | As fast as 6 sec   |

| First page out black (letter, sleep)         | As fast as 13 sec  |
|--|--|
| Fonts and typefaces                          | 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP postscriopt Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at Http://www.hp.com/go/laserjetfonts  |
| Input capacity                               | Up to 650 sheets   |
| Internal Storage                             | Standard, minimum 320 GB HP High-Performance Secure Hard Disk (AES 256 hardware encryption or greater)   |
| Junk fax barrier                             | Yes  |
| Left margin (A4)                             | 4.3 mm   |
| Levels of grayscale                          | 256  |
| Mac compatible                               | Yes  |
| Maximum Input Capacity (envelopes)           | Up to 10 envelopes   |
| Maximum Memory                               | 2.75 GB MAX memory, when Accessory DIMM is installed   |
| Maximum dimensions (W $\times$ D $\times$ H) | 507 x 631 x 497 mm   |
| Maximum dimensions (W x D x H)               | 19.96 x 24.83 x 19.55 in   |
| Maximum input capacity (sheets)              | Up to 2300 sheets  |
| Maximum metric depth                         | 631  |
| Maximum metric height                        | 497  |
| Maximum metric width                         | 507  |
| Maximum output capacity (sheets)             | Up to 250 sheets   |
| Maximum print area                           | 212 x 352 mm   |
| Media size (ADF)                             | Letter; legal; oficio; executive; statement; 16K; A4; RA4; A5; A6; B5; B6 (JIS); Postcard (JIS); DPostcard (JIS); 4 x 6 in; 5 x 7 in; 5 x 8 in   |
| Media size, tray 1                           | A4; A5; A6; RA4; B5 (JIS); B6 (JIS); 10 x 15 cm; Oficio (216 x 340); 16K; postcards (JIS single and double); envelopes (B5, C5, C6, DL); 76.2 x 127 to 215.9 x 355.6 mm  |
| Media size, tray 2                           | A4; A5; A6; RA4; B5 (JIS); B6 (JIS); Oficio (216 x 340); 16K; postcards (JIS double); 105 x 148 to 215.9 x 355.6 mm  |
| Media size, tray 3                           | A4; A5; A6; RA4; B5 (JIS); B6 (JIS); Oficio (216 x 340); 16K; postcards (JIS double); 105 x 148 to 215.9 x 355.6 mm  |
| Media sizes supported                        | Tray 1: letter, legal, executive, statement, $3 \times 5$ in, $4 \times 6$ in, $5 \times 7$ in, $5 \times 8$ in, $8.5 \times 13$ in, envelopes (No. 9, No. 10, Monarch); Tray 2: letter, legal, executive, statement, $5 \times 7$ in, $5 \times 8$ in, $8.5 \times 13$ in; Optional 550-sheet tray: letter, legal, executive, statement, $5 \times 7$ in, $5 \times 8$ in, $8.5 \times 13$ in; Optional Automatic Duplexer: letter, legal, $8.5 \times 13$ in |

| Media sizes supported                     | Tray 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340), 16K, postcards (JIS single and double), envelopes (B5, C5, C6, DL); Tray 2: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), Oficio (216 x 340), 16K, postcards (JIS double); Optional 550-sheet Tray: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), Oficio (216 x 340), 16K, postcards (JIS double); Optional Automatic Duplexer: A4, RA4, Oficio (216 x 340) |
|---|--|
| Media sizes supported, key                | 4 x 6 in; Letter; Legal; Envelopes   |
| Media sizes supported, key                | 10 x 15 cm; A4; Envelopes  |
| Media sizes, custom                       | Tray 1: 3 $\times$ 5 to 8.5 $\times$ 14 in; Tray 2: 4.14 $\times$ 5.83 to 8.5 $\times$ 14 in; Optional 550-sheet Tray: 4.14 $\times$ 5.83 to 8.5 $\times$ 14 in  |
| Media sizes, custom                       | Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2: 105 x 148 to 215.9 x 355.6 mm; Optional 550-sheet Tray: 105 x 148 to 215.9 x 355.6 mm  |
| Media type and capacity, ADF              | Sheets: 100, 75 g/m <sup>2</sup>   |
| Media type and capacity, tray 1           | Sheets: 100; Transparencies: 50; Envelopes: 10   |
| Media type and capacity, tray 2           | Sheets: 550  |
| Media type and capacity, tray 3           | Sheets: 550  |
| Media types                               | Paper (bond, color, letterhead, plain, preprinted, prepunched, recycled, rough); envelopes; labels; cardstock; transparencies; user-defined  |
| Media weight (tray 1)                     | 60 to 199 g/m <sup>2</sup>   |
| Media weight (tray 2)                     | 60 to 120 g/m²   |
| Media weight (tray 3)                     | 60 to 120 g/m²   |
| Media weight, supported                   | Tray 1: 60 to 199 g/m²; tray 2+: 60 to 120 g/m²  |
| Media weight, supported                   | Tray 1: 16 to 53 lb; Tray 2+: 16 to 32 lb  |
| Media weights, supported ADF              | 12 to 53 lb  |
| Media weights, supported ADF              | 45 to 200 g/m <sup>2</sup>   |
| Memory                                    | 1.25 GB (printer); 500 MB (Scanner)  |
| Memory Slots                              | 1 slot, 144-pin, SODIMM  |
| Memory upgrade                            | Expandable to 2.75 GB through one 144-Pin SODIMM HP accessory  |
| Metric depth                              | 496  |
| Metric height                             | 497  |
| Metric width                              | 482  |
| Minimum System Requirements               | 2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com   |
| Minimum System Requirements for Macintosh | 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com   |
| Number of print cartridges                | 1 (black)  |
| Number of users                           | 5-15 Users   |
| Operating humidity range                  | 10 to 80% RH   |
| Operating temperature range               | 50 to 90.5°F   |
| Operating temperature range               | 10 to 32.5℃  |

| Orderable supplies                  | HP Staple Cartridge Refill Q7432A, HP 200 ADF Roller Replacement Kit W5U23A   |
|-------------------------------------|---|
| Output capacity                     | Up to 250 sheets  |
| Package dimensions (W x D x H)      | 735 x 592 x 613 mm  |
| Package dimensions (W x D x H)      | 28.9 x 23.3 x 24.1 in   |
| Package weight                      | 65.0 lb   |
| Package weight                      | 29.3 kg   |
| Pallet dimensions                   | 47.2 x 31.5 x 77.7 in   |
| Pallet dimensions (W x D x H)       | 1200 x 800 x 1973 mm  |
| Pallet weight                       | 440 lb  |
| Pallet weight                       | 200 kg  |
| Paper handling input, optional      | Optional 550-sheet tray (add up to 3 trays)   |
| Paper handling input, standard      | 100-sheet multipurpose Tray 1, 550-sheet input Tray 2, automatic duplex printing  |
| Paper handling output, standard     | 250-sheet output bin, convenience stapler   |
| Paper trays, maximum                | 5   |
| Paper trays, standard               | 2   |
| Plug and play                       | HP Smart Install  |
| Power                               | Input voltage: 100V to 127V nominal (+/-10%), 50 - 60 Hz nominal (+/- 3 Hz), 7.5 A; Input voltage: 220V to 240V nominal (+/-10%), 50 - 60 Hz nominal (+/- 3 Hz), 4 A  |
| Print Technology                    | Laser   |
| Print colors                        | No  |
| Print languages                     | HP PCL 6, HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint $^{\text{TM}}$   |
| Print quality black (normal)        | Up to 600 x 600 dpi   |
| Print resolution black (fine lines) | Up to 1200 x 1200 dpi   |
| Print speed black (Landscape, A5)   | Up to 65 ppm  |
| Print speed duplex (A4)             | Up to 34 ipm  |
| Print speed duplex (letter)         | Up to 36 ipm  |
| Print speed footnote number (A5)    | [13]  |
| Print technology                    | Laser   |
| Printer Management                  | HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator) |
| Processor speed                     | 1.2 GHz   |
| Quantity per pallet                 | 6   |

| RMN number   | BOISB-1807-03  |
|--|--|
| Recommended media weight (duplex)  | 60 to 120 g/m²   |
| Recommended media weight (duplex)  | 16 to 32 lb  |
| Recommended monthly page volume  | 2000 to 7500 <sup>[6]</sup>  |
| Recommended monthly scan volume  | 8000 to 14,000   |
| Recommended operating humidity range   | 30 to 70% RH   |
| Recommended operating temperature range  | 15 to 27℃  |
| Recommended operating temperature range  | 59 to 80.6°F   |
| Resolution   | 600 dpi optical  |
| Resolution (black and white, standard mode)  | 203 x 98 dpi   |
| Resolution (black and white, superfine mode)   | Up to 203 x 392 or 300 x 300 dpi   |
|  |  |
| Resolution (black photo grayscale)   | $300 \times 300$ dpi ( $400 \times 400$ dpi for received faxes only)   |
| Resolution (black photo grayscale) Right margin (A4)   | 300 x 300 dpi (400 x 400 dpi for received faxes only) 4.3 mm   |
| ·  | ·  |
| Right margin (A4)  | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by  |
| Right margin (A4)  Safety  | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  |
| Right margin (A4)  Safety  Scan resolution, hardware   | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Up to 600 x 600 dpi   |
| Right margin (A4)  Safety  Scan resolution, hardware Scan resolution, optical  | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Up to 600 x 600 dpi  Up to 600 dpi  |
| Right margin (A4)  Safety  Scan resolution, hardware Scan resolution, optical Scan size (ADF), maximum   | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Up to 600 x 600 dpi  Up to 600 dpi  |
| Right margin (A4)  Safety  Scan resolution, hardware Scan resolution, optical Scan size (ADF), maximum Scan size (ADF), maximum  | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Up to 600 x 600 dpi  Up to 600 dpi  8.5 x 34.0 in  216 x 864 mm   |
| Right margin (A4)  Safety  Scan resolution, hardware Scan resolution, optical Scan size (ADF), maximum Scan size (ADF), minimum  | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Up to 600 x 600 dpi  Up to 600 dpi  8.5 x 34.0 in  216 x 864 mm  101.6 x 148 mm                           |
| Right margin (A4)  Safety  Scan resolution, hardware Scan resolution, optical Scan size (ADF), maximum Scan size (ADF), minimum Scan size (ADF), minimum Scan size (ADF), minimum                          | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Up to 600 x 600 dpi  Up to 600 dpi  8.5 x 34.0 in  216 x 864 mm  101.6 x 148 mm  4 x 5.8 in               |
| Right margin (A4)  Safety  Scan resolution, hardware Scan resolution, optical Scan size (ADF), maximum Scan size (ADF), minimum Scan size (ADF), minimum Scan size (ADF), minimum Scan size (ADF), minimum | 4.3 mm  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); IEC 62471:2006/EN 62471:2008 (LED lighting); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Up to 600 x 600 dpi  Up to 600 dpi  8.5 x 34.0 in  216 x 864 mm  101.6 x 148 mm  4 x 5.8 in  216 x 356 mm |

| Security management  | Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solutions (e.g.; badge readers); Network: IPsec/firewall with Certificate; Pre-Shared Key; and Kerberos authentication; Supports WJA-10 IPsec configuration Plug-in; 802.1X authentication (EAP-PEAP; EAP-TLS); SNMPv3; HTTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft); Secure Erase; SSL/TLS (HTTPS); Encrypted Credentials; Device: Security lock slot; USB port disablement; hardware integration pocket for security solutions; Intrusion Detection with Red Balloon Security Technology - Constant in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing capability; Whitelisting - loads only known good code (DLLs, EXEs,); Connection Inspector - helps ensure network connections to device are safe, Security management: Compatible with HP JetAdvantage Security Manager, HP Printer Security Plugin for Microsoft SCCM, Device Security Syslog Messages processed and accessable in ArcSight, Splunk, and McAfee(ESM) SIEMs |
|--|--|
| Standard media sizes (duplex)  | A4; RA4; Oficio  |
| Standard media sizes (duplex, imperial)  | Letter; Legal; Folio   |
| Standard output capacity (envelopes)   | Up to 10 envelopes   |
| Standard output capacity (transparencies)  | Up to 75 sheets  |
|  |  |
| Storage  | 500 GB hard disk drive   |
| Storage Storage device and direct print support  | 500 GB hard disk drive  USB Printing; Front-facing USB/Flash drive   |
| Storage device and direct print  |  |
| Storage device and direct print support  | USB Printing; Front-facing USB/Flash drive   |
| Storage device and direct print support Storage temperature range  | USB Printing; Front-facing USB/Flash drive -4 to 104°F   |
| Storage device and direct print support Storage temperature range Storage temperature range  | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C   |
| Storage device and direct print support  Storage temperature range  Storage temperature range  SureSupply supported  | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C  Yes  |
| Storage device and direct print support  Storage temperature range  Storage temperature range  SureSupply supported  Target user and print volume  | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C  Yes  For teams up to 15 users; Prints up to 7,500 pages/month  |
| Storage device and direct print support  Storage temperature range  Storage temperature range  SureSupply supported  Target user and print volume  Tariff numbers  Telecom compliance (fax   | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C  Yes  For teams up to 15 users; Prints up to 7,500 pages/month  (AMS) 8443321010; (EMEA) 8443321010; (APJ) 84433231  Telecom wired: ES 203 021-1 v2.1.1 / ES 203 021-2 v2.1.2 / ES 203 021-3 v2.1.2; FCC Rules & Regulations 47 CFR Part 68; Industry Canada CS-03;   |
| Storage device and direct print support  Storage temperature range  Storage temperature range  SureSupply supported  Target user and print volume  Tariff numbers  Telecom compliance (fax capability)   | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C  Yes  For teams up to 15 users; Prints up to 7,500 pages/month  (AMS) 8443321010; (EMEA) 8443321010; (APJ) 84433231  Telecom wired: ES 203 021-1 v2.1.1 / ES 203 021-2 v2.1.2 / ES 203 021-3 v2.1.2; FCC Rules & Regulations 47 CFR Part 68; Industry Canada CS-03; Other Telecom approvals as required by individual countries.  |
| Storage device and direct print support  Storage temperature range  Storage temperature range  SureSupply supported  Target user and print volume  Tariff numbers  Telecom compliance (fax capability)  Telephone handset supported  | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C  Yes  For teams up to 15 users; Prints up to 7,500 pages/month  (AMS) 8443321010; (EMEA) 8443321010; (APJ) 84433231  Telecom wired: ES 203 021-1 v2.1.1 / ES 203 021-2 v2.1.2 / ES 203 021-3 v2.1.2; FCC Rules & Regulations 47 CFR Part 68; Industry Canada CS-03; Other Telecom approvals as required by individual countries.  No  Front-facing USB printing; Scan to email; Two-sided printing; Two-sided   |
| Storage device and direct print support  Storage temperature range  Storage temperature range  SureSupply supported  Target user and print volume  Tariff numbers  Telecom compliance (fax capability)  Telephone handset supported  Top key features  | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C  Yes  For teams up to 15 users; Prints up to 7,500 pages/month  (AMS) 8443321010; (EMEA) 8443321010; (APJ) 84433231  Telecom wired: ES 203 021-1 v2.1.1 / ES 203 021-2 v2.1.2 / ES 203 021-3 v2.1.2; FCC Rules & Regulations 47 CFR Part 68; Industry Canada CS-03; Other Telecom approvals as required by individual countries.  No  Front-facing USB printing; Scan to email; Two-sided printing; Two-sided scanning  |
| Storage device and direct print support  Storage temperature range  Storage temperature range  SureSupply supported  Target user and print volume  Tariff numbers  Telecom compliance (fax capability)  Telephone handset supported  Top key features  Top margin (A4)   | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C  Yes  For teams up to 15 users; Prints up to 7,500 pages/month  (AMS) 8443321010; (EMEA) 8443321010; (APJ) 84433231  Telecom wired: ES 203 021-1 v2.1.1 / ES 203 021-2 v2.1.2 / ES 203 021-3 v2.1.2; FCC Rules & Regulations 47 CFR Part 68; Industry Canada CS-03; Other Telecom approvals as required by individual countries.  No  Front-facing USB printing; Scan to email; Two-sided printing; Two-sided scanning  4.3 mm  |
| Storage device and direct print support  Storage temperature range  Storage temperature range  SureSupply supported  Target user and print volume  Tariff numbers  Telecom compliance (fax capability)  Telephone handset supported  Top key features  Top margin (A4)  Tray capacity  Typical electricity consumption | USB Printing; Front-facing USB/Flash drive  -4 to 104°F  -20 to 40°C  Yes  For teams up to 15 users; Prints up to 7,500 pages/month  (AMS) 8443321010; (EMEA) 8443321010; (APJ) 84433231  Telecom wired: ES 203 021-1 v2.1.1 / ES 203 021-2 v2.1.2 / ES 203 021-3 v2.1.2; FCC Rules & Regulations 47 CFR Part 68; Industry Canada CS-03; Other Telecom approvals as required by individual countries.  No  Front-facing USB printing; Scan to email; Two-sided printing; Two-sided scanning  4.3 mm  650   |

| UPC number                             | (201) 192545079846; (AAZ) 192545079853; (AB0) 192545079693; (AB2) 192545079709; (ABJ) 192545079716; (ABT) 192545079754; (ABY) 192545079761; (AC8) 192545079839; (ACJ) 192545079723; (ACQ) 192545079778; (AKV) 192545696197; (B13) 192545079792; (B19) 192545079808; (BAZ) 192545079815; (BBU) 192545079730; (BGJ) 192545079860; (BGM) 192545079747; (AC4) 193808309809                      |
|--|---|
| Warm-up time                           | 106 sec   |
| Web address for additional information | Solutions: http://www.hp.com/go/gsc; Fonts and IPDS Emulation: http://www.hp.com/go/laserjetfonts; HP Web Jetadmin: http://www.hp.com/go/wja; HP Universal Print Driver: http://www.hp.com/go/upd; HP Imaging & Printing Security Center: http://www.hp.com/go/ipsc; On Demand Cloud Solutions: http://www.hpjetadvantage.com/ondemand Product Support: http://www.hp.com/support/ljM527MFP |

[1] In box cartridge yields 7,500 black pages based on ISO/IWC 19752 and continuous printing. Actual pages may vary considerably based on images printed and other factors. For more information, visit: http://www.hp.com/go/learnaboutsupplies.

#### [2] With print cartridges

- [3] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115V device.
- [6] HP recommends that the number of pages per month of imaged output be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.
- [8] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.
- [9] Best TEC is not applicable to ES 2.0 TEC. This measurement was made with the printer configuration optimized for energy efficiency. Minimum sleep delay was used, Wi-Fi Direct was disabled and Active I/O Energy Efficient Ethernet was used.
- [11] EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
- [16] Configuration tested: base model, simplex printing, A4 paper at an average of 43 ppm.

### **Accessories**

## **Security and Protection**

### **Smart Cards and SmartCard Readers**

| HP SmartCard NIPRNet Solution for US Government | CC543B |
|---|--------|
| HP Legic Secure USB Reader                      | 4QL32A |
| HP HIP2 Keystroke Reader                        | Y7C05A |
| HP Universal USB Proximity Card Reader          | X3D03A |

## **Network Print Servers**

### **External Print Servers**

| HP Jetdirect 3100w BLE/NFC/Wireless Accessory | 3JN69A |
|---|--------|
| HP Jetdirect 2900nw Print Server              | J8031A |
| HP Jetdirect 3000w NFC/Wireless Accessory     | J8030A |

## **Maintenance and Cleaning Kits**

### **Maintenance Kits**

| HP 200 ADF Roller Replacement Kit | W5U23A |
|-----------------------------------|--------|

## **PC Drives and Storage**

### **EIO Hard Drives**

| HP TAA Version Secure Hard Disk Drive | 5EL03A |  |
|---------------------------------------|--------|--|
| HP High-Performance Secure Hard Disk  | B5L29A |  |

## **Paper Handling**

### **Fax Upgrades**

| HP MFP Analog Fax Accessory 700 | 2EH31A |  |
|---------------------------------|--------|--|
|---------------------------------|--------|--|

## **Input Trays**

| HP LaserJet 550-sheet Paper Tray | F2A72A |  |
|----------------------------------|--------|--|
|----------------------------------|--------|--|

## Cables/Cable Kits/Cable Adapters

### **Port Cables and Cable Adapters**

| Printer Cables                                  |        |
|---|--------|
| HP Internal USB Ports Qty 100 for M507 and M528 | 1PV95A |
| HP Internal USB Ports                           | B5L28A |

### Printer Cables

| HP Foreign Interface Harness | B5L31A |
|------------------------------|--------|
|                              |        |

### **Cabinets and Stands**

### **Printer Cabinets and Stands**

| HP LaserJet Printer Cabinet | F2A73A |
|-----------------------------|--------|
|-----------------------------|--------|

# **Accessory Bundles**

### **Printer Accessibility Accessories**

| <u> </u>                          |        |
|-----------------------------------|--------|
| HP Accessibility Kit              | 2TD64A |
| HP Accessibility Assistant        | 2MU47A |
| Data Security Accessories         |        |
| HP Removable Hard Drive Enclosure | 2NR12A |

# **Memory**

### **DDR3 Memory**

| HP 1 GB x32 144-pin (800 MHz)DDR3 SODIMM  | E5K48A |
|---|--------|
| HP 2 GB x32 144-pin (800 MHz) DDR3 SODIMM | E5K49A |
| HP 2GB 144-Pin DDR3 TAA Version DIMM      | 2NR09A |

### **Solutions**

# **JetAdvantage Printing Solutions**

### **JetAdvantage Print Management**

| HP Web Jetadmin           | HPWEBJETADMIN   |
|---------------------------|-----------------|
| HP JetAdvantage Insights  | HPJETADINSIGHTS |
| HP Universal Print Driver | HPUNIVPRNTDRV   |

### JetAdvantage Printer Workflow

HP JetAdvantage Apps HPJA\_AP

## JetAdvantage Mobile Printing

HP Roam for Business HPROAM

# Ink/Toner/Paper/Printer Supplies

# **HP Laser Toner Cartridges and Kits**

## **HP Black and White Laser Toner Printer Cartridges**

| HP 89Y Extra High Yield Black Original LaserJet Toner Cartridge | CF289Y |
|---|--------|
| HP 89X High Yield Black Original LaserJet Toner Cartridge       | CF289X |
| HP 89A Black Original LaserJet Toner Cartridge                  | CF289A |

# **HP Paper Designed for Laser Printers**

## **HP Laser Brochure Paper**

| HP Laser Glossy Brochure Paper 200 gsm-150 sht/Letter/8.5 x 11 in | 4WN10A |
|---|--------|
| HP Laser Glossy Brochure Paper 120 gsm-150 sht/Letter 8.5 x 11 in | 4WN08A |
| HP Laser Matte Brochure Paper 200 gsm-150 sht/Letter/8.5 x 11 in  | 4WN05A |

## **HP Care Pack Services**

## **Imaging and Printing Commercial Care Pack Services**

| HP 2 year Post Warranty Parts Exchange Service for LaserJet M528 (Managed Component Only) | UB7D1PE |
|---|---------|
| HP 5 year Parts Exchange Service for LaserJet M528 (Managed Component Only)               | UB7C3E  |
| HP 4 year Parts Exchange Service for LaserJet M528 (Managed Component Only)               | UB7C2E  |
| HP 1 year Post Warranty Parts Exchange Service for LaserJet M528 (Managed Component Only) | UB7D0PE |
| HP 3 year Parts Exchange Service for LaserJet M528 (Managed Component Only)               | UB7C1E  |
| HP 1y Renewal Subscription Supply Svc for LaserJet (up to 1000 pages per month)           | U9PW2PE |
| HP 1y Subscription Supplies Svc for LaserJet (up to 5000 pages per month)                 | U9PV9E  |
| HP 1y Subscription Supplies Svc for LaserJet (up to 2000 pages per month)                 | U9PV6E  |
| HP 1y Renewal Subscription Supply Svc for LaserJet (up to 2000 pages per month)           | U9PW5PE |
| HP Inst SVC w/nw Workgroup Printer  | U9JT2E  |
| HP 1y Subscription Supplies Svc for LaserJet (up to 1000 pages per month)                 | U9PV3E  |
| HP 1y Renewal Subscription Supply Svc for LaserJet (up to 5000 pages per month)           | U9PW8PE |

# Imaging and Printing Hardware Support Onsite Svc

| HP 3 year Next Business Day w/DMR Service for LaserJet M528                                  | UB7B2E  |
|--|---------|
| HP 2 year Post Warranty Next Business Day w/DMR Service for LaserJet M528                    | UB7C5PE |
| HP 4 year Next Business Day w/DMR Service for LaserJet M528                                  | UB7B3E  |
| HP 4 year 4 hour 9x5 w/DMR Service for LaserJet M528   | UB7B6E  |
| HP 5 year 4 hour 9x5 w/DMR Service for LaserJet M528   | UB7B7E  |
| HP 1 year Print At Your Service Next Business Day with DMR Service for LaserJet M528         | UB8N7E  |
| HP 2 year Post Warranty 4 hour 9x5 w/DMR Service for LaserJet M528                           | UB7C7PE |
| HP 3 year 4 hour 9x5 w/DMR Service for LaserJet M528   | UB7B5E  |
| HP 1 year Post Warranty 4 hour 9x5 w/DMR Service for LaserJet M528                           | UB7C6PE |
| HP 1 year Post Warranty Next Business Day w/DMR Service for LaserJet M528                    | UB7C4PE |
| HP 1 year Print At Your Service Next Business Day with DMR Renewal Service for LaserJet M528 | UB8N8PE |

| HP 5 year Next Business Day w/DMR Service for LaserJet M528 | UB7B4E |
|---|--------|
| HP 3 year Next Business Day w/DMR Service for LaserJet M528 | UB7B2E |
| HP 3 year 4 hour 9x5 w/DMR Service for LaserJet M528        | UB7B5E |

Generated by Dynamic Collateral Tool – (us-en) – Jul 18, 2019 6:18 PM UTC+0000