

IN3144

Professional 3D Network Projector

Part #: IN3144

InFocus

The high-brightness, high-connectivity IN3144 projector brings superior performance to your meeting room or classroom at a price that fits your budget. Easily manage the IN3144 over your network and easily install it with AMX and Crestron room control systems.

Key Features

- ◆ XGA (1024 x 768) native resolution
- ◆ 5000 lumens
- ◆ 3D support for Blu-ray and more
- ◆ 10W speaker
- ◆ Two 1.4 HDMI, VGA and more
- ◆ Network Monitoring



High Connectivity

The IN3144 is loaded with connectivity options, including two HDMI ports and multiple audio ports. Project from PCs, Macs, video sources, tablets and smartphones.



Impressive Image Quality

With 5000 lumens, high contrast, six-segment color wheel, and BrilliantColor™ DLP imaging, the IN3144 projects big, bright,

colorful images with the lights on and the blinds open. The 1.5:1 zoom ratio and extensive throw ratio mean these projectors work in a wide variety of rooms.

Immersive 3D

The IN3144 incorporates 3D Triple Flash technology and supports multiple forms of 3D, including HDMI, Blu-Ray, 3D broadcasting, video games and NVIDIA 3DTV PC connectivity. Display 3D in 1080p full HD over HDMI. Compatible with [144Hz DLP Link™ 3D glasses](#).

Network Support and Digital Control

Remotely manage and support your projector from a single computer via your existing network with [free ProjectorNet 4.1 software](#) from InFocus. Crestron Roomview enables instant, intuitive operation without a control processor or custom programming. AMX Device Discovery lets an AMX controller detect the projector dynamically and configure it for the remote control.

Specifications*

| Projector | | IN3144 |
|-----------------------------------|---|--------|
| Resolution – Native | XGA (1024 x 768) | |
| Display Technology | DLP | |
| Video Standard Compatibility | NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p | |
| Speakers | Mono 10W x 1 | |
| Lamp Brightness | 5,000 lumens | |
| Lamp Brightness – Eco Mode | 4,000 lumens | |
| Lamp Life | 3,500 hours | |
| Lamp Life – Low Power | 4,500 hours | |
| Lamp Life – Dynamic Mode | 6,000 hours | |
| Lamp Power | 310W | |
| Lamp Power – Low Power | 245W | |
| Lamp Power – Dynamic Mode | 93W | |
| Replacement Lamp | SP-LAMP-098 | |
| Contrast Ratio | 16,000:1 | |
| Color Wheel | 6 segments | |
| Number of Colors | 16.7 million | |
| Synch Scan Frequency – Horizontal | 15 - 91,4 KHz | |
| Synch Scan Frequency – Vertical | 24 - 30 KHz | |
| Aspect Ratio | 4:3 | |
| Aspect Ratio Compatibility | 16:9, 16:10, 2.35:1 | |
| Projection Distance – Minimum | 1 m | |
| Projection Distance – Maximum | 10 m | |
| Projection Lens F-Stop – Minimum | 2.42 | |
| Projection Lens F-Stop – Maximum | 2.97 | |
| Lens Type | Manual zoom and focus | |
| Image Size – Minimum | 22 in | |
| Image Size – Maximum | 270 in | |
| Projection Offset | 14 % | |
| Keystone Correction | +/-40 ° | |
| Connectors – Inputs | 3.5mm microphone line in, 3.5mm audio, HDMI x2, Composite video, S-video, VGA x2, RCA L/R audio, USB mini (for service) | |
| Connectors – Outputs | 3.5mm audio output, VGA, USB-A 5V1.5A, 12V Screen trigger | |
| Control | RS232, RJ-45 | |
| Audible Noise | < 32 dBA at 0°F / -17.8°C | |
| Audible Noise – Eco Mode | < 30 dBA at 0°F / -17.8°C | |
| Included Accessories | Power cord, Remote, VGA cable, Documentation, Quick Start Guide, User Manual (CD) | |
| Product Warranty | 2 years | |
| Lamp Warranty | 6 months | |
| Accessories Warranty | 90 days | |
| Power Consumption | 410.0W max | |
| Power Consumption – Eco Mode | 320.0W max | |
| Power Consumption – Dynamic Mode | 93.0W max | |
| Power Standard | AC 100 to 240V, 50/60 | |
| Operating Conditions | 41 to 104°F at 2500 to 10000 ft / 5 to 40°C at 762 to 3048 m | |
| Menu Languages | English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Hungarian | |
| Throw and Zoom | | |
| Throw Ratio – Minimum | 1.83:1 | |
| Throw Ratio – Maximum | 2.75:1 | |
| Zoom Ratio | 1.5:1 | |
| Shipping | | |
| Product Dimensions | 5 x 12.4 x 8.5 in / 127 x 315 x 215.9 mm | |

| | |
|---------------------|--|
| Projector | IN3144 |
| Product Weight | 6.9 lbs / 3.1 kg |
| Shipping Dimensions | 8.2 x 15.4 x 14.5 in / 208.3 x 391.2 x 368.3 mm |
| Shipping Weight | 10.3 lbs / 4.7 kg |

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

- 1 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM1)
- Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
- Projector Lamp for IN3144, IN3146, IN3148HD (SP-LAMP-098)
- LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
- Motorized Electric Projector Screen: 100 in., 4:3 (SC-MOT-100)
- Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4)
- Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4)
- Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB)
- Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW)
- Motorized Electric Projector Screen: 84 in., 4:3 (SC-MOT-84)
- Motorized Electric Projector Screen: 120 in., 4:3 (SC-MOT-120)
- Manual Pull Down Projector Screen: 84 in., 4:3 (SC-MAN-84)
- Manual Pull Down Projector Screen: 100 in., 4:3 (SC-MAN-100)
- Manual Pull Down Projector Screen: 120 in., 4:3 (SC-MAN-120)
- Manual Pull Up Projector Screen: 80 in., 4:3 (SC-PU-80)
- Manual Pull Up Projector Screen: 100 in., 4:3 (SC-PU-100)
- Fixed Frame Projector Screen: 84 in., 4:3 (SC-FF-84)
- Fixed Frame Projector Screen: 100 in., 4:3 (SC-FF-100)
- Fixed Frame Projector Screen: 120 in., 4:3 (SC-FF-120)
- DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
- 2 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM2)