

## Key Features

SuperClear® IPS Panel Technology | Wide Quad HD Resolution |  
Seamless Viewing Experience | Loaded with Connectivity | Integrated  
Client Endpoint Mount



## Product Description

The ViewSonic® VG2765 is a 27" WQHD monitor that delivers stunning definition, robust ergonomics, and future-proof connectivity for the ultimate work environment. Featuring a premium panel with 2560 x 1440 quad HD resolution, this monitor delivers wide-angle viewing and incredibly vivid colors with 77% more pixels than standard Full HD monitors. A 3-sided thin-bezel design provides a nearly seamless viewing experience in multi-monitor setups. Future-proof connectivity options include DisplayPort, Mini DisplayPort, HDMI, and dual-USB hub for utmost compatibility with laptops, tablets and other computing devices. For maximum comfort and a customized fit, a robust fully ergonomic stand provides tilt, pivot, swivel, and height-adjustable options. In addition, VDI client endpoints can be easily attached to the integrated client mount, saving desktop space and minimizing cable clutter without interfering with ergonomic functionality. With amazing visuals, incredible versatility, and customized comfort, this monitor delivers a complete enterprise solution on the desktop.



27"  
**DISPLAY**



IPS  
**PANEL**



2560 x 1440  
**RESOLUTION**

**Contact Sales**

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

**Display:**

|                              |                                |
|------------------------------|--------------------------------|
| Display Size (in.):          | 27                             |
| Viewable Area (in.):         | 27                             |
| Panel Type:                  | IPS                            |
| Resolution:                  | 2560 x 1440                    |
| Resolution Type:             | WQHD (2560x1440)               |
| Static Contrast Ratio:       | 1,000:1                        |
| Dynamic Contrast Ratio:      | 80,000,000:1                   |
| Light Source:                | LED                            |
| Brightness:                  | 350 cd/m2                      |
| Colors:                      | 1.07B                          |
| Color Space Support:         | 10 bits                        |
| Aspect Ratio:                | 16:9                           |
| Response Time (Typical GTG): | 12ms                           |
| Response Time (GTG w/OD):    | 5ms                            |
| Viewing Angles:              | 178° horizontal, 178° vertical |
| Backlight Life (Hours):      | 30,000                         |
| Panel Surface:               | Anti-glare, Hard coating (3H)  |

**Compatibility:**

|                      |             |
|----------------------|-------------|
| PC Resolution (max): | 2560 x 1440 |
|----------------------|-------------|

**Connector:**

USB 3.0 Type A(2), USB 3.0 Type B(1), 3.5mm Audio Out(1), HDMI 1.4(1), Display Port(1), Mini Display Port(1)

**Audio:**

|                    |         |
|--------------------|---------|
| Internal Speakers: | 2W (x2) |
|--------------------|---------|

**Power:**

|                        |                                  |
|------------------------|----------------------------------|
| Eco Mode (Conserve):   | 23W                              |
| Eco Mode (optimized):  | 28W                              |
| Consumption (typical): | 30W                              |
| Consumption (max):     | 36W                              |
| Voltage:               | AC 100-240V (universal), 50-60Hz |
| Stand-by:              | 0.5                              |

**Additional Hardware:**

|                       |   |
|-----------------------|---|
| Kensington Lock Slot: | 1 |
|-----------------------|---|

**Controls:**

|                    |  |
|--------------------|--|
| Physical Controls: | 1, 2, Up, Down, Power  |
| On Screen Display: | Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) |

**Operating Conditions:**

|                            |                       |
|----------------------------|-----------------------|
| Temperature:               | 32-104° F (0 - 40° C) |
| Humidity (non-condensing): | 20-90%                |

**Mount:**

|                  |              |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

**Video Signal:**

|                       |            |
|-----------------------|------------|
| Frequency Horizontal: | 15 ~ 82KHz |
| Frequency Vertical:   | 50 ~ 75Hz  |

**Video Input:**

|               |             |
|---------------|-------------|
| Digital Sync: | TMD5, PCI-E |
|---------------|-------------|

**Ergonomics:**

|                      |                 |
|----------------------|-----------------|
| Height Adjust:       | 130 mm / 5.1 in |
| Swivel:              | 356°            |
| Pivot (Right/Left):  | 90° / 0°        |
| Tilt (Forward/Back): | 20° / ~ 5°      |

**Weight (imperial):**

|                          |      |
|--------------------------|------|
| Net (lbs):               | 15.9 |
| Net Without Stand (lbs): | 10.9 |
| Gross (lbs):             | 19.6 |

**Weight (metric):**

|                         |     |
|-------------------------|-----|
| Net (kg):               | 7.2 |
| Net Without Stand (kg): | 5.0 |
| Gross (kg):             | 8.9 |

**Dimensions (imperial) (WxHxD):**

|                               |                   |
|-------------------------------|-------------------|
| Packaging (in.):              | 28.9 x 17.9 x 8.0 |
| Physical (in.):               | 24.1 x 21.3 x 9.2 |
| Physical Without Stand (in.): | 24.1 x 14.6 x 2.1 |

**Dimensions (metric) (WxHxD):**

|                              |                       |
|------------------------------|-----------------------|
| Packaging (mm):              | 734 x 454 x 203       |
| Physical (mm):               | 611.2 x 540.0 x 233.3 |
| Physical Without Stand (mm): | 611.2 x 371.5 x 53.7  |

**General:**

Regulations: cULus, FCC-B, ICES003, Energy Star 7.0, EPEAT, UL-MX-CoC, Mexico Energy, CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, REACH, SVHC List & DoC, WEEE, GS

PACKAGE CONTENTS: LCD Display, Power Cable , Mini DP to DP Cable , USB3.0 Upstream Cable , Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907891713

**Accessories:**

CB-00008948, CB-00009950, CB-00010555, CB-00010684, LCD-CMK-001, LCD-EE-27-03, LCD-EEEW-27-01, LCD-EEEW-27-02, LCD-EW-27-01, LCD-EW-27-02, LCD-EW-27-03, LCD-WMK-001