

# Cisco Secure Network Server

## Product Overview

Granting and denying network access has evolved beyond simple user name and password verifications. Today, additional attributes related to users and their devices are used as decision criteria in determining authorized network access. Additionally, network service provisioning can be based on data such as the type of device accessing the network, including whether it is a corporate or personal device.

The Cisco® Secure Network Server is a scalable solution that helps network administrators meet complex network access control demands by managing the many different operations that can place heavy loads on applications and servers, including:

- Authorization and authentication requests
- Queries to identity stores such as Active Directory and LDAP databases
- Device profiling and posture checking
- Enforcement actions to remove devices from the network
- Reporting

The Cisco® Secure Network Server is based on the Cisco UCS® C220 Rack Server and is configured specifically to support the Cisco Identity Services Engine (ISE) and Access Control System (ACS) security applications. The Secure Network Server supports these applications in four versions. The Cisco Secure Network Server 3415 and 3515 are designed for small and medium-sized deployments. The Secure Network Server 3495 and 3595 have several redundant components such as hard disks and power supplies, making it suitable for large deployments that require highly reliable system configurations. The Secure Network Server 3515 and 3595 are recommended for new installations whereas the Secure Network Server 3415 and 3495 are recommended for existing installations.

When ordering a Secure Network Server, the customer has the flexibility to install the Cisco Identity Services Engine (ISE) or Access Control System (ACS) security applications.

Figure 1 shows the Cisco Secure Network Server.

**Figure 1.** Cisco Secure Network Server



SNS-3415 / SNS-3495



SNS-3515 / 3595

## Product Specifications

Table 1 lists specifications of the Cisco Secure Network Server.

**Table 1.** Product Specifications

Product Name	Secure Network Server 3415	Secure Network Server 3495	Secure Network Server 3515	Secure Network Server 3595
<b>Supported Applications</b>	Identity Services Engine Access Control System	Identity Services Engine Access Control System	Identity Services Engine Access Control System	Identity Services Engine Access Control System
<b>Processor</b>	1 - Intel Xenon 2.4-GHz E5-2609	2 - Intel Xenon 2.4-GHz E5-2609	1 – Intel Xenon 2.40 GHz E5-2620	1 – Intel Xenon 2.60 GHz E5-2640
<b>Cores per processor</b>	4	4	6	8
<b>Memory</b>	16 GB (4 x 4 GB)	32 GB (8 x 4 GB)	16 GB (2 x 8 GB)	64 GB (4 x 16 GB)
<b>Hard Disk</b>	1 - 2.5-in. 600-GB 6Gb SAS 10K RPM	2 - 2.5-in. 600-GB 6Gb SAS 10K RPM	1 - 2.5-in. 600-GB 6Gb SAS 10K RPM	4 - 2.5-in. 600-GB 6Gb SAS 10K RPM
<b>Hardware RAID</b>	No	Level 0 & 1 LSI 2008 SAS RAID Mezzanine Card	No	Level 10 Cisco 12G SAS Modular RAID Controller
<b>Network Interfaces</b>	4 x 1 GB	4 x 1 GB	6 x 1 GB	6 x 1 GB
<b>Power Supplies</b>	1 x 650W	2 x 650W	1 x 770W	2 x 770W

## Security Applications

The Cisco Secure Network Server supports Cisco's powerful network access and control security applications:

### Cisco Identity Services Engine

An integral component to Cisco's cybersecurity initiative, the Cisco Identity Services Engine (ISE) is a revolutionary product that extends the network access and admission control capabilities first offered in Cisco NAC and Cisco Secure ACS. Looking beyond user name and password, the Identity Services Engine delivers unprecedented abilities to acquire user and device identity and context information to forge flexible and powerful policies that govern authorized network access. ISE is an all-in-one enterprise policy control platform that can reliably provide secure access for wired, wireless and VPN networks. ISE can also help IT with secure BYOD on-boarding and allow IT to provide differentiated Guest Access. The Identity Services Engine provides enforcement actions that allow administrators to restrict devices from the network that are violating access and policies.

Table 2 lists ISE endpoint scalability metrics for the Secure Network Servers.

**Table 2.** Identity Services Engine Deployment Scalability

	Secure Network Server 3415	Secure Network Server 3495	Secure Network Server 3515	Secure Network Server 3595
<b>Endpoints supported in an ISE deployment per server</b>	5,000	20,000	5,000	20,000

## Cisco Secure Access Control System

Cisco Secure ACS is the world's most trusted enterprise network access policy and identity system, used by more than 40,000 enterprises worldwide. With powerful performance and a design-for-versatility approach, Cisco Secure ACS provides a critical building block for almost any network identity and access policy strategy.

Cisco Secure ACS interacts with external identity databases and RADIUS servers, becoming a control point for managing network access policy.

Cisco Secure ACS provides better control, monitoring, and enforcement of access to corporate resources to meet ever-changing business and regulatory needs.

## Ordering Information

Table 3 lists ordering information for the Cisco Secure Network Servers.

**Table 3.** Product Ordering Information

Server Part Numbers	Server Description	Comments
<b>SNS-3415-K9</b>	Secure Network Server for ISE and ACS applications (small)	Customer must choose either ACS or ISE
<b>SNS-3495-K9</b>	Secure Network Server for ISE and ACS applications (large)	Customer must choose either ACS or ISE
<b>SNS-3515-K9</b>	Secure Network Server for ISE and ACS applications (small)	Customer must choose either ACS or ISE
<b>SNS-3595-K9</b>	Secure Network Server for ISE and ACS applications (large)	Customer must choose either ACS or ISE

Table 4 lists the Secure Network Server component spares that can be used as Field Replaceable Units (FRUs).

**Table 4.** Spare Components for the Cisco Secure Network Server

Secure Network Server	Component Part Number	Component Description
<b>3415 / 3495 / 3515 / 3595</b>	A03-D600GA2=	600-GB 6-Gb SAS 10K RPM SFF hard disk; hot pluggable; drive sled mounted
<b>3415 / 3495</b>	UCSC-PSU-650W=	650W power supply
<b>3515 / 3595</b>	UCSC-PSU1-770W=	770W power supply
<b>3415 / 3495 / 3515 / 3595</b>	N20-BKVM=	KVM cable
<b>3415 / 3495</b>	UCSC-RAIL1=	Rail kit
<b>3515 / 3595</b>	UCSC-RAILB-M4=	Rail kit

## Cisco UCS C220 Server

The Cisco UCS C220 Rack Server is designed for performance and density over a wide range of business workloads, from web serving to distributed databases.

The Cisco UCS C220 Rack Server is a high-density general-purpose server optimized to deliver high performance for a large range of workloads. Cisco UCS C-Series servers extend unified computing innovations to an industry-standard form factor to help reduce total cost of ownership (TCO) and increase business agility. Designed to operate both in standalone environments and as part of Cisco UCS, the Cisco UCS C-Series Rack Servers employ Cisco technology to help customers handle the most challenging workloads.

## Connectors and LEDs

Table 5 lists Connectors and LEDs on the Cisco Secure Network Servers.

**Table 5.** Connectors and LEDs

Connector/LEDs	Description
<b>Front-panel connector</b>	One KVM console connector (supplies 2 USB, 1 VGA, and 1 serial connector)
<b>Front-panel locator LED</b>	Indicator to help direct administrators to specific servers in large data center environments
<b>Additional rear connectors</b>	Additional interfaces, including a VGA video port, 2 USB ports, an RJ-45 serial port, 1 Gigabit Ethernet management port, and dual 1 Gigabit Ethernet ports

## Form Factor

**3415 / 3495 Physical dimensions (H x W x D)** 1RU: 1.7 x 16.9 x 28.5 in. (4.32 x 43 x 72.4 cm)

**3415 / 3495 Physical dimensions (H x W x D)** 1RU: 1.7 x 16.9 x 29.8 in. (4.32 x 43 x 75.6 cm)

## Environmental

Table 6 lists environmental information for the Cisco Secure Network Servers.

**Table 6.** Regulatory Standards Compliance: Safety and EMC

Item	Specification
<b>Temperature: Operating</b>	41 to 95°F (5 to 35°C) (operating, sea level, no fan fail, no CPU throttling, turbo mode)
<b>Temperature: Nonoperating</b>	-40 to 149°F (-40 to 65°C)
<b>Humidity: Operating</b>	10 to 90% noncondensing
<b>Humidity: Nonoperating</b>	5 to 93% noncondensing
<b>Altitude: Operating</b>	0 to 10,000 ft (0 to 3000m); maximum ambient temperature decreases by 1°C per 1000 ft
<b>Altitude: Nonoperating</b>	0 to 40,000 ft (12,000m)
<b>Heat Dissipation</b>	Approximately 2500 BTU/h

## Regulatory Standards

Table 7 lists regulatory standards compliance information for the Cisco Secure Network Servers.

**Table 7.** Regulatory Standards Compliance: Safety and EMC

Specification	Description
<b>Safety</b>	<ul style="list-style-type: none"><li>• UL 60950-1 No. 21CFR1040 Second Edition</li><li>• CAN/CSA-C22.2 No. 60950-1 Second Edition</li><li>• IEC 60950-1 Second Edition</li><li>• EN 60950-1 Second Edition</li><li>• IEC 60950-1 Second Edition</li><li>• AS/NZS 60950-1</li><li>• GB4943 2001</li></ul>

Specification	Description
<b>EMC: Emissions</b>	<ul style="list-style-type: none"> <li>• 47CFR Part 15 (CFR 47) Class A</li> <li>• AS/NZS CISPR22 Class A</li> <li>• CISPR2 2 Class A</li> <li>• EN55022 Class A</li> <li>• ICES003 Class A</li> <li>• VCCI Class A</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> <li>• KN22 Class A</li> <li>• CNS13438 Class A</li> </ul>
<b>EMC: Immunity</b>	<ul style="list-style-type: none"> <li>• EN55024</li> <li>• CISPR24</li> <li>• EN300386</li> <li>• KN24</li> </ul>

## Cisco Capital

### Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more.](#)

### For More Information

For more information, please visit the following resources:

- Cisco Identity Services Engine: <http://www.cisco.com/go/ISE>
- Cisco Access Control System: <http://www.cisco.com/go/ACS>
- Cisco UCS Servers: <http://www.cisco.com/go/unifiedcomputing>



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)