

# 2500 LUMENS ● WXGA ● ULTRA SHORT THROW PROJECTOR

## PDG-DWL2500

### WXGA ULTRA SHORT THROW PROJECTOR



DLP



Built-in Network



Ultra Short-Throw



Closed Caption



3D Ready

#### THE WORLD'S SHORTEST PROJECTION DISTANCE

Project a large 80" diagonal image from the world's shortest projection distance of about 13 inches is achieved by a newly developed ultra short-focus mirror optical system. This projector is perfect for giving effective lectures or presentations in educational settings. A maximum projected image size of 110" diagonal. This projector can be placed in a variety of locations including table tops, walls, ceiling, or floors.

#### LARGE-SCREEN 3D PROJECTION CAPABILITY

The "Frame Sequential Display Format" a technology that rapidly alternates between left-eye and right-eye images for 3D technology enables the viewing of 3D images when wearing 3D glasses.\*<sup>2</sup>

<sup>2</sup> 3D glasses (sold separately) are required in order to view projected images in 3D. (DLP Link and IR formats compatible.)

#### NETWORKING CAPABILITY

The PDG-DWL2500 is equipped with SANYO's exclusive PJ Network Interface for wired networking. A common feature among SANYO's extensive line of commercial projectors. Networking allows the monitoring of projector functions and operation remotely via a web browser. Emails can be sent automatically to report operating status.

#### NEARLY MAINTENANCE FREE

This projector offers long periods of maintenance-free use, without the need for lamp replacement, and filter replacement. The PDG-DWL2500 is equipped with SANYO's proprietary hybrid filter, composed of multiple filter layers, and the lamp life has been improved compared to conventional models. The longer lamp lifespan and long life filter saves time and money.

#### COMPACT DESIGN FOR SAVING SPACE IN INSTALLATION

A newly developed single chip DLP format optical engine makes the projector more compact.

#### CLOSED CAPTION

The PDG-DWL2500 is Closed Caption compatible.

Resolution	WXGA (1280 x 800)	
Brightness (typical)	2500 Lm	
Contrast Ratio (Full on / off)	2000:1	
Image Size	60"-110"	
Aspect Ratio	16:10	
Projection Lamp	275W	
Scanning Frequency	H:15-93kHz, V:50-120Hz	
Fan Noise	28.0 dBA (Eco)	
Voltage	100-240V AC ; 50/60 Hz	
Power Consumption	400W(Normal), 320W(Eco)	
Input signal compatibility	WUXGA, WXGA, UXGA, SXGA+, XGA, SVGA, VGA, Mac Analog: 480i/p, 575i/p, 720p(50/60), 1080i(50/60) HDMI : 480p, 575p, 720p(50/60), 1080i/p(50/60)	
Color System	NTSC, PAL, SECAM, NTSC4.43, PAL-M/PAL-N	
Projection Lens (inch)	F 2.50 f=0.19"	
Throw Ratio	N/A	
Throw Distance (feet)	N/A	
Zoom / Focus	Fixed/Manual	
Up / Down Ratio	N/A	
Digital Keystone Correction	V +/- 5°	
Digital Zoom	4x - 1/4x	
Speaker Output	10W	
Weight (lbs)	13.7 lbs	
Dimensions (inch) W,H,D	12.6"x7.0"x15.2"	
Replacement Lamp	# 610 351 3744	
Replacement Remote	# 645 103 3048	
Filter hour* (hour)	4000h (Eco)	
Lamp Life* (hour)	3000h (Eco)	
Input	PC/Video	D-sub 15 x 1 (RGB, Component) D-sub 15 x 1 (RGB, Monitor out) Mini DIN 4pin x 1 (S-Video) RCA x 1 (Composite) HDMI x 1 (Ver.1.3)
	Audio	Stereo mini jack x 1 RCA x 2(R/L, mono)
Output	PC/Video	D-sub 15 x 1 (in common)
	Audio	Stereo mini jack x 1
Other Feature	D-sub 9pin x 1 (control port) RJ-45 x 1 (Wired LAN) Mini-DIN 3-pin x 1 (3D SYNC OUT)	
Included Accessories	Power cord VGA cable Lens cap	Quick reference guide Owner's manual (CD-ROM) Remote control
Optional Accessories	POA-COMPVGA POA-CA-SCART	(Component - VGA cable) (Scart - VGA cable)
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty	

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

\* Lamp/Filter hour may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.



#### PRESENTATION TECHNOLOGIES

21605 Plummer Street  
Chatsworth, CA 91311  
Ph: 888-337-1215 (toll-free)  
Fax: 818-717-2719  
www.sanyoprojectors.com



Back Panel