

Only

FONTAINE®

Gives You the TechLock® System Advantage

Parts List



Contents

Item	Page #
Parts List Section:	
Air Slides – 6ATB, 7ATB, HATB	3-5
Air Slides – 6AWB, 7AWB, HAWB, HAWS	6-8
Air Slides – 6LWS, 7LWS	9
Air Slides – XAWXS	10
Manual Slides – 6MTB, 7MTB, HMTB	11-13
Manual Slides – 6MWS, 7MWS, HMWS	14-16
Adjustable Flat Plate Mounts – 6PMA, 7PMA, HPMA	17-18
Stationary Long Plate Mounts – 6PLA, 7PLA, HPLA, XPLA	18-20
Stationary Short Plate Mounts – 6PSA, 7PSA, HPSA, XPSA	20-22
Stationary Frame Mounts – 6BSM, 7BSM, HBSM, 6FMA, 7FMA, HFMA	22-25
Stationary Angle Mounts – 6A36, 7A36, HA36	25-26
Blocked Slides & Blocked Stationary Mounts – BLHAWB, BLHMWS, BLHPLA, BLHPSA	27-28
Fifth Wheel Top Plates	28
Slide Bracket & Rails Sub-Assembly – ATB, AWB, LWS, MTB, MWS, AWX	29-33
Bracket Assembly – PMA	33
Air & Manual Slide Brackets – ATB, AWB, AWS, LWS, AWX, MTB, MWS	34-35
Mounting Brackets – FMA, PLA, PSA, A36, BSM	35
Slide Rails – ATB, MTB, AWB, AWS, MWS, LWS, XAWX	36
Mounting Angles – AWB, AWS, ATB, MTB, ASB, APB, LWS, MWS, PMA, XAWX	37
Mounting Plates	37
Service Parts / Kits Section	
Service Parts – Available In Case Quantities	38
Service Parts	39
Service Parts – Available Only In A Kit	40
Service Parts – Kits	41-43
Custom Duty Fifth Wheel Parts	44
3000 Series Fifth Wheel Parts	45-47

Air Slide – Model 6ATB

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 6000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL6ATB675012	6-3/4	171	12	305	436	198	BKTATB6PT	SLRTB12
SL6ATB675016			16	406	450	204		SLRTB16
SL6ATB675024			24	610	461	209		SLRTB24
SL6ATB675036			36	914	484	220		SLRTB36
SL6ATB675048			48	1219	510	231		SLRTB48
SL6ATB775012	7-3/4	197	12	305	441	200	BKTATB7PT	SLRTB12
SL6ATB775016			16	406	455	206		SLRTB16
SL6ATB775024			24	610	466	211		SLRTB24
SL6ATB775036			36	914	489	222		SLRTB36
SL6ATB775048			48	1219	515	234		SLRTB48
SL6ATB875012	8-3/4	222	12	305	446	202	BKTATB8PT	SLRTB12
SL6ATB875016			16	406	460	209		SLRTB16
SL6ATB875024			24	610	471	214		SLRTB24
SL6ATB875036			36	914	494	224		SLRTB36
SL6ATB875048			48	1219	520	236		SLRTB48
SL6ATB975012	9-3/4	248	12	305	451	205	BKTATB9PT	SLRTB12
SL6ATB975016			16	406	465	211		SLRTB16
SL6ATB975024			24	610	476	216		SLRTB24
SL6ATB975036			36	914	499	226		SLRTB36
SL6ATB975048			48	1219	525	238		SLRTB48
SL6ATB1075012	10-3/4	273	12	305	474	215	BKTATB10PT	SLRTB12
SL6ATB1075016			16	406	488	221		SLRTB16
SL6ATB1075024			24	610	499	226		SLRTB24
SL6ATB1075036			36	914	522	237		SLRTB36
SL6ATB1075048			48	1219	548	249		SLRTB48

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AA6ATB1075048**). Order KIT-AIR-DASH Installation Kit separately.
2. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
3. All the assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR".
4. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Air Slide – Model 7ATB

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 7000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL7ATB675012	6-3/4	171	12	305	446	202	BKTATB6PT	SLRTB12
SL7ATB675016			16	406	460	209		SLRTB16
SL7ATB675024			24	610	471	214		SLRTB24
SL7ATB675036			36	914	494	224		SLRTB36
SL7ATB675048			48	1219	520	236		SLRTB48
SL7ATB775012	7-3/4	197	12	305	451	205	BKTATB7PT	SLRTB12
SL7ATB775016			16	406	465	211		SLRTB16
SL7ATB775024			24	610	476	216		SLRTB24
SL7ATB775036			36	914	499	226		SLRTB36
SL7ATB775048			48	1219	525	238		SLRTB48
SL7ATB875012	8-3/4	222	12	305	456	207	BKTATB8PT	SLRTB12
SL7ATB875016			16	406	470	213		SLRTB16
SL7ATB875024			24	610	481	218		SLRTB24
SL7ATB875036			36	914	504	229		SLRTB36
SL7ATB875048			48	1219	530	240		SLRTB48
SL7ATB975012	9-3/4	248	12	305	461	209	BKTATB9PT	SLRTB12
SL7ATB975016			16	406	475	215		SLRTB16
SL7ATB975024			24	610	486	220		SLRTB24
SL7ATB975036			36	914	509	231		SLRTB36
SL7ATB975048			48	1219	535	243		SLRTB48
SL7ATB1075012	10-3/4	273	12	305	484	220	BKTATB10PT	SLRTB12
SL7ATB1075016			16	406	498	226		SLRTB16
SL7ATB1075024			24	610	509	231		SLRTB24
SL7ATB1075036			36	914	532	241		SLRTB36
SL7ATB1075048			48	1219	558	253		SLRTB48

NOTES:

- New!** To order a C7000 Clean-Connect™ Top Plate: 1) Add 3 lbs to the weight and 2) Replace the “SL7” prefix in the Part Number with “SLC” (Example: SLCATB1075048).
- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the “SL7” prefix in the Part Number with “AA” (Example: AA7ATB1075048). Order KIT-AIR-DASH Installation Kit separately.
- Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
- All the assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the “SL” prefix in the Part Number with “SR”.
- Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Air Slide – Model HATB

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Slide Travel		Weight		Includes H5092 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SLHATB875012	8-3/4	222	12	305	488	221	BKTATB8PT	SLRTB12
SLHATB875016			16	406	502	228		SLRTB16
SLHATB875024			24	610	513	233		SLRTB24
SLHATB875036			36	914	536	243		SLRTB36
SLHATB875048			48	1219	562	255		SLRTB48
SLHATB975012	9-3/4	248	12	305	493	224	BKTATB9PT	SLRTB12
SLHATB975016			16	406	507	230		SLRTB16
SLHATB975024			24	610	518	235		SLRTB24
SLHATB975036			36	914	541	245		SLRTB36
SLHATB975048			48	1219	567	257		SLRTB48
SLHATB1075012	10-3/4	273	12	305	516	234	BKTATB10PT	SLRTB12
SLHATB1075016			16	406	530	240		SLRTB16
SLHATB1075024			24	610	541	245		SLRTB24
SLHATB1075036			36	914	564	256		SLRTB36
SLHATB1075048			48	1219	590	268		SLRTB48

NOTES:

- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AAHATB1075048**). Order KIT-AIR-DASH Installation Kit separately.
- Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR".
- Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Air Slide – Model 6AWB

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 6000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL6AWB675012	6-3/4	171	12	305	469	213	BKTAWB6PT	SLR12B
SL6AWB675016			16	406	476	216		SLR16B
SL6AWB675024			24	610	489	222		SLR24B
SL6AWB675036			36	914	509	231		SLR36B
SL6AWB675048			48	1219	538	244		SLR48B
SL6AWB775012	7-3/4	197	12	305	475	215	BKTAWB7PT	SLR12B
SL6AWB775016			16	406	482	219		SLR16B
SL6AWB775024			24	610	495	225		SLR24B
SL6AWB775036			36	914	515	234		SLR36B
SL6AWB775048			48	1219	544	247		SLR48B
SL6AWB875012	8-3/4	222	12	305	481	218	BKTAWB8PT	SLR12B
SL6AWB875016			16	406	488	221		SLR16B
SL6AWB875024			24	610	501	227		SLR24B
SL6AWB875036			36	914	521	236		SLR36B
SL6AWB875048			48	1219	550	249		SLR48B
SL6AWB975012	9-3/4	248	12	305	487	221	BKTAWB9PT	SLR12B
SL6AWB975016			16	406	494	224		SLR16B
SL6AWB975024			24	610	507	230		SLR24B
SL6AWB975036			36	914	527	239		SLR36B
SL6AWB975048			48	1219	556	252		SLR48B
SL6AWB1075012	10-3/4	273	12	305	507	230	BKTAWB10PT	SLR12B
SL6AWB1075016			16	406	514	233		SLR16B
SL6AWB1075024			24	610	527	239		SLR24B
SL6AWB1075036			36	914	547	248		SLR36B
SL6AWB1075048			48	1219	576	261		SLR48B

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AA6AWB1075048**). Order KIT-AIR-DASH Installation Kit separately.
2. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
3. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR".
4. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Air Slide – Model 7AWB

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 7000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL7AWB675012	6-3/4	171	12	305	481	218	BKTAWB6PT	SLR12B
SL7AWB675016			16	406	488	221		SLR16B
SL7AWB675024			24	610	501	227		SLR24B
SL7AWB675036			36	914	521	236		SLR36B
SL7AWB675048			48	1219	550	249		SLR48B
SL7AWB775012	7-3/4	197	12	305	487	221	BKTAWB7PT	SLR12B
SL7AWB775016			16	406	494	224		SLR16B
SL7AWB775024			24	610	507	230		SLR24B
SL7AWB775036			36	914	527	239		SLR36B
SL7AWB775048			48	1219	556	252		SLR48B
SL7AWB875012	8-3/4	222	12	305	493	224	BKTAWB8PT	SLR12B
SL7AWB875016			16	406	500	227		SLR16B
SL7AWB875024			24	610	513	233		SLR24B
SL7AWB875036			36	914	533	242		SLR36B
SL7AWB875048			48	1219	562	255		SLR48B
SL7AWB975012	9-3/4	248	12	305	499	226	BKTAWB9PT	SLR12B
SL7AWB975016			16	406	506	230		SLR16B
SL7AWB975024			24	610	519	235		SLR24B
SL7AWB975036			36	914	539	244		SLR36B
SL7AWB975048			48	1219	568	258		SLR48B
SL7AWB1075012	10-3/4	273	12	305	519	235	BKTAWB10PT	SLR12B
SL7AWB1075016			16	406	526	239		SLR16B
SL7AWB1075024			24	610	539	244		SLR24B
SL7AWB1075036			36	914	559	254		SLR36B
SL7AWB1075048			48	1219	588	267		SLR48B

NOTES:

1. **New!** To order a C7000 Clean-Connect™ Top Plate: 1) Add 3 lbs to the weight and 2) Replace the “SL7” prefix in the Part Number with “SLC” (Example: SLCATB1075048).
2. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the “SL” prefix in the Part Number with “AA” (Example: AA7AWB1075048). Order KIT-AIR-DASH Installation Kit separately.
3. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
4. All the assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the “SL” prefix in the Part Number with “SR”.
5. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Air Slide – Model HAWB, HAWS

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Slide Travel		Weight		Includes H5092 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SLHAWS675024	6-3/4	171	24	610	557	253	BKTAWS6PT	SLR24B
SLHAWS675036			36	914	577	262		SLR36B
SLHAWB775012	7-3/4	197	12	305	531	241	BKTAWB7PT	SLR12B
SLHAWB775016			16	406	538	244		SLR16B
SLHAWB775024			24	610	551	250		SLR24B
SLHAWB775036			36	914	571	259		SLR36B
SLHAWB775048			48	1219	600	272		SLR48B
SLHAWB875012	8-3/4	222	12	305	537	244	BKTAWB8PT	SLR12B
SLHAWB875016			16	406	544	247		SLR16B
SLHAWB875024			24	610	557	253		SLR24B
SLHAWB875036			36	914	577	262		SLR36B
SLHAWB875048			48	1219	606	275		SLR48B
SLHAWB975012	9-3/4	248	12	305	543	246	BKTAWB9PT	SLR12B
SLHAWB975016			16	406	550	249		SLR16B
SLHAWB975024			24	610	563	255		SLR24B
SLHAWB975036			36	914	583	264		SLR36B
SLHAWB975048			48	1219	612	278		SLR48B
SLHAWB1075012	10-3/4	273	12	305	563	255	BKTAWB10PT	SLR12B
SLHAWB1075016			16	406	570	259		SLR16B
SLHAWB1075024			24	610	583	264		SLR24B
SLHAWB1075036			36	914	603	274		SLR36B
SLHAWB1075048			48	1219	632	287		SLR48B

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AAHAWB1075048**). Order KIT-AIR-DASH Installation Kit separately.
2. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
3. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR".
4. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Air Slide – Model 6LWS (Light Weight Slide)

Standard Duty On-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 6000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL6LWS675012	6-3/4	171	12	305	432	196	BKT6LWSPT	SLR12LWS
SL6LWS675016			16	406	442	200		SLR16LWS
SL6LWS675024			24	610	456	207		SLR24LWS
SL6LWS675036			36	914	455	206		SLR36LWS
SL6LWS775012	7-3/4	197	12	305	423	192	BKT7LWSPT	SLR12LWS
SL6LWS775016			16	406	445	202		SLR16LWS
SL6LWS775024			24	610	459	208		SLR24LWS
SL6LWS775036			36	914	476	216		SLR36LWS
SL6LWS875012	8-3/4	222	12	305	439	199	BKT8LWSPT	SLR12LWS
SL6LWS875016			16	406	449	204		SLR16LWS
SL6LWS875024			24	610	463	210		SLR24LWS
SL6LWS875036			36	914	480	218		SLR36LWS

Air Slide – Model 7LWS (Light Weight Slide)

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 7000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL7LWS675012	6-3/4	171	12	305	444	201	BKT6LWSPT	SLR12LWS
SL7LWS675016			16	406	454	206		SLR16LWS
SL7LWS675024			24	610	468	212		SLR24LWS
SL7LWS675036			36	914	485	220		SLR36LWS
SL7LWS775012	7-3/4	197	12	305	447	203	BKT7LWSPT	SLR12LWS
SL7LWS775016			16	406	457	207		SLR16LWS
SL7LWS775024			24	610	471	214		SLR24LWS
SL7LWS775036			36	914	488	221		SLR36LWS
SL7LWS875012	8-3/4	222	12	305	451	205	BKT8LWSPT	SLR12LWS
SL7LWS875016			16	406	461	209		SLR16LWS
SL7LWS875024			24	610	475	215		SLR24LWS
SL7LWS875036			36	914	492	223		SLR36LWS

NOTES for 6LWS & 7LWS:

- 1. New!** To order a C7000 Clean-Connect™ Top Plate (7LWS only): 1) Add 3 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "SLC" (Example: SLCLWS875036).
- To order a 6LWS or 7LWS Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AA6LWS675036). Order KIT-AIR-DASH Installation Kit separately.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."
- Models are adjustable in 2" increments.
- Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Air Slide – Model XAWX Xtra® Heavy Duty

Moderate Duty On/Off-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 75,000 lbs vertical 200,000 lbs drawbar

Assemblies are supplied with top plate SLTPLX5092.

Part Number	Mounted Height		Slide Travel		Weight		Includes X5092 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SLXAWX950012	9-1/2	241	12	305	649	294	BKTAWX9PT	SLR12X
SLXAWX950024			24	610	679	308		SLR24X
SLXAWX950036			36	914	718	326		SLR36X
SLXAWX950048			48	1219	748	339		SLR48X
SLXAWX1050012	10-1/2	267	12	305	655	297	BKTAWX10PT	SLR12X
SLXAWX1050024			24	610	685	311		SLR24X
SLXAWX1050036			36	914	724	328		SLR36X
SLXAWX1050048			48	1219	754	342		SLR48X
SLXAWX1150012	11-1/2	292	12	305	661	300	BKTAWX11PT	SLR12X
SLXAWX1150024			24	610	691	313		SLR24X
SLXAWX1150036			36	914	730	331		SLR36X
SLXAWX1150048			48	1219	760	345		SLR48X

NOTES:

1. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
2. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."
3. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits in Kits Section.

Manual Slide – Model 6MTB

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service
Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar
 Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 6000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL6MTB675012	6-3/4	171	12	305	436	198	BKTMTB6PT	SLRTB12
SL6MTB675016			16	406	450	204		SLRTB16
SL6MTB675024			24	610	461	209		SLRTB24
SL6MTB675036			36	914	484	220		SLRTB36
SL6MTB675048			48	1219	510	231		SLRTB48
SL6MTB775012	7-3/4	197	12	305	441	200	BKTMTB7PT	SLRTB12
SL6MTB775016			16	406	455	206		SLRTB16
SL6MTB775024			24	610	466	211		SLRTB24
SL6MTB775036			36	914	489	222		SLRTB36
SL6MTB775048			48	1219	515	234		SLRTB48
SL6MTB875012	8-3/4	222	12	305	446	202	BKTMTB8PT	SLRTB12
SL6MTB875016			16	406	460	209		SLRTB16
SL6MTB875024			24	610	471	214		SLRTB24
SL6MTB875036			36	914	494	224		SLRTB36
SL6MTB875048			48	1219	520	236		SLRTB48
SL6MTB975012	9-3/4	248	12	305	451	205	BKTMTB9PT	SLRTB12
SL6MTB975016			16	406	465	211		SLRTB16
SL6MTB975024			24	610	476	216		SLRTB24
SL6MTB975036			36	914	499	226		SLRTB36
SL6MTB975048			48	1219	525	238		SLRTB48
SL6MTB1075012	10-3/4	273	12	305	474	215	BKTMTB10PT	SLRTB12
SL6MTB1075016			16	406	488	221		SLRTB16
SL6MTB1075024			24	610	499	226		SLRTB24
SL6MTB1075036			36	914	522	237		SLRTB36
SL6MTB1075048			48	1219	548	249		SLRTB48

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the “SL” prefix in the Part Number with “AA” (Example: **AA6MTB1075048**). Order KIT-AIR-DASH Installation Kit separately.
2. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
3. All the assemblies are supplied with left side (driver’s side) release. If right side (curbside) release is required, replace the “SL” prefix in the Part Number with “SR”.
4. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.



Manual Slide – Model 7MTB

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 7000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL7MTB675012	6-3/4	171	12	305	446	202	BKTMTB6PT	SLRTB12
SL7MTB675016			16	406	460	209		SLRTB16
SL7MTB675024			24	610	471	214		SLRTB24
SL7MTB675036			36	914	494	224		SLRTB36
SL7MTB675048			48	1219	520	236		SLRTB48
SL7MTB775012	7-3/4	197	12	305	451	205	BKTMTB7PT	SLRTB12
SL7MTB775016			16	406	465	211		SLRTB16
SL7MTB775024			24	610	476	216		SLRTB24
SL7MTB775036			36	914	499	226		SLRTB36
SL7MTB775048			48	1219	525	238		SLRTB48
SL7MTB875012	8-3/4	222	12	305	456	207	BKTMTB8PT	SLRTB12
SL7MTB875016			16	406	470	213		SLRTB16
SL7MTB875024			24	610	481	218		SLRTB24
SL7MTB875036			36	914	504	229		SLRTB36
SL7MTB875048			48	1219	530	240		SLRTB48
SL7MTB975012	9-3/4	248	12	305	461	209	BKTMTB9PT	SLRTB12
SL7MTB975016			16	406	475	215		SLRTB16
SL7MTB975024			24	610	486	220		SLRTB24
SL7MTB975036			36	914	509	231		SLRTB36
SL7MTB975048			48	1219	535	243		SLRTB48
SL7MTB1075012	10-3/4	273	12	305	484	220	BKTMTB10PT	SLRTB12
SL7MTB1075016			16	406	498	226		SLRTB16
SL7MTB1075024			24	610	509	231		SLRTB24
SL7MTB1075036			36	914	532	241		SLRTB36
SL7MTB1075048			48	1219	558	253		SLRTB48

NOTES:

- New!** To order a C7000 Clean-Connect™ Top Plate: 1) Add 3 lbs to the weight and 2) Replace the “SL7” prefix in the Part Number with “SLC” (Example: SLCMTB1075048).
- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the “SL7” prefix in the Part Number with “AA” (Example: AA7MTB1075048). Order KIT-AIR-DASH Installation Kit separately.
- Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
- All the assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the “SL” prefix in the Part Number with “SR”.
- Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Manual Slide – Model HMTB

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Slide Travel		Weight		Includes H5092 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SLHMTB875012	8-3/4	222	12	305	488	221	BKTMTB8PT	SLRTB12
SLHMTB875016			16	406	502	228		SLRTB16
SLHMTB875024			24	610	513	233		SLRTB24
SLHMTB875036			36	914	536	243		SLRTB36
SLHMTB875048			48	1219	562	255		SLRTB48
SLHMTB975012	9-3/4	248	12	305	493	224	BKTMTB9PT	SLRTB12
SLHMTB975016			16	406	507	230		SLRTB16
SLHMTB975024			24	610	518	235		SLRTB24
SLHMTB975036			36	914	541	245		SLRTB36
SLHMTB975048			48	1219	567	257		SLRTB48
SLHMTB1075012	10-3/4	273	12	305	516	234	BKTMTB10PT	SLRTB12
SLHMTB1075016			16	406	530	240		SLRTB16
SLHMTB1075024			24	610	541	245		SLRTB24
SLHMTB1075036			36	914	564	256		SLRTB36
SLHMTB1075048			48	1219	590	268		SLRTB48

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AAHMTB1075048**). Order KIT-AIR-DASH Installation Kit separately.
2. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
3. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR".
4. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Manual Slide – Model 6MWS

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 6000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL6MWS675012	6-3/4	171	12	305	464	210	BKTMWS6PT	SLR12B
SL6MWS675016			16	406	471	214		SLR16B
SL6MWS675024			24	610	484	220		SLR24B
SL6MWS675036			36	914	504	229		SLR36B
SL6MWS675048			48	1219	533	242		SLR48B
SL6MWS775012	7-3/4	197	12	305	470	213	BKTMWS7PT	SLR12B
SL6MWS775016			16	406	477	216		SLR16B
SL6MWS775024			24	610	490	222		SLR24B
SL6MWS775036			36	914	510	231		SLR36B
SL6MWS775048			48	1219	539	244		SLR48B
SL6MWS875012	8-3/4	222	12	305	476	216	BKTMWS8PT	SLR12B
SL6MWS875016			16	406	483	219		SLR16B
SL6MWS875024			24	610	496	225		SLR24B
SL6MWS875036			36	914	516	234		SLR36B
SL6MWS875048			48	1219	545	247		SLR48B
SL6MWS975012	9-3/4	248	12	305	482	219	BKTMWS9PT	SLR12B
SL6MWS975016			16	406	489	222		SLR16B
SL6MWS975024			24	610	502	228		SLR24B
SL6MWS975036			36	914	522	237		SLR36B
SL6MWS975048			48	1219	551	250		SLR48B
SL6MWS1075012	10-3/4	273	12	305	502	228	BKTMWS10PT	SLR12B
SL6MWS1075016			16	406	509	231		SLR16B
SL6MWS1075024			24	610	522	237		SLR24B
SL6MWS1075036			36	914	542	246		SLR36B
SL6MWS1075048			48	1219	571	259		SLR48B

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AA6MWS1075048). Order KIT-AIR-DASH Installation Kit separately.
2. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
3. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR".
4. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Manual Slide – Model 7MWS

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 7000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL7MWS675012	6-3/4	171	12	305	476	216	BKTMWS6PT	SLR12B
SL7MWS675016			16	406	483	219		SLR16B
SL7MWS675024			24	610	496	225		SLR24B
SL7MWS675036			36	914	516	234		SLR36B
SL7MWS675048			48	1219	545	247		SLR48B
SL7MWS775012	7-3/4	197	12	305	482	219	BKTMWS7PT	SLR12B
SL7MWS775016			16	406	489	222		SLR16B
SL7MWS775024			24	610	502	228		SLR24B
SL7MWS775036			36	914	522	237		SLR36B
SL7MWS775048			48	1219	551	250		SLR48B
SL7MWS875012	8-3/4	222	12	305	488	221	BKTMWS8PT	SLR12B
SL7MWS875016			16	406	495	225		SLR16B
SL7MWS875024			24	610	508	230		SLR24B
SL7MWS875036			36	914	528	239		SLR36B
SL7MWS875048			48	1219	557	253		SLR48B
SL7MWS975012	9-3/4	248	12	305	494	224	BKTMWS9PT	SLR12B
SL7MWS975016			16	406	501	227		SLR16B
SL7MWS975024			24	610	514	233		SLR24B
SL7MWS975036			36	914	534	242		SLR36B
SL7MWS975048			48	1219	563	255		SLR48B
SL7MWS1075012	10-3/4	273	12	305	514	233	BKTMWS10PT	SLR12B
SL7MWS1075016			16	406	521	236		SLR16B
SL7MWS1075024			24	610	534	242		SLR24B
SL7MWS1075036			36	914	554	251		SLR36B
SL7MWS1075048			48	1219	583	264		SLR48B

NOTES:

- New!** To order a C7000 Clean-Connect™ Top Plate: 1) Add 3 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "SLC" (Example: SLCMWS1075048).
- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "AA" (Example: AA7MWS1075048). Order KIT-AIR-DASH Installation Kit separately.
- Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
- All the assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR".
- Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Manual Slide – Model HMWS

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Slide Travel		Weight		Includes H5092 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SLHMWS775012	7-3/4	197	12	305	527	239	BKTMWS7PT	SLR12B
SLHMWS775016			16	406	534	242		SLR16B
SLHMWS775024			24	610	547	248		SLR24B
SLHMWS775036			36	914	567	257		SLR36B
SLHMWS775048			48	1219	596	270		SLR48B
SLHMWS875012	8-3/4	222	12	305	533	242	BKTMWS8PT	SLR12B
SLHMWS875016			16	406	540	245		SLR16B
SLHMWS875024			24	610	553	251		SLR24B
SLHMWS875036			36	914	573	260		SLR36B
SLHMWS875048			48	1219	602	273		SLR48B
SLHMWS975012	9-3/4	248	12	305	539	244	BKTMWS9PT	SLR12B
SLHMWS975016			16	406	546	248		SLR16B
SLHMWS975024			24	610	559	254		SLR24B
SLHMWS975036			36	914	579	263		SLR36B
SLHMWS975048			48	1219	608	276		SLR48B
SLHMWS1075012	10-3/4	273	12	305	559	254	BKTMWS10PT	SLR12B
SLHMWS1075016			16	406	566	257		SLR16B
SLHMWS1075024			24	610	579	263		SLR24B
SLHMWS1075036			36	914	599	272		SLR36B
SLHMWS1075048			48	1219	628	285		SLR48B

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AAHMWS1075048**). Order KIT-AIR-DASH Installation Kit separately.
2. Complete assemblies with 60" and 72" of slide travel are available as special order items. These special order products are non-returnable and non-refundable.
3. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR".
4. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.

Adjustable Flat Plate Mount – Model 6PMA (Plate Mount Adjustable)

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service
 Rated maximum loads: **50,000 lbs vertical 150,000 lbs drawbar**
 Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Weight		Includes 6000 top plate and: Mtg. Bracket (Assembly)
	Inches	MM	Lbs	Kgs	
SL6PMA6250	6-1/4	159	305	138	ASYPMA6250
SL6PMA7250	7-1/4	184	311	141	ASYPMA7250
SL6PMA8250	8-1/4	210	317	144	ASYPMA8250
SL6PMA9250	9-1/4	235	324	147	ASYPMA9250
SL6PMA10250	10-1/4	260	363	165	ASYPMA10250

Adjustable Flat Plate Mount – Model 7PMA (Plate Mount Adjustable)

Standard Duty On-Highway to Severe Duty On/Off-Highway Service
 Rated maximum loads: **55,000 lbs vertical 150,000 lbs drawbar**
 Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Weight		Includes 7000 top plate and: Mtg. Bracket (Assembly)
	Inches	MM	Lbs	Kgs	
SL7PMA6250	6-1/4	159	317	144	ASYPMA6250
SL7PMA7250	7-1/4	184	323	147	ASYPMA7250
SL7PMA8250	8-1/4	210	329	149	ASYPMA8250
SL7PMA9250	9-1/4	235	336	152	ASYPMA9250
SL7PMA10250	10-1/4	260	343	156	ASYPMA10250

NOTE FOR 6PMA & 7PMA:

- New!** To order a C7000 Clean-Connect™ Top Plate (7PMA only): 1) Add 3 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "SLC" (Example: SLCPMA9250).
- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AA6PMA9250). Order KIT-AIR-DASH Installation Kit separately.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."
- Adjustable in 2" increments.
- Outboard angle measurements are 55" length with 36" adjustment.
- Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits in Kits Section.



Adjustable Flat Plate Mount – Model HPMA (Plate Mount Adjustable)

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Weight		Includes H5092 top plate and:
	Inches	MM	Lbs	Kgs	Mtg. Bracket (Assembly)
SLHPMA6250	6-1/4	159	362	164	ASYHPMA6250
SLHPMA7250	7-1/4	184	368	167	ASYHPMA7250
SLHPMA8250	8-1/4	210	374	170	ASYPMA8250
SLHPMA9250	9-1/4	235	381	173	ASYPMA9250
SLHPMA10250	10-1/4	260	387	176	ASYPMA10250

NOTES:

- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AAHPMA9250**). Order KIT-AIR-DASH Installation Kit separately.
- Adjustable in 2" increments.
- Outboard angles are available in 37" length with 18" adjustment, 43" length with 24" adjustment, and 55" length with 36" adjustment.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Stationary Long Plate Mount – Model 6PLA

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Weight		Includes 6000 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
SL6PLA7125	7-1/8	181	418	190	BKT6PLT7125	PLT5PLA
SL6PLA8125	8-1/8	206	422	191	BKT6PLT8125	PLT5PLA
SL6PLA9125	9-1/8	232	426	193	BKTPLT9125	PLT5PLA
SL6PLA10125	10-1/8	257	444	201	BKTPLT10125	PLT5PLA
SL6PLA11125	11-1/8	283	448	203	BKTPLT11125	PLT5PLA

NOTES:

- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AA6PLA11125**). Order KIT-AIR-DASH Installation Kit separately.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Stationary Long Plate Mount – Model 7PLA

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Weight		Includes 7000 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
SL7PLA7125	7-1/8	181	430	195	BKT6PLT7125	PLT5PLA
SL7PLA8125	8-1/8	206	434	197	BKT6PLT8125	PLT5PLA
SL7PLA9125	9-1/8	232	438	199	BKTPLT9125	PLT5PLA
SL7PLA10125	10-1/8	257	456	207	BKTPLT10125	PLT5PLA
SL7PLA11125	11-1/8	283	460	209	BKTPLT11125	PLT5PLA

NOTES:

1. **New!** To order a C7000 Clean-Connect™ Top Plate: 1) Add 3 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "SLC" (Example: SLCPLA11125).
2. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AA7PLA11125). Order KIT-AIR-DASH Installation Kit separately.
3. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Stationary Long Plate Mount – Model HPLA

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Weight		Includes H5902 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
SLHPLA7375	7-3/8	187	540	245	BKTPLT7125	PLTXPLA
SLHPLA8375	8-3/8	213	544	247	BKTPLT8125	PLTXPLA
SLHPLA9375	9-3/8	238	548	249	BKTPLT9125	PLTXPLA
SLHPLA10375	10-3/8	264	566	257	BKTPLT10125	PLTXPLA
SLHPLA11375	11-3/8	289	570	259	BKTPLT11125	PLTXPLA

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AAHPLA11375). Order KIT-AIR-DASH Installation Kit separately.
2. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Stationary Long Plate Mount – Model XPLA Xtra® Heavy Duty

Moderate Duty On/Off-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 75,000 lbs vertical 200,000 lbs drawbar

Assemblies are supplied with top plate SLTPLX5092.

Part Number	Mounted Height		Weight		Includes X5902 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
SLXPLA9125	9-1/8	232	639	290	BKTPLT8125	PLTXPLA
SLXPLA10125	10-1/8	257	640	290	BKTPLT9125	PLTXPLA
SLXPLA11125	11-1/8	283	653	296	BKTPLT10125	PLTXPLA
SLXPLA12125	12-1/8	308	660	299	BKTPLT11125	PLTXPLA

NOTES:

1. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Stationary Short Plate Mount – Model 6PSA

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Weight		Includes 6000 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
SL6PSA7125	7-1/8	181	374	190	BKT6PLT7125	PLT5PSA
SL6PSA8125	8-1/8	206	378	191	BKT6PLT8125	PLT5PSA
SL6PSA9125	9-1/8	232	382	193	BKTPLT9125	PLT5PSA
SL6PSA10125	10-1/8	257	400	201	BKTPLT10125	PLT5PSA
SL6PSA11125	11-1/8	283	404	203	BKTPLT11125	PLT5PSA

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AA6PSA11125**). Order KIT-AIR-DASH Installation Kit separately.
2. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Stationary Short Plate Mount – Model 7PSA

Standard Duty On-Highway to Severe Duty On/Off-Highway Service
Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar
 Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Weight		Includes 7000 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
SL7PSA7125	7-1/8	181	387	176	BKT6PLT7125	PLT5PSA
SL7PSA8125	8-1/8	206	390	177	BKT6PLT8125	PLT5PSA
SL7PSA9125	9-1/8	232	394	179	BKTPLT9125	PLT5PSA
SL7PSA10125	10-1/8	257	412	187	BKTPLT10125	PLT5PSA
SL7PSA11125	11-1/8	283	416	189	BKTPLT11125	PLT5PSA

NOTES:

- 1. New!** To order a C7000 Clean-Connect™ Top Plate: 1) Add 3 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "SLC" (Example: SLCPSA11125).
- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AA7PSA11125). Order KIT-AIR-DASH Installation Kit separately.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Stationary Short Plate Mount – Model HPSA

Standard Duty On-Highway to Severe Duty On/Off-Highway Service
Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar
 Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Weight		Includes H5902 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
SLHPSA7375	7-3/8	187	474	215	BKTPLT7125	PLTXPSA
SLHPSA8375	8-3/8	213	478	217	BKTPLT8125	PLTXPSA
SLHPSA9375	9-3/8	238	482	219	BKTPLT9125	PLTXPSA
SLHPSA10375	10-3/8	264	500	227	BKTPLT10125	PLTXPSA
SLHPSA11375	11-3/8	289	508	230	BKTPLT11125	PLTXPSA

NOTES:

- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AAHPSA11375). Order KIT-AIR-DASH Installation Kit separately.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."



Stationary Short Plate Mount – Model XPSA Xtra® Heavy Duty

Moderate Duty On/Off-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 75,000 lbs vertical 200,000 lbs drawbar

Assemblies are supplied with top plate SLTPLX5092.

Part Number	Mounted Height		Weight		Includes X5902 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
SLXPSA9125	9-1/8	232	559	254	BKTPLT8125	PLTXPSA
SLXPSA10125	10-1/8	257	565	256	BKTPLT9125	PLTXPSA
SLXPSA11125	11-1/8	283	573	260	BKTPLT10125	PLTXPSA
SLXPSA12125	12-1/8	308	580	263	BKTPLT11125	PLTXPSA

NOTES:

1. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Bracket Stationary Mount (Welded) – Model 6BSM

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Weight		Includes 6000 top plate and:
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SL6BSM5875	5-7/8	149	259	117	BKTWLD5875
SL6BSM6875	6-7/8	175	265	120	BKTWLD6875
SL6BSM7875	7-7/8	200	271	123	BKTWLD7875
SL6BSM8875	8-7/8	225	273	124	BKTWLD8875
SL6BSM9875	9-7/8	305	305	138	BKTWLD9875

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AA6BSM9875). Order KIT-AIR-DASH Installation Kit separately.
2. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Bracket Stationary Mount (Welded) – Model 7BSM

Standard Duty On-Highway to Severe Duty On/Off-Highway Service
Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar
 Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Weight		Includes 7000 top plate and:
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SL7BSM5875	5-7/8	149	272	123	BKTWLD5875
SL7BSM6875	6-7/8	175	278	126	BKTWLD6875
SL7BSM7875	7-7/8	200	284	129	BKTWLD7875
SL7BSM8875	8-7/8	225	273	124	BKTWLD8875
SL7BSM9875	9-7/8	305	315	143	BKTWLD9875

NOTES:

1. **New!** To order a C7000 Clean-Connect™ Top Plate: 1) Add 3 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "SLC" (Example: SLCBSM9875).
2. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AA7BSM9875). Order KIT-AIR-DASH Installation Kit separately.
3. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Bracket Stationary Mount (Welded) – Model HBSM

Standard Duty On-Highway to Severe Duty On/Off-Highway Service
Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar
 Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Weight		Includes H5092 top plate and:
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SLHBSM5875	5-7/8	149	317	144	BKTWLD5875
SLHBSM6875	6-7/8	175	323	147	BKTWLD6875
SLHBSM7875	7-7/8	200	329	149	BKTWLD7875
SLHBSM8875	8-7/8	225	332	151	BKTWLD8875
SLHBSM9875	9-7/8	305	347	157	BKTWLD9875

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AAHBSM9875). Order KIT-AIR-DASH Installation Kit separately.
2. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."



Stationary Frame Mount – Model 6FMA

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Weight		Includes 6000 top plate and:
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SL6FMA6375	6-3/8	162	290	132	BKT6FMA6375
SL6FMA7375	7-3/8	187	298	135	BKT6FMA7375
SL6FMA8375	8-3/8	213	306	139	BKTFMA8375
SL6FMA9375	9-3/8	238	314	142	BKTFMA9375
SL6FMA10375	10-3/8	264	336	152	BKTFMA10375

NOTES:

1. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AA6FMA10375**). Order KIT-AIR-DASH Installation Kit separately.
2. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."
3. These parts require mounting angles and mounting plate not supplied by Fontaine -- see your truck OEM.

Stationary Frame Mount – Model 7FMA

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Weight		Includes 7000 top plate and:
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SL7FMA6375	6-3/8	162	299	136	BKT6FMA6375
SL7FMA7375	7-3/8	187	307	139	BKT6FMA7375
SL7FMA8375	8-3/8	213	315	143	BKTFMA8375
SL7FMA9375	9-3/8	238	323	147	BKTFMA9375
SL7FMA10375	10-3/8	264	345	156	BKTFMA10375

NOTES:

1. **New!** To order a C7000 Clean-Connect™ Top Plate: 1) Add 3 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "SLC" (Example: **SLCFMA10375**).
2. To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AA7FMA10375**). Order KIT-AIR-DASH Installation Kit separately.
3. All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."
4. These parts require mounting angles and mounting plate not supplied by Fontaine -- see your truck OEM.

Stationary Frame Mount – Model HFMA

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Weight		Includes H5902 top plate and: Mtg. Bracket (pr)
	Inches	MM	Lbs	Kgs	
SLHFMA7375	7-3/8	187	354	161	BKTFMA7375
SLHFMA8375	8-3/8	213	362	164	BKTFMA8375
SLHFMA9375	9-3/8	238	370	168	BKTFMA9375
SLHFMA10375	10-3/8	264	432	196	BKTFMA10375

NOTES:

- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AAHFMA10375**). Order KIT-AIR-DASH Installation Kit separately.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."
- These parts require mounting angles and mounting plate not supplied by Fontaine -- see your truck OEM.

Stationary Angle Mount – Model 6A36

Standard Duty On-Highway to Moderate Duty On/Off-Highway Service

Rated maximum loads: 50,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL6000.

Part Number	Mounted Height		Frame Width		Weight		Includes 6000 top plate and: Mtg. Bracket (pr)
	Inches	MM	Inches	MM	Lbs	Kgs	
SL6A365750E	5-3/4	146	34	864	308	140	BKTA365750E
SL6A365750L			33.5	851	308	140	BKTA365750L
SL6A366250E	6-1/4	159	34	864	312	142	BKTA366250E
SL6A366250L			33.5	851	312	142	BKTA366250L
SL6A367250E	7-1/4	184	34	864	316	143	BKTA367250E
SL6A367250L			33.5	851	316	143	BKTA367250L
SL6A368250E	8-1/4	210	34	864	320	145	BKTA368250E
SL6A368250L			33.5	851	320	145	BKTA368250L
SL6A369250E	9-1/4	235	34	864	324	147	BKTA369250E
SL6A369250L			33.5	851	324	147	BKTA369250L
SL6A3610250E	10-1/4	260	34	864	342	155	BKTA3610250E
SL6A3610250L			33.5	851	342	155	BKTA3610250L

NOTES:

- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: **AA6A3610250L**). Order KIT-AIR-DASH Installation Kit separately.
- When ordering specify truck frame width. "E" indicates 34" frame width, and "L" indicates 33.5" frame width. Contact Customer Service for pricing on other available frame widths.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Stationary Angle Mount – Model 7A36

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 55,000 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPL7000.

Part Number	Mounted Height		Frame Width		Weight		Includes 7000 top plate and:
	Inches	MM	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SL7A365750E	5-3/4	146	34	864	325	147	BKTA365750E
SL7A365750L			33.5	851	325	147	BKTA365750L
SL7A366250E	6-1/4	159	34	864	329	149	BKTA366250E
SL7A366250L			33.5	851	329	149	BKTA366250L
SL7A367250E	7-1/4	184	34	864	333	151	BKTA367250E
SL7A367250L			33.5	851	333	151	BKTA367250L
SL7A368250E	8-1/4	210	34	864	337	153	BKTA368250E
SL7A368250L			33.5	851	337	153	BKTA368250L
SL7A369250E	9-1/4	235	34	864	341	155	BKTA369250E
SL7A369250L			33.5	851	341	155	BKTA369250L
SL7A3610250E	10-1/4	260	34	864	359	163	BKTA3610250E
SL7A3610250L			33.5	851	359	163	BKTA3610250L

Stationary Angle Mount – Model HA36

Standard Duty On-Highway to Severe Duty On/Off-Highway Service

Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar

Assemblies are supplied with top plate SLTPLH5092.

Part Number	Mounted Height		Frame Width		Weight		Includes H5092 top plate and:
	Inches	MM	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SLHA365750E	5-3/4	146	34	864	370	168	BKTA365750E
SLHA365750L			33.5	851	370	168	BKTA365750L
SLHA366250E	6-1/4	159	34	864	374	170	BKTA366250E
SLHA366250L			33.5	851	374	170	BKTA366250L
SLHA367250E	7-1/4	184	34	864	378	171	BKTA367250E
SLHA367250L			33.5	851	378	171	BKTA367250L
SLHA368250E	8-1/4	210	34	864	382	173	BKTA368250E
SLHA368250L			33.5	851	382	173	BKTA368250L
SLHA369250E	9-1/4	235	34	864	386	175	BKTA369250E
SLHA369250L			33.5	851	386	175	BKTA369250L
SLHA3610250E	10-1/4	260	34	864	404	183	BKTA3610250E
SLHA3610250L			33.5	851	404	183	BKTA3610250L

NOTES FOR 7A36 & HA36:

- 1. New!** To order a C7000 Clean-Connect™ Top Plate (7A36 only): 1) Add 3 lbs to the weight and 2) Replace the "SL7" prefix in the Part Number with "SLC" (Example: SLCA3610250L).
- To order an Air Actuated Top Plate: 1) Add 4 lbs to the weight and 2) Replace the "SL" prefix in the Part Number with "AA" (Example: AA7A3610250L). Order KIT-AIR-DASH Installation Kit separately.
- When ordering specify truck frame width. "E" indicates 34" frame width, and "L" indicates 33.5" frame width. Contact Customer Service for pricing on other available frame widths.
- All the above assemblies are supplied with left side (driver's side) release. If right side (curbside) release is required, replace the "SL" prefix in the Part Number with "SR."

Blocked Air Slide – Model BLHAWB

Standard Duty to Severe Duty On/Off-Highway Service
 Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar
 Blocked top plate not sold separately.

Part Number	Mounted Height		Slide Travel		Weight		Includes H5092 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
BLHAWB875012	8-3/4	222	12	305	579	263	See note 3	SLR12B
BLHAWB875024			24	610	599	272		SLR24B
BLHAWB875036			36	914	619	281		SLR36B
BLHAWB875048			48	1219	648	294		SLR48B
BLHAWB975012	9-3/4	248	12	305	585	265	See note 3	SLR12B
BLHAWB975024			24	610	605	274		SLR24B
BLHAWB975036			36	914	625	283		SLR36B
BLHAWB975048			48	1219	654	297		SLR48B
BLHAWB1075012	10-3/4	273	12	305	605	274	See note 3	SLR12B
BLHAWB1075024			24	610	625	283		SLR24B
BLHAWB1075036			36	914	645	293		SLR36B
BLHAWB1075048			48	1219	674	306		SLR48B

Blocked Manual Slide – Model BLHMWS

Standard Duty to Severe Duty On/Off-Highway Service
 Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar
 Blocked top plate not sold separately.

Part Number	Mounted Height		Slide Travel		Weight		Includes H5092 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
BLHMWS875012	8-3/4	222	12	305	575	261	See note 3	SLR12B
BLHMWS875024			24	610	595	270		SLR24B
BLHMWS875036			36	914	615	279		SLR36B
BLHMWS875048			48	1219	644	292		SLR48B
BLHMWS975012	9-3/4	248	12	305	581	264	See note 3	SLR12B
BLHMWS975024			24	610	601	273		SLR24B
BLHMWS975036			36	914	621	282		SLR36B
BLHMWS975048			48	1219	650	295		SLR48B
BLHMWS1075012	10-3/4	273	12	305	601	273	See note 3	SLR12B
BLHMWS1075024			24	610	621	282		SLR24B
BLHMWS1075036			36	914	641	291		SLR36B
BLHMWS1075048			48	1219	670	304		SLR48B

NOTES FOR BLHAWB & BLHMWS

1. The "L" in the blocked assembly Part Number indicates left side (driver's side) release.
2. Installation parts available: See Mounting Angles Section. See Mounting Bolt Kits and KIT-AIR in Kits Section.
3. Slide brackets for the above assemblies are specially modified for use with the blocked top plate and are not sold separately. Call Customer Service for assistance when ordering.

Blocked Long Plate Mount – Model BLHPLA

Standard Duty to Severe Duty On/Off-Highway Service
 Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar
 Blocked top plate not sold separately.

Part Number	Mounted Height		Weight		Includes H5092 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
BLHPLA8375	8-3/8	213	544	247	See note 2	
BLHPLA9375	9-3/8	238	548	249		
BLHPLA10375	10-3/8	264	566	257		

Blocked Short Plate Mount – Model BLHPSA

Standard Duty to Severe Duty On/Off-Highway Service
 Rated maximum loads: 62,500 lbs vertical 150,000 lbs drawbar
 Blocked top plate not sold separately.

Part Number	Mounted Height		Weight		Includes H5092 top plate and:	
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)	Mtg. Plate
BLHPSA8375	8-3/8	213	520	236	See note 2	
BLHPSA9375	9-3/8	238	524	238		
BLHPSA10375	10-3/8	264	542	246		

NOTES for BLHPLA & BLHPSA:

1. The "L" in the blocked assembly Part Number indicates left side (driver's side) release.
2. Top plates, mounting brackets and mounting plates for the above assemblies are not sold separately. Contact Customer Service for assistance.

Fifth Wheel Top Plates

Part Number	Weight		Load Ratings			
			Vertical (Imposed) Load		Drawbar (Towed) Load	
	Lbs	Kgs	Lbs	Kgs	Lbs	Kgs
SLTPL6000	235	107	50,000	22,680	150,000	68,039
SRTPL6000	235	107	50,000	22,680	150,000	68,039
AATPL6000	239	108	50,000	22,680	150,000	68,039
SLTPL7000	245	111	55,000	24,948	150,000	68,039
SRTPL7000	245	111	55,000	24,948	150,000	68,039
AATPL7000	249	113	55,000	24,948	150,000	68,039
SLTPL7000CC	248	112	55,000	24,948	150,000	68,039
AATPL7000CC	253	115	55,000	24,948	150,000	68,039
SLTPLH5092	277	126	62,500	28,350	150,000	68,039
SRTPLH5092	277	126	62,500	28,350	150,000	68,039
SLTPLX5092	334	151	75,000	34,019	200,000	90,718
SRTPLX5092	334	151	75,000	34,019	200,000	90,718
SLTPL3000	215	98	Approved to 94/20/EC Directive: D-Value 150 ; U-Value 20			

Air Slide Bracket & Rails Subassembly – Model ATB

Part Number	Asmby. Height		Slide Travel		Weight		Includes:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
ASYATB612	6-3/4	171	12	305	201	91	BKTATB6PT	SLRTB12
ASYATB616			16	406	215	98		SLRTB16
ASYATB624			24	610	226	103		SLRTB24
ASYATB636			36	914	249	113		SLRTB36
ASYATB648			48	1219	275	125		SLRTB48
ASYATB712	7-3/4	197	12	305	206	93	BKTATB7PT	SLRTB12
ASYATB716			16	406	220	100		SLRTB16
ASYATB724			24	610	231	105		SLRTB24
ASYATB736			36	914	254	115		SLRTB36
ASYATB748			48	1219	280	127		SLRTB48
ASYATB812	8-3/4	222	12	305	211	96	BKTATB8PT	SLRTB12
ASYATB816			16	406	225	102		SLRTB16
ASYATB824			24	610	236	107		SLRTB24
ASYATB836			36	914	259	117		SLRTB36
ASYATB848			48	1219	285	129		SLRTB48
ASYATB912	9-3/4	248	12	305	216	98	BKTATB9PT	SLRTB12
ASYATB916			16	406	230	104		SLRTB16
ASYATB924			24	610	241	109		SLRTB24
ASYATB936			36	914	264	120		SLRTB36
ASYATB948			48	1219	290	132		SLRTB48
ASYATB1012	10-3/4	273	12	305	239	108	BKTATB10PT	SLRTB12
ASYATB1016			16	406	253	115		SLRTB16
ASYATB1024			24	610	264	120		SLRTB24
ASYATB1036			36	914	287	130		SLRTB36
ASYATB1048			48	1219	313	142		SLRTB48

Air Slide Bracket & Rails Subassembly – Model AWB

Part Number	Asmbly. Height		Slide Travel		Weight		Includes:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
ASYAWB612	6-3/4	171	12	305	259	117	BKTAWB6PT	SLR12B
ASYAWB616			16	406	266	121		SLR16B
ASYAWB624			24	610	282	128		SLR24B
ASYAWB636			36	914	305	138		SLR36B
ASYAWB648			48	1219	337	153		SLR48B
ASYAWB712	7-3/4	197	12	305	265	120	BKTAWB7PT	SLR12B
ASYAWB716			16	406	272	123		SLR16B
ASYAWB724			24	610	288	131		SLR24B
ASYAWB736			36	914	311	141		SLR36B
ASYAWB748			48	1219	343	156		SLR48B
ASYAWB812	8-3/4	222	12	305	271	123	BKTAWB8PT	SLR12B
ASYAWB816			16	406	278	126		SLR16B
ASYAWB824			24	610	294	133		SLR24B
ASYAWB836			36	914	317	144		SLR36B
ASYAWB848			48	1219	349	158		SLR48B
ASYAWB912	9-3/4	248	12	305	277	126	BKTAWB9PT	SLR12B
ASYAWB916			16	406	284	129		SLR16B
ASYAWB924			24	610	300	136		SLR24B
ASYAWB936			36	914	323	147		SLR36B
ASYAWB948			48	1219	355	161		SLR48B
ASYAWB1012	10-3/4	273	12	305	297	135	BKTAWB10PT	SLR12B
ASYAWB1016			16	406	304	138		SLR16B
ASYAWB1024			24	610	320	145		SLR24B
ASYAWB1036			36	914	343	156		SLR36B
ASYAWB1048			48	1219	375	170		SLR48B

Air Slide Bracket & Rails Subassembly – Model LWS*

Part Number	Asmbly. Height		Slide Travel		Weight		Includes:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
ASYLWS612	6-3/4	171	12	305	211	96	BKT6LWSPT	SLR12LWS
ASYLWS624			24	610	235	107		SLR24LWS
ASYLWS636			36	914	252	114		SLR36LWS
ASYLWS712	7-3/4	197	12	305	214	97	BKT7LWSPT	SLR12LWS
ASYLWS724			24	610	238	108		SLR24LWS
ASYLWS736			36	914	255	116		SLR36LWS
ASYLWS812	8-3/4	222	12	305	220	100	BKT8LWSPT	SLR12LWS
ASYLWS824			24	610	244	111		SLR24LWS
ASYLWS836			36	914	261	118		SLR36LWS

* Used with 6000 & 7000 top plates only.

Manual Slide Bracket & Rails Subassembly – Model MTB

Part Number	Asmbly. Height		Slide Travel		Weight		Includes:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
ASYMTB612	6-3/4	171	12	305	201	91	BKTMTB6PT	SLRTB12
ASYMTB616			16	406	215	98		SLRTB16
ASYMTB624			24	610	226	103		SLRTB24
ASYMTB636			36	914	249	113		SLRTB36
ASYMTB648			48	1219	275	125		SLRTB48
ASYMTB712	7-3/4	197	12	305	206	93	BKTMTB7PT	SLRTB12
ASYMTB716			16	406	220	100		SLRTB16
ASYMTB724			24	610	231	105		SLRTB24
ASYMTB736			36	914	254	115		SLRTB36
ASYMTB748			48	1219	280	127		SLRTB48
ASYMTB812	8-3/4	222	12	305	211	96	BKTMTB8PT	SLRTB12
ASYMTB816			16	406	225	102		SLRTB16
ASYMTB824			24	610	236	107		SLRTB24
ASYMTB836			36	914	259	117		SLRTB36
ASYMTB848			48	1219	285	129		SLRTB48
ASYMTB912	9-3/4	248	12	305	216	98	BKTMTB9PT	SLRTB12
ASYMTB916			16	406	230	104		SLRTB16
ASYMTB924			24	610	241	109		SLRTB24
ASYMTB936			36	914	264	120		SLRTB36
ASYMTB948			48	1219	290	132		SLRTB48
ASYMTB1012	10-3/4	273	12	305	239	108	BKTMTB10PT	SLRTB12
ASYMTB1016			16	406	253	115		SLRTB16
ASYMTB1024			24	610	264	120		SLRTB24
ASYMTB1036			36	914	287	130		SLRTB36
ASYMTB1048			48	1219	313	142		SLRTB48

Manual Slide Bracket & Rails Subassembly – Model MWS

Part Number	Asmby. Height		Slide Travel		Weight		Includes:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
ASYMWS612	6-3/4	171	12	305	255	116	BKTMWS6PT	SLR12B
ASYMWS616			16	406	263	119		SLR16B
ASYMWS624			24	610	278	126		SLR24B
ASYMWS636			36	914	301	137		SLR36B
ASYMWS648			48	1219	333	151		SLR48B
ASYMWS712	7-3/4	197	12	305	261	118	BKTMWS7PT	SLR12B
ASYMWS716			16	406	269	122		SLR16B
ASYMWS724			24	610	284	129		SLR24B
ASYMWS736			36	914	307	139		SLR36B
ASYMWS748			48	1219	339	154		SLR48B
ASYMWS812	8-3/4	222	12	305	267	121	BKTMWS8PT	SLR12B
ASYMWS816			16	406	275	125		SLR16B
ASYMWS824			24	610	290	132		SLR24B
ASYMWS836			36	914	313	142		SLR36B
ASYMWS848			48	1219	345	156		SLR48B
ASYMWS912	9-3/4	248	12	305	273	124	BKTMWS9PT	SLR12B
ASYMWS916			16	406	281	127		SLR16B
ASYMWS924			24	610	296	134		SLR24B
ASYMWS936			36	914	319	145		SLR36B
ASYMWS948			48	1219	351	159		SLR48B
ASYMWS1012	10-3/4	273	12	305	293	133	BKTMWS10PT	SLR12B
ASYMWS1016			16	406	301	137		SLR16B
ASYMWS1024			24	610	316	143		SLR24B
ASYMWS1036			36	914	339	154		SLR36B
ASYMWS1048			48	1219	371	168		SLR48B

Air Slide Bracket & Rails Subassembly – Model AWX

Part Number	Asmby. Height		Slide Travel		Weight		Includes:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
ASYAWX912	9-1/2	241	12	305	315	143	BKTAWX9PT	SLR12X
ASYAWX924			24	610	345	156		SLR24X
ASYAWX936			36	914	384	174		SLR36X
ASYAWX948			48	1219	414	188		SLR48X
ASYAWX1012	10-1/2	267	12	305	321	146	BKTAWX10PT	SLR12X
ASYAWX1024			24	610	351	159		SLR24X
ASYAWX1036			36	914	390	177		SLR36X
ASYAWX1048			48	1219	420	191		SLR48X
ASYAWX1112	11-1/2	292	12	305	327	148	BKTAWX11PT	SLR12X
ASYAWX1124			24	610	357	162		SLR24X
ASYAWX1136			36	914	396	180		SLR36X
ASYAWX1148			48	1219	426	193		SLR48X

Bracket Assembly – Model PMA

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
ASYPMA6250	6-1/4	159	82	37
ASYPMA7250	7-1/4	184	88	40
ASYPMA8250	8-1/4	210	94	43
ASYPMA9250	9-1/4	235	101	46
ASYPMA10250	10-1/4	260	108	49
ASYHPMA6250*	7-1/4	184	83	38
ASYHPMA7250*	8-1/4	210	89	40

Note: AFP has been superceded to PMA

* Note: For H5092 only



Air Slide Bracket – Model ATB

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKTATB6PT	6-3/4	171	120	54
BKTATB7PT	7-3/4	197	125	57
BKTATB8PT	8-3/4	222	130	59
BKTATB9PT	9-3/4	248	135	61
BKTATB10PT	10-3/4	273	158	72

Air Slide Bracket – Model AWB, AWS

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKTAWS6PT*	6-3/4	171	140	64
BKTAWB6PT*	6-3/4	171	152	69
BKTAWB7PT*	7-3/4	197	158	72
BKTAWB8PT**	8-3/4	222	164	74
BKTAWB9PT**	9-3/4	248	170	77
BKTAWB10PT**	10-3/4	273	176	80

* BKTAWS6PT is a low mount assembly used with H5092 top plate only. BKTAWB6PT is used with 6000 & 7000 top plates only. All include front rocker limit blocks.

** BKTAWB8PT through BKTAWB10PT do not have front rocker limit blocks.

Air Slide Bracket – Model LWS*

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKT6LWSPT	6-3/4	171	119	54
BKT7LWSPT	7-3/4	197	122	55
BKT8LWSPT	8-3/4	222	128	58

* Used with 6000 & 7000 top plates only.

Air Slide Bracket – Model AWX*

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKTAWX9PT	9-1/2	241	180	82
BKTAWX10PT	10-1/2	267	186	84
BKTAWX11PT	11-1/2	292	192	87

* Used with X5092 top plate only.

Manual Slide Bracket – Model MTB

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKTMTB6PT	6-3/4	171	120	54
BKTMTB7PT	7-3/4	197	125	57
BKTMTB8PT	8-3/4	222	130	59
BKTMTB9PT	9-3/4	248	135	61
BKTMTB10PT	10-3/4	273	158	72

Manual Slide Bracket – Model MWS

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKTMWS6PT*	6-3/4	171	148	67
BKTMWS7PT	7-3/4	197	154	70
BKTMWS8PT	8-3/4	222	160	73
BKTMWS9PT	9-3/4	248	166	75
BKTMWS10PT	10-3/4	273	172	78

* BKTMWS6PT used with 6000 & 7000 top plates only.

Mounting Brackets – FMA, PLA, PSA, A36, BSM

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKT6FMA6375*	6-3/8	162	64	29
BKT6FMA7375*	7-3/8	187	72	33
BKTFMA6375	6-3/8	162	64	29
BKTFMA7375	7-3/8	187	72	33
BKTFMA8375	8-3/8	213	80	36
BKTFMA9375	9-3/8	238	88	40
BKTFMA10375	10-3/8	264	110	50
BKT6PLT7125*	7-1/8	181	60	27
BKT6PLT8125*	8-1/8	206	64	29
BKTPLT7125**	7-1/8	181	60	27
BKTPLT8125**	8-1/8	206	64	29
BKTPLT9125**	9-1/8	232	68	31
BKTPLT10125**	10-1/8	257	86	39
BKTPLT11125**	11-1/8	283	104	47
BKTA365750E***	5-3/4	146	90	41
BKTA365750L***	5-3/4	146	90	41
BKTA366250E***	6-1/4	159	94	43
BKTA366250L***	6-1/4	159	94	43
BKTA367250E***	7-1/4	184	98	44
BKTA367250L***	7-1/4	184	98	44
BKTA368250E***	8-1/4	210	102	46
BKTA368250L***	8-1/4	210	102	46
BKTA369250E***	9-1/4	235	106	48
BKTA369250L***	9-1/4	235	106	48
BKTA3610250E***	10-1/4	260	124	56
BKTA3610250L***	10-1/4	260	124	56
BKTWLD5875	5-7/8	149	37	17
BKTWLD6875	6-7/8	175	43	20
BKTWLD7875	7-7/8	200	49	22
BKTWLD8875	8-7/8	225	55	25
BKTWLD9875	9-7/8	251	61	28

* BKT6FMA and BKT6PLT brackets are used with 6000 & 7000 top plates only and include front rocker limit blocks (example BKT6FMA6375). BKTFMA and BKTPLT brackets (example BKTFMA6375) do not have front rocker limit blocks.

** BKTPLT Brackets used for PLA and PSA Mounts. Mounted height includes 3/4" mounting plate.

*** When ordering, specify truck frame width "E" to indicate 34" frame width or "L" to indicate 33 1/2" frame width. Contact Customer Service for pricing on other available frame widths, lengths greater than 36" or angles other than 4"x 4"x 3/8".

Note: PMA Brackets (BKTPMA) have been superseded to ASYPMA. See Bracket Assembly – Model PMA section on page 33.

Slide Rails – ATB, MTB

Part Number	Slide Travel		Length		Weight	
	Inches	MM	Inches	MM	Lbs	Kgs
SLRTB12	12	305	42	1067	81	37
SLRTB16	16	406	46	1168	95	43
SLRTB24	24	610	54	1372	106	48
SLRTB36	36	914	66	1676	129	59
SLRTB48	48	1219	78	1981	155	70

* Used with 6000, 7000 and H5092 top plates.

Slide Rails – Model AWB, AWS, MWS*

Part Number	Slide Travel		Length		Weight	
	Inches	MM	Inches	MM	Lbs	Kgs
SLR12B	12	305	42	1067	103	47
SLR16B	16	406	46	1168	111	50
SLR20B	20	508	50	1270	119	54
SLR24B	24	610	54	1372	126	57
SLR36B	36	914	66	1676	149	68
SLR48B	48	1219	78	1981	181	82

* Used with 6000, 7000 and H5092 top plates.

Slide Rails – Model LWS*

Part Number	Slide Travel		Length		Weight	
	Inches	MM	Inches	MM	Lbs	Kgs
SLR12LWS	12	305	37.25	946	92	42
SLR24LWS	24	610	49.25	1251	116	53
SLR36LWS	36	914	61.25	1556	133	60

* Used with 6000 & 7000 top plates only.

Slide Rails – Model XAWX*

Part Number	Slide Travel		Length		Weight	
	Inches	MM	Inches	MM	Lbs	Kgs
SLR12X	12	305	54	1372	135	61
SLR24X	24	610	66	1676	165	75
SLR36X	36	914	78	1981	204	93
SLR48X	48	1219	90	2286	243	110

* Used with X5092 top plate only.

Mounting Angles - $\frac{3}{8}$ " x 3" x 4" (AWB, AWS, ATB, MTB, ASB, APB, LWS, MWS, PMA)

Part Number	Slide Travel		Angle Length		Weight		Truck Frame Width	
	Inches	MM	Inches	MM	Lbs	Kgs	Inches	MM
ANGS67B175	36	914	67	1702	92	42	33.25 - 34.25	845 - 870
ANGS79B175	48	1219	79	2007	109	49	33.25 - 34.25	845 - 870

Note: All mounting angles are sold in pairs.

Mounting Angles - $\frac{3}{8}$ " x 3" x 4" (AWB, AWS, ATB, MTB, ASB, APB, LWS, MWS, PMA)

Part Number	Slide Travel		Angle Length		Weight		Truck Frame Width	
	Inches	MM	Inches	MM	Lbs	Kgs	Inches	MM
ANGP55B175	up to 24	up to 610	55	1397	78	35	33.25 - 34.25	845 - 870

ANGP - indicates that the angle can be cut to fit an appropriate slide rail length. 55" overall length = 24" slide rail length, 47" overall length = 16" slide rail length, and a 43" overall length = 12" slide rail length.

Mounting Angles - $\frac{3}{8}$ " x 3" x 5" (AWB, AWS, ATB, MTB, ASB, APB, LWS, MWS, PMA)

Part Number	Slide Travel		Angle Length		Weight		Truck Frame Width	
	Inches	MM	Inches	MM	Lbs	Kgs	Inches	MM
ANGP55C175	up to 24	up to 610	55	1397	90	41	33.25 - 34.25	845 - 870

ANGP - indicates that the angle can be cut to fit an appropriate slide rail length. 55" overall length = 24" slide rail length, 47" overall length = 16" slide rail length, and a 43" overall length = 12" slide rail length.

Mounting Angles - $\frac{3}{8}$ " x 5" x 5" (XAWX)

Part Number	Slide Travel		Angle Length		Weight		Truck Frame Width	
	Inches	MM	Inches	MM	Lbs	Kgs	Inches	MM
ANGX67E175	24	610	67	1702	138	63	33.25 - 34.25	845 - 870
ANGX79E175	36	914	79	2007	164	74	33.25 - 34.25	845 - 870
ANGX91E175	48	1219	91	2311	190	86	33.25 - 34.25	845 - 870

Note: All mounting angles are sold in pairs.

Mounting Plates

Part Number	Dimensions		Mount	Weight	
	Inches	CM		Lbs	Kgs
PLT5PLA	35-3/4 x 40 x 3/4	91 x 102 x 2	PLA	132	60
PLT5PSA	23-3/4 x 40 x 3/4	60 x 102 x 2	PSA	88	40
PLTXPLA*	35-3/4 x 40 x 1-1/8	91 x 102 x 3	XPLA	198	90
PLTXPSA*	23-3/4 x 40 x 1-1/8	60 x 102 x 3	XPSA	132	60

* Use H5092 or X5092 Top Plates with these part numbers.

Service Parts Available In Case Quantities*

Part Number	Description	Weight Each (lbs)	Quantity Per Case	Total Weight (lbs)
BLT-301-1	Flat Head Socket, 1/2" -13 x 1", Grade 5	0.25	10	2.50
BLT-301-3	Flat Head Socket, 1/2" -13 x 1-1/2", Grade 5	0.20	10	2.00
BLT-301-5	Flat Head Socket, 1/2" -13 x 2", Grade 5	0.20	10	2.00
BLT-301-12	Flat Head Socket, 5/8" -11 x 1-3/4", Grade 5	0.25	10	2.50
BLT-301-19	Flat Head Socket, 5/8"-11 x 3-1/2", Grade 5	0.25	10	2.50
BLT-313	Shoulder Bolt, 5/8"x 1-1/4" w/ 1/2" - 13, Grade 5	0.25	10	2.50
BLT-313-2	Shoulder Bolt, 1/2" x 1-3/8" w/ 3/8" -16, Grade 5	0.25	10	2.50
BSH-115	Bushing, 7/16"	0.00	25	2.00
BSH-150	Bracket Bushing (pr.) (Also see Kits)	2.00	8 Pairs	16.00
BSH-629	Bushing, 5/16"	0.04	25	1.00
CD-SPR-236	Timer Spring	0.01	6	0.4
MSC-370	Grease Fitting	0.05	50	2.50
MSC-375	Grease Fitting	0.05	50	2.50
NUT-303-1	Hex Lock Nut, 3/8" -16, Grade "B"	0.06	25	1.60
NUT-303-3	Hex Lock Nut, 5/8" -11, Grade "B"	0.07	25	1.80
NUT-303-6	Hex Jam Nut, 1/2" - 13, Grade "B"	0.06	25	1.50
NUT-303-9	Hex Lock Nut, 1/2" - 13, Grade "C"	0.07	25	1.80
NUT-319	Wedge Stop Rod Nut	0.06	10	0.60
PIN-95	Cotter Pin, 1/4" x 3" (Also see Kits)	0.08	20	1.50
PIN-124P	Bracket Retainer Pin (Pair) (Replaces PIN-124) (Also see Kits)	0.42	6 pairs	2.50
PIN-135-1P	Bracket Pin (Pair) (Replaces PIN-135-1) (Also see Kits)	2.40	6 pairs	14.40
PIN-191P	Universal Bracket Pin (Pair) (Replaces PIN-135, PIN-135P & PIN-6000P) (Also see Kits)	2.40	6 pairs	14.40
PIN-289P	Retainer Pin For an XHD Wheel (pr.)	0.30	6 pairs	1.80
PIN-306-3	Cotter Pin 5/32" x 1" (Also see Kits)	0.03	50	1.25
PIN-307-1	Clevis Pin, 3/4" x 3" (Also see Kits)	0.50	20	10.00
PIN-307-2	Clevis Pin 3/8" x 2"	0.43	20	8.50
PIN-307-4	Clevis Pin, 1/2" x 1" (Also see Kits)	0.40	20	8.00
PIN-331	Lock Pin	0.06	20	1.26
SPR-128	Bumper Spring (Also see Kits)	0.50	6	3.00
SPR-233	Latching Lever Spring (Also see Kits)	0.50	6	3.00
SPR-317	Wedge Stop Rod Spring	0.15	10	1.50
SPR-338	Handle Spring (Also see Kits)	0.50	6	3.00
SPR-374	Bumper/Handle Spring (Also see Kits)	0.50	6	3.00
SPR-569	Leaf Spring / with 2 self tapping screws (SCR-425)	0.11	6	0.66
SPR-632	Locking Member Spring	0.37	6	2.20
WSH-304-1	Flat Washer, 3/8", Plain	0.00	50	0.35
WSH-304-3	Flat Washer, 1/2" I.D. 1" O.D., Plain	0.00	50	1.00
WSH-304-4	Flat Washer, 1/2" I.D. 1-3/8" O.D., Plain	0.00	50	2.14
WSH-304-5	Flat Washer, 5/8", Plain	0.00	50	1.49
WSH-304-7	Flat Washer, 5/8", Hardened	0.00	50	1.75
WSH-304-8	Flat Washer 3/4", Plain	0.00	50	1.75
WSH-304-9	Flat Washer 3/4", Plain	0.00	50	1.95
WSH-304-16	Flat Washer, 5/8", Stainless Steel	0.00	50	1.51

The above parts are shipped direct from Fontaine® International in case quantities only. They may be available in individual quantities from your local distributor/dealer.

Service Parts

Part Number	Description	Weight (lbs)
BAR-396-BK	Blocked Slide Cross Shaft	21.0
BAR-596	Locking Wedge Connector Bar	1.0
BAR-610-4	Locking Wedge Support Bar	0.5
BLT-301-1	Flat Head Socket, 1/2" -13 x 1", Grade 5	See Case Quan. Section
BLT-301-3	Flat Head Socket, 1/2" -13 x 1-1/2", Grade 5	
BLT-301-5	Flat Head Socket, 1/2" -13 x 2", Grade 5	
BLT-301-12	Flat Head Socket, 5/8" -11 x 1-3/4", Grade 5	
BLT-301-19	Flat Head Socket, 5/8"-11 x 3-1/2", Grade 5	
BLT-313	Shoulder Bolt, 5/8"x 1-1/4" w/ 1/2" - 13, Grade 5	
BLT-313-2	Shoulder Bolt, 1/2" x 1-3/8" w/ 3/8" -16, Grade 5	
BSH-108-U	Upper Bracket Bushing (pr.) (Was Part # BSH-LWS-U)	0.3
BSH-109-L	Lower Bracket Bushing (pr.) (Was Part # BSH-LWS-L)	0.4
BSH-115	Bushing, 7/16"	See Case Quan. Section
BSH-150	Bracket Bushing (pr.) (Also see Kits)	2.0
BSH-150-1	Bracket Bushing (pr.)	
BSH-629	Bushing, 5/16"	See Case Quan. Section
CC-PLATES	Clean Connect Lube Plates (pr)	18.0
CYL-5AA-5092	Air Cylinder	6.2
CYL-5AWS-2	Air Cylinder	7.5
CYL-610-3	Air Cylinder	7.5
CYL-COMP	Air Cylinder Composite	3.8
CYL-LWS	Air Cylinder Assembly	6.9
CYL-XAWX	Air Cylinder	6.2
EXT-5000	Handle Extension	2.0
LAT-153L	Safety Latch Assembly (Left Side)	2.0
LAT-153R	Safety Latch Assembly (Right Side)	2.0
LAT-5000-FL	Lock Latch Front Release (Left Side)	0.5
LAT-5000-FR	Lock Latch Front Release (Right Side)	0.5
LAT-5000B-SL	Safety Lock Latch 5000 Series (Left Side)	1.0
LAT-5000B-SR	Safety Lock Latch 5000 Series (Right Side)	1.0
LNR-BKT-107	Bracket Liner (pr.) (Was Part # LNR-LWS)	0.3
LNR-BKT-171	Heavy Duty Bracket Liner (pr.)	0.3
LEV-601	Latching Lever	0.5
LEV-663	Latching Lever	0.5
LEV-686	Latching Lever	0.5
LOC-287	Locking Wedge ATB OR MTB (pr.)	7.0
LOC-607	Locking Wedge (pr.)	6.0
LOC-664	Locking Wedge Release Bar	0.5
LOC-669	Locking Wedge (pr.)	7.0
LOC-683	Locking Wedge Release Bar	0.5
LOC-LWS	Locking Wedge (pr.)	9.9
MSC-370	Grease Fitting	See Case Quan. Section
MSC-375	Grease Fitting	
MSC-385	Rear Slide Stop	2.3
MSC-580	Handle Guide Front Release	1.0
MSC-673	Rear Slide Stop	3.3
MSC-710	Spring Installation Tool	4.0
MSC-712	Test King Pin	20.0
MSC-1515	Rear Slide Stop	2.1
NUT-303-1	Hex Lock Nut, 3/8" -16, Grade "B"	See Case Quan. Section
NUT-303-3	Hex Lock Nut, 5/8" -11, Grade "B"	
NUT-303-6	Hex Jam Nut, 1/2" - 13, Grade "B"	
NUT-303-9	Hex Lock Nut, 1/2" - 13, Grade "C"	

Look in Kits Section for Service Parts not available separately.

Service Parts (Cont.)

Part Number	Description	Weight (lbs)	
OPR-5000-FL	Operating Handle (Left Side)	5.6	
OPR-5000-FR	Operating Handle (Right Side)	5.6	
OPR-5000-SL	Operating Handle (Left Side) (Also see Kits)	5.3	
OPR-5000-SR	Operating Handle (Right Side) (Also see Kits)	5.3	
OPR-5007-SL	Operating Handle (Left Side)	5.6	
OPR-5092-AA	Operating Handle	5.5	
PIN-95	Cotter Pin, 1/4" x 3" (Also see Kits)	See Case Quan. Section	
PIN-124P	Bracket Retainer Pin (Pair) (Replaces PIN-124) (Also see Kits)		
PIN-135-1P	Bracket Pin (Pair) (Replaces PIN-135-1) (Also see Kits)		
PIN-191P	Universal Bracket Pin (Pair) (Replaces PIN-135, PIN-135P & PIN-6000P) (Also see Kits)		
PIN-289P	Retainer Pin For an XHD Wheel		
PIN-306-3	Cotter Pin 5/32" x 1" (Also see Kits)		
PIN-307-1	Clevis Pin, 3/4" x 3" (Also see Kits)		
PIN-307-2	Clevis Pin 3/8" x 2"		
PIN-307-4	Clevis Pin, 1/2" x 1" (Also see Kits)		
PIN-331	Lock Pin		
PUL-139L	Pull Handle (Left Side)	2.2	
PUL-139R	Pull Handle (Right Side)	2.2	
PUL-5000-SL-B	Pull Handle (Left Side) (Also see Kits)	2.9	
PUL-5000-SR-B	Pull Handle (Right Side) (Also see Kits)	2.9	
PUL-5007	Pull Handle	3.8	
PUL-5007B	Pull Handle	4.0	
PUL-5MWS	Pull Handle	1.8	
ROD-5092	Knock Out Rod	-	
SCR-425	Self Tapping Screw, 1/4" - 20 x 3/8"	-	
SPR-128	Bumper Spring (Also see Kits)	See Case Quan. Section	
SPR-233	Latching Lever Spring (Also see Kits)		
SPR-317	Wedge Stop Rod Spring		
SPR-338	Handle Spring (Also see Kits)		
SPR-569	Leaf Spring		
SPR-632	Locking Member Spring		
VLV-676-G	Two Way Valve Guard	-	
VLV-676-S	Two Way Valve Sticker	-	
VLV-676-V	Valve w/NUT	-	
VLV-INV	Inversion Valve (Air Actuated Fifth Wheel)	1.0	
VLV-PUL	Pull Valve (Air Actuated Fifth Wheel)	1.0	
WSH-304-1	Flat Washer, 3/8", Plain	See Case Quan. Section	
WSH-304-3	Flat Washer, 1/2" I.D. 1" O.D., Plain		
WSH-304-4	Flat Washer, 1/2" I.D. 1-3/8" O.D., Plain		
WSH-304-5	Flat Washer, 5/8", Plain		
WSH-304-7	Flat Washer, 5/8", Hardened		
WSH-304-8	Flat Washer 3/4", Plain		
WSH-304-9	Flat Washer 3/4", Plain		
WSH-304-16	Flat Washer, 5/8", Stainless Steel		
XXT-5000-FL	Extra Long Handle Extension (Left Side)		5.1
XXT-5000-FR	Extra Long Handle Extension (Right Side)		5.1

Look in Kits Section for Service Parts not available separately.

Service Parts Available Only In A Kit – See Kits Section

Part Number	Description
AA-204	Handle Adapter
CYL-AA-5092L	Air Cylinder
CYL-AA-6000L	Air Cylinder (Left Side)
CYL-AA-6000R	Air Cylinder (Right Side)
BLT-302-1	Hex Head Bolt, 3/8" -16 x 1", Grade 2
BLT-302-2	Hex Head Bolt, 3/8" -16 x 1", Grade 5
BLT-302-11	Hex Head Bolt, 1/2" -13 x 1, Grade 5
BLT-302-13	Hex Head Bolt, 1/2" -13 x 1-1/2", Grade 5
BLT-302-14	Hex Head Bolt, 1/2" -13 x 1-3/4", Grade 5
BLT-302-15	Hex Head Bolt, 1/2" - 13 x 2", Grade 5
BLT-302-16	Hex Head Bolt, 1/2" - 13 x 2-1/4", Grade 5
BLT-302-23	Hex Head Bolt, 5/8" - 11 x 2", Grade 8
BLT-302-64	Hex Head Bolt, 1/2" - 13 x 3/4", Grade 5
BLT-302-67	Hex Head Bolt, 1/2" - 13 x 2-1/4", Grade 5
BPR-131-L	Bumper (Left Side)
BPR-131-R	Bumper (Right Side)
BPR-5092-L	Bumper (Left Side)
BPR-5092-R	Bumper (Right Side)
BPR-6000-L	Bumper (Left Side)
BPR-6000-R	Bumper (Right Side)
BSH-1225	Bushing
LAT-6000-L	Secondary Lock (Left Side)
LAT-6000-R	Secondary Lock (Right Side)
OPR-6000	Operating Handle
PIN-165	Cotter Pin, 3/16" x 1"
PIN-336-1	Hair Pin Cotter
PUL-5092	Pull Handle
PUL-5092-AA	Pull Handle – Air Actuated
PUL-6000-L	Pull Handle (Left Side)
PUL-6000-R	Pull Handle (Right Side)
PUL-GRIP	Pull Handle Grip
ROD-1108	Wedge Stop Rod
SPR-137-138	Jaw & Wedge Spring Set
TMR-134-L	Timer (Left Side)
TMR-134-R	Timer (Right Side)
TMR-6000-L	Timer (Left Side)
TMR-6000-R	Timer (Right Side)
WED-200-L	Step Jaw and Wedge Set (Left Side)
WED-200-R	Step Jaw and Wedge Set (Right Side)
WED-6000-L	6000 Series Step Jaw & Wedge Set (Left Side)
WED-6000-R	6000 Series Step Jaw & Wedge Set (Right Side)

Look in Service Parts Section for parts not available in a kit.

Kits				
Part Number	Description	Contents	Qty.	Wt. (lbs)
KIT-AA-5092L	Air Actuated Conversion Kit (Left Side)	AA-204	1	15.0
		BLT-302-64	1	
		CYL-AA-5092L	1	
		PIN-306-3	2	
		PIN-307-4	2	
		PUL-5092-AA	1	
		WSH-304-3	1	
KIT-AA-5092R	Air Actuated Conversion Kit (Right Side)	AA-204	1	15.0
		BLT-302-64	1	
		CYL-AA-5092R	1	
		PIN-306-3	2	
		PIN-307-4	2	
		PUL-5092-AA	1	
		WSH-304-3	1	
KIT-AA-6000L	Air Actuated Conversion Kit (Left Side)	BLT-302-14	1	6.0
		BLT-313-2	1	
		CYL-AA-6000L	1	
		NUT-303-1	1	
		NUT-303-9	1	
		SPR-374	1	
		WSH-304-1	1	
KIT-AA-6000R	Air Actuated Conversion Kit (Right Side)	BLT-302-14	1	6.0
		BLT-313-2	1	
		CYL-AA-6000R	1	
		NUT-303-1	1	
		NUT-303-9	1	
		SPR-374	1	
		WSH-304-1	1	
KIT-AIR	Air Slide Installation Kit	Includes Installation Hardware and Valve	1	1.1
KIT-AIR-DASH	Air Actuated Dash Installation Kit	Includes Installation Hardware and Valves	1	5.0
KIT-ATB	Complete ATB Slide Bracket Rebuild Kit	BLT-301-2	1	11.0
		BLT-301-3	1	
		BLT-301-5	2	
		BLT-302-12	1	
		BSH-115	2	
		BSH-629	5	
		CYL-COMP	1	
		LEV-686	1	
		LOC-287	2	
		LOC-664	1	
		LOC-683	1	
		NUT-303-6	3	
		NUT-303-9	4	
		SPR-632	2	
WSH-304-4	8			

Kits (Cont.)				
Part Number	Description	Contents	Qty.	Wt. (lbs)
KIT-AWB	Complete AWB Slide Bracket Rebuild Kit	BLT-301-2	2	10.0
		BLT-301-5	2	
		BLT-301-12	1	
		BSH-629	5	
		CYL-COMP	1	
		LEV-686	1	
		LOC-664	1	
		LOC-669	1	
		LOC-683	1	
		NUT-303-6	3	
		NUT-303-9	2	
		SPR-632	2	
		WSH-304-4	7	
KIT-BPR-131L	5000,5007, AA5092,X5092 Series Bumper Kit (Left Side)	BLT-302-15	1	3.2
		BPR-131-L	1	
		BSH-115	1	
		BSH-629	1	
		NUT-303-9	2	
		SPR-128	1	
		WSH-304-4	1	
KIT-BPR-131R	5000, X5092 Series Bumper Kit (Right Side)	BLT-302-15	1	3.2
		BPR-131-R	1	
		BSH-115	1	
		BSH-629	1	
		NUT-303-9	2	
		SPR-128	1	
		WSH-304-4	1	
KIT-BPR-5092L	5092 Series Bumper Kit (Left Side)	BPR-5092-L	1	3.5
		BLT-302-15	1	
		BSH-115	1	
		BSH-629	1	
		SPR-128	1	
		NUT-303-9	2	
		WSH-304-4	1	
KIT-BPR-5092R	5092 Series Bumper Kit (Right Side)	BLT-302-15	1	3.5
		BPR-5092-R	1	
		BSH-115	1	
		BSH-629	1	
		NUT-303-9	2	
		SPR-128	1	
		WSH-304-4	1	
KIT-BPR-6000L	6000 Series Bumper Kit (Left Side)	BLT-302-14	1	3.7
		BPR-6000-L	1	
		BSH-629	1	
		NUT-303-9	1	
		SPR-374	1	
		WSH-304-4	2	
		KIT-BPR-6000R	6000 Series Bumper Kit (Right Side)	
BPR-6000-R	1			
BSH-629	1			
NUT-303-9	1			
SPR-374	1			
WSH-304-4	2			

Continued next page.

Kits (Cont.)

Part Number	Description	Contents	Qty.	Wt. (lbs)
KIT-LAT-6000L	6000 Series Secondary Lock Kit (Left Side)	BLT-302-13 BSH-115 LAT-6000-L NUT-303-9 PIN-165 SPR-338 WSH-304-4	1 1 1 1 1 1 2	2.4
KIT-LAT-6000R	6000 Series Secondary Lock Kit (Right Side)	BLT-302-13 BSH-115 LAT-6000-R NUT-303-9 PIN-165 SPR-338 WSH-304-4	1 1 1 1 1 1 2	2.4
KIT-OPR-6000	6000 Series Operating Handle Kit	BLT-302-67 BSH-115 BSH-1225 BSH-629 NUT-303-9 OPR-6000 PIN-336-1 WSH-304-4	1 1 1 1 3 1 1 2	7.7
KIT-PIN-LLB	Pin and Bushing Kit ATB, MTB, LWS, PMA	BSH-108-U BSH-109-L LNR-BKT-171 PIN-124P PIN-165 PIN-191P	2 2 2 2 2 2	6.0
KIT-PIN-191	Universal Pin and Bushing Kit	BSH-150 PIN-124P PIN-191P PIN-165	1 2 2 2	7.2
KIT-PIN-XHD	XHD Series Pin & Bushing Kit	BSH-150 PIN-289P PIN-135P PIN-165	1 1 1 2	7.2
KIT-PMA	Plate Mount Adjustable Bolt Kit	BLT-302-25 NUT-303-3 WSH-304-7	12 12 24	6.0
KIT-PUL-5092	5092, X5092 Series Pull Handle Kit (Left Side)	PUL-5092 PIN-165 WSH-304-4	1 1 1	3.0
KIT-PUL-6000L	6000 Series Pull Handle Kit (Left Side)	PIN-165 PUL-6000-L WSH-304-4	1 1 1	2.2
KIT-PUL-6000R	6000 Series Pull Handle Kit (Right Side)	PIN-165 PUL-6000-R WSH-304-4	1 1 1	2.2

Kits (Cont.)

Part Number	Description	Contents	Qty.	Wt. (lbs)
KIT-ROD-1108	Wedge Stop Rod Kit	NUT-319 PIN-165 ROD-1108 SPR-317 WSH-304-4	1 1 1 1 2	2.1
KIT-ROD-5092	Knock Out Rod Kit	PIN-165 ROD-5092 SPR-317 WSH-304-15	1 1 1 2	2.0
KIT-RPR-5092L	5092 Repair Kit (Left Side)	BSH-115 BSH-629 NUT-303-9 PIN-95 SPR-128 SPR-137-138 WED-200-L	1 1 2 2 1 1 1	9.5
KIT-RPR-5092R	5092 Repair Kit (Right Side)	BSH-115 BSH-629 NUT-303-9 PIN-95 SPR-128 SPR-137-138 WED-200-R	1 1 2 2 1 1 1	9.5
KIT-RPR-6000L	No Slack II Repair Kit (Left Side)	BSH-115 BSH-629 CD-SPR-236 NUT-303-9 SPR-374 SPR-338 WED-6000-L	1 1 1 3 1 1 1	9.0
KIT-RPR-6000R	No Slack II Repair Kit (Right Side)	BSH-115 BSH-629 CD-SPR-236 NUT-303-9 SPR-374 SPR-338 WED-6000-R	1 1 1 3 1 1 1	9.0
KIT-RPR-5092L	5092 Repair Kit (Left Side)	BSH-115 BSH-629 NUT-303-9 PIN-95 SPR-128 SPR-137-138 WED-200-L	1 1 2 2 1 1 1	9.5
KIT-RPR-5092R	5092 Repair Kit (Right Side)	BSH-115 BSH-629 NUT-303-9 PIN-95 SPR-128 SPR-137-138 WED-200-R	1 1 2 2 1 1 1	9.5

Kits (Cont.)

Part Number	Description	Contents	Qty.	Wt. (lbs)
KIT-RPR-6000L	No Slack II Repair Kit (Left Side)	BSH-115	1	9.0
		BSH-629	1	
		CD-SPR-236	1	
		NUT-303-9	3	
		SPR-374	1	
		SPR-338	1	
		WED-6000-L	1	
KIT-RPR-6000R	No Slack II Repair Kit (Right Side)	BSH-115	1	9.0
		BSH-629	1	
		CD-SPR-236	1	
		NUT-303-9	3	
		SPR-374	1	
		SPR-338	1	
		WED-6000-R	1	
KIT-SLD-1412	Bolt Kit 12" Slide	BLT-302-25	2	6.0
		BLT-302-27	12	
		NUT-303-3	14	
		WSH-304-7	28	
KIT-SLD-1824	Bolt Kit 24" Slide	BLT-302-25	2	8.0
		BLT-302-27	16	
		NUT-303-3	18	
		WSH-304-7	36	
KIT-SLD-2236	Bolt Kit 36" Slide	BLT-302-25	2	10.0
		BLT-302-27	20	
		NUT-303-3	22	
		WSH-304-7	44	
KIT-SLD-2648	Bolt Kit 48" Slide	BLT-302-25	2	12.0
		NUT-303-2	2	
		NUT-303-3	26	
		WSH-304-7	52	
KIT-SLS	Slide Stop Kit	BLT-302-13	2	16.7
		NUT-303-2	2	
		WSH-304-4	2	
		600-178-1	1	
		600-178-2	1	
KIT-TMR-134L	5000,5007,5092, AA5092,X5092 Series Timer Kit (Left Side)	BSH-115	1	4.0
		BSH-629	1	
		NUT-303-9	2	
		TMR-134L	1	
KIT-TMR-134R	H5092,X5092 Series Timer Kit (Right Side)	BSH-115	1	4.0
		BSH-629	1	
		NUT-303-9	2	
		TMR-134R	1	
KIT-TMR-6000L	6000 Series Timer Kit (Left Side)	CD-SPR-236	1	5.5
		NUT-303-9	1	
		PIN-336-1	1	
		TMR-6000-L	1	
KIT-TMR-6000R	6000 Series Timer Kit (Right Side)	CD-SPR-236	1	5.5
		NUT-303-9	1	
		PIN-336-1	1	
		TMR-6000-R	1	
KIT-VALVE	Valve Kit (Guard, Nuts and Decal)	VLV-676-V	1	1.0
		VLV-676-G	1	

Kits (Cont.)

Part Number	Description	Contents	Qty.	Wt. (lbs)
KIT-XLD-1812	Bolt Kit - XHD 12" Slide	BLT-302-36	2	8.0
		BLT-302-38	16	
		NUT-303-7	18	
		WSH-304-10	36	
KIT-XLD-2224	Bolt Kit - XHD 24" Slide	BLT-302-36	2	12.0
		BLT-302-38	20	
		NUT-303-7	22	
		WSH-304-10	44	
KIT-XLD-2636	Bolt Kit - XHD 36" Slide	BLT-302-36	2	14.0
		BLT-302-38	24	
		NUT-303-7	26	
		WSH-304-10	52	
KIT-XLD-3048	Bolt Kit - XHD 48" Slide	BLT-302-36	2	16.0
		BLT-302-38	28	
		NUT-303-7	30	
		WSH-304-10	60	

Custom Duty Fifth Wheels

Custom Duty Assemblies

Part Number	Description	Weight	
		Lbs	Kgs
SLCD7FM5750*	CD700 with bracket for stationary mounting	174	78.9
SLCD7PA6125*	CD700 with a 6.125" plate mount.	206	93.4
CD7AWB675024	CD700 with a 6.75 air slide bracket and 24" slide rail.	518	235.0

* Some welding required.

Custom Duty Kits

Part Number	Description	Weight	
		Lbs	Kgs
KIT-RPR-S500	Repair Kit	7	3.2
KIT-CD-ROD	Wedge Stop Rod Kit	1	0.5
KIT-CD-STOP	Stop Rod Guide Kit	1	0.5
KIT-CD-6HDL	Operating and Pull Handle Kit for SLTPLCD600	9	4.1
KIT-CD-7HDL	Operating and Pull Handle Kit for SLTPLCD700	9	4.1
KIT-CD-PIN-224	Bracket Pin and Bushing Kit	4	1.8
KIT-CD6-LOCK-PIN	Lock Pin and Chain Kit for SLTPLCD600	3	1.4
KIT-CD7-LOCK-PIN	Lock Pin and Chain Kit for SLTPLCD700	3	1.4

Custom Duty Service Parts

Part Number	Description	Weight	
		Lbs	Kgs
SLTPLCD700	CD700 Replacement Fifth Wheel Top Plate	135	61.2
BKTCPLT	Bracket and Plate for the SLCDPA6125	70	31.8
BKTCD	Bracket for the SLCD7FM5750	38	17.2
CDBKTAWB6PT	CD Air Slide Bracket 6.75" Height	264	119.7
CDASYAWB624	6.75" CD AWB bracket with a 24" CD slide rail	382	173.3
CDSLR24B	24" CD Slide Rail	118	53.5
CYL-COMP	AWB Air Cylinder	6.2	2.8
LOC-669	Locking Wedge (pair)	7	3.2

Custom Duty Service Parts (available in case quantities only)

Part Number	Description	Weight Each (lbs)	Quan. Per Case	Total Weight (lbs)
BLT-301-19	Flat Head Socket, 5/8"-11 x 3-1/4", Grade 5	0.25	10	2.5
BSH-115	Bushing, 7/16"	0.08	25	2.0
CD-SPR-236	Timer Spring	0.01	6	0.4
NUT-303-1	Hex Lock Nut, 3/8" - 16, Grade "B"	0.06	25	1.6
NUT-303-3	Hex Lock Nut, 5/8" - 11, Grade "B"	0.07	25	1.8
PIN-124P	Bracket Retainer Pin (Pair)	0.42	6 pairs	2.5
PIN-307-1	Clevis Pin, 3/4" x 3"	0.50	20	10.0
PIN-331	Lock Pin	0.06	20	1.3

The above parts are shipped direct from Fontaine® International in case quantities only. They may be available in individual quantities from your local distributor/dealer.

3000 Air Slide – Model 3ASB

Standard Duty On-Highway

Assemblies are supplied with top plate SLTPL3000.

Part Number	Mounted Height		Slide Travel		Weight		Includes 3000 top plate and:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
SL3ASB675012	6-3/4	171	12	305	426	193	BKTASB6PT	SLRTB12
SL3ASB675016			16	406	440	200		SLRTB16
SL3ASB675024			24	610	451	205		SLRTB24
SL3ASB675036			36	914	474	215		SLRTB36
SL3ASB775012	7-3/4	197	12	305	431	195	BKTASB7PT	SLRTB12
SL3ASB775016			16	406	445	202		SLRTB16
SL3ASB775024			24	610	456	207		SLRTB24
SL3ASB775036			36	914	479	217		SLRTB36
SL3ASB875012	8-3/4	222	12	305	436	198	BKTASB8PT	SLRTB12
SL3ASB875016			16	406	450	204		SLRTB16
SL3ASB875024			24	610	461	209		SLRTB24
SL3ASB875036			36	914	484	220		SLRTB36

3000 Adjustable Plate Mount – Model 3APB

Standard Duty On-Highway

Assemblies are supplied with top plate SLTPL3000.

Part Number	Mounted Height		Weight		Includes 3000 top plate and:
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SL3APB6250	6-1/4	159	241	109	ASYAPB6250
SL3APB7250	7-1/4	184	247	112	ASYAPB7250
SL3APB8250	8-1/4	210	253	115	ASYAPB8250

3000 Stationary Frame Mount – Model 3SMB

Standard Duty On-Highway

Assemblies are supplied with top plate SLTPL3000.

Part Number	Mounted Height		Weight		Includes 3000 top plate and:
	Inches	MM	Lbs	Kgs	Mtg. Bracket (pr)
SL3SMB5875	5-7/8	149	235	107	BKTSMB5875
SL3SMB6875	6-7/8	175	241	109	BKTSMB6875
SL3SMB7875	7-7/8	200	247	112	BKTSMB7875

NOTES for ASB, APB, SMB:

1. 3000 Series models are approved to 94/20/EC Directive: D-Value 150 ; U-Value 20.
2. Only recommended for over the road applications excluding tankers.
3. See pages 36 - 37 for mounting angles for ASB and APB.

Air Slide Bracket & Rails Subassembly – Model ASB

Part Number	Asmby. Height		Slide Travel		Weight		Includes:	
	Inches	MM	Inches	MM	Lbs	Kgs	Slide Bracket	Slide Rails
ASYASB612	6-3/4	171	12	305	192	87	BKTASB6PT	SLRTB12
ASYASB616			16	406	206	93		SLRTB16
ASYASB624			24	610	217	98		SLRTB24
ASYASB636			36	914	240	109		SLRTB36
ASYASB712	7-3/4	197	12	305	197	89	BKTASB7PT	SLRTB12
ASYASB716			24	610	211	96		SLRTB16
ASYASB724			36	914	222	101		SLRTB24
ASYASB736			48	1219	245	111		SLRTB36
ASYASB812	8-3/4	222	12	305	202	92	BKTASB8PT	SLRTB12
ASYASB816			24	610	216	98		SLRTB16
ASYASB824			36	914	227	103		SLRTB24
ASYASB836			48	1219	250	113		SLRTB36

Air Slide Bracket – Model ASB

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKTASB6PT	6-3/4	171	111	50
BKTASB7PT	7-3/4	197	116	53
BKTASB8PT	8-3/4	222	121	55

NOTES:

1. See page 37 for mounting angles for ASB.

Bracket Assembly – Model APB

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
ASYAPB6250	6-1/4	159	64	29
ASYAPB7250	7-1/4	184	70	32
ASYAPB8250	8-1/4	210	77	35

NOTES:

1. See page 37 for mounting angles for APB.

Mounting Brackets – Model SMB

Part Number	Mounted Height		Weight	
	Inches	MM	Lbs	Kgs
BKTSMB5875	8-7/8	149	20	9
BKTSMB6875	6-7/8	175	26	12
BKTSMB7875	7-7/8	200	32	15

3000 Service Parts

Part Number	Description	Contents	Qty.	Wt. (lbs)
PIN-124P	Bracket Retainer Pin	PIN-124P	See Case Quan. Section	
PIN-3000	Bracket Pin	PIN-3000	2	1.5
CLIP-3000	Security Clip	CLIP-3000	1	0.2
LNR-3000	Bracket Liners	LNR-3000	2	0.2
BSH-3000	Bracket Bushings	BSH-3000	2	1.0

3000 Kits

Part Number	Description	Contents	Qty.	Wt. (lbs)
KIT-OPR-3000L	3000 Series Operating Handle Kit	Hex Head Bolt	1	6.0
		Nylok Nut	1	
		Operating Handle	1	
KIT-PIN-3000	3000 Series Pin Kit	Bracket Retainer Pin	2	8.0
		Bracket Pin	2	
		Cotter Pin	2	
		Bracket Bushings	2	
KIT-PUL-3000	3000 Pull Handle Kit	Pull Handle	1	5.0
		Hex Head Bolt	1	
		Nylok Nut	1	
KIT-RING-3000	3000 Wear Ring Kit	Wear Ring	1	3.5
		Flat Washer	4	
		Hex Socket Button Head Screw	4	
KIT-ROD-3000	Adjustment Rod Kit	Adjustment Rod Nut	1	8.0
		Adjustment Rod	1	
KIT-RPR-3000L	3000 Repair Kit	Pivot Pin Clip	2	13.0
		Pivot Pin	2	
		Rotating Locking Jaw	1	
		Locking Wedge	1	
		Main Spring	1	
		Jaw Spring	1	

