



The Model SV803 is an UltraHEAT™ II variable temperature heat gun. This lightweight, easy to use heat gun was designed to provide both high performance with outstanding value. Its quick heat-up and ultra quiet operation provides increased performance and productivity while the soft grip handle allows for user comfort. The SV803 also features 2 airflow settings with heat and a selectable cool air stage for the ultimate in user control.

Featuring Steinel's patented UltraHEAT™ heating system, this heat gun has a reinforced heating element with lateral supports to prolong coil life as well as a ceramic disk at the output tip to enhance stability and even heating. Injection molded plastic forms around the wiring which will not break or disconnect like traditional wiring. The fully enclosed slide switch and secured power cord also contribute to the durability and long life of the SV803 heat gun.



**Model SV803**

**Model HL1910E Specifications:**

Housing Material	PBT (Polybutylene Terephthalate)	Switch	Fully Enclosed Slide Switch
Self Extinguishing Material	Yes	Switch Functional Positions	High, Low, Cold, and Off
Current Type	AC	Power Cord	Industrial Grade Rubber
Voltage	120 Volts	Overall Length	9-1/2"
Frequency	60 Hz	Overall Width	3-1/4"
Phase	Single	Overall Height	8"
Double Insulated	Yes	Weight	1.25 pounds
Wattage Rating	1400 watts	Fungus Resistant	Yes
Heating Element	Heavy duty mica reinforced (included)	Suspension Feature	Built in stand
Temp Rating	140° F (min) and 1050° F (max)	Special Features	ROHS/WEEE/PENTADBE/OCTADBE Compliant
Temperature Control	Thermistat	Ability to use Reduction Nozzles	Yes
Air Flow	High and low setting independent of temperature	Certifications	UL, CUL (complies with UL standard 499)
Air Pressure	800 PA	Origin	European Union

**Distributed by:** ALL-SPEC INDUSTRIES  
 WILMINGTON, NC 28401  
[www.all-spec.com](http://www.all-spec.com)

**Phone:** 800-537-0351  
**Fax:** 800-379-9903  
**Email:** [sales@all-spec.com](mailto:sales@all-spec.com)