

## 3.3 ft. (1 m) USB-C to DisplayPort 1.2 Cable - Bi-Directional

Product ID: CDP2DP1MBD



This USB-C™ to DisplayPort™ 1.2 cable lets you connect your USB Type-C™ (or Thunderbolt 3™) device to a DisplayPort display, or a DP device to a USB-C display with just one cable.

### Easy & Clutter-Free Installation

At 3.3 ft. (1 m) in length, this bidirectional adapter cable delivers a compact connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For longer installations, we also offer a 6.6 ft. (2 m) USB-C to DP cable, enabling you to choose the right cable length for your custom installation needs.

As well, the cable works with both Mac and Windows devices and allows for plug-and-play installation, removing the need for any additional software or drivers.

## **Convenient, Bi-Directional Support**

Use this USB-C to DisplayPort adapter cable to output 4K video and audio to a DP display from the USB Type-C (or Thunderbolt 3) port on your laptop or mobile device. With bi-directional capabilities, this cable can also connect your DisplayPort-enabled devices to a display featuring USB-C input.

## **Ultra HD 4K Resolution at 60Hz**

This USB-C to DP 1.2 adapter cable lets you harness the video capabilities that are built into your computer's USB Type-C (or DisplayPort) connection, to deliver the astonishing quality of UHD to your 4K display. For even higher resolution and bandwidth support, we offer a USB-C to DP 1.4 cable, which is the perfect accessory for early adopters of 8K.

CDP2DP1MBD is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Note: Your USB 3.1 Type-C device must support DP Alt Mode to work with this cable.

### Certifications, Reports and Compatibility



### Applications

- Ideal for home, office or hot-desk applications
- Perfect accessory for creative professionals
- Deliver enriched presentations on the go
- Stream, view and edit 4K video

### Features

- Versatile, bi-directional support lets you connect either your USB Type-C (or DisplayPort) device to a DisplayPort (or USB-C) display
- Compatible with Thunderbolt 3 and USB 3.1 Type-C ports that support DP Alt Mode
- Reduce clutter with an adapter and display cable, in-one
- Enjoy astonishing picture quality with support for 4K 60Hz
- Latching DisplayPort connector ensures a secure connection

|                                     |                               |   |
|-------------------------------------|-------------------------------|---|
| <b>Hardware</b>                     | Warranty                      | 3 Years   |
|                                     | Active or Passive Adapter     | Active  |
|                                     | Audio                         | Yes   |
|                                     | AV Input                      | USB-C<br>DisplayPort - 1.2  |
|                                     | AV Output                     | DisplayPort<br>USB-C  |
|                                     | Chipset ID                    | Chrontel - CH7213C-BF<br>VIA Labs - VL170   |
|                                     | <b>Performance</b>            | Audio Specifications  |
| Supported Resolutions               |                               | DisplayPort: 3840x2160 (4K) / 60Hz<br>USB-C: 3840x2160 (4K) / 60Hz  |
| Video Revision                      |                               | DisplayPort 1.2   |
| Wide Screen Supported               |                               | Yes   |
| <b>Connector(s)</b>                 | Connector A                   | 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input<br>1 - Thunderbolt™ 3 USB-C (24-pin) (20Gbps) Male Input |
|                                     | Connector B                   | 1 - DisplayPort (20 pin) Male Output  |
| <b>Special Notes / Requirements</b> | <b>Note</b>                   | Maximum performance is dependent upon the specifications of your video source and destination               |
|                                     | System and Cable Requirements | Your USB-C device must support DisplayPort Alt Mode to work with this cable                                 |
| <b>Environmental</b>                | Humidity                      | 10%-85% RH  |
|                                     | Operating Temperature         | 0°C to 45°C (32°F to 113°F)   |
|                                     | Storage Temperature           | -10°C to 70°C (14°F to 158°F)   |
| <b>Physical Characteristics</b>     | Color                         | Black   |
|                                     | Material                      | Plastic   |
|                                     | Product Height                | 10.000  |
|                                     | Product Length                | 39.4 in [100 cm]  |
|                                     | Product Width                 | 20.000  |
|                                     | Weight of Product             | 44.000  |
| <b>Packaging Information</b>        | Package Height                | 25.000  |

|                          |                           |   |
|--------------------------|---------------------------|---|
|                          | Package Length            | 225.000   |
|                          | Package Width             | 152.000   |
|                          | Shipping (Package) Weight | 430.000   |
| <b>What's in the Box</b> | Included in Package       | 1 - 1 m USB-C to DisplayPort 1.2 Bi-Directional Adapter Cable |

Product appearance and specifications are subject to change without notice.