


Front view



Rear view



Resettable fuse



MCB

Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color : Black



NEMA 5-30P




NEMA L5-30P



NEMA 5-20P



NEMA L5-20P



NEMA 5-15P

<b>30A model :</b>	<b>Circuit Protection</b>
H8US-30A-W/F_530/3B-1	Resettable Fuse x 2
H8US-30A-W/CR_530/3B-1	1-pole MCB x 2
<b>30A model :</b>	<b>Circuit Protection</b>
H8US-30A-W/F_L530/3B-1	Resettable Fuse x 2
H8US-30A-W/CR_L530/3B-1	1-pole MCB x 2
<b>20A model :</b>	<b>Circuit Protection</b>
H8US-20A-W/F_520/3B-1	Resettable Fuse x 1
H8US-20A-W/CR_520/3B-1	1-pole MCB x 1
<b>20A model :</b>	<b>Circuit Protection</b>
H8US-20A-W/F_L520/3B-1	Resettable Fuse x 1
H8US-20A-W/CR_L520/3B-1	1-pole MCB x 1
<b>15A model :</b>	<b>Circuit Protection</b>
H8US-15A-W/F_515/3B-1	Resettable Fuse x 1
H8US-15A-W/CR_515/3B-1	1-pole MCB x 1

Input Rating : 30Amp ( 24A derated ), 110V  
Cordset : 10 feet UL SJT 10 AWG cordset  
Protection : 16A resettable fuse or 16A hydraulic MCB x 2  
Circuit A : Output 12A derated, US #1-4  
Circuit B : Output 12A derated, US #5-8  
Weight : Net 8.28 lb / Gross 9.38 lb

Input Rating : 30Amp ( 24A derated ), 110V  
Cordset : 10 feet UL SJT 10 AWG cordset  
Protection : 16A resettable fuse or 16A hydraulic MCB x 2  
Circuit A : Output 12A derated, US #1-4  
Circuit B : Output 12A derated, US #5-8  
Weight : Net 8.43 lb / Gross 9.53 lb

Input Rating : 20Amp ( 16A derated ), 110V  
Cordset : 10 feet UL SJT 12 AWG cordset  
Protection : 20A resettable fuse or 20A hydraulic MCB x 1  
Circuit : Output 16A derated, US #1-8  
Weight : Net 7.09 lb / Gross 8.19 lb

Input Rating : 20Amp ( 16A derated ), 110V  
Cordset : 10 feet UL SJT 12 AWG cordset  
Protection : 20A resettable fuse or 20A hydraulic MCB x 1  
Circuit : Output 16A derated, US #1-8  
Weight : Net 7.20 lb / Gross 8.30 lb

Input Rating : 15Amp ( 12A derated ), 110V  
Cordset : 10 feet UL SJT 14 AWG cordset  
Protection : 16A resettable fuse or 16A hydraulic MCB x 1  
Circuit : Output 12A derated, US #1-8  
Weight : Net 6.65 lb / Gross 7.75 lb

Remarks : To comply with UL® / National Electrical Code (NEC), the branch circuit Amp has been de-rated to 80% of the original.

Operating Temperature : -5 to 60 °C  
Storage Temperature : -25 to 65 °C  
Operating Altitude : 0 to 2,000 m  
Storage Altitude : 0 to 15,000 m  
Humidity : 8 to 95% RH, non-condensing

### Meter Features ( W monitored PDU )

Local Display : Field replaceable 2.0" color LCD with touchscreen  
Bank Measurement : Voltage ( V ), Current ( A ), energy ( kWh ) & power factor  
Accuracy : ±1% Billing-grade  
IP Access : via IP dongle, one IP Access up to 32 PDU Levels  
Cascade : Up to 32 PDU under single IP address via IP dongle  
SNMP : V2 / V3 via IP dongle  
Sensor Port x 2 : Temp. Sensor / Temp. + Humid. Sensor

### IP dongle ( option )

- Dual LAN Network Failover  
- 10/100 Ethernet & Gigabit Ethernet standard  
- Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol

EMC Compliance : FCC Part 15 Subpart B (Class A)  
Safety Compliance : Tested to UL 60730-1:2016 and CAN / CSA-E60730-1:2015  
Tested to UL 62368-1:2014 and CAN / CSA-C22.2 No. 62368-1:2014  
Environment Compliance : RoHS3 & REACH

Product Dimension : 17.4 (W) x 7.1 (D) x 1.8 (H) inch  
Packing Dimension : 20.7 (W) x 11.4 (D) x 3.1 (H) inch