


Cable Tie Mounts

Cable Markers Company offers a wide variety of mounting bases suited for many applications. Mounting bases are used in conjunction with cable ties to stabilize and secure wiring bundles, both indoors and outdoors. These mounting bases can be secured to a surface using rubber based adhesive, acrylic adhesive, or also can be screw mounted.

Cable Tie Mounting Bases


Our 4-way mounting bases are available in four sizes to accommodate T18 through T150 series cable ties. Insertion of ties can be made from all four sides. Each mount may be secured with two screws (four screws for the MB2.5 mount), with adhesive backing, or both, for ease of application and stability.

For applications where higher temperatures, certain chemicals, or UV radiation are a concern and an adhesive is the preferred method for securing, the acrylic adhesive 4-way mounting bases are recommended. The 2-way mounting bases may be secured with one screw, with adhesive backing, or both, and allow ties to be inserted from two sides.




Adhesive mounts are supplied in pairs connected together on an adhesive liner.


Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2 (excluding adhesive)



2-way mount



4-way, MB2.5 mount



4-way, MB3, MB4 and MB5 mounts


Cable Tie Mounting Bases - Screw Mount

CM US
File# E64139

Product Selection					Length (L)	Width (W)	Height (H)	Color	Pkg. Qty.
Article No.	Part No.	Type	Cable Tie Series	Mounting	in. (mm)	in. (mm)	in. (mm)		
2- Way Screw Mount									
151-29104	MB4SH10C2	MB4SH	T18 - T50	# 6 Screw	1.115 " (28.32)	1.115 " (28.32)	.202 " (5.13)	White	100
151-00323	MB4SH10H4	MB4SH			1.115 " (28.32)	1.115 " (28.32)	.202 " (5.13)	White	500
151-29100	MB4SH0C2	MB4SH			1.115 " (28.32)	1.115 " (28.32)	.202 " (5.13)	Black	100
151-29101	MB4SH0H4	MB4SH			1.115 " (28.32)	1.115 " (28.32)	.202 " (5.13)	Black	500
4- Way Screw Mount									
151-28901	MB2.510C2	MB2.5	T18	# 3 Screw	.625 " (15.88)	.625 " (15.88)	.130 " (3.3)	White	100
151-28902	MB2.510M4	MB2.5			.625 " (15.88)	.625 " (15.88)	.130 " (3.3)	White	1000
151-00285	MB2.50C2	MB2.5			.625 " (15.88)	.625 " (15.88)	.130 " (3.3)	Black	100
151-00286	MB2.50M4	MB2.5			.625 " (15.88)	.625 " (15.88)	.130 " (3.3)	Black	1000
151-28302	MB310C2	MB3	T18, T30	#4 Screw	.75 " (19.0)	.75 " (19.0)	.15 " (3.8)	White	100
151-28305	MB310M4	MB3			.75 " (19.0)	.75 " (19.0)	.15 " (3.8)	White	1000
151-00136	MB30C2	MB3			.75 " (19.0)	.75 " (19.0)	.15 " (3.8)	Black	100
151-28301	MB30M4	MB3			.75 " (19.0)	.75 " (19.0)	.15 " (3.8)	Black	1000
151-28802	MB410C2	MB4	T18 - T50	#8 Screw	1.12 " (28.5)	1.12 " (28.5)	.19 " (4.8)	White	100
151-00319	MB410H4	MB4			1.12 " (28.5)	1.12 " (28.5)	.19 " (4.8)	White	500
151-00320	MB40C2	MB4			1.12 " (28.5)	1.12 " (28.5)	.19 " (4.8)	Black	100
151-28801	MB40H4	MB4			1.12 " (28.5)	1.12 " (28.5)	.19 " (4.8)	Black	500
151-00324	MB510C2	MB5	T18 - T150	#8 Screw	1.485 " (37.7)	1.485 " (37.7)	.245 " (6.2)	White	100
151-28504	MB510F4	MB5			1.485 " (37.7)	1.485 " (37.7)	.245 " (6.2)	White	250
151-28500	MB50C2	MB5			1.485 " (37.7)	1.485 " (37.7)	.245 " (6.2)	Black	100
151-28501	MB50F4	MB5			1.485 " (37.7)	1.485 " (37.7)	.245 " (6.2)	Black	250

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Cable Tie Mounting Bases continued



Cable Tie Mounting Bases - Rubber-Based Adhesive



Product Selection									
Article No.	Part No.	Type	Cable Tie Series	Mounting	Length (L)	Width (W)	Height (H)	Color	Pkg. Qty.
					in. (mm)	in. (mm)	in. (mm)		
2- Way Mount with Rubber - Based Adhesive									
151-29203	MB4SHA10C2	MB4SHA	T18 - T50	Adhesive	1.115 " (28.32)	1.115 " (28.32)	.232 " (5.89)	White	100
151-29206	MB4SHA10H4	MB4SHA			1.115 " (28.32)	1.115 " (28.32)	.232 " (5.89)	White	500
151-29200	MB4SHA0C2	MB4SHA			1.115 " (28.32)	1.115 " (28.32)	.232 " (5.89)	Black	100
4- Way Mount with Rubber - Based Adhesive									
151-29002	MB2.5A10C2	MB2.5A	T18	Adhesive	.625 " (15.88)	.625 " (15.88)	.160 " (4.1)	White	100
151-00298	MB2.5A10M4	MB2.5A			.625 " (15.88)	.625 " (15.88)	.160 " (4.1)	White	1000
151-29000	MB2.5A0C2	MB2.5A			.625 " (15.88)	.625 " (15.88)	.160 " (4.1)	Black	100
151-29001	MB2.5A0M4	MB2.5A			.625 " (15.88)	.625 " (15.88)	.160 " (4.1)	Black	1000
151-28718	MB3A10C2	MB3A	T18, T30	Adhesive	.75 " (19.0)	.75 " (19.0)	.18 " (4.6)	White	100
151-28721	MB3A10M4	MB3A			.75 " (19.0)	.75 " (19.0)	.18 " (4.6)	White	1000
151-28710	MB3A0C2	MB3A			.75 " (19.0)	.75 " (19.0)	.18 " (4.6)	Black	100
151-28713	MB3A0M4	MB3A			.75 " (19.0)	.75 " (19.0)	.18 " (4.6)	Black	1000
151-28421	MB4A10C2	MB4A	T18 - T50	Adhesive	1.12 " (28.0)	1.12 " (28.0)	.22 " (5.6)	White	100
151-00321	MB4A10H4	MB4A			1.12 " (28.0)	1.12 " (28.0)	.22 " (5.6)	White	500
151-28403	MB4A0C2	MB4A			1.12 " (28.0)	1.12 " (28.0)	.22 " (5.6)	Black	100
151-28406	MB4A0H4	MB4A			1.12 " (28.0)	1.12 " (28.0)	.22 " (5.6)	Black	500
151-28529	MB5A10C2	MB5A	T18 - T150	Adhesive	1.485 " (37.7)	1.485 " (37.7)	.275 " (6.9)	White	100
151-00427	MB5A10F4	MB5A			1.485 " (37.7)	1.485 " (37.7)	.275 " (6.9)	White	250
151-28602	MB5A0C2	MB5A			1.485 " (37.7)	1.485 " (37.7)	.275 " (6.9)	Black	100
151-28605	MB5A0F4	MB5A			1.485 " (37.7)	1.485 " (37.7)	.275 " (6.9)	Black	250

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Cable Tie Mounting Bases - Acrylic Adhesive

Product Selection									
Article No.	Part No.	Type	Cable Tie Series	Mounting	Length (L)	Width (W)	Height (H)	Color	Pkg. Qty.
					in. (mm)	in. (mm)	in. (mm)		
4 - Way Screw Mount Acrylic Adhesive									
151-00331	MB3A10A2C2	MB3A	T18, T30	Adhesive	.75 " (19.0)	.75 " (19.0)	.18 " (4.6)	White	100
151-28717	MB3A10A2H4	MB3A			.75 " (19.0)	.75 " (19.0)	.18 " (4.6)	White	500
151-28711	MB3A0A2C2	MB3A			.75 " (19.0)	.75 " (19.0)	.18 " (4.6)	Black	100
151-28709	MB3A0A2H4	MB3A			.75 " (19.0)	.75 " (19.0)	.18 " (4.6)	Black	500
151-28420	MB4A10A2C2	MB4A	T18 - T50	Adhesive	1.12 " (28.5)	1.12 " (28.5)	.23 " (5.9)	White	100
151-00322	MB4A10A2H4	MB4A			1.12 " (28.5)	1.12 " (28.5)	.23 " (5.9)	White	500
151-28402	MB4A0A2C2	MB4A			1.12 " (28.5)	1.12 " (28.5)	.23 " (5.9)	Black	100
151-28405	MB4A0A2H4	MB4A			1.12 " (28.5)	1.12 " (28.5)	.23 " (5.9)	Black	500
151-28607	MB5A10A2C2	MB5A	T18 - T150	Adhesive	1.485 " (37.7)	1.485 " (37.7)	.275 " (6.9)	White	100
151-28610	MB5A10A2F4	MB5A			1.485 " (37.7)	1.485 " (37.7)	.275 " (6.9)	White	250
151-28600	MB5A0A2C2	MB5A			1.485 " (37.7)	1.485 " (37.7)	.275 " (6.9)	Black	100
151-28604	MB5A10A2F4	MB5A			1.485 " (37.7)	1.485 " (37.7)	.275 " (6.9)	Black	250



Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Cable Tie Mounts

The CTM series is designed to provide stability to wire bundles. These mounts can accommodate miniature, intermediate, or standard cross-section cable ties. Each mount is secured with a single screw.



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2



UL
File# E64139

Product Selection

Article No.	Part No.	Type	Cable Tie Series	Mounting	Length (L)	Width (W)	Height (H)	Color	Pkg. Qty.	
					in. (mm)	in. (mm)	in. (mm)			
151-30303	CTM010C2	CTM0	T18 - T50	# 6 Screw	.578" (14.68)	.375" (9.52)	.266" (6.76)	White	100	
151-30305	CTM010M4				.578" (14.68)	.375" (9.52)	.266" (6.76)	White	1000	
151-30300	CTM00C2				.578" (14.68)	.375" (9.52)	.266" (6.76)	Black	100	
151-30301	CTM00M4				.578" (14.68)	.375" (9.52)	.266" (6.76)	Black	1000	
151-30404	CTM110C2	CTM1		T18 - T120	# 8 Screw	.579" (14.71)	.370" (9.40)	.266" (6.76)	White	100
151-30406	CTM110M4					.579" (14.71)	.370" (9.40)	.266" (6.76)	White	1000
151-30400	CTM10C2					.579" (14.71)	.370" (9.40)	.266" (6.76)	Black	100
151-30402	CTM10M4					.579" (14.71)	.370" (9.40)	.266" (6.76)	Black	1000
151-30504	CTM210C2	CTM2	T18 - T120		# 8 Screw	.857" (21.77)	.605" (15.37)	.372" (9.45)	White	100
151-30506	CTM210M4					.857" (21.77)	.605" (15.37)	.372" (9.45)	White	1000
151-30500	CTM20C2					.857" (21.77)	.605" (15.37)	.372" (9.45)	Black	100
151-30501	CTM20M4					.857" (21.77)	.605" (15.37)	.372" (9.45)	Black	1000
151-30605	CTM310C2	CTM3		T18 - T120	#10 Screw	.858" (21.79)	.609" (15.47)	.374" (9.50)	White	100
151-30607	CTM310M4					.858" (21.79)	.609" (15.47)	.374" (9.50)	White	1000
151-30600	CTM30C2					.858" (21.79)	.609" (15.47)	.374" (9.50)	Black	100
151-30603	CTM30M4					.858" (21.79)	.609" (15.47)	.374" (9.50)	Black	1000
151-30703	CTM410C2	CTM4	T18 - T120		.25" Screw	.864" (21.95)	.616" (15.65)	.372" (9.45)	White	100
151-30705	CTM410M4					.864" (21.95)	.616" (15.65)	.372" (9.45)	White	1000
151-30700	CTM40C2					.864" (21.95)	.616" (15.65)	.372" (9.45)	Black	100
151-30702	CTM40M4					.864" (21.95)	.616" (15.65)	.372" (9.45)	Black	1000



Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Low Profile Cable Tie Mounts

Low profile mounts are intended for use in securing bundles where space is limited. Each mount is fastened with a single screw.



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2



UL US
File# E64139

Product Selection					Length (L)	Width (W)	Height (H)	Color	Pkg. Qty.
Article No.	Part No.	Type	Cable Tie Series	Mounting	in. (mm)	in. (mm)	in. (mm)		
151-00226	MB19C2	MB1	T18	#2 Screw	.500" (12.70)	.312" (7.92)	.130" (3.30)	Natural	100
151-00294	MB19M4				.500" (12.70)	.312" (7.92)	.130" (3.30)	Natural	1000
151-00295	MB10C2				.500" (12.70)	.312" (7.92)	.130" (3.30)	Black	100
151-00296	MB10M4				.500" (12.70)	.312" (7.92)	.130" (3.30)	Black	1000
151-00227	MB29C2	MB2	T18 - T50	# 8 Screw	.807" (20.50)	.490" (12.45)	.130" (3.30)	Natural	100
151-00297	MB29M4				.807" (20.50)	.490" (12.45)	.130" (3.30)	Natural	1000
151-28210	MB20C2				.807" (20.50)	.490" (12.45)	.130" (3.30)	Black	100
151-28202	MB20M4				.807" (20.50)	.490" (12.45)	.130" (3.30)	Black	1000



Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Low Profile Rivet Mounts

The low profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole. This mount is ideal for use in applications where space is limited.



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2




Product Selection				Mounting Hole Ø	Max. Panel Thickness	Length (L)	Width (W)	Height (H)	Color	Pkg. Qty.
Article No.	Part No.	Type	Cable Tie Series	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)		
151-27000	LKCRF19C2	LKCRF1	T18 -	.250" (6.35)	.134" (3.4)	.938" (23.82)	.470" (11.94)	.157" (3.99)	Natural	100
151-27009	LKCRF19H4	LKCRF1	T50	.250" (6.35)	.134" (3.4)	.938" (23.82)	.470" (11.91)	.157" (3.99)	Natural	500

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Push Mounts

Intended for use in a predrilled hole, this push mount accepts T18 through T50 series cable ties. Once inserted through the hole, the mount locks into place.



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2



US
File# E64139


Product Selection

Article No.	Part No.	Type	Cable Tie Series	Mounting Hole Ø	Max. Panel Thickness	Length (L)	Width (W)	Height (H)	Color	Pkg. Qty.
				in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)		
151-40106	TM1SF10C2	TM1SF	T18 - T50	.25" (6.3)	.134" (3.4)	.616" (15.65)	.401" (10.19)	.181" (4.60)	White	100
151-00328	TM1SF10M4	TM1SF		.25" (6.3)	.134" (3.4)	.616" (15.65)	.401" (10.19)	.181" (4.60)	White	1000
151-40100	TM1SF0C2	TM1SF		.25" (6.3)	.134" (3.4)	.616" (15.65)	.401" (10.19)	.181" (4.60)	Black	100
151-40101	TM1SF0M4	TM1SF		.25" (6.3)	.134" (3.4)	.616" (15.65)	.401" (10.19)	.181" (4.60)	Black	1000

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Push Button Mounts

The push button mounts are used where the back of the panel is accessible.



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2



US
File# E64139


Product Selection

Article No.	Part No.	Type	Cable Tie Series	Mounting Hole Ø	Max. Panel Thickness	Width (W)	Height (H)	Height (H2)	Color	Pkg. Qty.
				in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)		
151-00230	PBM10C2	PBM	T18 - T50	.25" (6.4)	.122" (3.1)	.26" (6.60)	.40" (10.16)	.08" (2.03)	White	100
151-00231	PBM10M4	PBM		.25" (6.4)	.122" (3.1)	.26" (6.60)	.40" (10.16)	.08" (2.03)	White	1000
151-00228	PBM0C2	PBM		.25" (6.4)	.122" (3.1)	.26" (6.60)	.40" (10.16)	.08" (2.03)	Black	100
151-00229	PBM0M4	PBM		.25" (6.4)	.122" (3.1)	.26" (6.60)	.40" (10.16)	.08" (2.03)	Black	1000

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Cable Tie Anchor Mounts

Cable ties may be inserted from any of the four sides of the CTAM. This feature allows the mount to be placed either parallel or perpendicular to the wires.



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2





Product Selection					Width (W)	Length (L)	Height (H)	Color	Pkg. Qty.
Article No.	Part No.	Type	Cable Tie Series	Mounting	in. (mm)	in. (mm)	in. (mm)		
151-31103	CTAM110C2	CTAM1	T18 - T50	#8 screw	.400" (10.16)	.800" (20.32)	.200" (5.08)	White	100
151-31106	CTAM110M4	CTAM1			.400" (10.16)	.800" (20.32)	.200" (5.08)	White	1000
151-31101	CTAM10C2	CTAM1			.400" (10.16)	.800" (20.32)	.200" (5.08)	Black	100
151-00287	CTAM10M4	CTAM1			.400" (10.16)	.800" (20.32)	.200" (5.08)	Black	1000
151-31203	CTAM210C2	CTAM2		#10 screw	.400" (10.16)	.800" (20.32)	.200" (5.08)	White	100
151-31205	CTAM210M4	CTAM2			.400" (10.16)	.800" (20.32)	.200" (5.08)	White	1000
151-31201	CTAM20C2	CTAM2			.400" (10.16)	.800" (20.32)	.200" (5.08)	Black	100
151-31202	CTAM20M4	CTAM2			.400" (10.16)	.800" (20.32)	.200" (5.08)	Black	1000

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Cable Tie Anchor Plates

These plates have slotted mounting holes to provide for easier alignment of mount and bundles. Once aligned, they are fastened securely by tightening the applied screw. The CTAP2 allows an additional screw for maximum stability. Both plates are used perpendicularly to the wire bundle.



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2




Product Selection					Width (W)	Length (L)	Height (H)	Color	Pkg. Qty.
Article No.	Part No.	Type	Cable Tie Series	Mounting	in. (mm)	in. (mm)	in. (mm)		
151-30100	CTAP110C2	CTAP1	T18 - T50	#10 screw	.50" (12.7)	1.34" (34.04)	.15" (3.81)	White	100
151-00288	CTAP110M4	CTAP1			.50" (12.7)	1.34" (34.04)	.15" (3.81)	White	1000
151-00289	CTAP10C2	CTAP1			.50" (12.7)	1.34" (34.04)	.15" (3.81)	Black	100
151-00290	CTAP10M4	CTAP1			.50" (12.7)	1.34" (34.04)	.15" (3.81)	Black	1000
151-30200	CTAP210C2	CTAP2			.50" (12.7)	2.13" (54.1)	.14" (3.5)	White	100
151-00308	CTAP210H4	CTAP2			.50" (12.7)	2.13" (54.1)	.14" (3.5)	White	500
151-00291	CTAP20C2	CTAP2			.50" (12.7)	2.13" (54.1)	.14" (3.5)	Black	100
151-00292	CTAP20M4	CTAP2			.50" (12.7)	2.13" (54.1)	.14" (3.5)	Black	500

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Lashing Tie Mounts

The lashing tie mount is designed to snap into the T250 lashing tie. The tie head is assembled perpendicular to the mount. The strap is parallel to the mount when inserted into the head. The lashing tie mount is recommended for indoor or outdoor wall mount cable applications.



Material Data	
Material	Polyamide 6.6 UV-resistant (PA66UV)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2




Product Selection					Width (W)	Length (L)	Height (H)	Color	Pkg. Qty.
Article No.	Part No.	Type	Cable Tie Series	Mounting	in. (mm)	in. (mm)	in. (mm)		
151-00358	LTM2500C2	LTM250	T250	.25" screw	.733" (18.62)	1.46" (37.08)	.378" (9.60)	Black	100
151-00293	LTM2500H4	LTM250			.733" (18.62)	1.46" (37.08)	.378" (9.60)	Black	500

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Masonry Mounts

Masonry mounts provide a permanent method of attaching wire and cable to masonry surfaces. HellermannTyton's masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications.



Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Flammability	UL94 V2






Product Selection													
Article No.	Part No.	Type	Cable Tie Series	Mounting Hole Ø	Min. Depth	Length (L)		Width (W)		Width (W2)		Color	Pkg. Qty.
				in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)		
151-29800	MMB00C2	MMB0	T18-T50	.188" (4.7)	1.0" (25.4)	1.185" (30.1)	.355" (9.02)	.218" (5.54)	.236" (5.99)	Black	100		
151-00325	MMB00M4	MMB0		.188" (4.7)		1.185" (30.1)	.355" (9.02)	.218" (5.54)	.236" (5.99)	Black	1000		
151-00116	MMB.50C2	MMB.5		.25" (6.25)		1.244" (31.60)	.375" (9.53)	.220" (5.59)	.308" (7.82)	Black	100		
151-30001	MMB.50M4	MMB.5		.25" (6.25)		1.244" (31.60)	.375" (9.53)	.220" (5.59)	.308" (7.82)	Black	1000		
151-00326	MMB10C2	MMB1		.312" (8.0)	1.5" (38.10)	1.71" (43.49)	.508" (12.9)	.374" (9.50)	.362" (9.19)	Black	100		
151-00327	MMB10H4	MMB1		.312" (8.0)		1.71" (43.49)	.508" (12.9)	.374" (9.50)	.362" (9.19)	Black	500		

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Cable Tie Mounting Plates

Allowing multiple cables to be run in parallel, these mounting plates are secured with two screws. The cables are attached to the mounting plate by using a cable tie through any combination of the available slots.

Material Data	
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C) continuous
Color	Natural
Flammability	UL94 V2



Product Selection			Cable Tie Series	Mounting	Width (W)	Length (L)	Height (H)	Pkg. Qty.
Article No.	Part No.	Type			in. (mm)	in. (mm)	in. (mm)	
154-00000	MP1M3.NN3P	MP1M3	T18 - T50	# 6 (M3) screw	.50" (12.7)	1.75" (44.4)	.125" (3.2)	100
154-00100	MP1M5.NN3P	MP1M5		#10 (M5) screw	.50" (12.7)	1.75" (44.4)	.125" (3.2)	100
151-24219	MP2M3.NN3P	MP2M3		# 6 (M3) screw	.50" (12.7)	3.00" (76.2)	.125" (3.2)	100
154-00300	MP2M5.NN3P	MP2M5		#10 (M5) screw	.50" (12.7)	3.00" (76.2)	.125" (3.2)	100
151-24319	MP3M3.NN3P	MP3M3		# 6 (M3) screw	.50" (12.7)	4.25" (108.0)	.125" (3.2)	100
154-00500	MP3M5.NN3P	MP3M5		#10 (M5) screw	.50" (12.7)	4.25" (108.0)	.125" (3.2)	100
151-24419	MP4M3.NN3P	MP4M3		# 6 (M3) screw	.50" (12.7)	5.50" (139.8)	.125" (3.2)	100
154-00700	MP4M5.NN3P	MP4M5		#10 (M5) screw	.50" (12.7)	5.50" (139.8)	.125" (3.2)	100
151-24519	MP5M3.NN3P	MP5M3		# 6 (M3) screw	.50" (12.7)	6.75" (171.6)	.125" (3.2)	100
154-00900	MP5M5.NN3P	MP5M5		#10 (M5) screw	.50" (12.7)	6.75" (171.6)	.125" (3.2)	100
154-00018	MSMP5/69C2	MSMP5/6		# 6 (M3) screw	.618" (15.7)	8.08" (205.3)	.21" (5.33)	100
154-01200	MSMP5/109C2	MSMP5/10		#10 (M5) screw	.618" (15.7)	8.08" (205.3)	.21" (5.33)	100
154-01302	MSMP6/69C2	MSMP6/7		# 6 (M3) screw	.618" (15.7)	9.58" (243.3)	.21" (5.33)	100
154-01300	MSMP6/109C2	MSMP6/10		#10 (M5) screw	.618" (15.7)	9.58" (243.3)	.21" (5.33)	100

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.