

Conex | Bänninger

>B< Press Inox



Proven >B< Press technology now available in stainless steel

The >B< Press family is now complete

Conex Bänninger >B< Press is the quick and easy-to-use plumbing fitting with a permanent 3-point press joint. The fittings are user friendly, very quick and easy to install, leading to time and cost savings. >B< Press offers the advantage of a flame-free installation, eliminating the need for welding therefore posing no on-site fire risk.

Conex Bänninger is now pleased to present its high quality stainless steel press fitting to the family of products. >B< Press Inox completes the range, whether it's copper, bronze, carbon steel and now stainless steel - Conex Bänninger offers the perfect fitting for your application.



Press fittings made of stainless steel - Hygienic and versatile.

Conex Bänninger now offers high quality stainless steel press fittings in sizes 15mm to 54mm.

>B< Press Inox, with its famous and unique >B< profile 3-point press feature, can be used in almost all domestic applications, such as hot and cold drinking water, heating, cooling, and rainwater systems, as well as many other industrial applications.

Made from chloride and corrosion resistant materials in accordance with EN 1.4 404 which is hygienically suitable for potable water.

Additionally, the unique high quality EPDM O-ring seal provides a permanent leak free joint .

The >B< Press Inox range is available with stainless steel tubes made of EN 1.4404 and EN 1.4521 as a stainless steel press system.

>B< Press Inox fittings can be combined with tubes in accordance to BS EN10312 series 1 and 2.

>B< Press Inox is WRAS approved and tested.


A choice of press tools: >B< Press Inox is installed the same way as other >B< Press ranges.



Andez Hotel Liverpool Street | London



Thurrock Campus
South Essex
College



























Abbots Wood | Chester

Did you know?

Conex Bänninger jointing technology has been used in many well-known buildings?

Conex Bänninger Press fittings are proven for its long-term reliability and durability.

>B<Press Stainless Steel Fittings

<p>Straight Coupler</p>  <p>PS5270 From: 15mm To: 54mm</p>	<p>Slip Coupler</p>  <p>PS4275 From: 15mm To: 54mm</p>	<p>Straight Coupler with Female Thread</p>  <p>PS4270G From: 15mm x 1/2" To: 54mm x 2"</p>	<p>Straight Coupler with Male Thread</p>  <p>PS4243G From: 15mm x 1/2" To: 54mm x 2"</p>	<p>Female Straight Union Connector</p>  <p>PS4330G From: 15mm x 1/2" To: 54mm x 2"</p>	<p>Male Straight Union Connector</p>  <p>PS4331G From: 15mm x 1/2" To: 54mm x 2"</p>
<p>Flat Face Union</p>  <p>PS4355 From: 15mm x 3/4" To: 35mm x 1. 1/2"</p>	<p>Fitting Reducer</p>  <p>PS5243 From: 22 x 15mm To: 54 x 42mm</p>	<p>90° Street Elbow</p>  <p>PS5002 From: 15mm To: 54mm</p>	<p>90° Elbow</p>  <p>PS5001 From: 15mm To: 54mm</p>	<p>Bend with Male Thread</p>  <p>PS4001G From: 15mm x 1/2" To: 54mm x 2"</p>	<p>Bend with Female Thread</p>  <p>PS4090G From: 15mm x 1/2" To: 28mm x 1"</p>
<p>90° Bend with Female Thread</p>  <p>PS4002G From: 15mm x 1/2" To: 54mm x 2"</p>	<p>45° Obtuse Elbow</p>  <p>PS5041 From: 15mm To: 54mm</p>	<p>45° Obtuse Street Elbow</p>  <p>PS5040 From: 15mm To: 54mm</p>	<p>Equal Tee</p>  <p>PS5130 From: 15 x 15 x 15mm To: 54 x 54 x 54mm</p>	<p>Tee with Reduced Branch</p>  <p>PS5130 From: 22 x 22 x 15mm To: 54 x 54 x 42mm</p>	<p>Tee with Female Branch</p>  <p>PS4130G From: 15 x 1/2 x 15mm To: 54 x 2 x 54mm</p>
<p>Cross Over (long)</p>  <p>PS5088 From: 15mm To: 28mm</p>	<p>Short Cross Over</p>  <p>PS5087 From: 15mm To: 28mm</p>	<p>Male Street Bend</p>  <p>PS5030 From: 15mm To: 54mm</p>	<p>Wall Plate Elbow</p>  <p>PS4471G From: 15mm x 1/2" To: 28mm x 1"</p>	<p>Stop End</p>  <p>PS5301 From: 15mm To: 54mm</p>	<p>Stainless Steel Tube</p>  <p>From: 15mm x 1,00 To: 54mm x 1,50</p>

✓ For all potable waters

✓ Press indicator
Fittings will leak from 0.1 to 0.5 bar if they have not been pressed

Conex | Bänninger



Conex | Bänninger
Conex Compression

Conex | Bänninger
Triflow Solder Ring

Conex | Bänninger
Delcop End Feed

Conex | Bänninger
Delbraze

Conex | Bänninger
>B< Press

Conex | Bänninger
>B< Press Gas

Conex | Bänninger
>B< Press Solar

Conex | Bänninger
>B< Press XL

Conex | Bänninger
>B< Press Carbon

Conex | Bänninger
>B< Press Inox

Conex | Bänninger
>B< Flex

Conex | Bänninger
>B< Push

Conex | Bänninger
Push-Fit

Conex | Bänninger
Cuprofit

Conex | Bänninger
K65®

Conex | Bänninger
Valves

Conex | Bänninger
>B< Oyster

Conex | Bänninger
Medical Gas

Conex | Bänninger
OEM

Conex | Bänninger
>B< ACR

Conex | Bänninger
Series 3000

Conex | Bänninger
Series 8000

Conex | Bänninger
Series 8000 M



United Kingdom
Conex Universal Limited

Germany
IBP GmbH

Spain/France
IBP Atcosa SL

Italy
IBP Banninger Italia srl

Poland Sales, Marketing and Logistics
IBP Instalittings Sp z o.o.

China
IBP China

Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 557 0185 | Email: sales@ibpgroup.com | Website: www.conexbanninger.com

The content of this publication is for general information only. It is the user's responsibility to determine suitability of any product for the purpose intended and reference should be made to our Technical Department if clarification is required. In the interests of technical development we reserve the right to change specification, design and materials without notice. *Conex Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com. This is a representation of the full range from Conex Universal. IBP trade marks are registered in numerous countries.