

Lexmark Forms Printer 2580+ Series



Fast, Reliable Forms Printing

The Lexmark Forms Printer 2580+ series provides high-speed forms printing and features such as high-yield ribbons, multi-part form support, and character and page monitoring.



Black



Up to 618 cps at 12 cpi



Multi-Part Forms



Network Model



Lexmark Forms Printer 2580+

Overview:

Reliability and performance

With fast print speeds up to 618 cps at 12 cpi and a rugged design that can handle extreme environments and workloads, the Lexmark Forms Printer 2580+ series helps you to be productive no matter where you are. Benefit from the 2MB of built-in flash memory that expands support for bar codes, non-volatile fonts and remote management.

Flexible paper handling

Easily switch between push and pull feeds and select the type of paper-handling that best suits your needs. Use the optional Automatic Sheet Feeder to load stacks of cut-sheet media, envelopes or multi-part forms. Use the Tractor 2 option to simultaneously load two types of continuous forms.

Flexible media support

Print on multiple types of media, including single-part or multi-part continuous forms, and single-part or multi-part cut forms. Multi-part forms can include one original and up to five copies.

Easy to use

The easy-to-use operator panel lets you access all of the printer functions, as well as monitor printer usage with character and page counts. The panel also includes a font preview, so you can make sure that the correct font is used on your document.

Easy to maintain

For multi-national groups, the universal power supply reduces the need to maintain separate low-voltage and high-voltage power supplies. On the 2580n+ and 2581n+, Lexmark Markvision Enterprise helps you easily maintain multiple devices from a centralized location.

Easy to connect

Connecting to your network is easy and secure with built-in Ethernet and security features such as IPSec, HTTPS, SNMPv3 and 802.1x authentication with the Forms Printer 2580n+ and 2581n+.

Long lasting supplies

Replace supplies less often with powerful printheads that last up to 300 million characters and the availability of re-inking ribbons that can print up to 8 million characters.

LEXMARK
TM

Lexmark Forms Printer 2580+ Series

Product specifications

Lexmark Forms Printer 2580+

Lexmark Forms Printer 2580n+

Lexmark Forms Printer 2581+

Lexmark Forms Printer 2581n+

Printing				
Printer Part Number	11C2946	11C2947	11C2948	11C2928
Print Technology	9-Pin Dot Matrix			
Print Speeds	Up to 618 cps Fast Draft @ 12 cpi, Up to 400 cps Draft @ 12 cpi, Up to 100 cps Near Letter Quality @ 12 cpi			
Maximum Print Line	203.2 mm		345.4 mm	
Resolution	240 x 144 dots per inch			
Memory	512 KB			
Mean Time Between Failures (MTBF)	12,500 POH @ 25% duty cycle			
Supplies Yield	Optional 8 million characters (draft mode at 10 cpi)- Re-Inking Ribbon, Standard 4 million characters (draft mode at 10 cpi) - Re-Inking Ribbon			
Supplies Part Number	3070169 - High Yield Black Re-Inking Ribbon 3070166 - Standard Yield Black Re-inking Ribbon			
Text Fonts	Fast Draft, Draft, Courier, Gothic, 10, 12, 15, 17.1, 20 cpi, Proportional Spaced (PS)			
Acoustics/Noise level (Idle mode)	15 dBA			
Acoustics/Noise level (Operating mode)	56 dBA		57 dBA	
Paper Handling				
Paper Handling Standard	Front Tractor Feeder			
Paper Handling Optional	Automatic Sheet Feeder (narrow), Tractor 2 (narrow)		Automatic Sheet Feeder (wide), Tractor 2 (wide)	
Paper Option Part Number	12T0693 - Automatic Sheet Feed (narrow) 12T0695 - Tractor 2 (narrow) 12T0697 - Cut Sheet Output Support Stand		12T0696 - Tractor 2 (wide) 12T0694 - Automatic Sheet Feed (wide) 12T0697 - Cut Sheet Output Support Stand	
Media Sizes Supported	Single-part or multi-part continuous forms, Narrow sheet fed paper, Single-part or multi-part cut forms		Single-part or multi-part continuous forms, Wide sheet fed paper, Single-part or multi-part cut forms	
Media Types Supported	Multi-part forms - Up to 1+5 parts (up to 0.020" or 0.51 mm paper thickness), Single-part forms - 16 to 24 lbs, 60 to 90 gsm (0.0045" or 0.11 mm paper thickness), Forms or Paper - 16 to 24 lbs, 60 to 90 gsm (0.0045" or 0.11mm maximum paper thickness)			
General				
Size (mm - H x W x D)	195 x 492 x 290 mm		195 x 634 x 290 mm	
Weight (kg)	8 kg		9.8 kg	
Product Guarantee	1-Year Onsite Repair Base	1-Year Onsite Service, Next Business Day	1-Year Onsite Service, Next Business Day	1-Year Onsite Service, Next Business Day
Product Certifications	www.lexmark.com			
Specified Operating Environment	Humidity: 8 to 90% Relative Humidity, Temperature: 10 to 40°C (50 to 104°F)			
Compatibility				
Linux Operating Systems Supported	Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10, 11, Debian GNU/Linux 3.1, 4.0, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2			
Microsoft Windows Operating Systems Supported	2000, XP, Server 2003, XP x64, Server 2003 x64, Vista, Vista x64, Server 2008, Server 2008 x64, Windows 7, Windows 7 x64, Server 2008 R2			
Connectivity (standard)	Centronics IEEE 1284 Bidirectional Parallel, USB Compatible with USB 2.0 Specification	Fast Ethernet, USB Compatible with USB 2.0 Specification	Centronics IEEE 1284 Bidirectional Parallel, USB Compatible with USB 2.0 Specification	Fast Ethernet, USB Compatible with USB 2.0 Specification
Other Attachment Options	RS-232C Serial Interface Card		RS-232C Serial Interface Card	
Connectivity (optional)	External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7000e Fast Ethernet (USB), External MarkNet™ N7002e Fast Ethernet (parallel)	External MarkNet™ N7020e Gigabit Ethernet	External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7000e Fast Ethernet (USB), External MarkNet™ N7002e Fast Ethernet (parallel)	External MarkNet™ N7020e Gigabit Ethernet
Printer Languages (Standard)	Epson Emulation, PPDS, Okidata MICROLINE Emulation			

Which model is best for you?



2580+	2580n+	2581+	2581n+
9-pin	9-pin	9-pin	9 pin
Narrow format	Narrow format	Wide format	Wide format
	Network ready		Network ready