



# HP 2920 Switch Series



## Key features

- High-performance Gigabit Ethernet access switch
- Four optional 10GbE (SFP+ and/or 10GBASE-T) ports
- Stacking capability with a total of four switches
- Layer 2 and Layer 3 plus static and RIP routing, PoE, and PoE+ support
- Lifetime warranty, sFlow, ACLs, OpenFlow, and rate limiting

## Product overview

The HP 2920 Switch Series consists of five switches: the HP 2920-24G and 2920-24G-PoE+ Switches with 24 10/100/1000 ports, and the HP 2920-48G and 2920-48G-PoE+ and 2920-48G 740W PoE+ Switches with 48 10/100/1000 ports. Each switch has four dual-personality ports for 10/100/1000 or SFP connectivity.

In addition, the 2920 switch series supports up to four optional 10 Gigabit Ethernet (SFP+ and/or 10GBASE-T) ports, as well as a two-port stacking module. These options provide you with flexible and easy-to-deploy uplinks and stacking.

Together with static and RIP routing, robust security and management, enterprise-class features, free lifetime warranty, and free software updates, the HP 2920 Switch Series is a cost-effective, scalable solution for customers who are building high-performance networks. These switches can be deployed at the enterprise edge, in remote branch offices, and in converged networks.

## Features and benefits

### Quality of Service (QoS)

- **Traffic prioritization (IEEE 802.1p)**  
allows real-time traffic classification into eight priority levels mapped to eight queues
- **Layer 4 prioritization**  
enables prioritization based on TCP/UDP port numbers
- **Class of Service (CoS)**  
sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- **Rate limiting**  
sets per-port ingress enforced maximums and per-port, per-queue minimums
- **Large buffers**  
provide graceful congestion management

### Connectivity

- **Flexible 10 Gb/s Ethernet connectivity**  
up to four optional 10-Gigabit ports (SFP+ and/or 10GBASE-T)
- **Two-port stacking module with up to 40 Gb/s per port**  
optional two-port stacking module allows stacking of up to four switch units into a single virtual device
- **Auto-MDIX**  
provides automatic adjustments for straight-through or crossover cables on all 10/100 and 10/100/1000 ports
- **IPv6**
  - **IPv6 host**  
allows the switches to be managed and deployed at the edge of IPv6 networks
  - **Dual stack (IPv4/IPv6)**  
provides transition mechanism from IPv4 to IPv6; supports connectivity for both protocols
  - **MLD snooping**  
forwards IPv6 multicast traffic to the appropriate interface; prevents IPv6 multicast traffic from flooding the network
- **IEEE 802.3at Power over Ethernet (PoE+)**  
provides up to 30 W per port that allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af-compliant end device; eliminates the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments
- **Pre-standard PoE support**  
detects and provides power to pre-standard PoE devices
- **Dual-personality functionality**  
includes four 10/100/1000 ports or SFP slots for optional fiber connectivity such as Gigabit-SX, -LX, and -LH, or 100-FX

### Performance

- **Energy-efficient design**
  - **High-efficiency power supplies**  
80 PLUS Silver Certified power supply increases power savings
  - **Energy-efficient Ethernet (EEE) support**  
reduces power consumption in accordance with IEEE 802.3az
- **HP ProVision ASIC architecture**  
is designed with the latest HP ProVision ASIC, providing very low latency, increased packet buffering, and adaptive power consumption
- **Selectable queue configurations**  
allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications

### Software-defined networking

- **NEW OpenFlow**  
is a key technology that enables software-defined networking by allowing the separation of data (packet forwarding) and control (routing decision) paths

### Convergence

- **IP multicast snooping and data-driven IGMP**  
automatically prevent flooding of IP multicast traffic
- **LLDP-MED (Media Endpoint Discovery)**  
defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**  
facilitates easy mapping using network management applications with LLDP automated device discovery protocol
- **PoE and PoE+ allocations**  
support multiple methods (automatic, IEEE 802.3at dynamic, LLDP-MED fine grain, IEEE 802.3af device class, or user-specified) to allocate and manage PoE/PoE+ power for more efficient energy savings

### Resiliency and high availability

- **IEEE 802.1s Multiple Spanning Tree**  
provides high link availability in multiple VLAN environments by allowing multiple spanning trees; provides legacy support for IEEE 802.1d and IEEE 802.1w
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP) and HP port trunking**  
support up to 60 static, dynamic, or distributed trunks active across a stack, with each trunk having up to eight links (ports) per static trunk; support trunking across stack members
- **Ring and chain stacking topology**  
allows failure of a link or switch in the ring of stacked switches, while the remaining connected switches continue operation

## Management

- **SNMPv1, v2, and v3**  
provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption
- **Out-of-band Ethernet management port**  
enables management over a separate physical management network, keeping management traffic segmented from network data traffic

## Manageability

- **Dual flash images**  
provides independent primary and secondary operating system files for backup while upgrading
- **Friendly port names**  
allow assignment of descriptive names to ports
- **Find-Fix-Inform**  
finds and fixes common network problems automatically, then informs administrator
- **Multiple configuration files**  
allow multiple configuration files to be stored to a flash image
- **Software updates**  
free downloads from the Web
- **RMON, XRMON, and sFlow**  
provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Troubleshooting**  
ingress and egress port monitoring enable network problem solving
- **Uni-Directional Link Detection (UDLD)**  
monitors a link between two switches and blocks the ports on both ends of the link if the link goes down at any point between the two devices

## Layer 2 switching

- **VLAN support and tagging**  
supports IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously
- **GARP VLAN Registration Protocol**  
allows automatic learning and dynamic assignment of VLANs
- **Jumbo packet support**  
improves the performance of large data transfers; supports frame size of up to 9220 bytes
- **IEEE 802.1v protocol VLANs**  
isolate select non-IPv4 protocols automatically into their own VLANs
- **Rapid Per-VLAN Spanning Tree (RPVST+)**  
allows each VLAN to build a separate spanning tree to improve link bandwidth usage; is compatible with PVST+

## Layer 3 routing

- **Static IP routing**  
provides manually configured routing; includes ECMP capability
- **Routing Information Protocol (RIP)**  
provides RIPv1 and RIPv2 routing
- **256 static and 2,048 RIP routes**  
facilitate segregation of user data without adding external hardware

## Security

- **Multiple user authentication methods**
  - **IEEE 802.1X**  
uses an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server to authenticate in accordance with industry standards
  - **Web-based authentication**  
provides a browser-based environment, similar to IEEE 802.1X, to authenticate clients that do not support the IEEE 802.1X supplicant
  - **MAC-based authentication**  
authenticates the client with the RADIUS server based on the client's MAC address
- **Authentication flexibility**
  - **Multiple IEEE 802.1X users per port**  
provides authentication of multiple IEEE 802.1X users per port; prevents a user from "piggybacking" on another user's IEEE 802.1X authentication
  - **Concurrent IEEE 802.1X, Web, and MAC authentication schemes per port**  
switch port will accept up to 32 sessions of IEEE 802.1X, Web, and MAC authentications
- **Access control lists (ACLs)**  
provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number
- **Source-port filtering**  
allows only specified ports to communicate with each other
- **RADIUS/TACACS+**  
eases switch management security administration by using a password authentication server
- **IEEE 802.1X, MAC, or Web authentication**  
provides concurrent network access control and Web authentication of up to 24 clients per port
- **Secure shell**  
encrypts all transmitted data for secure remote CLI access over IP networks
- **Secure Sockets Layer (SSL)**  
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch

- **Port security**  
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC address lockout**  
prevents particular configured MAC addresses from connecting to the network
- **Secure FTP**  
allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Switch management logon security**  
helps secure switch CLI logon by optionally requiring either RADIUS or TACACS+ authentication
- **Custom banner**  
displays security policy when users log in to the switch
- **STP BPDU port protection**  
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **DHCP protection**  
blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection**  
blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **STP root guard**  
protects the root bridge from malicious attacks or configuration mistakes
- **Identity-driven ACL**  
enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- **Per-port broadcast throttling**  
selectively configures broadcast control on heavy traffic port uplinks

## Monitor and diagnostics

- **Digital optical monitoring of SFP+ and 1000BASE-T transceivers**  
allows detailed monitoring of the transceiver settings and parameters

## Warranty and support

- **Lifetime Warranty 2.0**  
advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)†

- **Electronic and telephone support (for Lifetime Warranty 2.0)**  
limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases**  
to find software for your product, refer to [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zL Modules, HP Threat Management Services zL Module, HP AllianceOne Extended zL Module with Riverbed Steelhead, HP MSM765 zL Mobility Controller and HP Survivable Branch Communication zL Module powered by Microsoft® Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at [www.hp.com/networking/warranty](http://www.hp.com/networking/warranty).

# HP 2920 Switch Series

## Specifications



	HP 2920-24G Switch (J9726A)	HP 2920-24G-PoE Switch (J9727A)	HP 2920-48G Switch (J9728A)
<b>Ports</b>	<p>20 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>4 RJ-45 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)</p> <p>2 module slots</p> <p>1 stacking module slot</p> <p>1 dual-personality (RJ-45 or USB micro-B)</p> <p>1 USB 1.1</p> <p>1 RJ-45 out-of-band management port</p>	<p>20 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>4 RJ-45 dual-personality 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+)</p> <p>2 module slots</p> <p>1 stacking module slot</p> <p>1 dual-personality (RJ-45 or USB micro-B)</p> <p>1 USB 1.1</p> <p>1 RJ-45 out-of-band management port</p>	<p>44 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>4 RJ-45 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)</p> <p>2 module slots</p> <p>1 stacking module slot</p> <p>1 dual-personality (RJ-45 or USB micro-B)</p> <p>1 USB 1.1</p> <p>1 RJ-45 out-of-band management port</p>
<b>Power supplies</b>	<p>1 power supply slot</p> <p>1 minimum power supply required</p> <p>includes: 1 x J9739A (HP X331 165W 100-240VAC to 12VDC Modular Power Supply)</p>	<p>1 power supply slot</p> <p>1 minimum power supply required</p> <p>includes: 1 x J9738A (HP X332 575W 100-240VAC to 54VDC Modular Power Supply)</p>	<p>1 power supply slot</p> <p>1 minimum power supply required</p> <p>includes: 1 x J9739A (HP X331 165W 100-240VAC to 12VDC Modular Power Supply)</p>
<b>Physical characteristics</b>	<p>17.42(w) x 13.23(d) x 1.75(h) in (44.25 x 33.6 x 4.45 cm) (1U height)</p> <p>Weight: 11.57 lb (5.25 kg)</p>	<p>17.42(w) x 13.23(d) x 1.73(h) in (44.25 x 33.6 x 4.4 cm) (1U height)</p> <p>Weight: 12.04 lb (5.46 kg)</p>	<p>17.42(w) x 13.23(d) x 1.73(h) in (44.25 x 33.6 x 4.4 cm) (1U height)</p> <p>Weight: 11.95 lb (5.42 kg)</p>
<b>Memory and processor</b>	<p>Tri Core ARM1176 @ 625 MHz, 512 MB SDRAM, 1 GB flash MB; packet buffer size: 11.25 MB (6.75 MB dynamic egress + 4.5 MB ingress)</p>	<p>Tri Core ARM1176 @ 625 MHz, 512 MB SDRAM, 1 GB flash; packet buffer size: 11.25 MB (6.5 MB dynamic egress + 4.5 MB ingress)</p>	<p>Tri Core ARM1176 @ 625 MHz, 512 MB SDRAM, 1 GB flash; packet buffer size: 11.25 MB (6.75 MB dynamic egress + 4.5 MB ingress)</p>
<b>Performance</b>	<p>100 Mb Latency &lt; 9.0 μs (FIFO 64-byte packets)</p> <p>1000 Mb Latency &lt; 3.3 μs (FIFO 64-byte packets)</p> <p>10 Gb/s Latency &lt; 3.3 μs (FIFO 64-byte packets)</p> <p>Throughput 95.2 million pps</p> <p>Switching capacity 128 Gb/s</p> <p>Routing table size 2048 entries (IPv4), 256 entries (IPv6)</p> <p>MAC address table size 16000 entries</p>	<p>100 Mb Latency &lt; 9.0 μs (FIFO 64-byte packets)</p> <p>1000 Mb Latency &lt; 3.3 μs (FIFO 64-byte packets)</p> <p>10 Gb/s Latency &lt; 3.3 μs (FIFO 64-byte packets)</p> <p>Throughput 95.2 million pps</p> <p>Switching capacity 128 Gb/s</p> <p>Routing table size 2048 entries (IPv4), 256 entries (IPv6)</p> <p>MAC address table size 16000 entries</p>	<p>100 Mb Latency &lt; 9.0 μs (FIFO 64-byte packets)</p> <p>1000 Mb Latency &lt; 3.3 μs (FIFO 64-byte packets)</p> <p>10 Gb/s Latency &lt; 3.2 μs (FIFO 64-byte packets)</p> <p>Throughput 130.9 million pps</p> <p>Switching capacity 176 Gb/s</p> <p>Routing table size 2048 entries (IPv4), 256 entries (IPv6)</p> <p>MAC address table size 16000 entries</p>
<b>Environment</b>	<p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 15% to 95%, noncondensing</p> <p>Altitude up to 10,000 ft (3 km)</p> <p>Acoustic Power: 57 dB, Pressure: 41.4 dB</p>	<p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 15% to 95%, noncondensing</p> <p>Altitude up to 10,000 ft (3 km)</p> <p>Acoustic Power: 61 dB, Pressure: 44.9 dB</p>	<p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 15% to 95%, noncondensing</p> <p>Altitude up to 10,000 ft (3 km)</p> <p>Acoustic Power: 57 dB, Pressure: 41.8 dB</p>
<b>Electrical characteristics</b>	<p>Frequency 50/60 Hz</p> <p>80plus.org Certification Silver</p> <p>Maximum heat dissipation 198 BTU/hr (208.89 kJ/hr)</p> <p>Voltage 100-240 VAC</p> <p>Maximum power rating 58 W</p> <p>Idle power 26 W</p> <p>PoE power</p>	<p>Frequency 50/60 Hz</p> <p>80plus.org Certification Silver</p> <p>Maximum heat dissipation 358 BTU/hr (377.69 kJ/hr)</p> <p>Voltage 100-240 VAC</p> <p>Maximum power rating 475 W</p> <p>Idle power 42 W</p> <p>PoE power 370 W</p>	<p>Frequency 50/60 Hz</p> <p>Achieved Miercom Certified Green Award</p> <p>80plus.org Certification Silver</p> <p>Maximum heat dissipation 239 BTU/hr (252.15 kJ/hr)</p> <p>Voltage 100-240 VAC</p> <p>Maximum power rating 70 W</p> <p>Idle power 27 W</p> <p>PoE power</p>

# HP 2920 Switch Series

## Specifications (continued)

	HP 2920-24G Switch (J9726A)	HP 2920-24G-PoE+ Switch (J9727A)	HP 2920-48G Switch (J9728A)
<b>Notes</b>	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). 370 W of PoE+ power is available using the internal default power supply.	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	CE Labeled; EN 60825-1 Safety of Laser Products-Part 1; FCC Part 15, Subpart B; GOST; EU RoHS Compliant; EN 55022 Class A; EN 55024: 1998; C-Tick; ICES-003, Class A; VCCI Class A; IEC 60950-1 -Second Edition ; IEC 60825-1; EN62479:2010; CSA C22.2 No. 60950-1-07 2nd Edition; EN 60950-1:2006+A11:2009+A1:2010+A12:2011; IEC 60950-1 (ed.2): am1	CE Labeled; EN 60825-1 Safety of Laser Products-Part 1; FCC Part 15, Subpart B; GOST; EU RoHS Compliant; EN 55022 Class A; EN 55024: 1998; C-Tick; ICES-003, Class A; VCCI Class A; IEC 60825-1; IEC 60950-1, Second Edition; EN62479:2010; CSA C22.2 No. 60950-1-07 2nd Edition; EN 60950-1:2006+A11:2009+A1:2010+A12:2011; IEC 60950-1 (ed.2): am1	CE Labeled; EN 60825-1 Safety of Laser Products-Part 1; FCC Part 15, Subpart B; GOST; EU RoHS Compliant; EN 55022 Class A; EN 55024: 1998; C-Tick; ICES-003, Class A; VCCI Class A; IEC 60825-1; IEC 60950-1, Second Edition; EN62479:2010; CSA C22.2 No. 60950-1-07 2nd Edition; EN 60950-1:2006+A11:2009+A1:2010+A12:2011; IEC 60950-1 (ed.2): am1
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022/CISPR 22 Class A	FCC part 15 Class A; VCCI Class A; EN 55022/CISPR 22 Class A	FCC part 15 Class A; VCCI Class A; EN 55022/CISPR 22 Class A
<b>Immunity</b>			
EN	EN 55024, CISPR 24	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2	IEC 61000-4-2	IEC 61000-4-2
Radiated	IEC 61000-4-3	IEC 61000-4-3	IEC 61000-4-3
EFT/Burst	IEC 61000-4-4	IEC 61000-4-4	IEC 61000-4-4
Surge	IEC 61000-4-5	IEC 61000-4-5	IEC 61000-4-5
Conducted	IEC 61000-4-6	IEC 61000-4-6	IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8	IEC 61000-4-8	IEC 61000-4-8
Voltage dips and interruptions	IEC 61000-4-11	IEC 61000-4-11	IEC 61000-4-11
Harmonics	IEC 61000-3-2	IEC 61000-3-2	IEC 61000-3-2
Flicker	IEC 61000-3-3	IEC 61000-3-3	IEC 61000-3-3
<b>Management</b>	HP PCM+; IMC - Intelligent Management Center; command-line interface; Web browser; configuration menu; out-of-band management (RJ-45 Ethernet); SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; out-of-band management (serial RS-232C or Micro USB)	HP PCM+; IMC - Intelligent Management Center; command-line interface; Web browser; configuration menu; out-of-band management (RJ-45 Ethernet); SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; out-of-band management (serial RS-232C or Micro USB)	HP PCM+; IMC - Intelligent Management Center; command-line interface; Web browser; configuration menu; out-of-band management (RJ-45 Ethernet); SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; out-of-band management (serial RS-232C or Micro USB)
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

# HP 2920 Switch Series

## Specifications (continued)



	HP 2920-48G-PoE+ Switch (J9729A)	HP 2920-48G-PoE+ 740W Switch (J9836A)
<b>Ports</b>	<p>44 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>4 RJ-45 dual-personality 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+)</p> <p>2 module slots</p> <p>1 stacking module slot</p> <p>1 dual-personality (RJ-45 or USB micro-B)</p> <p>1 USB 1.1</p> <p>1 RJ-45 out-of-band management port</p>	<p>44 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>4 RJ-45 dual-personality 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+)</p> <p>2 module slots</p> <p>1 stacking module slot</p> <p>1 dual-personality (RJ-45 or USB micro-B)</p> <p>1 USB 1.1</p> <p>1 RJ-45 out-of-band management port</p>
<b>Power supplies</b>	<p>1 power supply slot</p> <p>1 minimum power supply required</p> <p>includes: 1 x J9738A (HP X332 575W 100-240VAC to 54VDC Modular Power Supply)</p>	<p>1 power supply slot</p> <p>1 minimum power supply required</p> <p>includes: 1 x J9737A (HP X332 1050W 110-240VAC to 54VDC Power Supply)</p>
<b>Physical characteristics</b>	<p>17.42(w) x 13.23(d) x 1.73(h) in (44.25 x 33.6 x 4.39 cm) (1U height)</p>	<p>17.42(w) x 13.23(d) x 1.73(h) in (44.25 x 33.6 x 4.39 cm) (1U height)</p>
<b>Weight</b>	12.57 lb (5.7 kg)	12.86 lb (5.83 kg)
<b>Memory and processor</b>	Tri Core ARM1176 @ 625 MHz, 512 MB SDRAM, 1 GB flash; packet buffer size: 11.25 MB (6.75 MB dynamic egress + 4.5 MB ingress)	Tri Core ARM1176 @ 625 MHz, 512 MB SDRAM, 1 GB flash; packet buffer size: 11.25 MB (6.75 MB dynamic egress + 4.5 MB ingress)
<b>Performance</b>	<p>100 Mb Latency &lt; 9.0 μs (FIFO 64-byte packets)</p> <p>1000 Mb Latency &lt; 3.2 μs (FIFO 64-byte packets)</p> <p>10 Gb/s Latency &lt; 3.2 μs (FIFO 64-byte packets)</p> <p>Throughput 130.9 million pps</p> <p>Switching capacity 176 Gb/s</p> <p>Routing table size 2048 entries (IPv4), 256 entries (IPv6)</p> <p>MAC address table size 16000 entries</p>	<p>100 Mb Latency &lt; 9.0 μs (FIFO 64-byte packets)</p> <p>1000 Mb Latency &lt; 3.2 μs (FIFO 64-byte packets)</p> <p>10 Gb/s Latency &lt; 3.2 μs (FIFO 64-byte packets)</p> <p>Throughput 130.9 million pps</p> <p>Switching capacity 176 Gb/s</p> <p>Routing table size 2048 entries (IPv4), 256 entries (IPv6)</p> <p>MAC address table size 16000 entries</p>
<b>Environment</b>	<p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 15% to 95%, noncondensing</p> <p>Altitude up to 10,000 ft (3 km)</p> <p>Acoustic Power: 62 dB, Pressure: 45.2 dB</p>	<p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 15% to 95%, noncondensing</p> <p>Altitude up to 10,000 ft (3 km)</p> <p>Acoustic Power: -53 dB, Pressure: -38.3 dB</p>
<b>Electrical characteristics</b>	<p>Frequency 50/60 Hz</p> <p>80plus.org Certification Silver</p> <p>Maximum heat dissipation 399 BTU/hr (420.95 kJ/hr)</p> <p>Voltage 100-240 VAC</p> <p>Maximum power rating 487 W</p> <p>Idle power 46 W</p> <p>PoE power 370 W</p> <p>Notes Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). 370 W of PoE+ power is available using the internal default power supply.</p>	<p>Frequency 50/60 Hz</p> <p>80plus.org Certification Gold</p> <p>Maximum heat dissipation 399 BTU/hr (420.95 kJ/hr)</p> <p>Voltage 110-240 VAC</p> <p>Maximum power rating 487 W</p> <p>Idle power 46 W</p> <p>PoE power 740 W</p> <p>Notes Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). 740 W of PoE+ power is available using the internal default power supply.</p>
<b>Safety</b>	CE Labeled; EN 60825-1 Safety of Laser Products-Part 1; FCC Part 15, Subpart B; GOST; EU RoHS Compliant; EN 55022 Class A; EN 55024: 1998; C-Tick; ICES-003, Class A; VCCI Class A; IEC 60950-1 :Second Edition ; IEC 60825-1; EN62479:2010; CSA C22.2 No. 60950-1-07 2nd Edition; EN 60950-1:2006+A11:2009+A1:2010+A12:2011; IEC 60950-1 (ed.2): am1	CE Labeled; EN 60825-1 Safety of Laser Products-Part 1; FCC Part 15, Subpart B; GOST; EU RoHS Compliant; EN 55022 Class A; EN 55024: 1998; C-Tick; ICES-003, Class A; VCCI Class A; IEC 60950-1 :Second Edition ; IEC 60825-1; EN62479:2010; CSA C22.2 No. 60950-1-07 2nd Edition; EN 60950-1:2006+A11:2009+A1:2010+A12:2011; IEC 60950-1 (ed.2): am1

# HP 2920 Switch Series

## Specifications (continued)

	HP 2920-48G-PoE+ Switch (J9729A)	HP 2920-48G-PoE+ 740W Switch (J9836A)
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022/CISPR 22 Class A	FCC part 15 Class A; VCCI Class A; EN 55022/CISPR 22 Class A
<b>Immunity</b>		
EN	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2	IEC 61000-4-2
Radiated	IEC 61000-4-3	IEC 61000-4-3
EFT/Burst	IEC 61000-4-4	IEC 61000-4-4
Surge	IEC 61000-4-5	IEC 61000-4-5
Conducted	IEC 61000-4-6	IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8	IEC 61000-4-8
Voltage dips and interruptions	IEC 61000-4-11	IEC 61000-4-11
Harmonics	IEC 61000-3-2	IEC 61000-3-2
Flicker	IEC 61000-3-3	IEC 61000-3-3
<b>Management</b>	HP PCM+; IMC - Intelligent Management Center; command-line interface; Web browser; configuration menu; out-of-band management (RJ-45 Ethernet); SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; out-of-band management (serial RS-232C or Micro USB)	HP PCM+; IMC - Intelligent Management Center; command-line interface; Web browser; configuration menu; out-of-band management (RJ-45 Ethernet); SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; out-of-band management (serial RS-232C or Micro USB)
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



**Standards and Protocols**

(applies to all products in series)

<b>Denial of service protection</b>		CPU DoS Protection	
<b>Device management</b>	RFC 1155 Structure and Mgmt Information (SMIv1) RFC 1157 SNMPv1/v2c RFC 1591 DNS (client) RFC 1901 (Community based SNMPv2) RFC 1901-1907 SNMPv2c, SMIv2 and Revised MIB-II RFC 1908 (SNMP v1/2 Coexistence)	RFC 2578-2580 SMIv2 RFC 2579 (SMIv2 Text Conventions) RFC 2580 (SMIv2 Conformance) RFC 2819 (RMON groups Alarm, Event, History and Statistics only) RFC 3416 (SNMP Protocol Operations v2) RFC 3417 (SNMP Transport Mappings)	HTML and telnet management HTTP, SSHv1, and Telnet Multiple Configuration Files Multiple Software Images SNMP v3 and RMON RFC support SSHv1/SSHv2 Secure Shell TACACS/TACACS+
<b>General protocols</b>	IEEE 802.1AX-2008 Link Aggregation IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ab 1000BASE-T IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3af Power over Ethernet IEEE 802.3at PoE+ IEEE 802.3az Energy Efficient Ethernet IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 792 ICMP RFC 793 TCP	RFC 826 ARP RFC 854 TELNET RFC 868 Time Protocol RFC 951 BOOTP RFC 1058 RIPv1 RFC 1256 ICMP Router Discovery Protocol (IRDP) RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1542 BOOTP Extensions RFC 2030 Simple Network Time Protocol (SNTP) v4 RFC 2131 DHCP RFC 2236 IGMP Snooping RFC 2453 RIPv2 RFC 2865 Remote Authentication Dial In User Service (RADIUS) RFC 2866 RADIUS Accounting RFC 3046 DHCP Relay Agent Information Option RFC 3411 An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks	RFC 3412 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP) RFC 3413 Simple Network Management Protocol (SNMP) Applications RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3) RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP) RFC 3416 Protocol Operations for SNMP RFC 3417 Transport Mappings for the Simple Network Management Protocol (SNMP) RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP) RFC 3576 Ext to RADIUS (CoA only) RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches RFC 4675 RADIUS VLAN & Priority RFC 4861 Neighbor Discovery for IP version 6 (IPv6) RFC 4862 IPv6 Stateless Address Autoconfiguration UDLD (Uni-directional Link Detection)
<b>IP multicast</b>	RFC 1112 IGMP	RFC 2236 IGMPv2 RFC 2710 Multicast Listener Discovery (MLD) for IPv6	RFC 3376 IGMPv3 (host joins only)
<b>IPv6</b>	RFC 1981 IPv6 Path MTU Discovery RFC 2460 IPv6 Specification RFC 2710 Multicast Listener Discovery (MLD) for IPv6 RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only) RFC 2925 Remote Operations MIB (Ping only) RFC 3019 MLDv1 MIB	RFC 3315 DHCPv6 (client and relay) RFC 3513 IPv6 Addressing Architecture RFC 3596 DNS Extension for IPv6 RFC 3810 MLDv2 (host joins only) RFC 4022 MIB for TCP RFC 4113 MIB for UDP RFC 4251 SSHv6 Architecture RFC 4252 SSHv6 Authentication	RFC 4253 SSHv6 Transport Layer RFC 4254 SSHv6 Connection RFC 4293 MIB for IP RFC 4419 Key Exchange for SSH RFC 4443 ICMPv6 RFC 4541 IGMP & MLD Snooping Switch RFC 4861 IPv6 Neighbor Discovery RFC 4862 IPv6 Stateless Address Auto-configuration
<b>MIBs</b>	IEEE 802.1ap (MSTP and STP MIB's only) RFC 1156 (TCP/IP MIB) RFC 1157 A Simple Network Management Protocol (SNMP) RFC 1213 MIB II RFC 1493 Bridge MIB RFC 1724 RIPv2 MIB RFC 2021 RMONv2 MIB	RFC 2578 Structure of Management Information Version 2 (SMIv2) RFC 2579 Textual Conventions for SMIv2 RFC 2580 Conformance Statements for SMIv2 RFC 2613 SMON MIB RFC 2618 RADIUS Client MIB RFC 2620 RADIUS Accounting MIB RFC 2665 Ethernet-Like-MIB RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB	RFC 2737 Entity MIB (Version 2) RFC 2819 RMON MIB RFC 2863 The Interfaces Group MIB RFC 2925 Ping MIB RFC 2933 IGMP MIB RFC 3414 SNMP-User based-SM MIB RFC 3415 SNMP-View based-ACM MIB RFC 3417 Simple Network Management Protocol (SNMP) over IEEE 802 Networks RFC 3418 MIB for SNMPv3
<b>Network management</b>	IEEE 802.1AB Link Layer Discovery Protocol (LLDP) RFC 1155 Structure of Management Information RFC 1157 SNMPv1 RFC 2021 Remote Network Monitoring Management Information Base Version 2 using SMIv2 RFC 2576 Coexistence between SNMP versions RFC 2578 Structure of Management Information Version 2 (SMIv2) RFC 2579 Textual Conventions for SMIv2	RFC 2580 Conformance Statements for SMIv2 RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events) RFC 2819 Remote Network Monitoring Management Information Base RFC 2856 Textual Conventions for Additional High Capacity Data Types RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations RFC 3164 BSD syslog Protocol	RFC 3176 sFlow RFC 3411 SNMP Management Frameworks RFC 3412 SNMPv3 Message Processing RFC 3414 SNMPv3 User-based Security Model (USM) RFC 3415 SNMPv3 View-based Access Control Model (VACM) ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) SNMPv1/v2c/v3 XRMON

---

**Standards and Protocols (continued)**

(applies to all products in series)

---

<b>QoS/CoS</b>	IEEE 802.1P (CoS)	RFC 2474 DiffServ Precedence, including 8 queues/port RFC 2597 DiffServ Assured Forwarding (AF)	RFC 2598 DiffServ Expedited Forwarding (EF) Ingress Rate Limiting
<b>Security</b>	IEEE 802.1X Port Based Network Access Control IEEE 802.1X:Port-Based Network Access Control (2001) RFC 1321 The MD5 Message-Digest Algorithm RFC 1334 PPP Authentication Protocols (PAP) RFC 1492 An Access Control Protocol, Sometimes Called TACACS RFC 1492 TACACS+ RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) RFC 2082 RIP-2 MD5 Authentication RFC 2104 Keyed-Hashing for Message Authentication RFC 2138 RADIUS Authentication RFC 2139 RADIUS Accounting RFC 2246 Transport Layer Security (TLS) RFC 2548 Microsoft Vendor-specific RADIUS Attributes	RFC 2618 RADIUS Authentication Client MIB RFC 2620 RADIUS Accounting Client MIB RFC 2716 PPP EAP TLS Authentication Protocol RFC 2818 HTTP Over TLS RFC 2865 RADIUS (client only) RFC 2865 RADIUS Authentication RFC 2866 RADIUS Accounting RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support RFC 2868 RADIUS Attributes for Tunnel Protocol Support RFC 2869 RADIUS Extensions RFC 2882 NAS Requirements: Extended RADIUS Practices RFC 3162 RADIUS and IPv6 RFC 3576 Dynamic Authorization Extensions to RADIUS	RFC 3579 RADIUS Support For Extensible Authentication Protocol (EAP) RFC 3580 IEEE 802.1X RADIUS RFC 3580 IEEE 802.1X Remote Authentication Dial In User Service (RADIUS) Usage Guidelines RFC 4576 RADIUS Attributes Access Control Lists (ACLs) draft-grant-tacacs-02 (TACACS) Guest VLAN for 802.1x MAC Authentication MAC Lockdown MAC Lockout Port Security Secure Sockets Layer (SSL) SSHv2 Secure Shell Web Authentication

## HP 2920 Switch Series accessories

### Modules

**NEW** HP 2920 2-Port 10GbE SFP+ Module (J9731A)

**NEW** HP 2920 2-port 10GBASE-T Module (J9732A)

**NEW** HP 2920 2-Port Stacking Module (J9733A)

### Transceivers

HP X121 1G SFP LC SX Transceiver (J4858C)

HP X121 1G SFP LC LX Transceiver (J4859C)

HP X122 1G SFP LC BX-D Transceiver (J9142B)

HP X122 1G SFP LC BX-U Transceiver (J9143B)

HP X121 1G SFP LC LH Transceiver (J4860C)

HP X121 1G SFP RJ45 T Transceiver (J8177C)

HP X111 100M SFP LC FX Transceiver (J9054C)

HP X112 100M SFP LC BX-D Transceiver (J9099B)

HP X112 100M SFP LC BX-U Transceiver (J9100B)

HP X132 10G SFP+ LC SR Transceiver (J9150A)

HP X132 10G SFP+ LC LR Transceiver (J9151A)

HP X132 10G SFP+ LC LRM Transceiver (J9152A)

HP X132 10G SFP+ LC ER Transceiver (J9153A)

HP X242 10G SFP+ to SFP+ 1m Direct Attach Copper Cable (J9281B)

HP X242 10G SFP+ to SFP+ 3m Direct Attach Copper Cable (J9283B)

HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable (J9285B)

HP X242 10G SFP+ to SFP+ 10m Direct Attach Copper Cable (J9286B)

HP X242 10G SFP+ to SFP+ 15m Direct Attach Copper Cable (J9287B)

HP X244 10G XFP to SFP+ 1m Direct Attach Copper Cable (J9300A)

HP X244 10G XFP to SFP+ 3m Direct Attach Copper Cable (J9301A)

HP X244 10G XFP to SFP+ 5m Direct Attach Copper Cable (J9302A)

### Cables

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)

HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)

HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)

HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)

HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)

HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A)

HP 2920 0.5m Stacking Cable (J9734A)

HP 2920 1.0m Stacking Cable (J9735A)

HP 2920 3.0m Stacking Cable (J9736A)

**NEW** HP 640 External/Redundant Power Supply 1m Cable (J9806A)

### Power Supply

**NEW** HP 640 Redundant/External Power Supply Shelf (J9805A)

### Mounting Kit

HP X410 1U Universal 4-post Rack Mounting Kit (J9583A)

### HP 2920-24G Switch (J9726A)

**NEW** HP X331 165W 100-240VAC to 12VDC Modular Power Supply (J9739A)

### HP 2920-24G-PoE+ Switch (J9727A)

**NEW** HP X332 575W 100-240VAC to 54VDC Modular Power Supply (J9738A)

**NEW** HP X332 1050W 110-240VAC to 54VDC Power Supply (J9737A)

### HP 2920-48G Switch (J9728A)

**NEW** HP X331 165W 100-240VAC to 12VDC Modular Power Supply (J9739A)

### HP 2920-48G-PoE+ Switch (J9729A)

**NEW** HP X332 575W 100-240VAC to 54VDC Modular Power Supply (J9738A)

**NEW** HP X332 1050W 110-240VAC to 54VDC Power Supply (J9737A)

### HP 2920-48G-PoE+ 740W Switch (J9836A)

**NEW** HP X332 575W 100-240VAC to 54VDC Modular Power Supply (J9738A)

**NEW** HP X332 1050W 110-240VAC to 54VDC Power Supply (J9737A)



Products within this series have achieved sufficient scores in each of the rated criteria to achieve the Miercom Certified Green distinction Award. See the Specifications section of this series for more information.

---

**To learn more, visit [hp.com/networking](http://hp.com/networking)**

© Copyright 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is a U.S. registered trademark of Microsoft Corporation.

4AA4-5213ENW, Created February 2013; Updated September 2013, Rev. 3

