ES9465 MFP/ ES9475 MFP Specifications





Productive, secure, efficient and easy to use. These A3 colour multi-function products can bring paper feed versatility, maximum performance and workflow productivity.

The ES9465 MFP and ES9475 MFP offer High Definition colour printing and superior performance enabling users to generate a wide range of professional documents in-house. With advanced security features and seamless integration with document workflows, users can be their most productive and efficient even when dealing with confidential documents.

Flexible configuration for efficient productivity

Select the configuration and paper output options including several finishers to meet your business needs.

- Configurations available: Cabinet (1,200 sheets), Paper Feed Pedestal (1,750 sheets) or Large Capacity Feeder (3,200 sheets)
- Finishing options include 2-tray Inner finisher (ES9465 MFP only), Multi-Stapling finisher and Saddle-Stitch finisher
- 100-sheet Multi-Purpose Tray (MPT)
- Paper sizes from A6 to SRA3
- Print on stock from 60 to 280gsm
- A4 print/copy speeds up to 50ppm
- Time to first copy, from 6.1 secs colour and 4.7 secs mono (ES9475 MFP)
- High capacity 38.4k mono and 33.6k colour toner cartridge

Enhanced efficiency through ease of use

Designed to be used by many, the intuitive touch screen can be customised for each and every user to ensure maximum productivity.

- 9' (23cm) adjustable, ergonomic, colour touch screen
- Customisable Menu function for individual user setup

Print smart - by printing in-house

Digital LED print technology and versatile paper handling produces high quality professional documents, on a multitude of different media inhouse, without having to rely on a professional print house or a high street print shop.

- Advanced image processing
- Wide range of paper weights, sizes and types
- ICC colour profiles
- Extensive output options from posters to booklets and N-up

Flexible open architecture for simple integration into your document workflow

The embedded platform, sXP (smart Extendable Platform), enhances productivity by allowing users to electronically capture, distribute and manage document workflows.

- Customisable open architecture for ease of integration
- Scan preview to ensure the correct image is input to the workflow process

- Store commonly printed documents in your personal inbox for easy retrieval with E-Filing
- 100-sheet RADF automatic duplex (double sided) document scanning

Advanced security to protect your business

Advanced security features to preserve the confidentiality of sensitive data. Sophisticated user authentication prevents unauthorised access.

- Secure Hard Disk Drive
- Secure networking with SNMPv3, SSL-Encryption
- Role Based Access Control
- Secure Print/PDF
- Hard Disk Drive secure data overwrite enabler option available

Improving efficiency and your carbon foot print

A wide range of eco features help reduce energy consumption, environmental impact and ongoing costs.

- Digital LED reduces power consumption
- Sleep Mode reduces standby power
- Duplex printing, copying, scanning and faxing - reduces paper usage and enables printing in-house
- Energy Star and Blue Angel compliant



ES9465 MFP and ES9475 MFP - Colour and Mono Multifunction Products

Time to first print Warm up time Processor Resolution Printer fonts	ES9465 MFP: A4: 35ppm colour/mono; A3: 18ppm colour/mono ES9475 MFP: A4: 50ppm colour/mono; A3: 25ppm colour/mono ES9465 MFP: Approx 8.1 seconds colour, 6.4 seconds mono ES9475 MFP: Approx 6.1 seconds colour 4.7 seconds mono Power On: 27 seconds; Low-power mode and Sleep Mode: 12 seconds	Standard paper capacity	Cabinet: Tray 1: 550 sheets; Tray 2: 550 sheets; Multi-purpose tray: 100 sheets; RADF: 100 sheets Paper Feed Pedestal (PFP): Tray 1: 550 sheets; Tray 2: 550 sheets; Tray 3: 550 sheets; Optional Tray 4: 550 sheets (Draw
Warm up time Processor Resolution Printer fonts	ES9475 MFP: Approx 6.1 seconds colour 4.7 seconds mono Power On: 27 seconds;		
Processor Resolution Printer fonts		Standard paper capacity (80gsm)	Module); Multi-purpose tray: 100 sheets; RADF: 100 sheets
Resolution Printer fonts	, -p		Large Capacity Feeder (LCF): Tray 1: 550 sheets; Tray 2: 550 sheets; Tray 3: 2,000 sheets (A4 only); Multi-purpose tray: 100
Printer fonts	Power PC Appliedmicro APM86190 1.2GHz		sheets; RADF: 100 sheets
1	600 x 600dpi, 5 bit; 600 x 1200 dpi, 1 bit (PS only)	Maximum paper capacity	3,200 sheets of 80gsm
SCANNER	80 PCL fonts & 136 PostScript fonts, PCL Bitmap fonts	Paper sizes	Tray 1: A3, A4, A5, B4, B5; Tray 2/PFP/Drawer Module: SRA3, A3, A4, A5, B4, B5; LCF: A4; Multi-purpose tray: SRA3, A3, A4, A5 B4, B5, OHP. Support Custom size: Width 100-305mm Length 148-1200mm; RADF: A3, A4, A5; Duplex: SRA3, A3, A4, A5, B4, B5
	Max. 600 x 600dpi Up to 73spm (300 x 300dpi)		Tray 1/2/PFP/Drawer Module: 60 to 256gsm; LCF: 64 to 105gsm;
	Output 24 bit (8 bit x 3 RGB)	Paper weight	Multi-purpose tray: 52 to 280gsm; RADF(Simplex): 35 to 157gsm; RADF(Duplex): 50 to 157gsm; Duplex: 60 to 256gsm
	Up to 100 sheet RADF and Platen	Dunlan and DADE	Standard
	9 Levels	Duplex and RADF	A4: 550 sheets of 80gsm; A3: 300 sheets of 80gsm
	JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page, Slim PDF,	Paper output	Inner Finisher: 2 trays, 600-sheet capacity (ES9465 MFP only);
romat	XPS-Multi/Single Page	Options: paper output	Multi-Stapling Finisher: 2 trays, 2,250-sheet capacity; Saddle-Stitch Finisher: 2 trays, 3,250-sheet capacity
	LDAP & internal address book		,,
	WS Scan, Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Scan to e-Filing, Meta Scan (option)	GENERAL FEATURES	
Сору	, , , , , , , , , , , , , , , , , , , ,	Memory	Standard: 2GB RAM + 320GB HDD
First conviout	ES9465 MFP: Approx 8.1 seconds colour, 6.4 seconds mono ES9475 MFP: Approx 6.1 seconds colour 4.7 seconds mono	Environment	Operating temperature/humidity: 10°C to 30°C / 20% to 85% RH Storage temperature/humidity: -10°C to 35°C / less than 85%
Speed colour and mone	ES9465 MFP: A4: 35cpm; A3: 18cpm	Power supply	RH (w/ supplies) Single phase 220–240VAC, frequency 50/60Hz
	ES9475 MFP: A4: 50cpm; A3: 25cpm	Power consumption	Max: 2000W; Sleep: <1W
	25-400% (platen), 25-200% (RADF) in 1% increments	Noise level	Operating: <71dB(A); Standby: <51dB(A);
	999		Power save: Background level (with full options)
FAX (OPTIONAL)		Dimensions (HxWxD)	Cabinet: 1191 x 585 (max 820) x 644 (max 790) mm PFP: 1191 x 585 (max 665) x 644 (max 725) mm LCF: 1191 x 585 (max 665) x 644 (max 730) mm
Connectivity	RJ11 x 2 (Line/Tel) PSTN	Weight ⁴	Cabinet: 101.3kg; PFP: 102.8kg; LCF: 112.5kg
Speed	33.6kbps2.4Kbps (automatic fallback)	Warranty	1 year standard parts warranty
Groups	Max. 200 groups, 400 destinations/group		ES9465 MFP with Cabinet: 45744606
Broadcast	Max. 400 destinations	Product order numbers	ES9465 MFP with PFP: 45744604 ES9465 MFP with LCF: 45744605
Page memory	Max. 100 Jobs, 400 destinations/job, 2000 destinations, Max. 1000 pages/file		ES9475 MFP with Cabinet: 45744609 ES9475 MFP with PFP: 45744607 ES9475 MFP with LCF: 45744608
INTERFACE AND SOFTWARE	10/100/1000heasT 2 v Heat HSD 2 0 1 v Dovins HSD 2 0	Accessories (Order Number	s)
	10/100/1000baseT, 2 x Host USB 2.0, 1 x Device USB 2.0 PCL5e, PCL5c, PCL6, PS3, PDF, XPS	Paper Feeders / Furniture	Cabinet: 45588601; PFP: 45587501; LCF: 45587601;
Network & protocols	10Base-T/100Base-TX Ethernet Card with internal Web Server		Drawer Module: 45588001 (PFP only) Multi-Stapling: 45587301; Saddle-Stitch: 45587101;
	for MFP and network card set-up and management. Includes POP3/APOP and SMTP Mail client for submission of print jobs and for alerts. All major network protocols supported - TCP/IP:-ARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), DHCP, SNMPv1/v3, DNS, Dynamic DNS, Secure DDNS, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, JetDirect protocols, NetBIOSoverTCP, Kerberos. NetWare 6.5 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via Novell NDPS Gateway. Ethertalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:- EAP.	Finisher Units	Inner: 45587001 (ES9465 MFP only)
		Hole Punch Units	2, 4 and Swedish: 45011202/3/4 (Inner Finisher); 2, 4 and Swedish: 45587402/3/4 (Multi-Stapling or Saddle- Stitch Finisher)
		Fax	Fax board: 45588702; 2nd line fax unit: 44955102
		Connectivity	Wireless LAN Module: 45517901; Anntena: 45518001
		Card Reader	HID: 45518501; Mifare: 45518601
OS Compatibility ^a	Windows 7 SP1 (32-bit & 64-bit) / Vista SP2 (32-bit & 64-bit) / XP SP3 (32-bit) / XP 64-bit / Server 2008 (32-bit & 64-bit) / Server 2003 SP1 (32-bit & 64-bit) / Server 2008 R2 SP1 (64-bit); Mac OS X 10.4.11, 10.5.7, 10.6.7, 10.7.2, 10.8; Linux Redhat 7.x, 8.x, 9.x / Redhat Enterprise WS2 / SuSE Linux V7.x, 8.x, 9.x / Mandrake v7.x, 8.x, 9.x / Turbo Linux 8, 10; Solaris v2.6, 2.7, 7.8, 8, 9, 10 / HP-UK v10.20, 11.x / AIX 4.3.3	Enablers	Data Overwrite: 45518101; IPSec: 45518401; Meta scan: 45518201
		Other options Consumables (Order Numbe	Manual Pocket: 44985501; Damp Heater: 45588401; Work Tray: 44954701; Bridge Kit: 45588101; Job Separator: 45011902
		Toner cartridges*	
Advanced networking	IPv6 Phase 2, IEEE 2600.1, IEEE 802.1x, IPSec², SNMPv3, SSL3/ TLS HTTPS encryption, Secure Erase³, Data Encryption³, MAC	(33,600 pages)	Cyan: 45643511; Magenta: 45643510; Yellow: 45643509
	address filtering, IP address filtering, Secure Print	Toner cartridges* (38,400 pages)	Black: 45643512
		Waste Toner Box	

 1 Check local OKI Executive Series website for latest driver releases and OS compatibility; 2 Optional IPsec Enabler required.

³Optional Disk Overwrite Kit required; ⁴Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI EUROPE LTD.

Blays House, Wick Road
Egham, TW20 0HJ
United Kingdom
T +44(0) 20 8219 2190
F +44(0) 20 8219 2199
www.okiexecutiveseries.com

