



Application Optimized

New!

Widest Server Selection for Enterprise IT

Supports up to: 1.5TB DDR4- 2133MHz in 24 DIMMs • 7 PCI-E 3.0 • SAS 3.0 (12Gbps) • Quad 10GBase-T Quad Gigabit Ethernet LAN • Redundant Titanium/Platinum Level Digital Power Supplies Dual 18 Cores and 145W TDP Intel® Xeon® processor E5-2600/1600 v3 Product Families



1U

SYS-6018R-MT / MTR
SYS-5018R-M / MR (UP)



2U

SYS-6028R-T(T) / TR(T)
SYS-2028R-C1R(T)4+ (shown)



Tower/4U Rack

SYS-7048R-C1R4+ / C1RT4+
SYS-7048R-C1R / C1RT / TR(T)

Widest Server Selection for Enterprise IT, support up to:

- 1.5TB DDR4-2133MHz memory in 16 DIMM slots
- 7 PCI-E 3.0 slots
- 8 SAS 3.0 (12Gbps) ports with LSI® 3108 controller
- 10 SATA 3.0 (6Gbps) ports with Intel® C612 controller
- Quad 10GBase-T or Quad Gigabit Ethernet LAN options
- Redundant Titanium (96%+)/Platinum (95%+) Level Digital power supplies
- Integrated IPMI 2.0 plus KVM with dedicated LAN
- Up to 18 Cores and 145W TDP dual Intel® Xeon® Processor E5-2600/1600 v3 product families



Flexible Designs Optimized for a variety of Applications, including:

- Data Center / Cloud / Hadoop applications
- HPC / GPU applications
- Science / Research environments
- Finance / Oil & Gas markets



www.supermicro.com/X10

© Super Micro Computer, Inc. Specifications subject to change without notice. Intel, the Intel logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and/or other countries. All other brands and names are the property of their respective owners.



SMC20140616-A