

NetBotz 250 Environmental Monitoring and Access Control Appliance

NetBotz 250 Environmental Monitoring Appliance

Product Specifications	
NetBotz 250 Environmental Monitoring Appliance	NBRK0250
NetBotz Compatibility	
Number of NetBotz wireless sensors supported	47
Number of NetBotz wired sensors supported	42
Sensors supported	wireless temperature (NBWS100T), wireless temp/humidity (NBWS100H), temp (AP9335T), temp/humidity (AP9335TH), spot fluid (NBES0301), door contact (NBES0303), dry contact (NBES0304), vibration (NBES0306), smoke (NBES0307), beacon (AP9324)
Sensor pods supported	Wired sensor pod 150 (NBPD0150), wireless sensor pod 180 (NBPD0180)
Additional connections supported	Switched outlet, voltage output
Electrical	
Input Voltage, nominal	100-240 VAC; 50/60 Hz
Maximum total current draw for AC Line Inlet	10 A (defined by switched outlet load + 0.25 A)
Maximum output voltage for switched outlet	Defined by input voltage
Maximum output current for switched outlet	10 A (defined by switched outlet load)
Voltage for Voltage Output contacts	12 Vdc, 24 VAC
Current capacity of Relay Output contacts	1 A, 30 V AC/DC (rated for Class 2 circuits only)
Physical	
Dimensions (H x W x D)	43.6 x 431.8 x 59.2 mm (1.72 x 17.00 x 2.33 in)
Shipping dimensions (H x W x D)	67 x 450 x 225 mm (2.6 x 17.8 x 8.9 in)
Weight	1.26 kg (2.80 lb)
Shipping Weight	3.00 kg (6.50 lb)

NetBotz 250 Rack Access Control

	NBACS125	NBACS1356
Description	Netbotz 250 appliance and rack access control solution with 125 kHz Handles	Netbotz 250 appliance and rack access control solution with 13.56 MHz Handles
Included	NetBotz 250 Appliance, wireless temperature sensor, wireless coordinator, wired temp/humidity sensor, (2) door contacts, (2) 125 kHz handle kits	NetBotz 250 Appliance, wireless temperature sensor, wireless coordinator, wired temp/humidity sensor, (2) door contacts, (2) 13.56 MHz handle kits
Supported cards	H10301 – Standard 26 Bit H10302 – 37 Bit w/o facility code H10304 – 37 bit w/ facility code CORP1000	MIFAREC4 – Mifare Classic 4 byte MIFAREC7 – Mifare Classic 7 byte MIFAREDF – Mifare DESfire MIFAREPL – Mifare Plus
Compatible racks	Netshelter SX	Netshelter SX
No. of doors per appliance	2	2
Physical		
Dimensions (H x W)	212.6 x 37.0 mm (8.37 x 1.45 in)	
Shipping dimensions (H x W x D)	78.7 x 222.3 x 139.7 mm (3.1 x 8.75 x 5.5 in)	
Weight	0.4 kg (0.9 lb)	
Shipping Weight	0.7 kg (1.5 lb)	